

# Kea Messages Manual

---

Copyright © 2011-2018 Internet Systems Consortium, Inc. ("ISC")

---

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Kea Log Messages</b>	<b>2</b>
2.1	ALLOC Module . . . . .	2
2.2	ASIODNS Module . . . . .	13
2.3	COMMAND Module . . . . .	17
2.4	CTRL Module . . . . .	20
2.5	DATABASE Module . . . . .	22
2.6	DCTL Module . . . . .	24
2.7	DHCP4 Module . . . . .	27
2.8	DHCP6 Module . . . . .	47
2.9	DHCPSRV Module . . . . .	69
2.10	DHCP Module . . . . .	99
2.11	EVAL Module . . . . .	113
2.12	HA Module . . . . .	118
2.13	HOOKS Module . . . . .	127
2.14	HOSTS Module . . . . .	132
2.15	HTTP Module . . . . .	137
2.16	LEASE Module . . . . .	140
2.17	LFC Module . . . . .	141
2.18	LOGIMPL Module . . . . .	142
2.19	LOG Module . . . . .	143
2.20	NETCONF Module . . . . .	146
2.21	STAT Module . . . . .	149
2.22	USER Module . . . . .	151

---

## **Abstract**

This is the messages manual for Kea version 1.5.0-beta1. The most up-to-date version of this document, along with other documents for Kea, can be found at <http://oldkea.isc.org/docs>.

# Chapter 1

## Introduction

This document lists each message that can be logged by the programs in the Kea package. Each entry in this manual is of the form:

```
IDENTIFICATION message-text
```

... where "IDENTIFICATION" is the message identification included in each message logged and "message-text" is the accompanying message text. The "message-text" may include placeholders of the form "%1", "%2" etc.; these parameters are replaced by relevant values when the message is logged.

Each entry is also accompanied by a description giving more information about the circumstances that result in the message being logged.

For information on configuring and using Kea logging, refer to the [Kea Guide](#).

## Chapter 2

# Kea Log Messages

### ALLOC Module

**ALLOC\_ENGINE\_LEASE\_RECLAIMED successfully reclaimed lease %1**

This debug message is logged when the allocation engine successfully reclaims a lease. The lease is now available for assignment.

**ALLOC\_ENGINE\_LEASE\_RECLAIMED (1) successfully reclaimed lease %1**

This debug message is logged when the allocation engine successfully reclaims a lease. The lease is now available for assignment.

**ALLOC\_ENGINE\_REMOVAL\_NCR\_FAILED sending removal name change request failed for lease %1: %2**

This error message is logged when sending a removal name change request to DHCP DDNS failed. This name change request is usually generated when the lease reclamation routine acts upon expired leases. If a lease being reclaimed has a corresponding DNS entry it needs to be removed. This message indicates that removal of the DNS entry has failed. Nevertheless the lease will be reclaimed.

**ALLOC\_ENGINE\_REMOVAL\_NCR\_FAILED (1) sending removal name change request failed for lease %1: %2**

This error message is logged when sending a removal name change request to DHCP DDNS failed. This name change request is usually generated when the lease reclamation routine acts upon expired leases. If a lease being reclaimed has a corresponding DNS entry it needs to be removed. This message indicates that removal of the DNS entry has failed. Nevertheless the lease will be reclaimed.

**ALLOC\_ENGINE\_V4\_ALLOC\_ERROR %1: error during attempt to allocate an IPv4 address: %2**

An error occurred during an attempt to allocate an IPv4 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_ALLOC\_ERROR (1) %1: error during attempt to allocate an IPv4 address: %2**

An error occurred during an attempt to allocate an IPv4 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_ALLOC\_FAIL %1: failed to allocate an IPv4 address after %2 attempt(s)**

The DHCP allocation engine gave up trying to allocate an IPv4 address after the specified number of attempts. This probably means that the address pool from which the allocation is being attempted is either empty, or very nearly empty. As a result, the client will have been refused a lease. The first argument includes the client identification information.

This message may indicate that your address pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if you know that the number of concurrently active clients is less than the addresses you have available, you may want to consider reducing the lease lifetime. In this way, addresses allocated to clients that are no longer active on the network will become available sooner.

**ALLOC\_ENGINE\_V4\_ALLOC\_FAIL (1) %1: failed to allocate an IPv4 address after %2 attempt(s)**

The DHCP allocation engine gave up trying to allocate an IPv4 address after the specified number of attempts. This probably means that the address pool from which the allocation is being attempted is either empty, or very nearly empty. As a result, the client will have been refused a lease. The first argument includes the client identification information.

This message may indicate that your address pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if you know that the number of concurrently active clients is less than the addresses you have available, you may want to consider reducing the lease lifetime. In this way, addresses allocated to clients that are no longer active on the network will become available sooner.

**ALLOC\_ENGINE\_V4\_DECLINED\_RECOVERED IPv4 address %1 was recovered after %2 seconds of probation-period**

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes decline recovery process.

**ALLOC\_ENGINE\_V4\_DECLINED\_RECOVERED (1) IPv4 address %1 was recovered after %2 seconds of probation-period**

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes decline recovery process.

**ALLOC\_ENGINE\_V4\_DISCOVER\_ADDRESS\_CONFLICT %1: conflicting reservation for address %2 with existing lease %2**

This warning message is issued when the DHCP server finds that the address reserved for the client can't be offered because this address is currently allocated to another client. The server will try to allocate a different address to the client to use until the conflict is resolved. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_DISCOVER\_ADDRESS\_CONFLICT (1) %1: conflicting reservation for address %2 with existing lease %2**

This warning message is issued when the DHCP server finds that the address reserved for the client can't be offered because this address is currently allocated to another client. The server will try to allocate a different address to the client to use until the conflict is resolved. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_DISCOVER\_HR client %1 sending DHCPDISCOVER has reservation for the address %2**

This message is issued when the allocation engine determines that the client sending the DHCPDISCOVER has a reservation for the specified address. The allocation engine will try to offer this address to the client.

**ALLOC\_ENGINE\_V4\_DISCOVER\_HR (1) client %1 sending DHCPDISCOVER has reservation for the address %2**

This message is issued when the allocation engine determines that the client sending the DHCPDISCOVER has a reservation for the specified address. The allocation engine will try to offer this address to the client.

**ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_COMPLETE reclaimed %1 leases in %2**

This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

**ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_COMPLETE (1) reclaimed %1 leases in %2**

This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

**ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_SLOW expired leases still exist after %1 reclamations**

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the

number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

**ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_SLOW (1) expired leases still exist after %1 reclamations**

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

**ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_START starting reclamation of expired leases (limit = %1 leases or %2 m**

This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

**ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_START (1) starting reclamation of expired leases (limit = %1 leases or %2**

This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

**ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_TIMEOUT timeout of %1 ms reached while reclaiming IPv4 leases**

This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

**ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_TIMEOUT (1) timeout of %1 ms reached while reclaiming IPv4 leases**

This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

**ALLOC\_ENGINE\_V4\_LEASE\_RECLAIM %1: reclaiming expired lease for address %2**

This debug message is issued when the server begins reclamation of the expired DHCPv4 lease. The first argument specifies the client identification information. The second argument holds the leased IPv4 address.

**ALLOC\_ENGINE\_V4\_LEASE\_RECLAIM (1) %1: reclaiming expired lease for address %2**

This debug message is issued when the server begins reclamation of the expired DHCPv4 lease. The first argument specifies the client identification information. The second argument holds the leased IPv4 address.

**ALLOC\_ENGINE\_V4\_LEASE\_RECLAMATION\_FAILED failed to reclaim the lease %1: %2**

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

**ALLOC\_ENGINE\_V4\_LEASE\_RECLAMATION\_FAILED (1) failed to reclaim the lease %1: %2**

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

**ALLOC\_ENGINE\_V4\_NO\_MORE\_EXPIRED\_LEASES all expired leases have been reclaimed**

This debug message is issued when the server reclaims all expired DHCPv4 leases in the database.

**ALLOC\_ENGINE\_V4\_NO\_MORE\_EXPIRED\_LEASES (1) all expired leases have been reclaimed**

This debug message is issued when the server reclaims all expired DHCPv4 leases in the database.

---



**ALLOC\_ENGINE\_V4\_OFFER\_EXISTING\_LEASE allocation engine will try to offer existing lease to the client %1**

This message is issued when the allocation engine determines that the client has a lease in the lease database, it doesn't have reservation for any other lease, and the leased address is not reserved for any other client. The allocation engine will try to offer the same lease to the client.

**ALLOC\_ENGINE\_V4\_OFFER\_EXISTING\_LEASE (1) allocation engine will try to offer existing lease to the client %1**

This message is issued when the allocation engine determines that the client has a lease in the lease database, it doesn't have reservation for any other lease, and the leased address is not reserved for any other client. The allocation engine will try to offer the same lease to the client.

**ALLOC\_ENGINE\_V4\_OFFER\_NEW\_LEASE allocation engine will try to offer new lease to the client %1**

This message is issued when the allocation engine will try to offer a new lease to the client. This is the case when the client doesn't have any existing lease, it has no reservation or the existing or reserved address is leased to another client. Also, the client didn't specify a hint, or the address in the hint is in use.

**ALLOC\_ENGINE\_V4\_OFFER\_NEW\_LEASE (1) allocation engine will try to offer new lease to the client %1**

This message is issued when the allocation engine will try to offer a new lease to the client. This is the case when the client doesn't have any existing lease, it has no reservation or the existing or reserved address is leased to another client. Also, the client didn't specify a hint, or the address in the hint is in use.

**ALLOC\_ENGINE\_V4\_OFFER\_REQUESTED\_LEASE allocation engine will try to offer requested lease %1 to the client %2**

This message is issued when the allocation engine will try to offer the lease specified in the hint. This situation may occur when: (a) client doesn't have any reservations, (b) client has reservation but the reserved address is leased to another client.

**ALLOC\_ENGINE\_V4\_OFFER\_REQUESTED\_LEASE (1) allocation engine will try to offer requested lease %1 to the client %2**

This message is issued when the allocation engine will try to offer the lease specified in the hint. This situation may occur when: (a) client doesn't have any reservations, (b) client has reservation but the reserved address is leased to another client.

**ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE begin deletion of reclaimed leases expired more than %1 seconds ago**

This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

**ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE (1) begin deletion of reclaimed leases expired more than %1 seconds ago**

This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

**ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_COMPLETE successfully deleted %1 expired-reclaimed leases**

This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

**ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_COMPLETE (1) successfully deleted %1 expired-reclaimed leases**

This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

**ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_FAILED deletion of expired-reclaimed leases failed: %1**

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

**ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_FAILED (1) deletion of expired-reclaimed leases failed: %1**

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

**ALLOC\_ENGINE\_V4\_REQUEST\_ADDRESS\_RESERVED %1: requested address %2 is reserved**

This message is issued when the allocation engine refused to allocate address requested by the client because this address is reserved for another client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REQUEST\_ADDRESS\_RESERVED (1) %1: requested address %2 is reserved**

This message is issued when the allocation engine refused to allocate address requested by the client because this address is reserved for another client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REQUEST\_ALLOC\_REQUESTED %1: trying to allocate requested address %2**

This message is issued when the allocation engine is trying to allocate (or reuse an expired) address which has been requested by the client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REQUEST\_ALLOC\_REQUESTED (1) %1: trying to allocate requested address %2**

This message is issued when the allocation engine is trying to allocate (or reuse an expired) address which has been requested by the client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REQUEST\_EXTEND\_LEASE %1: extending lifetime of the lease for address %2**

This message is issued when the allocation engine determines that the client already has a lease whose lifetime can be extended, and which can be returned to the client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REQUEST\_EXTEND\_LEASE (1) %1: extending lifetime of the lease for address %2**

This message is issued when the allocation engine determines that the client already has a lease whose lifetime can be extended, and which can be returned to the client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REQUEST\_INVALID client %1 having a reservation for address %2 is requesting invalid address %3**

This message is logged when the client, having a reservation for one address, is requesting a different address. The client is only allowed to do this when the reserved address is in use by another client. However, the allocation engine has determined that the reserved address is available and the client should request the reserved address.

**ALLOC\_ENGINE\_V4\_REQUEST\_INVALID (1) client %1 having a reservation for address %2 is requesting invalid address %3**

This message is logged when the client, having a reservation for one address, is requesting a different address. The client is only allowed to do this when the reserved address is in use by another client. However, the allocation engine has determined that the reserved address is available and the client should request the reserved address.

**ALLOC\_ENGINE\_V4\_REQUEST\_IN\_USE %1: requested address %2 is in use**

This message is issued when the client is requesting or has a reservation for an address which is in use. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REQUEST\_IN\_USE (1) %1: requested address %2 is in use**

This message is issued when the client is requesting or has a reservation for an address which is in use. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REQUEST\_OUT\_OF\_POOL client %1, which doesn't have a reservation, requested address %2 out of pool**

This message is issued when the client has requested allocation of the address which doesn't belong to any address pool from which addresses are dynamically allocated. The client also doesn't have reservation for this address. This address could only be allocated if the client had reservation for it.

**ALLOC\_ENGINE\_V4\_REQUEST\_OUT\_OF\_POOL (1) client %1, which doesn't have a reservation, requested address %2 out of pool**

This message is issued when the client has requested allocation of the address which doesn't belong to any address pool from which addresses are dynamically allocated. The client also doesn't have reservation for this address. This address could only be allocated if the client had reservation for it.

**ALLOC\_ENGINE\_V4\_REQUEST\_PICK\_ADDRESS client %1 hasn't specified an address - picking available address from the**

This message is logged when the client hasn't specified any preferred address (the client should always do it, but Kea tries to be forgiving). The allocation engine will try to pick an available address from the dynamic pool and allocate it to the client.

**ALLOC\_ENGINE\_V4\_REQUEST\_PICK\_ADDRESS (1) client %1 hasn't specified an address - picking available address from the**

This message is logged when the client hasn't specified any preferred address (the client should always do it, but Kea tries to be forgiving). The allocation engine will try to pick an available address from the dynamic pool and allocate it to the client.

**ALLOC\_ENGINE\_V4\_REQUEST\_REMOVE\_LEASE %1: removing previous client's lease %2**

This message is logged when the allocation engine removes previous lease for the client because the client has been allocated new one.

**ALLOC\_ENGINE\_V4\_REQUEST\_REMOVE\_LEASE (1) %1: removing previous client's lease %2**

This message is logged when the allocation engine removes previous lease for the client because the client has been allocated new one.

**ALLOC\_ENGINE\_V4\_REQUEST\_USE\_HR client %1 hasn't requested specific address, using reserved address %2**

This message is issued when the client is not requesting any specific address but the allocation engine has determined that there is a reservation for this client. The allocation engine will try to allocate the reserved address.

**ALLOC\_ENGINE\_V4\_REQUEST\_USE\_HR (1) client %1 hasn't requested specific address, using reserved address %2**

This message is issued when the client is not requesting any specific address but the allocation engine has determined that there is a reservation for this client. The allocation engine will try to allocate the reserved address.

**ALLOC\_ENGINE\_V4\_REUSE\_EXPIRED\_LEASE\_DATA %1: reusing expired lease, updated lease information: %2**

This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V4\_REUSE\_EXPIRED\_LEASE\_DATA (1) %1: reusing expired lease, updated lease information: %2**

This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_ALLOC\_ERROR %1: error during attempt to allocate an IPv6 address: %2**

An error occurred during an attempt to allocate an IPv6 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_ALLOC\_ERROR (1) %1: error during attempt to allocate an IPv6 address: %2**

An error occurred during an attempt to allocate an IPv6 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_ALLOC\_FAIL %1: failed to allocate an IPv6 address after %2 attempt(s)**

The DHCP allocation engine gave up trying to allocate an IPv6 address after the specified number of attempts. This probably means that the address pool from which the allocation is being attempted is either empty, or very nearly empty. As a result, the client will have been refused a lease. The first argument includes the client identification information.

This message may indicate that your address pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if you know that the number of concurrently active clients is less than the addresses you have available, you may want to consider reducing the lease lifetime. In this way, addresses allocated to clients that are no longer active on the network will become available sooner.

**ALLOC\_ENGINE\_V6\_ALLOC\_FAIL (1) %1: failed to allocate an IPv6 address after %2 attempt(s)**

The DHCP allocation engine gave up trying to allocate an IPv6 address after the specified number of attempts. This probably means that the address pool from which the allocation is being attempted is either empty, or very nearly empty. As a result, the client will have been refused a lease. The first argument includes the client identification information.

---

This message may indicate that your address pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if you know that the number of concurrently active clients is less than the addresses you have available, you may want to consider reducing the lease lifetime. In this way, addresses allocated to clients that are no longer active on the network will become available sooner.

**ALLOC\_ENGINE\_V6\_ALLOC\_HR\_LEASE\_EXISTS %1: lease type %2 for reserved address/prefix %3 already exists**

This debug message is issued when the allocation engine determines that the lease for the IPv6 address or prefix has already been allocated for the client and the client can continue using it. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_ALLOC\_HR\_LEASE\_EXISTS (1) %1: lease type %2 for reserved address/prefix %3 already exists**

This debug message is issued when the allocation engine determines that the lease for the IPv6 address or prefix has already been allocated for the client and the client can continue using it. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_HR leases and static reservations found for client %1**

This message is logged when the allocation engine is in the process of allocating leases for the client, it found existing leases and static reservations for the client. The allocation engine will verify if existing leases match reservations. Those leases that are reserved for other clients and those that are not reserved for the client will be removed. All leases matching the reservations will be renewed and returned.

**ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_HR (1) leases and static reservations found for client %1**

This message is logged when the allocation engine is in the process of allocating leases for the client, it found existing leases and static reservations for the client. The allocation engine will verify if existing leases match reservations. Those leases that are reserved for other clients and those that are not reserved for the client will be removed. All leases matching the reservations will be renewed and returned.

**ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_NO\_HR no reservations found but leases exist for client %1**

This message is logged when the allocation engine is in the process of allocating leases for the client, there are no static reservations, but lease(s) exist for the client. The allocation engine will remove leases which are reserved for other clients, and return all remaining leases to the client.

**ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_NO\_HR (1) no reservations found but leases exist for client %1**

This message is logged when the allocation engine is in the process of allocating leases for the client, there are no static reservations, but lease(s) exist for the client. The allocation engine will remove leases which are reserved for other clients, and return all remaining leases to the client.

**ALLOC\_ENGINE\_V6\_ALLOC\_NO\_LEASES\_HR no leases found but reservations exist for client %1**

This message is logged when the allocation engine is in the process of allocating leases for the client. It hasn't found any existing leases for this client, but the client appears to have static reservations. The allocation engine will try to allocate the reserved resources for the client.

**ALLOC\_ENGINE\_V6\_ALLOC\_NO\_LEASES\_HR (1) no leases found but reservations exist for client %1**

This message is logged when the allocation engine is in the process of allocating leases for the client. It hasn't found any existing leases for this client, but the client appears to have static reservations. The allocation engine will try to allocate the reserved resources for the client.

**ALLOC\_ENGINE\_V6\_ALLOC\_NO\_V6\_HR %1: unable to allocate reserved leases - no IPv6 reservations**

This message is logged when the allocation engine determines that the client has no IPv6 reservations and thus the allocation engine will have to try to allocate leases from the dynamic pool or stop the allocation process if none can be allocated. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_ALLOC\_NO\_V6\_HR (1) %1: unable to allocate reserved leases - no IPv6 reservations**

This message is logged when the allocation engine determines that the client has no IPv6 reservations and thus the allocation engine will have to try to allocate leases from the dynamic pool or stop the allocation process if none can be allocated. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_ALLOC\_UNRESERVED no static reservations available - trying to dynamically allocate leases for client**

This debug message is issued when the allocation engine will attempt to allocate leases from the dynamic pools. This may be due to one of (a) there are no reservations for this client, (b) there are reservations for the client but they are not usable because the addresses are in use by another client or (c) we had a reserved lease but that has now been allocated to another client.

**ALLOC\_ENGINE\_V6\_ALLOC\_UNRESERVED (1) no static reservations available - trying to dynamically allocate leases for client**

This debug message is issued when the allocation engine will attempt to allocate leases from the dynamic pools. This may be due to one of (a) there are no reservations for this client, (b) there are reservations for the client but they are not usable because the addresses are in use by another client or (c) we had a reserved lease but that has now been allocated to another client.

**ALLOC\_ENGINE\_V6\_DECLINED\_RECOVERED IPv6 address %1 was recovered after %2 seconds of probation-period**

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes decline recovery process.

**ALLOC\_ENGINE\_V6\_DECLINED\_RECOVERED (1) IPv6 address %1 was recovered after %2 seconds of probation-period**

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes decline recovery process.

**ALLOC\_ENGINE\_V6\_EXPIRED\_HINT\_RESERVED %1: expired lease for the client's hint %2 is reserved for another client**

This message is logged when the allocation engine finds that the expired lease for the client's hint can't be reused because it is reserved for another client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_EXPIRED\_HINT\_RESERVED (1) %1: expired lease for the client's hint %2 is reserved for another client**

This message is logged when the allocation engine finds that the expired lease for the client's hint can't be reused because it is reserved for another client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_EXTEND\_ALLOC\_UNRESERVED allocate new (unreserved) leases for the renewing client %1**

This debug message is issued when the allocation engine is trying to allocate new leases for the renewing client because it was unable to renew any of the existing client's leases, e.g. because leases are reserved for another client or for any other reason.

**ALLOC\_ENGINE\_V6\_EXTEND\_ALLOC\_UNRESERVED (1) allocate new (unreserved) leases for the renewing client %1**

This debug message is issued when the allocation engine is trying to allocate new leases for the renewing client because it was unable to renew any of the existing client's leases, e.g. because leases are reserved for another client or for any other reason.

**ALLOC\_ENGINE\_V6\_EXTEND\_ERROR %1: allocation engine experienced error with attempting to extend lease lifetime: %2**

This error message indicates that an error was experienced during Renew or Rebind processing. Additional explanation is provided with this message. Depending on its nature, manual intervention may be required to continue processing messages from this particular client; other clients will be unaffected. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_EXTEND\_ERROR (1) %1: allocation engine experienced error with attempting to extend lease lifetime: %2**

This error message indicates that an error was experienced during Renew or Rebind processing. Additional explanation is provided with this message. Depending on its nature, manual intervention may be required to continue processing messages from this particular client; other clients will be unaffected. The first argument includes the client identification information.

---

**ALLOC\_ENGINE\_V6\_EXTEND\_LEASE %1: extending lifetime of the lease type %2, address %3**

This debug message is issued when the allocation engine is trying to extend lifetime of the lease. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_EXTEND\_LEASE (1) %1: extending lifetime of the lease type %2, address %3**

This debug message is issued when the allocation engine is trying to extend lifetime of the lease. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_EXTEND\_LEASE\_DATA %1: detailed information about the lease being extended: %2**

This debug message prints detailed information about the lease which lifetime is being extended (renew or rebind). The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_EXTEND\_LEASE\_DATA (1) %1: detailed information about the lease being extended: %2**

This debug message prints detailed information about the lease which lifetime is being extended (renew or rebind). The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_EXTEND\_NEW\_LEASE\_DATA %1: new lease information for the lease being extended: %2**

This debug message prints updated information about the lease to be extended. If the lease update is successful, the information printed by this message will be stored in the database. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_EXTEND\_NEW\_LEASE\_DATA (1) %1: new lease information for the lease being extended: %2**

This debug message prints updated information about the lease to be extended. If the lease update is successful, the information printed by this message will be stored in the database. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_HINT\_RESERVED %1: lease for the client's hint %2 is reserved for another client**

This message is logged when the allocation engine cannot allocate the lease using the client's hint because the lease for this hint is reserved for another client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_HINT\_RESERVED (1) %1: lease for the client's hint %2 is reserved for another client**

This message is logged when the allocation engine cannot allocate the lease using the client's hint because the lease for this hint is reserved for another client. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_HR\_ADDR\_GRANTED reserved address %1 was assigned to client %2**

This informational message signals that the specified client was assigned the address reserved for it.

**ALLOC\_ENGINE\_V6\_HR\_ADDR\_GRANTED (1) reserved address %1 was assigned to client %2**

This informational message signals that the specified client was assigned the address reserved for it.

**ALLOC\_ENGINE\_V6\_HR\_PREFIX\_GRANTED reserved prefix %1/%2 was assigned to client %3**

This informational message signals that the specified client was assigned the prefix reserved for it.

**ALLOC\_ENGINE\_V6\_HR\_PREFIX\_GRANTED (1) reserved prefix %1/%2 was assigned to client %3**

This informational message signals that the specified client was assigned the prefix reserved for it.

**ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_COMPLETE reclaimed %1 leases in %2**

This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

**ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_COMPLETE (1) reclaimed %1 leases in %2**

This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

**ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_SLOW expired leases still exist after %1 reclamations**

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

**ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_SLOW (1) expired leases still exist after %1 reclamations**

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

**ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_START starting reclamation of expired leases (limit = %1 leases or %2 minutes)**

This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

**ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_START (1) starting reclamation of expired leases (limit = %1 leases or %2 minutes)**

This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

**ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_TIMEOUT timeout of %1 ms reached while reclaiming IPv6 leases**

This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

**ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_TIMEOUT (1) timeout of %1 ms reached while reclaiming IPv6 leases**

This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

**ALLOC\_ENGINE\_V6\_LEASE\_RECLAIM %1: reclaiming expired lease for prefix %2/%3**

This debug message is issued when the server begins reclamation of the expired DHCPv6 lease. The reclaimed lease may either be an address lease or delegated prefix. The first argument provides the client identification information. The other arguments specify the prefix and the prefix length for the lease. The prefix length for address lease is equal to 128.

**ALLOC\_ENGINE\_V6\_LEASE\_RECLAIM (1) %1: reclaiming expired lease for prefix %2/%3**

This debug message is issued when the server begins reclamation of the expired DHCPv6 lease. The reclaimed lease may either be an address lease or delegated prefix. The first argument provides the client identification information. The other arguments specify the prefix and the prefix length for the lease. The prefix length for address lease is equal to 128.

**ALLOC\_ENGINE\_V6\_LEASE\_RECLAMATION\_FAILED failed to reclaim the lease %1: %2**

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

**ALLOC\_ENGINE\_V6\_LEASE\_RECLAMATION\_FAILED (1) failed to reclaim the lease %1: %2**

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

**ALLOC\_ENGINE\_V6\_NO\_MORE\_EXPIRED\_LEASES all expired leases have been reclaimed**

This debug message is issued when the server reclaims all expired DHCPv6 leases in the database.

**ALLOC\_ENGINE\_V6\_NO\_MORE\_EXPIRED\_LEASES (1) all expired leases have been reclaimed**

This debug message is issued when the server reclaims all expired DHCPv6 leases in the database.

**ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE begin deletion of reclaimed leases expired more than %1 seconds ago**

This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

**ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE (1) begin deletion of reclaimed leases expired more than %1 seconds ago**

This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

**ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_COMPLETE successfully deleted %1 expired-reclaimed leases**

This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

**ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_COMPLETE (1) successfully deleted %1 expired-reclaimed leases**

This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

**ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_FAILED deletion of expired-reclaimed leases failed: %1**

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

**ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_FAILED (1) deletion of expired-reclaimed leases failed: %1**

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

**ALLOC\_ENGINE\_V6\_RENEW\_HR allocating leases reserved for the client %1 as a result of Renew**

This debug message is issued when the allocation engine tries to allocate reserved leases for the client sending a Renew message. The server will also remove any leases that the client is trying to renew that are not reserved for the client.

**ALLOC\_ENGINE\_V6\_RENEW\_HR (1) allocating leases reserved for the client %1 as a result of Renew**

This debug message is issued when the allocation engine tries to allocate reserved leases for the client sending a Renew message. The server will also remove any leases that the client is trying to renew that are not reserved for the client.

**ALLOC\_ENGINE\_V6\_RENEW\_REMOVE\_RESERVED %1: checking if existing client's leases are reserved for another client**

This message is logged when the allocation engine finds leases for the client and will check if these leases are reserved for another client. If they are, they will not be renewed for the client requesting their renewal. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_RENEW\_REMOVE\_RESERVED (1) %1: checking if existing client's leases are reserved for another client**

This message is logged when the allocation engine finds leases for the client and will check if these leases are reserved for



another client. If they are, they will not be renewed for the client requesting their renewal. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_RENEW\_REMOVE\_UNRESERVED dynamically allocating leases for the renewing client %1**

This debug message is issued as the allocation engine is trying to dynamically allocate new leases for the renewing client. This is the case when the server couldn't renew any of the existing client's leases, e.g. because leased resources are reserved for another client.

**ALLOC\_ENGINE\_V6\_RENEW\_REMOVE\_UNRESERVED (1) dynamically allocating leases for the renewing client %1**

This debug message is issued as the allocation engine is trying to dynamically allocate new leases for the renewing client. This is the case when the server couldn't renew any of the existing client's leases, e.g. because leased resources are reserved for another client.

**ALLOC\_ENGINE\_V6\_REUSE\_EXPIRED\_LEASE\_DATA %1: reusing expired lease, updated lease information: %2**

This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_REUSE\_EXPIRED\_LEASE\_DATA (1) %1: reusing expired lease, updated lease information: %2**

This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

**ALLOC\_ENGINE\_V6\_REVOKED\_ADDR\_LEASE address %1 was revoked from client %2 as it is reserved for client %3**

This informational message is an indication that the specified IPv6 address was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their addresses.

**ALLOC\_ENGINE\_V6\_REVOKED\_ADDR\_LEASE (1) address %1 was revoked from client %2 as it is reserved for client %3**

This informational message is an indication that the specified IPv6 address was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their addresses.

**ALLOC\_ENGINE\_V6\_REVOKED\_PREFIX\_LEASE Prefix %1/%2 was revoked from client %3 as it is reserved for client %4**

This informational message is an indication that the specified IPv6 prefix was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their prefixes.

**ALLOC\_ENGINE\_V6\_REVOKED\_PREFIX\_LEASE (1) Prefix %1/%2 was revoked from client %3 as it is reserved for client %4**

This informational message is an indication that the specified IPv6 prefix was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their prefixes.

## ASIODNS Module

**ASIODNS\_FD\_ADD\_TCP adding a new TCP server by opened fd %1**

A debug message informing about installing a file descriptor as a server. The file descriptor number is noted.

**ASIODNS\_FD\_ADD\_TCP (1) adding a new TCP server by opened fd %1**

A debug message informing about installing a file descriptor as a server. The file descriptor number is noted.

**ASIODNS\_FD\_ADD\_UDP adding a new UDP server by opened fd %1**

A debug message informing about installing a file descriptor as a server. The file descriptor number is noted.

**ASIODNS\_FD\_ADD\_UDP (1) adding a new UDP server by opened fd %1**

A debug message informing about installing a file descriptor as a server. The file descriptor number is noted.

**ASIODNS\_FETCH\_COMPLETED upstream fetch to %1(%2) has now completed**

A debug message, this records that the upstream fetch (a query made by the resolver on behalf of its client) to the specified address has completed.

**ASIODNS\_FETCH\_COMPLETED (1) upstream fetch to %1(%2) has now completed**

A debug message, this records that the upstream fetch (a query made by the resolver on behalf of its client) to the specified address has completed.

**ASIODNS\_FETCH\_STOPPED upstream fetch to %1(%2) has been stopped**

An external component has requested the halting of an upstream fetch. This is an allowed operation, and the message should only appear if debug is enabled.

**ASIODNS\_FETCH\_STOPPED (1) upstream fetch to %1(%2) has been stopped**

An external component has requested the halting of an upstream fetch. This is an allowed operation, and the message should only appear if debug is enabled.

**ASIODNS\_OPEN\_SOCKET error %1 opening %2 socket to %3(%4)**

The asynchronous I/O code encountered an error when trying to open a socket of the specified protocol in order to send a message to the target address. The number of the system error that caused the problem is given in the message.

**ASIODNS\_OPEN\_SOCKET (1) error %1 opening %2 socket to %3(%4)**

The asynchronous I/O code encountered an error when trying to open a socket of the specified protocol in order to send a message to the target address. The number of the system error that caused the problem is given in the message.

**ASIODNS\_READ\_DATA error %1 reading %2 data from %3(%4)**

The asynchronous I/O code encountered an error when trying to read data from the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

**ASIODNS\_READ\_DATA (1) error %1 reading %2 data from %3(%4)**

The asynchronous I/O code encountered an error when trying to read data from the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

**ASIODNS\_READ\_TIMEOUT receive timeout while waiting for data from %1(%2)**

An upstream fetch from the specified address timed out. This may happen for any number of reasons and is most probably a problem at the remote server or a problem on the network. The message will only appear if debug is enabled.

**ASIODNS\_READ\_TIMEOUT (1) receive timeout while waiting for data from %1(%2)**

An upstream fetch from the specified address timed out. This may happen for any number of reasons and is most probably a problem at the remote server or a problem on the network. The message will only appear if debug is enabled.

**ASIODNS\_SEND\_DATA error %1 sending data using %2 to %3(%4)**

The asynchronous I/O code encountered an error when trying to send data to the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

**ASIODNS\_SEND\_DATA (1) error %1 sending data using %2 to %3(%4)**

The asynchronous I/O code encountered an error when trying to send data to the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

**ASIODNS\_SYNC\_UDP\_CLOSE\_FAIL failed to close a DNS/UDP socket: %1**

This is the same to ASIODNS\_UDP\_CLOSE\_FAIL but happens on the "synchronous UDP server", mainly used for the authoritative DNS server daemon.

**ASIODNS\_SYNC\_UDP\_CLOSE\_FAIL (1) failed to close a DNS/UDP socket: %1**

This is the same to ASIODNS\_UDP\_CLOSE\_FAIL but happens on the "synchronous UDP server", mainly used for the authoritative DNS server daemon.

---

**ASIODNS\_TCP\_ACCEPT\_FAIL failed to accept TCP DNS connection: %1**

Accepting a TCP connection from a DNS client failed due to an error that could happen but should be rare. The reason for the error is included in the log message. The server still keeps accepting new connections, so unless it happens often it's probably okay to ignore this error. If the shown error indicates something like "too many open files", it's probably because the run time environment is too restrictive on this limitation, so consider adjusting the limit using a tool such as ulimit. If you see other types of errors too often, there may be something overlooked; please file a bug report in that case.

**ASIODNS\_TCP\_ACCEPT\_FAIL (1) failed to accept TCP DNS connection: %1**

Accepting a TCP connection from a DNS client failed due to an error that could happen but should be rare. The reason for the error is included in the log message. The server still keeps accepting new connections, so unless it happens often it's probably okay to ignore this error. If the shown error indicates something like "too many open files", it's probably because the run time environment is too restrictive on this limitation, so consider adjusting the limit using a tool such as ulimit. If you see other types of errors too often, there may be something overlooked; please file a bug report in that case.

**ASIODNS\_TCP\_CLEANUP\_CLOSE\_FAIL failed to close a DNS/TCP socket on port cleanup: %1**

A TCP DNS server tried to close a TCP socket (one created on accepting a new connection or is already unused) as a step of cleaning up the corresponding listening port, but it failed to do that. This is generally an unexpected event and so is logged as an error. See also the description of ASIODNS\_TCP\_CLOSE\_ACCEPTOR\_FAIL.

**ASIODNS\_TCP\_CLEANUP\_CLOSE\_FAIL (1) failed to close a DNS/TCP socket on port cleanup: %1**

A TCP DNS server tried to close a TCP socket (one created on accepting a new connection or is already unused) as a step of cleaning up the corresponding listening port, but it failed to do that. This is generally an unexpected event and so is logged as an error. See also the description of ASIODNS\_TCP\_CLOSE\_ACCEPTOR\_FAIL.

**ASIODNS\_TCP\_CLOSE\_ACCEPTOR\_FAIL failed to close listening TCP socket: %1**

A TCP DNS server tried to close a listening TCP socket (for accepting new connections) as a step of cleaning up the corresponding listening port (e.g., on server shutdown or updating port configuration), but it failed to do that. This is generally an unexpected event and so is logged as an error. See ASIODNS\_TCP\_CLOSE\_FAIL on the implication of related system resources.

**ASIODNS\_TCP\_CLOSE\_ACCEPTOR\_FAIL (1) failed to close listening TCP socket: %1**

A TCP DNS server tried to close a listening TCP socket (for accepting new connections) as a step of cleaning up the corresponding listening port (e.g., on server shutdown or updating port configuration), but it failed to do that. This is generally an unexpected event and so is logged as an error. See ASIODNS\_TCP\_CLOSE\_FAIL on the implication of related system resources.

**ASIODNS\_TCP\_CLOSE\_FAIL failed to close DNS/TCP socket with a client: %1**

A TCP DNS server tried to close a TCP socket used to communicate with a client, but it failed to do that. While closing a socket should normally be an error-free operation, there have been known cases where this happened with a "connection reset by peer" error. This might be because of some odd client behavior, such as sending a TCP RST after establishing the connection and before the server closes the socket, but how exactly this could happen seems to be system dependent (i.e., it's not part of the standard socket API), so it's difficult to provide a general explanation. In any case, it is believed that an error on closing a socket doesn't mean leaking system resources (the kernel should clean up any internal resource related to the socket, just reporting an error detected in the close call), but, again, it seems to be system dependent. This message is logged at a debug level as it's known to happen and could be triggered by a remote node and it would be better to not be too verbose, but you might want to increase the log level and make sure there's no resource leak or other system level troubles when it's logged.

**ASIODNS\_TCP\_CLOSE\_FAIL (1) failed to close DNS/TCP socket with a client: %1**

A TCP DNS server tried to close a TCP socket used to communicate with a client, but it failed to do that. While closing a socket should normally be an error-free operation, there have been known cases where this happened with a "connection reset by peer" error. This might be because of some odd client behavior, such as sending a TCP RST after establishing the connection and before the server closes the socket, but how exactly this could happen seems to be system dependent (i.e., it's not part of the standard socket API), so it's difficult to provide a general explanation. In any case, it is believed that an error on closing a socket doesn't mean leaking system resources (the kernel should clean up any internal resource related to the socket, just reporting an error detected in the close call), but, again, it seems to be system dependent. This message is logged at a debug level as it's known to happen and could be triggered by a remote node and it would be better to not be too verbose, but you might want to increase the log level and make sure there's no resource leak or other system level troubles when it's logged.

**ASIODNS\_TCP\_CLOSE\_NORESP\_FAIL failed to close DNS/TCP socket with a client: %1**

A TCP DNS server tried to close a TCP socket used to communicate with a client without returning an answer (which normally happens for zone transfer requests), but it failed to do that. See `ASIODNS_TCP_CLOSE_FAIL` for more details.

**ASIODNS\_TCP\_CLOSE\_NORESP\_FAIL (1) failed to close DNS/TCP socket with a client: %1**

A TCP DNS server tried to close a TCP socket used to communicate with a client without returning an answer (which normally happens for zone transfer requests), but it failed to do that. See `ASIODNS_TCP_CLOSE_FAIL` for more details.

**ASIODNS\_TCP\_GETREMOTE\_FAIL failed to get remote address of a DNS TCP connection: %1**

A TCP DNS server tried to get the address and port of a remote client on a connected socket but failed. It's expected to be rare but can still happen. See also `ASIODNS_TCP_READLEN_FAIL`.

**ASIODNS\_TCP\_GETREMOTE\_FAIL (1) failed to get remote address of a DNS TCP connection: %1**

A TCP DNS server tried to get the address and port of a remote client on a connected socket but failed. It's expected to be rare but can still happen. See also `ASIODNS_TCP_READLEN_FAIL`.

**ASIODNS\_TCP\_READDATA\_FAIL failed to get DNS data on a TCP socket: %1**

A TCP DNS server tried to read a DNS message (that follows a 2-byte length field) but failed. It's expected to be rare but can still happen. See also `ASIODNS_TCP_READLEN_FAIL`.

**ASIODNS\_TCP\_READDATA\_FAIL (1) failed to get DNS data on a TCP socket: %1**

A TCP DNS server tried to read a DNS message (that follows a 2-byte length field) but failed. It's expected to be rare but can still happen. See also `ASIODNS_TCP_READLEN_FAIL`.

**ASIODNS\_TCP\_READLEN\_FAIL failed to get DNS data length on a TCP socket: %1**

A TCP DNS server tried to get the length field of a DNS message (the first 2 bytes of a new chunk of data) but failed. This is generally expected to be rare but can still happen, e.g, due to an unexpected reset of the connection. A specific reason for the failure is included in the log message.

**ASIODNS\_TCP\_READLEN\_FAIL (1) failed to get DNS data length on a TCP socket: %1**

A TCP DNS server tried to get the length field of a DNS message (the first 2 bytes of a new chunk of data) but failed. This is generally expected to be rare but can still happen, e.g, due to an unexpected reset of the connection. A specific reason for the failure is included in the log message.

**ASIODNS\_TCP\_WRITE\_FAIL failed to send DNS message over a TCP socket: %1**

A TCP DNS server tried to send a DNS message to a remote client but failed. It's expected to be rare but can still happen. See also `ASIODNS_TCP_READLEN_FAIL`.

**ASIODNS\_TCP\_WRITE\_FAIL (1) failed to send DNS message over a TCP socket: %1**

A TCP DNS server tried to send a DNS message to a remote client but failed. It's expected to be rare but can still happen. See also `ASIODNS_TCP_READLEN_FAIL`.

**ASIODNS\_UDP\_ASYNC\_SEND\_FAIL Error sending UDP packet to %1: %2**

The low-level ASIO library reported an error when trying to send a UDP packet in asynchronous UDP mode. This can be any error reported by `send_to()`, and can indicate problems such as too high a load on the network, or a problem in the underlying library or system. This packet is dropped and will not be sent, but service should resume normally. If you see a single occurrence of this message, it probably does not indicate any significant problem, but if it is logged often, it is probably a good idea to inspect your network traffic.

**ASIODNS\_UDP\_ASYNC\_SEND\_FAIL (1) Error sending UDP packet to %1: %2**

The low-level ASIO library reported an error when trying to send a UDP packet in asynchronous UDP mode. This can be any error reported by `send_to()`, and can indicate problems such as too high a load on the network, or a problem in the underlying library or system. This packet is dropped and will not be sent, but service should resume normally. If you see a single occurrence of this message, it probably does not indicate any significant problem, but if it is logged often, it is probably a good idea to inspect your network traffic.

**ASIODNS\_UDP\_CLOSE\_FAIL failed to close a DNS/UDP socket: %1**

A UDP DNS server tried to close its UDP socket, but failed to do that. This is generally an unexpected event and so is logged as an error.

**ASIODNS\_UDP\_CLOSE\_FAIL (1) failed to close a DNS/UDP socket: %1**

A UDP DNS server tried to close its UDP socket, but failed to do that. This is generally an unexpected event and so is logged as an error.

**ASIODNS\_UDP\_RECEIVE\_FAIL failed to receive UDP DNS packet: %1**

Receiving a UDP packet from a DNS client failed due to an error that could happen but should be very rare. The server still keeps receiving UDP packets on this socket. The reason for the error is included in the log message. This log message is basically not expected to appear at all in practice; if it does, there may be some system level failure and other system logs may have to be checked.

**ASIODNS\_UDP\_RECEIVE\_FAIL (1) failed to receive UDP DNS packet: %1**

Receiving a UDP packet from a DNS client failed due to an error that could happen but should be very rare. The server still keeps receiving UDP packets on this socket. The reason for the error is included in the log message. This log message is basically not expected to appear at all in practice; if it does, there may be some system level failure and other system logs may have to be checked.

**ASIODNS\_UDP\_SYNC\_RECEIVE\_FAIL failed to receive UDP DNS packet: %1**

This is the same to ASIODNS\_UDP\_RECEIVE\_FAIL but happens on the "synchronous UDP server", mainly used for the authoritative DNS server daemon.

**ASIODNS\_UDP\_SYNC\_RECEIVE\_FAIL (1) failed to receive UDP DNS packet: %1**

This is the same to ASIODNS\_UDP\_RECEIVE\_FAIL but happens on the "synchronous UDP server", mainly used for the authoritative DNS server daemon.

**ASIODNS\_UDP\_SYNC\_SEND\_FAIL Error sending UDP packet to %1: %2**

The low-level ASIO library reported an error when trying to send a UDP packet in synchronous UDP mode. See ASIODNS\_UDP\_ASYNC\_SEND\_FAIL for more information.

**ASIODNS\_UDP\_SYNC\_SEND\_FAIL (1) Error sending UDP packet to %1: %2**

The low-level ASIO library reported an error when trying to send a UDP packet in synchronous UDP mode. See ASIODNS\_UDP\_ASYNC\_SEND\_FAIL for more information.

**ASIODNS\_UNKNOWN\_ORIGIN unknown origin for ASIO error code %1 (protocol: %2, address %3)**

An internal consistency check on the origin of a message from the asynchronous I/O module failed. This may indicate an internal error; please submit a bug report.

**ASIODNS\_UNKNOWN\_ORIGIN (1) unknown origin for ASIO error code %1 (protocol: %2, address %3)**

An internal consistency check on the origin of a message from the asynchronous I/O module failed. This may indicate an internal error; please submit a bug report.

**ASIODNS\_UNKNOWN\_RESULT unknown result (%1) when IOFetch::stop() was executed for I/O to %2(%3)**

An internal error indicating that the termination method of the resolver's upstream fetch class was called with an unknown result code (which is given in the message). Please submit a bug report.

**ASIODNS\_UNKNOWN\_RESULT (1) unknown result (%1) when IOFetch::stop() was executed for I/O to %2(%3)**

An internal error indicating that the termination method of the resolver's upstream fetch class was called with an unknown result code (which is given in the message). Please submit a bug report.

## COMMAND Module

**COMMAND\_ACCEPTOR\_START Starting to accept connections via unix domain socket bound to %1**

This informational message is issued when the Kea server starts an acceptor via which it is going to accept new control connections. The acceptor is bound to the endpoint associated with the filename provided as an argument. If starting the acceptor fails, subsequent error messages will provide a reason for failure.

**COMMAND\_ACCEPTOR\_START (1) Starting to accept connections via unix domain socket bound to %1**

This informational message is issued when the Kea server starts an acceptor via which it is going to accept new control connections. The acceptor is bound to the endpoint associated with the filename provided as an argument. If starting the acceptor fails, subsequent error messages will provide a reason for failure.

---

**COMMAND\_DEREGISTERED Command %1 deregistered**

This debug message indicates that the daemon stopped supporting specified command. This command can no longer be issued. If the command socket is open and this command is issued, the daemon will not be able to process it.

**COMMAND\_DEREGISTERED (1) Command %1 deregistered**

This debug message indicates that the daemon stopped supporting specified command. This command can no longer be issued. If the command socket is open and this command is issued, the daemon will not be able to process it.

**COMMAND\_EXTENDED\_REGISTERED Command %1 registered**

This debug message indicates that the daemon started supporting specified command. The handler for the registered command includes a parameter holding entire command to be processed.

**COMMAND\_EXTENDED\_REGISTERED (1) Command %1 registered**

This debug message indicates that the daemon started supporting specified command. The handler for the registered command includes a parameter holding entire command to be processed.

**COMMAND\_PROCESS\_ERROR1 Error while processing command: %1**

This warning message indicates that the server encountered an error while processing received command. Additional information will be provided, if available. Additional log messages may provide more details.

**COMMAND\_PROCESS\_ERROR1 (1) Error while processing command: %1**

This warning message indicates that the server encountered an error while processing received command. Additional information will be provided, if available. Additional log messages may provide more details.

**COMMAND\_PROCESS\_ERROR2 Error while processing command: %1**

This warning message indicates that the server encountered an error while processing received command. The difference, compared to COMMAND\_PROCESS\_ERROR1 is that the initial command was well formed and the error occurred during logic processing, not the command parsing. Additional information will be provided, if available. Additional log messages may provide more details.

**COMMAND\_PROCESS\_ERROR2 (1) Error while processing command: %1**

This warning message indicates that the server encountered an error while processing received command. The difference, compared to COMMAND\_PROCESS\_ERROR1 is that the initial command was well formed and the error occurred during logic processing, not the command parsing. Additional information will be provided, if available. Additional log messages may provide more details.

**COMMAND\_RECEIVED Received command '%1'**

This informational message indicates that a command was received over command socket. The nature of this command and its possible results will be logged with separate messages.

**COMMAND\_RECEIVED (1) Received command '%1'**

This informational message indicates that a command was received over command socket. The nature of this command and its possible results will be logged with separate messages.

**COMMAND\_REGISTERED Command %1 registered**

This debug message indicates that the daemon started supporting specified command. If the command socket is open, this command can now be issued.

**COMMAND\_REGISTERED (1) Command %1 registered**

This debug message indicates that the daemon started supporting specified command. If the command socket is open, this command can now be issued.

**COMMAND\_RESPONSE\_ERROR Server failed to generate response for command: %1**

This error message indicates that the server failed to generate response for specified command. This likely indicates a server logic error, as the server is expected to generate valid responses for all commands, even malformed ones.

**COMMAND\_RESPONSE\_ERROR (1) Server failed to generate response for command: %1**

This error message indicates that the server failed to generate response for specified command. This likely indicates a server logic error, as the server is expected to generate valid responses for all commands, even malformed ones.

**COMMAND\_SOCKET\_ACCEPT\_FAIL Failed to accept incoming connection on command socket %1: %2**

This error indicates that the server detected incoming connection and executed accept system call on said socket, but this call returned an error. Additional information may be provided by the system as second parameter.

**COMMAND\_SOCKET\_ACCEPT\_FAIL (1) Failed to accept incoming connection on command socket %1: %2**

This error indicates that the server detected incoming connection and executed accept system call on said socket, but this call returned an error. Additional information may be provided by the system as second parameter.

**COMMAND\_SOCKET\_CLOSED\_BY\_FOREIGN\_HOST Closed command socket %1 by foreign host, %2**

This is an information message indicating that the command connection has been closed by a command control client, and whether or not any partially read data was discarded.

**COMMAND\_SOCKET\_CLOSED\_BY\_FOREIGN\_HOST (1) Closed command socket %1 by foreign host, %2**

This is an information message indicating that the command connection has been closed by a command control client, and whether or not any partially read data was discarded.

**COMMAND\_SOCKET\_CONNECTION\_CANCEL\_FAIL Failed to cancel read operation on socket %1: %2**

This error message is issued to indicate an error to cancel asynchronous read of the control command over the control socket. The cancel operation is performed when the timeout occurs during communication with a client. The error message includes details about the reason for failure.

**COMMAND\_SOCKET\_CONNECTION\_CANCEL\_FAIL (1) Failed to cancel read operation on socket %1: %2**

This error message is issued to indicate an error to cancel asynchronous read of the control command over the control socket. The cancel operation is performed when the timeout occurs during communication with a client. The error message includes details about the reason for failure.

**COMMAND\_SOCKET\_CONNECTION\_CLOSED Closed socket %1 for existing command connection**

This is a debug message indicating that the socket created for handling client's connection is closed. This usually means that the client disconnected, but may also mean a timeout.

**COMMAND\_SOCKET\_CONNECTION\_CLOSED (1) Closed socket %1 for existing command connection**

This is a debug message indicating that the socket created for handling client's connection is closed. This usually means that the client disconnected, but may also mean a timeout.

**COMMAND\_SOCKET\_CONNECTION\_CLOSE\_FAIL Failed to close command connection: %1**

This error message is issued when an error occurred when closing a command connection and/or removing it from the connections pool. The detailed error is provided as an argument.

**COMMAND\_SOCKET\_CONNECTION\_CLOSE\_FAIL (1) Failed to close command connection: %1**

This error message is issued when an error occurred when closing a command connection and/or removing it from the connections pool. The detailed error is provided as an argument.

**COMMAND\_SOCKET\_CONNECTION\_OPENED Opened socket %1 for incoming command connection**

This is a debug message indicating that a new incoming command connection was detected and a dedicated socket was opened for that connection.

**COMMAND\_SOCKET\_CONNECTION\_OPENED (1) Opened socket %1 for incoming command connection**

This is a debug message indicating that a new incoming command connection was detected and a dedicated socket was opened for that connection.

**COMMAND\_SOCKET\_CONNECTION\_SHUTDOWN\_FAIL Encountered error %1 while trying to gracefully shutdown socket**

This message indicates an error while trying to gracefully shutdown command connection. The type of the error is included in the message.

**COMMAND\_SOCKET\_CONNECTION\_SHUTDOWN\_FAIL (1) Encountered error %1 while trying to gracefully shutdown socket**

This message indicates an error while trying to gracefully shutdown command connection. The type of the error is included in the message.

**COMMAND\_SOCKET\_CONNECTION\_TIMEOUT Timeout occurred for connection over socket %1**

This is an informational message that indicates that the timeout has occurred for one of the command channel connections. The response sent by the server indicates a timeout and is then closed.

**COMMAND\_SOCKET\_CONNECTION\_TIMEOUT (1) Timeout occurred for connection over socket %1**

This is an informational message that indicates that the timeout has occurred for one of the command channel connections. The response sent by the server indicates a timeout and is then closed.

---

**COMMAND\_SOCKET\_READ Received %1 bytes over command socket %2**

This debug message indicates that specified number of bytes was received over command socket identified by specified file descriptor.

**COMMAND\_SOCKET\_READ (1) Received %1 bytes over command socket %2**

This debug message indicates that specified number of bytes was received over command socket identified by specified file descriptor.

**COMMAND\_SOCKET\_READ\_FAIL Encountered error %1 while reading from command socket %2**

This error message indicates that an error was encountered while reading from command socket.

**COMMAND\_SOCKET\_READ\_FAIL (1) Encountered error %1 while reading from command socket %2**

This error message indicates that an error was encountered while reading from command socket.

**COMMAND\_SOCKET\_WRITE Sent response of %1 bytes (%2 bytes left to send) over command socket %3**

This debug message indicates that the specified number of bytes was sent over command socket identifier by the specified file descriptor.

**COMMAND\_SOCKET\_WRITE (1) Sent response of %1 bytes (%2 bytes left to send) over command socket %3**

This debug message indicates that the specified number of bytes was sent over command socket identifier by the specified file descriptor.

**COMMAND\_SOCKET\_WRITE\_FAIL Error while writing to command socket %1 : %2**

This error message indicates that an error was encountered while attempting to send a response to the command socket.

**COMMAND\_SOCKET\_WRITE\_FAIL (1) Error while writing to command socket %1 : %2**

This error message indicates that an error was encountered while attempting to send a response to the command socket.

**COMMAND\_WATCH\_SOCKET\_CLEAR\_ERROR watch socket failed to clear: %1**

This error message is issued when the command manager was unable to reset the ready status after completing a send. This is a programmatic error that should be reported. The command manager may or may not continue to operate correctly.

**COMMAND\_WATCH\_SOCKET\_CLEAR\_ERROR (1) watch socket failed to clear: %1**

This error message is issued when the command manager was unable to reset the ready status after completing a send. This is a programmatic error that should be reported. The command manager may or may not continue to operate correctly.

**COMMAND\_WATCH\_SOCKET\_CLOSE\_ERROR watch socket failed to close: %1**

This error message is issued when command manager attempted to close the socket used for indicating the ready status for send operations. This should not have any negative impact on the operation of the command manager as it happens when the connection is being terminated.

**COMMAND\_WATCH\_SOCKET\_CLOSE\_ERROR (1) watch socket failed to close: %1**

This error message is issued when command manager attempted to close the socket used for indicating the ready status for send operations. This should not have any negative impact on the operation of the command manager as it happens when the connection is being terminated.

**COMMAND\_WATCH\_SOCKET\_MARK\_READY\_ERROR watch socket failed to mark ready: %1**

This error message is issued when the command manager was unable to set ready status after scheduling asynchronous send. This is programmatic error that should be reported. The command manager may or may not continue to operate correctly.

**COMMAND\_WATCH\_SOCKET\_MARK\_READY\_ERROR (1) watch socket failed to mark ready: %1**

This error message is issued when the command manager was unable to set ready status after scheduling asynchronous send. This is programmatic error that should be reported. The command manager may or may not continue to operate correctly.

## CTRL Module

---



**CTRL\_AGENT\_COMMAND\_FORWARDED command %1 successfully forwarded to the service %2**

This informational message is issued when the CA successfully forwards the control message to the specified Kea service and receives a response.

**CTRL\_AGENT\_COMMAND\_FORWARDED (1) command %1 successfully forwarded to the service %2**

This informational message is issued when the CA successfully forwards the control message to the specified Kea service and receives a response.

**CTRL\_AGENT\_COMMAND\_FORWARD\_BEGIN begin forwarding command %1 to service %2**

This debug message is issued when the Control Agent starts forwarding a received command to one of the Kea servers.

**CTRL\_AGENT\_COMMAND\_FORWARD\_BEGIN (1) begin forwarding command %1 to service %2**

This debug message is issued when the Control Agent starts forwarding a received command to one of the Kea servers.

**CTRL\_AGENT\_COMMAND\_FORWARD\_FAILED failed forwarding command %1: %2**

This debug message is issued when the Control Agent failed forwarding a received command to one of the Kea servers. The second argument provides the details of the error.

**CTRL\_AGENT\_COMMAND\_FORWARD\_FAILED (1) failed forwarding command %1: %2**

This debug message is issued when the Control Agent failed forwarding a received command to one of the Kea servers. The second argument provides the details of the error.

**CTRL\_AGENT\_CONFIG\_CHECK\_FAIL Control Agent configuration check failed: %1**

This error message indicates that the CA had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**CTRL\_AGENT\_CONFIG\_CHECK\_FAIL (1) Control Agent configuration check failed: %1**

This error message indicates that the CA had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**CTRL\_AGENT\_CONFIG\_FAIL Control Agent configuration failed: %1**

This error message indicates that the CA had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**CTRL\_AGENT\_CONFIG\_FAIL (1) Control Agent configuration failed: %1**

This error message indicates that the CA had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**CTRL\_AGENT\_FAILED application experienced a fatal error: %1**

This is a fatal error message issued when the Control Agent application encounters an unrecoverable error from within the event loop.

**CTRL\_AGENT\_FAILED (1) application experienced a fatal error: %1**

This is a fatal error message issued when the Control Agent application encounters an unrecoverable error from within the event loop.

**CTRL\_AGENT\_HTTP\_SERVICE\_STARTED HTTP service bound to address %1:%2**

This informational message indicates that the server has started HTTP service on the specified address and port. All control commands should be sent to this address and port.

**CTRL\_AGENT\_HTTP\_SERVICE\_STARTED (1) HTTP service bound to address %1:%2**

This informational message indicates that the server has started HTTP service on the specified address and port. All control commands should be sent to this address and port.

**CTRL\_AGENT\_RUN\_EXIT application is exiting the event loop**

This is a debug message issued when the Control Agent exits its event loop.

**CTRL\_AGENT\_RUN\_EXIT (1) application is exiting the event loop**

This is a debug message issued when the Control Agent exits its event loop.

**CTRL\_AGENT\_STARTED Kea Control Agent version %1 started**

This informational message indicates that the Control Agent has processed all configuration information and is ready to begin processing. The version is also printed.

**CTRL\_AGENT\_STARTED (1) Kea Control Agent version %1 started**

This informational message indicates that the Control Agent has processed all configuration information and is ready to begin processing. The version is also printed.

**DATABASE Module****DATABASE\_CQL\_CONNECTION\_BEGIN\_TRANSACTION begin transaction on current connection.**

The server has issued a begin transaction call.

**DATABASE\_CQL\_CONNECTION\_BEGIN\_TRANSACTION (1) begin transaction on current connection.**

The server has issued a begin transaction call.

**DATABASE\_CQL\_CONNECTION\_COMMIT committing to Cassandra database on current connection.**

A commit call been issued on the server. For Cassandra, this is a no-op.

**DATABASE\_CQL\_CONNECTION\_COMMIT (1) committing to Cassandra database on current connection.**

A commit call been issued on the server. For Cassandra, this is a no-op.

**DATABASE\_CQL\_CONNECTION\_ROLLBACK rolling back Cassandra database on current connection.**

The code has issued a rollback call. For Cassandra, this is a no-op.

**DATABASE\_CQL\_CONNECTION\_ROLLBACK (1) rolling back Cassandra database on current connection.**

The code has issued a rollback call. For Cassandra, this is a no-op.

**DATABASE\_CQL\_DEALLOC\_ERROR An error occurred while closing the CQL connection: %1**

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing CQL database resources as part of closing its connection to the Cassandra database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

**DATABASE\_CQL\_DEALLOC\_ERROR (1) An error occurred while closing the CQL connection: %1**

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing CQL database resources as part of closing its connection to the Cassandra database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

**DATABASE\_INVALID\_ACCESS invalid database access string: %1**

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. The access string in question - which should be of the form 'keyword=value keyword=value...' is included in the message.

**DATABASE\_INVALID\_ACCESS (1) invalid database access string: %1**

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. The access string in question - which should be of the form 'keyword=value keyword=value...' is included in the message.

**DATABASE\_MYSQL\_COMMIT committing to MySQL database**

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the committal may not include a write to disk.

**DATABASE\_MYSQL\_COMMIT (1) committing to MySQL database**

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the committal may not include a write to disk.

**DATABASE\_MYSQL\_FATAL\_ERROR Unrecoverable MySQL error occurred: %1 for <%2>, reason: %3 (error code: %4).**

An error message indicating that communication with the MySQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover connectivity. If not the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the MySQL server has gone down.

**DATABASE\_MYSQL\_FATAL\_ERROR (1) Unrecoverable MySQL error occurred: %1 for <%2>, reason: %3 (error code: %4)**

An error message indicating that communication with the MySQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover connectivity. If not the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the MySQL server has gone down.

**DATABASE\_MYSQL\_ROLLBACK rolling back MySQL database**

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

**DATABASE\_MYSQL\_ROLLBACK (1) rolling back MySQL database**

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

**DATABASE\_MYSQL\_START\_TRANSACTION starting new MySQL transaction**

A debug message issued when a new MySQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

**DATABASE\_MYSQL\_START\_TRANSACTION (1) starting new MySQL transaction**

A debug message issued when a new MySQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

**DATABASE\_PGSQL\_COMMIT committing to PostgreSQL database**

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the committal may not include a write to disk.

**DATABASE\_PGSQL\_COMMIT (1) committing to PostgreSQL database**

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the committal may not include a write to disk.

**DATABASE\_PGSQL\_DEALLOC\_ERROR An error occurred deallocating SQL statements while closing the PostgreSQL lease**

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing database SQL resources as part of closing its connection to the PostgreSQL database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

**DATABASE\_PGSQL\_DEALLOC\_ERROR (1) An error occurred deallocating SQL statements while closing the PostgreSQL lease**

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing database SQL resources as part of closing its connection to the PostgreSQL database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

**DATABASE\_PGSQL\_FATAL\_ERROR Unrecoverable PostgreSQL error occurred: Statement: <%1>, reason: %2 (error code: %3)**

An error message indicating that communication with the PostgreSQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover the connectivity. If not the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the PostgreSQL server has gone down.

**DATABASE\_PGSQL\_FATAL\_ERROR (1) Unrecoverable PostgreSQL error occurred: Statement: <%1>, reason: %2 (error code: %3)**

An error message indicating that communication with the PostgreSQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover the connectivity. If not the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the PostgreSQL server has gone down.

**DATABASE\_PGSQL\_ROLLBACK rolling back PostgreSQL database**

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

---

**DATABASE\_PGSQL\_ROLLBACK (1) rolling back PostgreSQL database**

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

**DATABASE\_PGSQL\_START\_TRANSACTION starting a new PostgreSQL transaction**

A debug message issued when a new PostgreSQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

**DATABASE\_PGSQL\_START\_TRANSACTION (1) starting a new PostgreSQL transaction**

A debug message issued when a new PostgreSQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

**DATABASE\_TO\_JSON\_ERROR Internal logic error: unknown %1 element found in state: %2**

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains unrecognized parameter. This is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The unknown parameter will not be converted.

**DATABASE\_TO\_JSON\_ERROR (1) Internal logic error: unknown %1 element found in state: %2**

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains unrecognized parameter. This is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The unknown parameter will not be converted.

## DCTL Module

**DCTL\_ALREADY\_RUNNING %1 already running? %2**

This is an error message that occurs when a module encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of a module using the same configuration file. It is possible, though unlikely, that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than Kea process. In such an event, it would be necessary to manually remove the PID file. The first argument is the process name, the second contains the PID and PID file.

**DCTL\_ALREADY\_RUNNING (1) %1 already running? %2**

This is an error message that occurs when a module encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of a module using the same configuration file. It is possible, though unlikely, that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than Kea process. In such an event, it would be necessary to manually remove the PID file. The first argument is the process name, the second contains the PID and PID file.

**DCTL\_CCSESSION\_ENDING %1 ending control channel session**

This debug message is issued just before the controller attempts to disconnect from its session with the Kea control channel.

**DCTL\_CCSESSION\_ENDING (1) %1 ending control channel session**

This debug message is issued just before the controller attempts to disconnect from its session with the Kea control channel.

**DCTL\_CCSESSION\_STARTING %1 starting control channel session, specfile: %2**

This debug message is issued just before the controller attempts to establish a session with the Kea control channel.

**DCTL\_CCSESSION\_STARTING (1) %1 starting control channel session, specfile: %2**

This debug message is issued just before the controller attempts to establish a session with the Kea control channel.

**DCTL\_CFG\_FILE\_RELOAD\_ERROR configuration reload failed: %1, reverting to current configuration.**

This is an error message indicating that the application attempted to reload its configuration from file and encountered an error. This is likely due to invalid content in the configuration file. The application should continue to operate under its current configuration.

**DCTL\_CFG\_FILE\_RELOAD\_ERROR (1) configuration reload failed: %1, reverting to current configuration.**

This is an error message indicating that the application attempted to reload its configuration from file and encountered an error. This is likely due to invalid content in the configuration file. The application should continue to operate under its current configuration.

**DCTL\_CFG\_FILE\_RELOAD\_SIGNAL\_RECVD OS signal %1 received, reloading configuration from file: %2**

This is an informational message indicating the application has received a signal instructing it to reload its configuration from file.

**DCTL\_CFG\_FILE\_RELOAD\_SIGNAL\_RECVD (1) OS signal %1 received, reloading configuration from file: %2**

This is an informational message indicating the application has received a signal instructing it to reload its configuration from file.

**DCTL\_COMMAND\_RECEIVED %1 received command: %2, arguments: %3**

A debug message listing the command (and possible arguments) received from the Kea control system by the controller.

**DCTL\_COMMAND\_RECEIVED (1) %1 received command: %2, arguments: %3**

A debug message listing the command (and possible arguments) received from the Kea control system by the controller.

**DCTL\_CONFIG\_CHECK\_COMPLETE server has completed configuration check: %1, result: %2**

This is an informational message announcing the successful processing of a new configuration check is complete. The result of that check is printed. This informational message is printed when configuration check is requested.

**DCTL\_CONFIG\_CHECK\_COMPLETE (1) server has completed configuration check: %1, result: %2**

This is an informational message announcing the successful processing of a new configuration check is complete. The result of that check is printed. This informational message is printed when configuration check is requested.

**DCTL\_CONFIG\_COMPLETE server has completed configuration: %1**

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

**DCTL\_CONFIG\_COMPLETE (1) server has completed configuration: %1**

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

**DCTL\_CONFIG\_FILE\_LOAD\_FAIL %1 reason: %2**

This fatal error message indicates that the application attempted to load its initial configuration from file and has failed. The service will exit.

**DCTL\_CONFIG\_FILE\_LOAD\_FAIL (1) %1 reason: %2**

This fatal error message indicates that the application attempted to load its initial configuration from file and has failed. The service will exit.

**DCTL\_CONFIG\_LOAD\_FAIL %1 configuration failed to load: %2**

This critical error message indicates that the initial application configuration has failed. The service will start, but will not process requests until the configuration has been corrected.

**DCTL\_CONFIG\_LOAD\_FAIL (1) %1 configuration failed to load: %2**

This critical error message indicates that the initial application configuration has failed. The service will start, but will not process requests until the configuration has been corrected.

**DCTL\_CONFIG\_START parsing new configuration: %1**

A debug message indicating that the application process has received an updated configuration and has passed it to its configuration manager for parsing.

**DCTL\_CONFIG\_START (1) parsing new configuration: %1**

A debug message indicating that the application process has received an updated configuration and has passed it to its configuration manager for parsing.

**DCTL\_CONFIG\_STUB %1 configuration stub handler called**

This debug message is issued when the dummy handler for configuration events is called. This only happens during initial startup.

**DCTL\_CONFIG\_STUB (1) %1 configuration stub handler called**

This debug message is issued when the dummy handler for configuration events is called. This only happens during initial startup.

**DCTL\_CONFIG\_UPDATE %1 updated configuration received: %2**

A debug message indicating that the controller has received an updated configuration from the Kea configuration system.

**DCTL\_CONFIG\_UPDATE (1) %1 updated configuration received: %2**

A debug message indicating that the controller has received an updated configuration from the Kea configuration system.

**DCTL\_INIT\_PROCESS %1 initializing the application**

This debug message is issued just before the controller attempts to create and initialize its application instance.

**DCTL\_INIT\_PROCESS (1) %1 initializing the application**

This debug message is issued just before the controller attempts to create and initialize its application instance.

**DCTL\_INIT\_PROCESS\_FAIL %1 application initialization failed: %2**

This error message is issued if the controller could not initialize the application and will exit.

**DCTL\_INIT\_PROCESS\_FAIL (1) %1 application initialization failed: %2**

This error message is issued if the controller could not initialize the application and will exit.

**DCTL\_NOT\_RUNNING %1 application instance is not running**

A warning message is issued when an attempt is made to shut down the application when it is not running.

**DCTL\_NOT\_RUNNING (1) %1 application instance is not running**

A warning message is issued when an attempt is made to shut down the application when it is not running.

**DCTL\_PARSER\_FAIL : %1**

On receipt of a new configuration, the server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

**DCTL\_PARSER\_FAIL (1) : %1**

On receipt of a new configuration, the server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

**DCTL\_PID\_FILE\_ERROR %1 could not create a PID file: %2**

This is an error message that occurs when the server is unable to create its PID file. The log message should contain details sufficient to determine the underlying cause. The most likely culprits are that some portion of the pathname does not exist or a permissions issue. The default path is determined by `--localstatedir` configure parameter but may be overridden by setting environment variable, `KEA_PIDFILE_DIR`. The first argument is the process name.

**DCTL\_PID\_FILE\_ERROR (1) %1 could not create a PID file: %2**

This is an error message that occurs when the server is unable to create its PID file. The log message should contain details sufficient to determine the underlying cause. The most likely culprits are that some portion of the pathname does not exist or a permissions issue. The default path is determined by `--localstatedir` configure parameter but may be overridden by setting environment variable, `KEA_PIDFILE_DIR`. The first argument is the process name.

**DCTL\_PROCESS\_FAILED %1 application execution failed: %2**

The controller has encountered a fatal error while running the application and is terminating. The reason for the failure is included in the message.

**DCTL\_PROCESS\_FAILED (1) %1 application execution failed: %2**

The controller has encountered a fatal error while running the application and is terminating. The reason for the failure is included in the message.

**DCTL\_RUN\_PROCESS %1 starting application event loop**

This debug message is issued just before the controller invokes the application run method.

**DCTL\_RUN\_PROCESS (1) %1 starting application event loop**

This debug message is issued just before the controller invokes the application run method.

---

**DCTL\_SESSION\_FAIL %1 controller failed to establish Kea session: %1**

The controller has failed to establish communication with the rest of Kea and will exit.

**DCTL\_SESSION\_FAIL (1) %1 controller failed to establish Kea session: %1**

The controller has failed to establish communication with the rest of Kea and will exit.

**DCTL\_SHUTDOWN %1 has shut down, pid: %2, version: %3**

This is an informational message indicating that the service has shut down. The argument specifies a name of the service.

**DCTL\_SHUTDOWN (1) %1 has shut down, pid: %2, version: %3**

This is an informational message indicating that the service has shut down. The argument specifies a name of the service.

**DCTL\_SHUTDOWN\_SIGNAL\_RECVD OS signal %1 received, starting shutdown**

This is a debug message indicating the application has received a signal instructing it to shutdown.

**DCTL\_SHUTDOWN\_SIGNAL\_RECVD (1) OS signal %1 received, starting shutdown**

This is a debug message indicating the application has received a signal instructing it to shutdown.

**DCTL\_SIGNAL\_ERROR signal handler for signal %1, threw an unexpected exception: %2**

This is an error message indicating that the application encountered an unexpected error after receiving a signal. This is a programmatic error and should be reported. While The application will likely continue to operating, it may be unable to respond correctly to signals.

**DCTL\_SIGNAL\_ERROR (1) signal handler for signal %1, threw an unexpected exception: %2**

This is an error message indicating that the application encountered an unexpected error after receiving a signal. This is a programmatic error and should be reported. While The application will likely continue to operating, it may be unable to respond correctly to signals.

**DCTL\_STANDALONE %1 skipping message queue, running standalone**

This is a debug message indicating that the controller is running in the application in standalone mode. This means it will not connected to the Kea message queue. Standalone mode is only useful during program development, and should not be used in a production environment.

**DCTL\_STANDALONE (1) %1 skipping message queue, running standalone**

This is a debug message indicating that the controller is running in the application in standalone mode. This means it will not connected to the Kea message queue. Standalone mode is only useful during program development, and should not be used in a production environment.

**DCTL\_STARTING %1 starting, pid: %2, version: %3**

This is an informational message issued when controller for the service first starts. Version is also reported.

**DCTL\_STARTING (1) %1 starting, pid: %2, version: %3**

This is an informational message issued when controller for the service first starts. Version is also reported.

**DCTL\_UNSUPPORTED\_SIGNAL ignoring reception of unsupported signal: %1**

This is a debug message indicating that the application received an unsupported signal. This is a programming error indicating that the application has registered to receive the signal but no associated processing logic has been added.

**DCTL\_UNSUPPORTED\_SIGNAL (1) ignoring reception of unsupported signal: %1**

This is a debug message indicating that the application received an unsupported signal. This is a programming error indicating that the application has registered to receive the signal but no associated processing logic has been added.

## DHCP4 Module

**DHCP4\_ACTIVATE\_INTERFACE activating interface %1**

This message is printed when DHCPv4 server enabled an interface to be used to receive DHCPv4 traffic. IPv4 socket on this interface will be opened once Interface Manager starts up procedure of opening sockets.

**DHCP4\_ACTIVATE\_INTERFACE (1) activating interface %1**

This message is printed when DHCPv4 server enabled an interface to be used to receive DHCPv4 traffic. IPv4 socket on this interface will be opened once Interface Manager starts up procedure of opening sockets.

**DHCP4\_ALREADY\_RUNNING %1 already running? %2**

This is an error message that occurs when the DHCPv4 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv4 process name, the second contains the PID and PID file.

**DHCP4\_ALREADY\_RUNNING (1) %1 already running? %2**

This is an error message that occurs when the DHCPv4 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv4 process name, the second contains the PID and PID file.

**DHCP4\_BUFFER\_RECEIVED received buffer from %1:%2 to %3:%4 over interface %5**

This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination IPv4 addresses/ports.

**DHCP4\_BUFFER\_RECEIVED (1) received buffer from %1:%2 to %3:%4 over interface %5**

This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination IPv4 addresses/ports.

**DHCP4\_BUFFER\_RECEIVE\_FAIL error on attempt to receive packet: %1**

The DHCPv4 server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

**DHCP4\_BUFFER\_RECEIVE\_FAIL (1) error on attempt to receive packet: %1**

The DHCPv4 server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

**DHCP4\_BUFFER\_UNPACK parsing buffer received from %1 to %2 over interface %3**

This debug message is issued when the server starts parsing the received buffer holding the DHCPv4 message. The arguments specify the source and destination IPv4 addresses as well as the interface over which the buffer has been received.

**DHCP4\_BUFFER\_UNPACK (1) parsing buffer received from %1 to %2 over interface %3**

This debug message is issued when the server starts parsing the received buffer holding the DHCPv4 message. The arguments specify the source and destination IPv4 addresses as well as the interface over which the buffer has been received.

**DHCP4\_BUFFER\_WAIT\_SIGNAL signal received while waiting for next packet, next waiting signal is %1**

This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets. The argument specifies the next signal to be handled by the server.

**DHCP4\_BUFFER\_WAIT\_SIGNAL (1) signal received while waiting for next packet, next waiting signal is %1**

This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets. The argument specifies the next signal to be handled by the server.

**DHCP4\_CLASS\_ASSIGNED %1: client packet has been assigned to the following class(es): %2**

This debug message informs that incoming packet has been assigned to specified class or classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.



**DHCP4\_CLASS\_ASSIGNED (1) %1: client packet has been assigned to the following class(es): %2**

This debug message informs that incoming packet has been assigned to specified class or classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

**DHCP4\_CLASS\_UNCONFIGURED %1: client packet belongs to an unconfigured class: %2**

This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

**DHCP4\_CLASS\_UNCONFIGURED (1) %1: client packet belongs to an unconfigured class: %2**

This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

**DHCP4\_CLASS\_UNDEFINED required class %1 has no definition**

This debug message informs that a class is listed for required evaluation but has no definition.

**DHCP4\_CLASS\_UNDEFINED (1) required class %1 has no definition**

This debug message informs that a class is listed for required evaluation but has no definition.

**DHCP4\_CLASS\_UNTESTABLE required class %1 has no test expression**

This debug message informs that a class was listed for required evaluation but its definition does not include a test expression to evaluate.

**DHCP4\_CLASS\_UNTESTABLE (1) required class %1 has no test expression**

This debug message informs that a class was listed for required evaluation but its definition does not include a test expression to evaluate.

**DHCP4\_CLIENTID\_IGNORED\_FOR\_LEASES %1: not using client identifier for lease allocation for subnet %2**

This debug message is issued when the server is processing the DHCPv4 message for which client identifier will not be used when allocating new lease or renewing existing lease. The server is explicitly configured to not use client identifier to lookup existing leases for the client and will not record client identifier in the lease database. This mode of operation is useful when clients don't use stable client identifiers, e.g. multi stage booting. The first argument includes the client and transaction identification information. The second argument specifies the identifier of the subnet where the client is connected and for which this mode of operation is configured on the server.

**DHCP4\_CLIENTID\_IGNORED\_FOR\_LEASES (1) %1: not using client identifier for lease allocation for subnet %2**

This debug message is issued when the server is processing the DHCPv4 message for which client identifier will not be used when allocating new lease or renewing existing lease. The server is explicitly configured to not use client identifier to lookup existing leases for the client and will not record client identifier in the lease database. This mode of operation is useful when clients don't use stable client identifiers, e.g. multi stage booting. The first argument includes the client and transaction identification information. The second argument specifies the identifier of the subnet where the client is connected and for which this mode of operation is configured on the server.

**DHCP4\_CLIENT\_FQDN\_DATA %1: Client sent FQDN option: %2**

This debug message includes the detailed information extracted from the Client FQDN option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the detailed information about the FQDN option received by the server.

**DHCP4\_CLIENT\_FQDN\_DATA (1) %1: Client sent FQDN option: %2**

This debug message includes the detailed information extracted from the Client FQDN option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the detailed information about the FQDN option received by the server.

**DHCP4\_CLIENT\_FQDN\_PROCESS %1: processing Client FQDN option**

This debug message is issued when the server starts processing the Client FQDN option sent in the client's query. The argument includes the client and transaction identification information.

**DHCP4\_CLIENT\_FQDN\_PROCESS (1) %1: processing Client FQDN option**

This debug message is issued when the server starts processing the Client FQDN option sent in the client's query. The argument includes the client and transaction identification information.

**DHCP4\_CLIENT\_HOSTNAME\_DATA %1: client sent Hostname option: %2**

This debug message includes the detailed information extracted from the Hostname option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the hostname carried in the Hostname option sent by the client.

**DHCP4\_CLIENT\_HOSTNAME\_DATA (1) %1: client sent Hostname option: %2**

This debug message includes the detailed information extracted from the Hostname option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the hostname carried in the Hostname option sent by the client.

**DHCP4\_CLIENT\_HOSTNAME\_PROCESS %1: processing client's Hostname option**

This debug message is issued when the server starts processing the Hostname option sent in the client's query. The argument includes the client and transaction identification information.

**DHCP4\_CLIENT\_HOSTNAME\_PROCESS (1) %1: processing client's Hostname option**

This debug message is issued when the server starts processing the Hostname option sent in the client's query. The argument includes the client and transaction identification information.

**DHCP4\_CLIENT\_NAME\_PROC\_FAIL %1: failed to process the fqdn or hostname sent by a client: %2**

This debug message is issued when the DHCP server was unable to process the FQDN or Hostname option sent by a client. This is likely because the client's name was malformed or due to internal server error. The first argument contains the client and transaction identification information. The second argument holds the detailed description of the error.

**DHCP4\_CLIENT\_NAME\_PROC\_FAIL (1) %1: failed to process the fqdn or hostname sent by a client: %2**

This debug message is issued when the DHCP server was unable to process the FQDN or Hostname option sent by a client. This is likely because the client's name was malformed or due to internal server error. The first argument contains the client and transaction identification information. The second argument holds the detailed description of the error.

**DHCP4\_COMMAND\_RECEIVED received command %1, arguments: %2**

A debug message listing the command (and possible arguments) received from the Kea control system by the DHCPv4 server.

**DHCP4\_COMMAND\_RECEIVED (1) received command %1, arguments: %2**

A debug message listing the command (and possible arguments) received from the Kea control system by the DHCPv4 server.

**DHCP4\_CONFIG\_COMPLETE DHCPv4 server has completed configuration: %1**

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

**DHCP4\_CONFIG\_COMPLETE (1) DHCPv4 server has completed configuration: %1**

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

**DHCP4\_CONFIG\_LOAD\_FAIL configuration error using file: %1, reason: %2**

This error message indicates that the DHCPv4 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

**DHCP4\_CONFIG\_LOAD\_FAIL (1) configuration error using file: %1, reason: %2**

This error message indicates that the DHCPv4 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

**DHCP4\_CONFIG\_NEW\_SUBNET a new subnet has been added to configuration: %1**

This is an informational message reporting that the configuration has been extended to include the specified IPv4 subnet.

**DHCP4\_CONFIG\_NEW\_SUBNET (1) a new subnet has been added to configuration: %1**

This is an informational message reporting that the configuration has been extended to include the specified IPv4 subnet.

**DHCP4\_CONFIG\_OPTION\_DUPLICATE multiple options with the code %1 added to the subnet %2**

This warning message is issued on an attempt to configure multiple options with the same option code for a particular subnet. Adding multiple options is uncommon for DHCPv4, but is not prohibited.

**DHCP4\_CONFIG\_OPTION\_DUPLICATE (1) multiple options with the code %1 added to the subnet %2**

This warning message is issued on an attempt to configure multiple options with the same option code for a particular subnet. Adding multiple options is uncommon for DHCPv4, but is not prohibited.

**DHCP4\_CONFIG\_PACKET\_QUEUE DHCPv4 packet queue info after configuration: %1**

This debug message is emitted during DHCPv4 server configuration, immediately after configuring the DHCPv4 packet queue. The information shown depends upon the packet queue type selected.

**DHCP4\_CONFIG\_PACKET\_QUEUE (1) DHCPv4 packet queue info after configuration: %1**

This debug message is emitted during DHCPv4 server configuration, immediately after configuring the DHCPv4 packet queue. The information shown depends upon the packet queue type selected.

**DHCP4\_CONFIG\_RECEIVED received configuration %1**

A debug message listing the configuration received by the DHCPv4 server. The source of that configuration depends on used configuration backend.

**DHCP4\_CONFIG\_RECEIVED (1) received configuration %1**

A debug message listing the configuration received by the DHCPv4 server. The source of that configuration depends on used configuration backend.

**DHCP4\_CONFIG\_START DHCPv4 server is processing the following configuration: %1**

This is a debug message that is issued every time the server receives a configuration. That happens at start up and also when a server configuration change is committed by the administrator.

**DHCP4\_CONFIG\_START (1) DHCPv4 server is processing the following configuration: %1**

This is a debug message that is issued every time the server receives a configuration. That happens at start up and also when a server configuration change is committed by the administrator.

**DHCP4\_CONFIG\_UPDATE updated configuration received: %1**

A debug message indicating that the DHCPv4 server has received an updated configuration from the Kea configuration system.

**DHCP4\_CONFIG\_UPDATE (1) updated configuration received: %1**

A debug message indicating that the DHCPv4 server has received an updated configuration from the Kea configuration system.

**DHCP4\_DB\_RECONNECT\_ATTEMPT\_FAILED database reconnect failed: %1**

An error message indicating that an attempt to reconnect to the lease and/or host data bases has failed. This occurs after connectivity to either one has been lost and an automatic attempt to reconnect has failed.

**DHCP4\_DB\_RECONNECT\_ATTEMPT\_FAILED (1) database reconnect failed: %1**

An error message indicating that an attempt to reconnect to the lease and/or host data bases has failed. This occurs after connectivity to either one has been lost and an automatic attempt to reconnect has failed.

**DHCP4\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE scheduling attempt %1 of %2 in %3 seconds**

An informational message indicating that the server is scheduling the next attempt to reconnect to its lease and/or host databases. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

**DHCP4\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE (1) scheduling attempt %1 of %2 in %3 seconds**

An informational message indicating that the server is scheduling the next attempt to reconnect to its lease and/or host databases. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

**DHCP4\_DB\_RECONNECT\_DISABLED database reconnect is disabled: max-reconnect-tries %1, reconnect-wait-time %2**

This is an informational message indicating that connectivity to either the lease or host database or both and that automatic reconnect is not enabled.

**DHCP4\_DB\_RECONNECT\_DISABLED (1) database reconnect is disabled: max-reconnect-tries %1, reconnect-wait-time %2**

This is an informational message indicating that connectivity to either the lease or host database or both and that automatic reconnect is not enabled.

---

**DHCP4\_DB\_RECONNECT\_NO\_DB\_CTL unexpected error in database reconnect**

This is an error message indicating a programmatic error that should not occur. It will prohibit the server from attempting to reconnect to its databases if connectivity is lost, and the server will exit. This error should be reported.

**DHCP4\_DB\_RECONNECT\_NO\_DB\_CTL (1) unexpected error in database reconnect**

This is an error message indicating a programmatic error that should not occur. It will prohibit the server from attempting to reconnect to its databases if connectivity is lost, and the server will exit. This error should be reported.

**DHCP4\_DB\_RECONNECT\_RETRIES\_EXHAUSTED maximum number of database reconnect attempts: %1, has been exhausted**

This error indicates that the server is shutting down after failing to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. Loss of connectivity is typically a network or database server issue.

**DHCP4\_DB\_RECONNECT\_RETRIES\_EXHAUSTED (1) maximum number of database reconnect attempts: %1, has been exhausted**

This error indicates that the server is shutting down after failing to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. Loss of connectivity is typically a network or database server issue.

**DHCP4\_DDNS\_REQUEST\_SEND\_FAILED failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2**

This error message indicates that DHCP4 server attempted to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

**DHCP4\_DDNS\_REQUEST\_SEND\_FAILED (1) failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2**

This error message indicates that DHCP4 server attempted to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

**DHCP4\_DEACTIVATE\_INTERFACE deactivate interface %1**

This message is printed when DHCPv4 server disables an interface from being used to receive DHCPv4 traffic. Sockets on this interface will not be opened by the Interface Manager until interface is enabled.

**DHCP4\_DEACTIVATE\_INTERFACE (1) deactivate interface %1**

This message is printed when DHCPv4 server disables an interface from being used to receive DHCPv4 traffic. Sockets on this interface will not be opened by the Interface Manager until interface is enabled.

**DHCP4\_DECLINE\_LEASE Received DHCPDECLINE for addr %1 from client %2. The lease will be unavailable for %3 seconds**

This informational message is printed when a client received an address, but discovered that it is being used by some other device and notified the server by sending a DHCPDECLINE message. The server checked that this address really was leased to the client and marked this address as unusable for a certain amount of time. This message may indicate a misconfiguration in a network, as there is either a buggy client or more likely a device that is using an address that it is not supposed to. The server will fully recover from this situation, but if the underlying problem of a misconfigured or rogue device is not solved, this address may be declined again in the future.

**DHCP4\_DECLINE\_LEASE (1) Received DHCPDECLINE for addr %1 from client %2. The lease will be unavailable for %3 seconds**

This informational message is printed when a client received an address, but discovered that it is being used by some other device and notified the server by sending a DHCPDECLINE message. The server checked that this address really was leased to the client and marked this address as unusable for a certain amount of time. This message may indicate a misconfiguration in a network, as there is either a buggy client or more likely a device that is using an address that it is not supposed to. The server will fully recover from this situation, but if the underlying problem of a misconfigured or rogue device is not solved, this address may be declined again in the future.

**DHCP4\_DECLINE\_LEASE\_MISMATCH Received DHCPDECLINE for addr %1 from client %2, but the data doesn't match**

This informational message means that a client attempted to report his address as declined (i.e. used by unknown entity). The server has information about a lease for that address, but the client's hardware address or client identifier does not match the server's stored information. The client's request will be ignored.

**DHCP4\_DECLINE\_LEASE\_MISMATCH (1) Received DHCPDECLINE for addr %1 from client %2, but the data doesn't match**

This informational message means that a client attempted to report his address as declined (i.e. used by unknown entity). The server has information about a lease for that address, but the client's hardware address or client identifier does not match the server's stored information. The client's request will be ignored.

**DHCP4\_DECLINE\_LEASE\_NOT\_FOUND Received DHCPDECLINE for addr %1 from client %2, but no such lease found.**

This warning message indicates that a client reported that his address was detected as a duplicate (i.e. another device in the network is using this address). However, the server does not have a record for this address. This may indicate a client's error or a server's purged database.

**DHCP4\_DECLINE\_LEASE\_NOT\_FOUND (1) Received DHCPDECLINE for addr %1 from client %2, but no such lease found.**

This warning message indicates that a client reported that his address was detected as a duplicate (i.e. another device in the network is using this address). However, the server does not have a record for this address. This may indicate a client's error or a server's purged database.

**DHCP4\_DHCP4O6\_BAD\_PACKET received malformed DHCPv4o6 packet: %1**

A malformed DHCPv4o6 packet was received.

**DHCP4\_DHCP4O6\_BAD\_PACKET (1) received malformed DHCPv4o6 packet: %1**

A malformed DHCPv4o6 packet was received.

**DHCP4\_DHCP4O6\_PACKET\_RECEIVED received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 on interface %3**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

**DHCP4\_DHCP4O6\_PACKET\_RECEIVED (1) received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 on interface %3**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

**DHCP4\_DHCP4O6\_PACKET\_SEND %1: trying to send packet %2 (type %3) to %4 port %5 on interface %6 encapsulating %7**

The arguments specify the client identification information (HW address and client identifier), DHCPv6 message name and type, source IPv6 address and port, and interface name, DHCPv4 client identification, message name and type.

**DHCP4\_DHCP4O6\_PACKET\_SEND (1) %1: trying to send packet %2 (type %3) to %4 port %5 on interface %6 encapsulating %7**

The arguments specify the client identification information (HW address and client identifier), DHCPv6 message name and type, source IPv6 address and port, and interface name, DHCPv4 client identification, message name and type.

**DHCP4\_DHCP4O6\_PACKET\_SEND\_FAIL %1: failed to send DHCPv4o6 packet: %2**

This error is output if the IPv4 DHCP server fails to send an DHCPv4o6 message to the IPv6 DHCP server. The reason for the error is included in the message.

**DHCP4\_DHCP4O6\_PACKET\_SEND\_FAIL (1) %1: failed to send DHCPv4o6 packet: %2**

This error is output if the IPv4 DHCP server fails to send an DHCPv4o6 message to the IPv6 DHCP server. The reason for the error is included in the message.

**DHCP4\_DHCP4O6\_RECEIVE\_FAIL failed to receive DHCPv4o6: %1**

This debug message indicates the inter-process communication with the DHCPv6 server failed. The reason for the error is included in the message.

**DHCP4\_DHCP4O6\_RECEIVE\_FAIL (1) failed to receive DHCPv4o6: %1**

This debug message indicates the inter-process communication with the DHCPv6 server failed. The reason for the error is included in the message.

---

**DHCP4\_DHCP4O6\_RECEIVING receiving DHCPv4o6 packet from DHCPv6 server**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv6 server over inter-process communication socket.

**DHCP4\_DHCP4O6\_RECEIVING (1) receiving DHCPv4o6 packet from DHCPv6 server**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv6 server over inter-process communication socket.

**DHCP4\_DHCP4O6\_RESPONSE\_DATA %1: responding with packet %2 (type %3), packet details: %4**

A debug message including the detailed data about the packet being sent to the DHCPv6 server to be forwarded to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

**DHCP4\_DHCP4O6\_RESPONSE\_DATA (1) %1: responding with packet %2 (type %3), packet details: %4**

A debug message including the detailed data about the packet being sent to the DHCPv6 server to be forwarded to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

**DHCP4\_DYNAMIC\_RECONFIGURATION initiate server reconfiguration using file: %1, after receiving SIGHUP signal**

This is the info message logged when the DHCPv4 server starts reconfiguration as a result of receiving SIGHUP signal.

**DHCP4\_DYNAMIC\_RECONFIGURATION (1) initiate server reconfiguration using file: %1, after receiving SIGHUP signal**

This is the info message logged when the DHCPv4 server starts reconfiguration as a result of receiving SIGHUP signal.

**DHCP4\_DYNAMIC\_RECONFIGURATION\_FAIL dynamic server reconfiguration failed with file: %1**

This is an error message logged when the dynamic reconfiguration of the DHCP server failed.

**DHCP4\_DYNAMIC\_RECONFIGURATION\_FAIL (1) dynamic server reconfiguration failed with file: %1**

This is an error message logged when the dynamic reconfiguration of the DHCP server failed.

**DHCP4\_EMPTY\_HOSTNAME %1: received empty hostname from the client, skipping processing of this option**

This debug message is issued when the server received an empty Hostname option from a client. Server does not process empty Hostname options and therefore option is skipped. The argument holds the client and transaction identification information.

**DHCP4\_EMPTY\_HOSTNAME (1) %1: received empty hostname from the client, skipping processing of this option**

This debug message is issued when the server received an empty Hostname option from a client. Server does not process empty Hostname options and therefore option is skipped. The argument holds the client and transaction identification information.

**DHCP4\_FLEX\_ID flexible identifier generated for incoming packet: %1**

This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

**DHCP4\_FLEX\_ID (1) flexible identifier generated for incoming packet: %1**

This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

**DHCP4\_GENERATE\_FQDN %1: client did not send a FQDN or hostname; FQDN will be generated for the client**

This debug message is issued when the server did not receive a Hostname option from the client and hostname generation is enabled. This provides a means to create DNS entries for unsophisticated clients.

**DHCP4\_GENERATE\_FQDN (1) %1: client did not send a FQDN or hostname; FQDN will be generated for the client**

This debug message is issued when the server did not receive a Hostname option from the client and hostname generation is enabled. This provides a means to create DNS entries for unsophisticated clients.

---

**DHCP4\_HANDLE\_SIGNAL\_EXCEPTION An exception was thrown while handing signal: %1**

This error message is printed when an ISC or standard exception was raised during signal processing. This likely indicates a coding error and should be reported to ISC.

**DHCP4\_HANDLE\_SIGNAL\_EXCEPTION (1) An exception was thrown while handing signal: %1**

This error message is printed when an ISC or standard exception was raised during signal processing. This likely indicates a coding error and should be reported to ISC.

**DHCP4\_HOOKS\_LIBS\_RELOAD\_FAIL reload of hooks libraries failed**

A "libreload" command was issued to reload the hooks libraries but for some reason the reload failed. Other error messages issued from the hooks framework will indicate the nature of the problem.

**DHCP4\_HOOKS\_LIBS\_RELOAD\_FAIL (1) reload of hooks libraries failed**

A "libreload" command was issued to reload the hooks libraries but for some reason the reload failed. Other error messages issued from the hooks framework will indicate the nature of the problem.

**DHCP4\_HOOK\_BUFFER\_RCVD\_DROP received buffer from %1 to %2 over interface %3 was dropped because a callout set**

This debug message is printed when a callout installed on buffer4\_receive hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

**DHCP4\_HOOK\_BUFFER\_RCVD\_DROP (1) received buffer from %1 to %2 over interface %3 was dropped because a callout set**

This debug message is printed when a callout installed on buffer4\_receive hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

**DHCP4\_HOOK\_BUFFER\_RCVD\_SKIP received buffer from %1 to %2 over interface %3 is not parsed because a callout set**

This debug message is printed when a callout installed on buffer4\_receive hook point set the next step to SKIP. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

**DHCP4\_HOOK\_BUFFER\_RCVD\_SKIP (1) received buffer from %1 to %2 over interface %3 is not parsed because a callout set**

This debug message is printed when a callout installed on buffer4\_receive hook point set the next step to SKIP. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

**DHCP4\_HOOK\_BUFFER\_SEND\_SKIP %1: prepared response is dropped because a callout set the next step to SKIP.**

This debug message is printed when a callout installed on buffer4\_send hook point set the next step to SKIP. For this particular hook point, the SKIP value set by a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be send to the client.

**DHCP4\_HOOK\_BUFFER\_SEND\_SKIP (1) %1: prepared response is dropped because a callout set the next step to SKIP.**

This debug message is printed when a callout installed on buffer4\_send hook point set the next step to SKIP. For this particular hook point, the SKIP value set by a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be send to the client.

**DHCP4\_HOOK\_DECLINE\_SKIP Decline4 hook callouts set status to DROP, ignoring packet.**

This message indicates that the server received DHCPDECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for decline4 hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

**DHCP4\_HOOK\_DECLINE\_SKIP (1) Decline4 hook callouts set status to DROP, ignoring packet.**

This message indicates that the server received DHCPDECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for decline4 hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

**DHCP4\_HOOK\_LEASE4\_RELEASE\_SKIP %1: lease was not released because a callout set the next step to SKIP**

This debug message is printed when a callout installed on lease4\_release hook point set the next step status to SKIP. For this particular hook point, the value set by a callout instructs the server to not release a lease.

**DHCP4\_HOOK\_LEASE4\_RELEASE\_SKIP (1) %1: lease was not released because a callout set the next step to SKIP**

This debug message is printed when a callout installed on lease4\_release hook point set the next step status to SKIP. For this particular hook point, the value set by a callout instructs the server to not release a lease.

**DHCP4\_HOOK\_LEASES4\_COMMITTED\_DROP %1: packet is dropped, because a callout set the next step to DROP**

This debug message is printed when a callout installed on the leases4\_committed hook point sets the next step to DROP.

**DHCP4\_HOOK\_LEASES4\_COMMITTED\_DROP (1) %1: packet is dropped, because a callout set the next step to DROP**

This debug message is printed when a callout installed on the leases4\_committed hook point sets the next step to DROP.

**DHCP4\_HOOK\_LEASES4\_COMMITTED\_PARK %1: packet is parked, because a callout set the next step to PARK**

This debug message is printed when a callout installed on the lease4\_committed hook point sets the next step to PARK.

**DHCP4\_HOOK\_LEASES4\_COMMITTED\_PARK (1) %1: packet is parked, because a callout set the next step to PARK**

This debug message is printed when a callout installed on the lease4\_committed hook point sets the next step to PARK.

**DHCP4\_HOOK\_PACKET\_RCVD\_SKIP %1: packet is dropped, because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the pkt4\_receive hook point sets the next step to SKIP. For this particular hook point, the value setting of the flag instructs the server to drop the packet.

**DHCP4\_HOOK\_PACKET\_RCVD\_SKIP (1) %1: packet is dropped, because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the pkt4\_receive hook point sets the next step to SKIP. For this particular hook point, the value setting of the flag instructs the server to drop the packet.

**DHCP4\_HOOK\_PACKET\_SEND\_SKIP %1: prepared response is not sent, because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the pkt4\_send hook point sets the next step to SKIP. For this particular hook point, this setting instructs the server to drop the packet. This means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease).

**DHCP4\_HOOK\_PACKET\_SEND\_SKIP (1) %1: prepared response is not sent, because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the pkt4\_send hook point sets the next step to SKIP. For this particular hook point, this setting instructs the server to drop the packet. This means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease).

**DHCP4\_HOOK\_SUBNET4\_SELECT\_DROP %1: packet was dropped, because a callout set the next step to 'drop'**

This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to 'drop' value. For this particular hook point, the setting to that value instructs the server to drop the received packet. The argument specifies the client and transaction identification information.

**DHCP4\_HOOK\_SUBNET4\_SELECT\_DROP (1) %1: packet was dropped, because a callout set the next step to 'drop'**

This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to 'drop' value. For this particular hook point, the setting to that value instructs the server to drop the received packet. The argument specifies the client and transaction identification information.



**DHCP4\_HOOK\_SUBNET4\_SELECT\_SKIP %1: no subnet was selected, because a callout set the next skip flag**

This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to SKIP value. For this particular hook point, the setting of the flag instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses will be assigned. The argument specifies the client and transaction identification information.

**DHCP4\_HOOK\_SUBNET4\_SELECT\_SKIP (1) %1: no subnet was selected, because a callout set the next skip flag**

This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to SKIP value. For this particular hook point, the setting of the flag instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses will be assigned. The argument specifies the client and transaction identification information.

**DHCP4\_INFORM\_DIRECT\_REPLY %1: DHCPACK in reply to the DHCPINFORM will be sent directly to %2 over %3**

This debug message is issued when the DHCPACK will be sent directly to the client, rather than via a relay. The first argument contains the client and transaction identification information. The second argument contains the client's IPv4 address to which the response will be sent. The third argument contains the local interface name.

**DHCP4\_INFORM\_DIRECT\_REPLY (1) %1: DHCPACK in reply to the DHCPINFORM will be sent directly to %2 over %3**

This debug message is issued when the DHCPACK will be sent directly to the client, rather than via a relay. The first argument contains the client and transaction identification information. The second argument contains the client's IPv4 address to which the response will be sent. The third argument contains the local interface name.

**DHCP4\_INIT\_FAIL failed to initialize Kea server: %1**

The server has failed to initialize. This may be because the configuration was not successful, or it encountered any other critical error on startup. Attached error message provides more details about the issue.

**DHCP4\_INIT\_FAIL (1) failed to initialize Kea server: %1**

The server has failed to initialize. This may be because the configuration was not successful, or it encountered any other critical error on startup. Attached error message provides more details about the issue.

**DHCP4\_INIT\_REBOOT %1: client is in INIT-REBOOT state and requests address %2**

This informational message is issued when the client is in the INIT-REBOOT state and is requesting an IPv4 address it is using to be allocated for it. The first argument includes the client and transaction identification information. The second argument specifies the requested IPv4 address.

**DHCP4\_INIT\_REBOOT (1) %1: client is in INIT-REBOOT state and requests address %2**

This informational message is issued when the client is in the INIT-REBOOT state and is requesting an IPv4 address it is using to be allocated for it. The first argument includes the client and transaction identification information. The second argument specifies the requested IPv4 address.

**DHCP4\_LEASE\_ADVERT %1: lease %2 will be advertised**

This informational message indicates that the server has found the lease to be offered to the client. It is up to the client to choose one server out of those which offered leases and continue allocation with that server. The first argument specifies the client and the transaction identification information. The second argument specifies the IPv4 address to be offered.

**DHCP4\_LEASE\_ADVERT (1) %1: lease %2 will be advertised**

This informational message indicates that the server has found the lease to be offered to the client. It is up to the client to choose one server out of those which offered leases and continue allocation with that server. The first argument specifies the client and the transaction identification information. The second argument specifies the IPv4 address to be offered.

**DHCP4\_LEASE\_ALLOC %1: lease %2 has been allocated**

This informational message indicates that the server successfully granted a lease in response to client's DHCPREQUEST message. The lease information will be sent to the client in the DHCPACK message. The first argument contains the client and the transaction identification information. The second argument contains the allocated IPv4 address.

**DHCP4\_LEASE\_ALLOC (1) %1: lease %2 has been allocated**

This informational message indicates that the server successfully granted a lease in response to client's DHCPREQUEST message. The lease information will be sent to the client in the DHCPACK message. The first argument contains the client and the transaction identification information. The second argument contains the allocated IPv4 address.

**DHCP4\_NCR\_CREATE %1: DDNS updates enabled, therefore sending name change requests**

This debug message is issued when the server is starting to send name change requests to the D2 module to update records for the client in the DNS. This includes removal of old records and addition of the new records as required. Details of the name change requests will be logged in additional log entries. The argument includes the client and the transaction identification information.

**DHCP4\_NCR\_CREATE (1) %1: DDNS updates enabled, therefore sending name change requests**

This debug message is issued when the server is starting to send name change requests to the D2 module to update records for the client in the DNS. This includes removal of old records and addition of the new records as required. Details of the name change requests will be logged in additional log entries. The argument includes the client and the transaction identification information.

**DHCP4\_NCR\_CREATION\_FAILED %1: failed to generate name change requests for DNS: %2**

This message indicates that server was unable to generate NameChangeRequests which should be sent to the kea-dhcp\_ddns module to create new DNS records for the lease being acquired or to update existing records for the renewed lease. The first argument contains the client and transaction identification information. The second argument includes the reason for the failure.

**DHCP4\_NCR\_CREATION\_FAILED (1) %1: failed to generate name change requests for DNS: %2**

This message indicates that server was unable to generate NameChangeRequests which should be sent to the kea-dhcp\_ddns module to create new DNS records for the lease being acquired or to update existing records for the renewed lease. The first argument contains the client and transaction identification information. The second argument includes the reason for the failure.

**DHCP4\_NOT\_RUNNING DHCPv4 server is not running**

A warning message is issued when an attempt is made to shut down the DHCPv4 server but it is not running.

**DHCP4\_NOT\_RUNNING (1) DHCPv4 server is not running**

A warning message is issued when an attempt is made to shut down the DHCPv4 server but it is not running.

**DHCP4\_NO\_LEASE\_INIT\_REBOOT %1: no lease for address %2 requested by INIT-REBOOT client**

This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address but this client is unknown. The server will not respond. The first argument includes the client and the transaction id identification information. The second argument includes the IPv4 address requested by the client.

**DHCP4\_NO\_LEASE\_INIT\_REBOOT (1) %1: no lease for address %2 requested by INIT-REBOOT client**

This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address but this client is unknown. The server will not respond. The first argument includes the client and the transaction id identification information. The second argument includes the IPv4 address requested by the client.

**DHCP4\_NO\_SOCKETS\_OPEN no interface configured to listen to DHCP traffic**

This warning message is issued when current server configuration specifies no interfaces that server should listen on, or specified interfaces are not configured to receive the traffic.

**DHCP4\_NO\_SOCKETS\_OPEN (1) no interface configured to listen to DHCP traffic**

This warning message is issued when current server configuration specifies no interfaces that server should listen on, or specified interfaces are not configured to receive the traffic.

**DHCP4\_OPEN\_CONFIG\_DB Opening configuration database: %1**

This message is printed when the DHCPv4 server is attempting to open a configuration database. The database access string with password redacted is logged.

**DHCP4\_OPEN\_CONFIG\_DB (1) Opening configuration database: %1**

This message is printed when the DHCPv4 server is attempting to open a configuration database. The database access string with password redacted is logged.

**DHCP4\_OPEN\_SOCKET opening sockets on port %1**

A debug message issued during startup, this indicates that the DHCPv4 server is about to open sockets on the specified port.

**DHCP4\_OPEN\_SOCKET (1) opening sockets on port %1**

A debug message issued during startup, this indicates that the DHCPv4 server is about to open sockets on the specified port.

**DHCP4\_OPEN\_SOCKET\_FAIL failed to open socket: %1**

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

**DHCP4\_OPEN\_SOCKET\_FAIL (1) failed to open socket: %1**

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

**DHCP4\_PACKET\_DROP\_0001 failed to parse packet from %1 to %2, received over interface %3, reason: %4**

The DHCPv4 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

**DHCP4\_PACKET\_DROP\_0001 (1) failed to parse packet from %1 to %2, received over interface %3, reason: %4**

The DHCPv4 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

**DHCP4\_PACKET\_DROP\_0002 %1, from interface %2: no suitable subnet configured for a direct client**

This info message is logged when received a message from a directly connected client but there is no suitable subnet configured for the interface on which this message has been received. The IPv4 address assigned on this interface must belong to one of the configured subnets. Otherwise received message is dropped.

**DHCP4\_PACKET\_DROP\_0002 (1) %1, from interface %2: no suitable subnet configured for a direct client**

This info message is logged when received a message from a directly connected client but there is no suitable subnet configured for the interface on which this message has been received. The IPv4 address assigned on this interface must belong to one of the configured subnets. Otherwise received message is dropped.

**DHCP4\_PACKET\_DROP\_0003 %1, from interface %2: it contains a foreign server identifier**

This debug message is issued when received DHCPv4 message is dropped because it is addressed to a different server, i.e. a server identifier held by this message doesn't match the identifier used by our server. The arguments of this message hold the name of the transaction id and interface on which the message has been received.

**DHCP4\_PACKET\_DROP\_0003 (1) %1, from interface %2: it contains a foreign server identifier**

This debug message is issued when received DHCPv4 message is dropped because it is addressed to a different server, i.e. a server identifier held by this message doesn't match the identifier used by our server. The arguments of this message hold the name of the transaction id and interface on which the message has been received.

**DHCP4\_PACKET\_DROP\_0004 %1, from interface %2: missing msg-type option**

This is a debug message informing that incoming DHCPv4 packet did not have mandatory DHCP message type option and thus was dropped. The arguments specify the client and transaction identification information, as well as the interface on which the message has been received.

**DHCP4\_PACKET\_DROP\_0004 (1) %1, from interface %2: missing msg-type option**

This is a debug message informing that incoming DHCPv4 packet did not have mandatory DHCP message type option and thus was dropped. The arguments specify the client and transaction identification information, as well as the interface on which the message has been received.

**DHCP4\_PACKET\_DROP\_0005 %1: unrecognized type %2 in option 53**

This debug message indicates that the message type carried in DHCPv4 option 53 is unrecognized by the server. The valid message types are listed on the IANA website: <http://www.iana.org/assignments/bootp-dhcp-parameters/bootp-dhcp-parameters.xhtml#message-type-53>. The message will not be processed by the server. The arguments specify the client and transaction identification information, as well as the received message type.

**DHCP4\_PACKET\_DROP\_0005 (1) %1: unrecognized type %2 in option 53**

This debug message indicates that the message type carried in DHCPv4 option 53 is unrecognized by the server. The valid message types are listed on the IANA website: <http://www.iana.org/assignments/bootp-dhcp-parameters/bootp-dhcp-parameters.xhtml#message-type-53>. The message will not be processed by the server. The arguments specify the client and transaction identification information, as well as the received message type.

**DHCP4\_PACKET\_DROP\_0006 %1: unsupported DHCPv4 message type %2**

This debug message indicates that the message type carried in DHCPv4 option 53 is valid but the message will not be processed by the server. This includes messages being normally sent by the server to the client, such as DHCPOFFER, DHCPACK, DHCPNAK etc. The first argument specifies the client and transaction identification information. The second argument specifies the message type.

**DHCP4\_PACKET\_DROP\_0006 (1) %1: unsupported DHCPv4 message type %2**

This debug message indicates that the message type carried in DHCPv4 option 53 is valid but the message will not be processed by the server. This includes messages being normally sent by the server to the client, such as DHCPOFFER, DHCPACK, DHCPNAK etc. The first argument specifies the client and transaction identification information. The second argument specifies the message type.

**DHCP4\_PACKET\_DROP\_0007 %1: failed to process packet: %2**

This is a general catch-all message indicating that the processing of a received packet failed. The reason is given in the message. The server will not send a response but will instead ignore the packet. The first argument contains the client and transaction identification information. The second argument includes the details of the error.

**DHCP4\_PACKET\_DROP\_0007 (1) %1: failed to process packet: %2**

This is a general catch-all message indicating that the processing of a received packet failed. The reason is given in the message. The server will not send a response but will instead ignore the packet. The first argument contains the client and transaction identification information. The second argument includes the details of the error.

**DHCP4\_PACKET\_DROP\_0008 %1: DHCP service is globally disabled**

This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

**DHCP4\_PACKET\_DROP\_0008 (1) %1: DHCP service is globally disabled**

This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

**DHCP4\_PACKET\_DROP\_0009 %1: Option 53 missing (no DHCP message type), is this a BOOTP packet?**

This debug message is issued when a packet is dropped because it did contain option 53 and thus has no DHCP message type. The most likely explanation is that it was BOOTP packet.

**DHCP4\_PACKET\_DROP\_0009 (1) %1: Option 53 missing (no DHCP message type), is this a BOOTP packet?**

This debug message is issued when a packet is dropped because it did contain option 53 and thus has no DHCP message type. The most likely explanation is that it was BOOTP packet.

**DHCP4\_PACKET\_NAK\_0001 %1: failed to select a subnet for incoming packet, src %2, type %3**

This error message is output when a packet was received from a subnet for which the DHCPv4 server has not been configured. The most probable cause is a misconfiguration of the server. The first argument contains the client and transaction identification information. The second argument contains the source IPv4 address of the packet. The third argument contains the name of the received packet.

**DHCP4\_PACKET\_NAK\_0001 (1) %1: failed to select a subnet for incoming packet, src %2, type %3**

This error message is output when a packet was received from a subnet for which the DHCPv4 server has not been configured. The most probable cause is a misconfiguration of the server. The first argument contains the client and transaction identification information. The second argument contains the source IPv4 address of the packet. The third argument contains the name of the received packet.

**DHCP4\_PACKET\_NAK\_0002 %1: invalid address %2 requested by INIT-REBOOT**

This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address which is not assigned to him. The server will respond to this client with DHCPNAK. The first argument contains the client and the transaction identification information. The second arguments holds the IPv4 address requested by the client.

**DHCP4\_PACKET\_NAK\_0002 (1) %1: invalid address %2 requested by INIT-REBOOT**

This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address which is not assigned to him. The server will respond to this client with DHCPNAK. The first argument contains the client and the transaction identification information. The second arguments holds the IPv4 address requested by the client.

---

**DHCP4\_PACKET\_NAK\_0003 %1: failed to advertise a lease, client sent ciaddr %2, requested-ip-address %3**

This message indicates that the server has failed to offer a lease to the specified client after receiving a DISCOVER message from it. There are many possible reasons for such a failure. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

**DHCP4\_PACKET\_NAK\_0003 (1) %1: failed to advertise a lease, client sent ciaddr %2, requested-ip-address %3**

This message indicates that the server has failed to offer a lease to the specified client after receiving a DISCOVER message from it. There are many possible reasons for such a failure. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

**DHCP4\_PACKET\_NAK\_0004 %1: failed to grant a lease, client sent ciaddr %2, requested-ip-address %3**

This message indicates that the server failed to grant a lease to the specified client after receiving a REQUEST message from it. There are many possible reasons for such a failure. Additional messages will indicate the reason. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

**DHCP4\_PACKET\_NAK\_0004 (1) %1: failed to grant a lease, client sent ciaddr %2, requested-ip-address %3**

This message indicates that the server failed to grant a lease to the specified client after receiving a REQUEST message from it. There are many possible reasons for such a failure. Additional messages will indicate the reason. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

**DHCP4\_PACKET\_OPTIONS\_SKIPPED An error unpacking an option, caused subsequent options to be skipped: %1**

A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will server will still attempt to service the packet.

**DHCP4\_PACKET\_OPTIONS\_SKIPPED (1) An error unpacking an option, caused subsequent options to be skipped: %1**

A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will server will still attempt to service the packet.

**DHCP4\_PACKET\_PACK %1: preparing on-wire format of the packet to be sent**

This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

**DHCP4\_PACKET\_PACK (1) %1: preparing on-wire format of the packet to be sent**

This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

**DHCP4\_PACKET\_PACK\_FAIL %1: preparing on-wire-format of the packet to be sent failed %2**

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the DHCP transaction. The second argument includes the error string.

**DHCP4\_PACKET\_PACK\_FAIL (1) %1: preparing on-wire-format of the packet to be sent failed %2**

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the DHCP transaction. The second argument includes the error string.

**DHCP4\_PACKET\_PROCESS\_EXCEPTION exception occurred during packet processing**

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

**DHCP4\_PACKET\_PROCESS\_EXCEPTION (1) exception occurred during packet processing**

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

**DHCP4\_PACKET\_PROCESS\_STD\_EXCEPTION exception occurred during packet processing: %1**

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

**DHCP4\_PACKET\_PROCESS\_STD\_EXCEPTION (1) exception occurred during packet processing: %1**

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

**DHCP4\_PACKET\_RECEIVED %1: %2 (type %3) received from %4 to %5 on interface %6**

A debug message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv4 message and its numeric type respectively. The remaining arguments specify the source IPv4 address, destination IPv4 address and the name of the interface on which the message has been received.

**DHCP4\_PACKET\_RECEIVED (1) %1: %2 (type %3) received from %4 to %5 on interface %6**

A debug message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv4 message and its numeric type respectively. The remaining arguments specify the source IPv4 address, destination IPv4 address and the name of the interface on which the message has been received.

**DHCP4\_PACKET\_SEND %1: trying to send packet %2 (type %3) from %4:%5 to %6:%7 on interface %8**

The arguments specify the client identification information (HW address and client identifier), DHCP message name and type, source IPv4 address and port, destination IPv4 address and port and the interface name.

This debug message is issued when the server is trying to send the response to the client. When the server is using an UDP socket to send the packet there are cases when this operation may be unsuccessful and no error message will be displayed. One such situation occurs when the server is unicasting the response to the 'ciaddr' of a DHCPINFORM message. This often requires broadcasting an ARP message to obtain the link layer address of the unicast destination. If broadcast ARP messages are blocked in the network, according to the firewall policy, the ARP message will not cause a response. Consequently, the response to the DHCPINFORM will not be sent. Since the ARP communication is under the OS control, Kea is not notified about the drop of the packet which it is trying to send and it has no means to display an error message.

**DHCP4\_PACKET\_SEND (1) %1: trying to send packet %2 (type %3) from %4:%5 to %6:%7 on interface %8**

The arguments specify the client identification information (HW address and client identifier), DHCP message name and type, source IPv4 address and port, destination IPv4 address and port and the interface name.

This debug message is issued when the server is trying to send the response to the client. When the server is using an UDP socket to send the packet there are cases when this operation may be unsuccessful and no error message will be displayed. One such situation occurs when the server is unicasting the response to the 'ciaddr' of a DHCPINFORM message. This often requires broadcasting an ARP message to obtain the link layer address of the unicast destination. If broadcast ARP messages are blocked in the network, according to the firewall policy, the ARP message will not cause a response. Consequently, the response to the DHCPINFORM will not be sent. Since the ARP communication is under the OS control, Kea is not notified about the drop of the packet which it is trying to send and it has no means to display an error message.

**DHCP4\_PACKET\_SEND\_FAIL %1: failed to send DHCPv4 packet: %2**

This error is output if the DHCPv4 server fails to send an assembled DHCP message to a client. The first argument includes the client and the transaction identification information. The second argument includes the reason for failure.

**DHCP4\_PACKET\_SEND\_FAIL (1) %1: failed to send DHCPv4 packet: %2**

This error is output if the DHCPv4 server fails to send an assembled DHCP message to a client. The first argument includes the client and the transaction identification information. The second argument includes the reason for failure.

**DHCP4\_PARSER\_COMMIT\_EXCEPTION parser failed to commit changes**

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

**DHCP4\_PARSER\_COMMIT\_EXCEPTION (1) parser failed to commit changes**

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

**DHCP4\_PARSER\_COMMIT\_FAIL parser failed to commit changes: %1**

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

**DHCP4\_PARSER\_COMMIT\_FAIL (1) parser failed to commit changes: %1**

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

**DHCP4\_PARSER\_EXCEPTION failed to create or run parser for configuration element %1**

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information.

**DHCP4\_PARSER\_EXCEPTION (1) failed to create or run parser for configuration element %1**

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information.

**DHCP4\_PARSER\_FAIL failed to create or run parser for configuration element %1: %2**

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

**DHCP4\_PARSER\_FAIL (1) failed to create or run parser for configuration element %1: %2**

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

**DHCP4\_POST\_ALLOCATION\_NAME\_UPDATE\_FAIL %1: failed to update hostname %2 in a lease after address allocation**

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server or reserved for the client belonging to a shared network. The latter is the case when the server dynamically switches to another subnet (than initially selected for allocation) from the same shared network.

**DHCP4\_POST\_ALLOCATION\_NAME\_UPDATE\_FAIL (1) %1: failed to update hostname %2 in a lease after address allocation**

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server or reserved for the client belonging to a shared network. The latter is the case when the server dynamically switches to another subnet (than initially selected for allocation) from the same shared network.

**DHCP4\_QUERY\_DATA %1, packet details: %2**

A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

**DHCP4\_QUERY\_DATA (1) %1, packet details: %2**

A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

**DHCP4\_RELEASE %1: address %2 was released properly.**

This informational message indicates that an address was released properly. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

**DHCP4\_RELEASE (1) %1: address %2 was released properly.**

This informational message indicates that an address was released properly. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

---

**DHCP4\_RELEASE\_EXCEPTION %1: while trying to release address %2 an exception occurred: %3**

This message is output when an error was encountered during an attempt to process a DHCPRELEASE message. The error will not affect the client, which does not expect any response from the server for DHCPRELEASE messages. Depending on the nature of problem, it may affect future server operation. The first argument includes the client and the transaction identification information. The second argument includes the IPv4 address which release was attempted. The last argument includes the detailed error description.

**DHCP4\_RELEASE\_EXCEPTION (1) %1: while trying to release address %2 an exception occurred: %3**

This message is output when an error was encountered during an attempt to process a DHCPRELEASE message. The error will not affect the client, which does not expect any response from the server for DHCPRELEASE messages. Depending on the nature of problem, it may affect future server operation. The first argument includes the client and the transaction identification information. The second argument includes the IPv4 address which release was attempted. The last argument includes the detailed error description.

**DHCP4\_RELEASE\_FAIL %1: failed to remove lease for address %2**

This error message indicates that the software failed to remove a lease from the lease database. It is probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address which release was attempted.

**DHCP4\_RELEASE\_FAIL (1) %1: failed to remove lease for address %2**

This error message indicates that the software failed to remove a lease from the lease database. It is probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address which release was attempted.

**DHCP4\_RELEASE\_FAIL\_NO\_LEASE %1: client is trying to release non-existing lease %2**

This debug message is printed when client attempts to release a lease, but no such lease is known to the server. The first argument contains the client and transaction identification information. The second argument contains the IPv4 address which the client is trying to release.

**DHCP4\_RELEASE\_FAIL\_NO\_LEASE (1) %1: client is trying to release non-existing lease %2**

This debug message is printed when client attempts to release a lease, but no such lease is known to the server. The first argument contains the client and transaction identification information. The second argument contains the IPv4 address which the client is trying to release.

**DHCP4\_RELEASE\_FAIL\_WRONG\_CLIENT %1: client is trying to release the lease %2 which belongs to a different client**

This debug message is issued when a client is trying to release the lease for the address which is currently used by another client, i.e. the 'client identifier' or 'chaddr' doesn't match between the client and the lease. The first argument includes the client and the transaction identification information. The second argument specifies the leased address.

**DHCP4\_RELEASE\_FAIL\_WRONG\_CLIENT (1) %1: client is trying to release the lease %2 which belongs to a different client**

This debug message is issued when a client is trying to release the lease for the address which is currently used by another client, i.e. the 'client identifier' or 'chaddr' doesn't match between the client and the lease. The first argument includes the client and the transaction identification information. The second argument specifies the leased address.

**DHCP4\_RESERVED\_HOSTNAME\_ASSIGNED %1: server assigned reserved hostname %2**

This debug message is issued when the server found a hostname reservation for a client and uses this reservation in a hostname option sent back to this client. The reserved hostname is qualified with a value of 'qualifying-suffix' parameter, if this parameter is specified.

**DHCP4\_RESERVED\_HOSTNAME\_ASSIGNED (1) %1: server assigned reserved hostname %2**

This debug message is issued when the server found a hostname reservation for a client and uses this reservation in a hostname option sent back to this client. The reserved hostname is qualified with a value of 'qualifying-suffix' parameter, if this parameter is specified.



**DHCP4\_RESPONSE\_DATA %1: responding with packet %2 (type %3), packet details: %4**

A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

**DHCP4\_RESPONSE\_DATA (1) %1: responding with packet %2 (type %3), packet details: %4**

A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

**DHCP4\_RESPONSE\_FQDN\_DATA %1: including FQDN option in the server's response: %2**

This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

**DHCP4\_RESPONSE\_FQDN\_DATA (1) %1: including FQDN option in the server's response: %2**

This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

**DHCP4\_RESPONSE\_HOSTNAME\_DATA %1: including Hostname option in the server's response: %2**

This debug message is issued when the server is adding the Hostname option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the Hostname option may be modified by the server when the lease is acquired for the client.

**DHCP4\_RESPONSE\_HOSTNAME\_DATA (1) %1: including Hostname option in the server's response: %2**

This debug message is issued when the server is adding the Hostname option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the Hostname option may be modified by the server when the lease is acquired for the client.

**DHCP4\_RESPONSE\_HOSTNAME\_GENERATE %1: server has generated hostname %2 for the client**

This debug message includes the auto-generated hostname which will be used for the client which message is processed. Hostnames may need to be generated when required by the server's configuration or when the client hasn't supplied its hostname. The first argument includes the client and the transaction identification information. The second argument holds the generated hostname.

**DHCP4\_RESPONSE\_HOSTNAME\_GENERATE (1) %1: server has generated hostname %2 for the client**

This debug message includes the auto-generated hostname which will be used for the client which message is processed. Hostnames may need to be generated when required by the server's configuration or when the client hasn't supplied its hostname. The first argument includes the client and the transaction identification information. The second argument holds the generated hostname.

**DHCP4\_SERVER\_FAILED server failed: %1**

The DHCPv4 server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

**DHCP4\_SERVER\_FAILED (1) server failed: %1**

The DHCPv4 server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

**DHCP4\_SHUTDOWN server shutdown**

The DHCPv4 server has terminated normally.

**DHCP4\_SHUTDOWN (1) server shutdown**

The DHCPv4 server has terminated normally.

**DHCP4\_SHUTDOWN\_REQUEST shutdown of server requested**

This debug message indicates that a shutdown of the DHCPv4 server has been requested via a call to the 'shutdown' method of the core Dhcpv4Srv object.

**DHCP4\_SHUTDOWN\_REQUEST (1) shutdown of server requested**

This debug message indicates that a shutdown of the DHCPv4 server has been requested via a call to the 'shutdown' method of the core Dhcpv4Srv object.

**DHCP4\_SRV\_CONSTRUCT\_ERROR error creating Dhcpv4Srv object, reason: %1**

This error message indicates that during startup, the construction of a core component within the DHCPv4 server (the Dhcpv4 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

**DHCP4\_SRV\_CONSTRUCT\_ERROR (1) error creating Dhcpv4Srv object, reason: %1**

This error message indicates that during startup, the construction of a core component within the DHCPv4 server (the Dhcpv4 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

**DHCP4\_SRV\_D2STOP\_ERROR error stopping IO with DHCP\_DDNS during shutdown: %1**

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCP\_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

**DHCP4\_SRV\_D2STOP\_ERROR (1) error stopping IO with DHCP\_DDNS during shutdown: %1**

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCP\_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

**DHCP4\_SRV\_DHCP4O6\_ERROR error stopping IO with DHCPv4o6 during shutdown: %1**

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCPv6o6 server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

**DHCP4\_SRV\_DHCP4O6\_ERROR (1) error stopping IO with DHCPv4o6 during shutdown: %1**

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCPv6o6 server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

**DHCP4\_STARTED Kea DHCPv4 server version %1 started**

This informational message indicates that the DHCPv4 server has processed all configuration information and is ready to process DHCPv4 packets. The version is also printed.

**DHCP4\_STARTED (1) Kea DHCPv4 server version %1 started**

This informational message indicates that the DHCPv4 server has processed all configuration information and is ready to process DHCPv4 packets. The version is also printed.

**DHCP4\_STARTING Kea DHCPv4 server version %1 starting**

This informational message indicates that the DHCPv4 server has processed any command-line switches and is starting. The version is also printed.

**DHCP4\_STARTING (1) Kea DHCPv4 server version %1 starting**

This informational message indicates that the DHCPv4 server has processed any command-line switches and is starting. The version is also printed.

**DHCP4\_START\_INFO pid: %1, port: %2, verbose: %3**

This is a debug message issued during the DHCPv4 server startup. It lists some information about the parameters with which the server is running.

**DHCP4\_START\_INFO (1) pid: %1, port: %2, verbose: %3**

This is a debug message issued during the DHCPv4 server startup. It lists some information about the parameters with which the server is running.

**DHCP4\_SUBNET\_DATA %1: the selected subnet details: %2**

This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second arguments includes the subnet details.

**DHCP4\_SUBNET\_DATA (1) %1: the selected subnet details: %2**

This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second arguments includes the subnet details.

**DHCP4\_SUBNET\_DYNAMICALLY\_CHANGED %1: changed selected subnet %2 to subnet %3 from shared network %4 for**

This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

**DHCP4\_SUBNET\_DYNAMICALLY\_CHANGED (1) %1: changed selected subnet %2 to subnet %3 from shared network %4**

This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

**DHCP4\_SUBNET\_SELECTED %1: the subnet with ID %2 was selected for client assignments**

This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

**DHCP4\_SUBNET\_SELECTED (1) %1: the subnet with ID %2 was selected for client assignments**

This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

**DHCP4\_SUBNET\_SELECTION\_FAILED %1: failed to select subnet for the client**

This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The server will not be able to offer any lease to the client and will drop its message if the received message was DHCPDISCOVER, and will send DHCPNAK if the received message was DHCPREQUEST. The argument includes the client and the transaction identification information.

**DHCP4\_SUBNET\_SELECTION\_FAILED (1) %1: failed to select subnet for the client**

This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The server will not be able to offer any lease to the client and will drop its message if the received message was DHCPDISCOVER, and will send DHCPNAK if the received message was DHCPREQUEST. The argument includes the client and the transaction identification information.

## DHCP6 Module

**DHCP6\_ACTIVATE\_INTERFACE activating interface %1**

This message is printed when DHCPv6 server enabled an interface to be used to receive DHCPv6 traffic. IPv6 socket on this interface will be opened once Interface Manager starts up procedure of opening sockets.

**DHCP6\_ACTIVATE\_INTERFACE (1) activating interface %1**

This message is printed when DHCPv6 server enabled an interface to be used to receive DHCPv6 traffic. IPv6 socket on this interface will be opened once Interface Manager starts up procedure of opening sockets.

**DHCP6\_ADD\_GLOBAL\_STATUS\_CODE %1: adding Status Code to DHCPv6 packet: %2**

This message is logged when the server is adding the top-level Status Code option. The first argument includes the client and the transaction identification information. The second argument includes the details of the status code.

**DHCP6\_ADD\_GLOBAL\_STATUS\_CODE (1) %1: adding Status Code to DHCPv6 packet: %2**

This message is logged when the server is adding the top-level Status Code option. The first argument includes the client and the transaction identification information. The second argument includes the details of the status code.

**DHCP6\_ADD\_STATUS\_CODE\_FOR\_IA %1: adding Status Code to IA with iaid=%2: %3**

This message is logged when the server is adding the Status Code option to an IA. The first argument includes the client and the transaction identification information. The second argument specifies the IAID. The third argument includes the details of the status code.

**DHCP6\_ADD\_STATUS\_CODE\_FOR\_IA (1) %1: adding Status Code to IA with iaid=%2: %3**

This message is logged when the server is adding the Status Code option to an IA. The first argument includes the client and the transaction identification information. The second argument specifies the IAID. The third argument includes the details of the status code.

**DHCP6\_ALREADY\_RUNNING %1 already running? %2**

This is an error message that occurs when the DHCPv6 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv6 process name, the second contains the PID and PID file.

**DHCP6\_ALREADY\_RUNNING (1) %1 already running? %2**

This is an error message that occurs when the DHCPv6 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv6 process name, the second contains the PID and PID file.

**DHCP6\_BUFFER\_RECEIVED received buffer from %1:%2 to %3:%4 over interface %5**

This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination addresses/ports.

**DHCP6\_BUFFER\_RECEIVED (1) received buffer from %1:%2 to %3:%4 over interface %5**

This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination addresses/ports.

**DHCP6\_BUFFER\_UNPACK parsing buffer received from %1 to %2 over interface %3**

This debug message is issued when the server starts parsing the received buffer holding the DHCPv6 message. The arguments specify the source and destination addresses as well as the interface over which the buffer has been received.

**DHCP6\_BUFFER\_UNPACK (1) parsing buffer received from %1 to %2 over interface %3**

This debug message is issued when the server starts parsing the received buffer holding the DHCPv6 message. The arguments specify the source and destination addresses as well as the interface over which the buffer has been received.

**DHCP6\_BUFFER\_WAIT\_SIGNAL signal received while waiting for next packet, next waiting signal is %1**

This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets. The argument specifies the next signal to be handled by the server.

**DHCP6\_BUFFER\_WAIT\_SIGNAL (1) signal received while waiting for next packet, next waiting signal is %1**

This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets. The argument specifies the next signal to be handled by the server.

**DHCP6\_CLASS\_ASSIGNED %1: client packet has been assigned to the following class(es): %2**

This debug message informs that incoming packet has been assigned to specified class or classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

**DHCP6\_CLASS\_ASSIGNED (1) %1: client packet has been assigned to the following class(es): %2**

This debug message informs that incoming packet has been assigned to specified class or classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

**DHCP6\_CLASS\_UNCONFIGURED %1: client packet belongs to an unconfigured class: %2**

This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

**DHCP6\_CLASS\_UNCONFIGURED (1) %1: client packet belongs to an unconfigured class: %2**

This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

**DHCP6\_CLASS\_UNDEFINED required class %1 has no definition**

This debug message informs that a class is listed for required evaluation but has no definition.

**DHCP6\_CLASS\_UNDEFINED (1) required class %1 has no definition**

This debug message informs that a class is listed for required evaluation but has no definition.

**DHCP6\_CLASS\_UNTESTABLE required class %1 has no test expression**

This debug message informs that a class was listed for required evaluation but its definition does not include a test expression to evaluate.

**DHCP6\_CLASS\_UNTESTABLE (1) required class %1 has no test expression**

This debug message informs that a class was listed for required evaluation but its definition does not include a test expression to evaluate.

**DHCP6\_COMMAND\_RECEIVED received command %1, arguments: %2**

A debug message listing the command (and possible arguments) received from the Kea control system by the IPv6 DHCP server.

**DHCP6\_COMMAND\_RECEIVED (1) received command %1, arguments: %2**

A debug message listing the command (and possible arguments) received from the Kea control system by the IPv6 DHCP server.

**DHCP6\_CONFIG\_COMPLETE DHCPv6 server has completed configuration: %1**

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

**DHCP6\_CONFIG\_COMPLETE (1) DHCPv6 server has completed configuration: %1**

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

**DHCP6\_CONFIG\_LOAD\_FAIL configuration error using file: %1, reason: %2**

This error message indicates that the DHCPv6 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

**DHCP6\_CONFIG\_LOAD\_FAIL (1) configuration error using file: %1, reason: %2**

This error message indicates that the DHCPv6 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

**DHCP6\_CONFIG\_PACKET\_QUEUE DHCPv6 packet queue info after configuration: %1**

This debug message is emitted during DHCPv6 server configuration, immediately after configuring the DHCPv6 packet queue. The information shown depends upon the packet queue type selected.

**DHCP6\_CONFIG\_PACKET\_QUEUE (1) DHCPv6 packet queue info after configuration: %1**

This debug message is emitted during DHCPv6 server configuration, immediately after configuring the DHCPv6 packet queue. The information shown depends upon the packet queue type selected.

**DHCP6\_CONFIG\_RECEIVED received configuration: %1**

A debug message listing the configuration received by the DHCPv6 server. The source of that configuration depends on used configuration backend.

**DHCP6\_CONFIG\_RECEIVED (1) received configuration: %1**

A debug message listing the configuration received by the DHCPv6 server. The source of that configuration depends on used configuration backend.

**DHCP6\_CONFIG\_START DHCPv6 server is processing the following configuration: %1**

This is a debug message that is issued every time the server receives a configuration. That happens start up and also when a server configuration change is committed by the administrator.

**DHCP6\_CONFIG\_START (1) DHCPv6 server is processing the following configuration: %1**

This is a debug message that is issued every time the server receives a configuration. That happens start up and also when a server configuration change is committed by the administrator.

**DHCP6\_CONFIG\_UPDATE updated configuration received: %1**

A debug message indicating that the IPv6 DHCP server has received an updated configuration from the Kea configuration system.

**DHCP6\_CONFIG\_UPDATE (1) updated configuration received: %1**

A debug message indicating that the IPv6 DHCP server has received an updated configuration from the Kea configuration system.

**DHCP6\_DB\_BACKEND\_STARTED lease database started (type: %1, name: %2)**

This informational message is printed every time the IPv6 DHCP server is started. It indicates what database backend type is being to store lease and other information.

**DHCP6\_DB\_BACKEND\_STARTED (1) lease database started (type: %1, name: %2)**

This informational message is printed every time the IPv6 DHCP server is started. It indicates what database backend type is being to store lease and other information.

**DHCP6\_DB\_RECONNECT\_ATTEMPT\_FAILED database reconnect failed: %1**

An error message indicating that an attempt to reconnect to the lease and/or host data bases has failed. This occurs after connectivity to either one has been lost and an automatic attempt to reconnect has failed.

**DHCP6\_DB\_RECONNECT\_ATTEMPT\_FAILED (1) database reconnect failed: %1**

An error message indicating that an attempt to reconnect to the lease and/or host data bases has failed. This occurs after connectivity to either one has been lost and an automatic attempt to reconnect has failed.

**DHCP6\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE scheduling attempt %1 of %2 in %3 seconds**

An informational message indicating that the server is scheduling the next attempt to reconnect to its lease and/or host databases. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

**DHCP6\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE (1) scheduling attempt %1 of %2 in %3 seconds**

An informational message indicating that the server is scheduling the next attempt to reconnect to its lease and/or host databases. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

**DHCP6\_DB\_RECONNECT\_DISABLED database reconnect is disabled: max-reconnect-tries %1, reconnect-wait-time %2**

This is an informational message indicating that connectivity to either the lease or host database or both and that automatic reconnect is not enabled.

**DHCP6\_DB\_RECONNECT\_DISABLED (1) database reconnect is disabled: max-reconnect-tries %1, reconnect-wait-time %2**

This is an informational message indicating that connectivity to either the lease or host database or both and that automatic reconnect is not enabled.

**DHCP6\_DB\_RECONNECT\_NO\_DB\_CTL unexpected error in database reconnect**

This is an error message indicating a programmatic error that should not occur. It will prohibit the server from attempting to reconnect to its databases if connectivity is lost, and the server will exit. This error should be reported.

**DHCP6\_DB\_RECONNECT\_NO\_DB\_CTL (1) unexpected error in database reconnect**

This is an error message indicating a programmatic error that should not occur. It will prohibit the server from attempting to reconnect to its databases if connectivity is lost, and the server will exit. This error should be reported.

**DHCP6\_DB\_RECONNECT\_RETRIES\_EXHAUSTED maximum number of database reconnect attempts: %1, has been exhausted**

This error indicates that the server is shutting down after failing to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. Loss of connectivity is typically a network or database server issue.

**DHCP6\_DB\_RECONNECT\_RETRIES\_EXHAUSTED (1) maximum number of database reconnect attempts: %1, has been exhausted**

This error indicates that the server is shutting down after failing to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. Loss of connectivity is typically a network or database server issue.

**DHCP6\_DDNS\_CREATE\_ADD\_NAME\_CHANGE\_REQUEST created name change request: %1**

This debug message is logged when the new Name Change Request has been created to perform the DNS Update, which adds new RRs.

**DHCP6\_DDNS\_CREATE\_ADD\_NAME\_CHANGE\_REQUEST (1) created name change request: %1**

This debug message is logged when the new Name Change Request has been created to perform the DNS Update, which adds new RRs.

**DHCP6\_DDNS\_FQDN\_GENERATED %1: generated FQDN for the client: %2**

This debug message is logged when the server generated FQDN (name) for the client which message is processed. The names may be generated by the server when required by the server's policy or when the client doesn't provide any specific FQDN in its message to the server. The first argument includes the client and transaction identification information. The second argument includes the generated FQDN.

**DHCP6\_DDNS\_FQDN\_GENERATED (1) %1: generated FQDN for the client: %2**

This debug message is logged when the server generated FQDN (name) for the client which message is processed. The names may be generated by the server when required by the server's policy or when the client doesn't provide any specific FQDN in its message to the server. The first argument includes the client and transaction identification information. The second argument includes the generated FQDN.

**DHCP6\_DDNS\_GENERATED\_FQDN\_UPDATE\_FAIL %1: failed to update the lease using address %2, after generating FQDN**

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server from the acquired address. The first argument includes the client and the transaction identification information. The second argument is a leased address. The third argument includes the reason for the failure.

**DHCP6\_DDNS\_GENERATED\_FQDN\_UPDATE\_FAIL (1) %1: failed to update the lease using address %2, after generating FQDN**

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server from the acquired address. The first argument includes the client and the transaction identification information. The second argument is a leased address. The third argument includes the reason for the failure.

**DHCP6\_DDNS\_GENERATE\_FQDN %1: client did not send a FQDN option; FQDN will be**

generated for the client. This debug message is issued when the server did not receive a FQDN option from the client and client name replacement is enabled. This provides a means to create DNS entries for unsophisticated clients.

**DHCP6\_DDNS\_GENERATE\_FQDN (1) %1: client did not send a FQDN option; FQDN will be**

generated for the client. This debug message is issued when the server did not receive a FQDN option from the client and client name replacement is enabled. This provides a means to create DNS entries for unsophisticated clients.

**DHCP6\_DDNS\_LEASE\_RENEW\_FQDN\_CHANGE FQDN %1: FQDN for the renewed lease: %2 has changed. New values: %3**

This debug message is logged when FQDN mapping for a particular lease has been changed by the recent Renew message. This mapping will be changed in DNS. The first argument includes the client and the transaction identification information. The second argument holds the details about the lease for which the FQDN information and/or mappings have changed. The remaining arguments hold the new FQDN information and flags for mappings.

**DHCP6\_DDNS\_LEASE\_RENEW\_FQDN\_CHANGE (1) FQDN %1: FQDN for the renewed lease: %2 has changed. New values: %3**

This debug message is logged when FQDN mapping for a particular lease has been changed by the recent Renew message. This mapping will be changed in DNS. The first argument includes the client and the transaction identification information. The second argument holds the details about the lease for which the FQDN information and/or mappings have changed. The remaining arguments hold the new FQDN information and flags for mappings.

**DHCP6\_DDNS\_RECEIVE\_FQDN %1: received DHCPv6 Client FQDN option: %2**

This debug message is logged when server has found the DHCPv6 Client FQDN Option sent by a client and started processing it. The first argument includes the client and transaction identification information. The second argument includes the received FQDN.

**DHCP6\_DDNS\_RECEIVE\_FQDN (1) %1: received DHCPv6 Client FQDN option: %2**

This debug message is logged when server has found the DHCPv6 Client FQDN Option sent by a client and started processing it. The first argument includes the client and transaction identification information. The second argument includes the received FQDN.

**DHCP6\_DDNS\_REQUEST\_SEND\_FAILED failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2**

This error message indicates that IPv6 DHCP server failed to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

**DHCP6\_DDNS\_REQUEST\_SEND\_FAILED (1) failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2**

This error message indicates that IPv6 DHCP server failed to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

**DHCP6\_DDNS\_RESPONSE\_FQDN\_DATA %1: including FQDN option in the server's response: %2**

This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

**DHCP6\_DDNS\_RESPONSE\_FQDN\_DATA (1) %1: including FQDN option in the server's response: %2**

This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

**DHCP6\_DDNS\_SEND\_FQDN sending DHCPv6 Client FQDN Option to the client: %1**

This debug message is logged when server includes an DHCPv6 Client FQDN Option in its response to the client.

**DHCP6\_DDNS\_SEND\_FQDN (1) sending DHCPv6 Client FQDN Option to the client: %1**

This debug message is logged when server includes an DHCPv6 Client FQDN Option in its response to the client.

**DHCP6\_DEACTIVATE\_INTERFACE deactivate interface %1**

This message is printed when DHCPv6 server disables an interface from being used to receive DHCPv6 traffic. Sockets on this interface will not be opened by the Interface Manager until interface is enabled.

**DHCP6\_DEACTIVATE\_INTERFACE (1) deactivate interface %1**

This message is printed when DHCPv6 server disables an interface from being used to receive DHCPv6 traffic. Sockets on this interface will not be opened by the Interface Manager until interface is enabled.

**DHCP6\_DECLINE\_FAIL\_DUID\_MISMATCH Client %1 sent DECLINE for address %2, but it belongs to client with DUID %3**

This informational message is printed when a client attempts to decline a lease, but that lease belongs to a different client. The decline request will be rejected.

**DHCP6\_DECLINE\_FAIL\_DUID\_MISMATCH (1) Client %1 sent DECLINE for address %2, but it belongs to client with DUID %3**

This informational message is printed when a client attempts to decline a lease, but that lease belongs to a different client. The decline request will be rejected.

**DHCP6\_DECLINE\_FAIL\_IAID\_MISMATCH Client %1 sent DECLINE for address %2, but used a wrong IAID (%3), instead of %4**

This informational message is printed when a client attempts to decline a lease. The server has a lease for this address, it belongs to this client, but the recorded IAID does not match what client has sent. This means the server will reject this Decline.



**DHCP6\_DECLINE\_FAIL\_IAID\_MISMATCH (1) Client %1 sent DECLINE for address %2, but used a wrong IAID (%3), instead of %4**

This informational message is printed when a client attempts to decline a lease. The server has a lease for this address, it belongs to this client, but the recorded IAID does not match what client has sent. This means the server will reject this Decline.

**DHCP6\_DECLINE\_FAIL\_LEASE\_WITHOUT\_DUID Client %1 sent DECLINE for address %2, but the associated lease has no DUID**

This error condition likely indicates database corruption, as every IPv6 lease is supposed to have a DUID, even if it is an empty one.

**DHCP6\_DECLINE\_FAIL\_LEASE\_WITHOUT\_DUID (1) Client %1 sent DECLINE for address %2, but the associated lease has no DUID**

This error condition likely indicates database corruption, as every IPv6 lease is supposed to have a DUID, even if it is an empty one.

**DHCP6\_DECLINE\_FAIL\_NO\_LEASE Client %1 sent DECLINE for address %2, but there's no lease for it**

This informational message is printed when a client tried to decline an address, but the server has no lease for said address. This means that the server's and client's perception of the leases are different. The likely causes of this could be: a confused (e.g. skewed clock) or broken client (e.g. client moved to a different location and didn't notice) or possibly an attack (a rogue client is trying to decline random addresses). The server will inform the client that his decline request was rejected and client should be able to recover from that.

**DHCP6\_DECLINE\_FAIL\_NO\_LEASE (1) Client %1 sent DECLINE for address %2, but there's no lease for it**

This informational message is printed when a client tried to decline an address, but the server has no lease for said address. This means that the server's and client's perception of the leases are different. The likely causes of this could be: a confused (e.g. skewed clock) or broken client (e.g. client moved to a different location and didn't notice) or possibly an attack (a rogue client is trying to decline random addresses). The server will inform the client that his decline request was rejected and client should be able to recover from that.

**DHCP6\_DECLINE\_LEASE Client %1 sent DECLINE for address %2 and the server marked it as declined. The lease will be re-assigned**

This informational message indicates that the client leased an address, but discovered that it is being used by some other device and reported this to the server by sending a Decline message. The server marked the lease as declined. This likely indicates a misconfiguration in the network. Either the server is configured with an incorrect pool or there are devices that have statically assigned addresses that are supposed to be assigned by the DHCP server. Both client (will request a different address) and server (will recover the lease after decline-probation-time elapses) will recover automatically. However, if the underlying problem is not solved, the conditions leading to this message may reappear.

**DHCP6\_DECLINE\_LEASE (1) Client %1 sent DECLINE for address %2 and the server marked it as declined. The lease will be re-assigned**

This informational message indicates that the client leased an address, but discovered that it is being used by some other device and reported this to the server by sending a Decline message. The server marked the lease as declined. This likely indicates a misconfiguration in the network. Either the server is configured with an incorrect pool or there are devices that have statically assigned addresses that are supposed to be assigned by the DHCP server. Both client (will request a different address) and server (will recover the lease after decline-probation-time elapses) will recover automatically. However, if the underlying problem is not solved, the conditions leading to this message may reappear.

**DHCP6\_DECLINE\_PROCESS\_IA Processing of IA (IAID: %1) from client %2 started.**

This debug message is printed when the server starts processing an IA\_NA option received in Decline message. It's expected that the option will contain an address that is being declined. Specific information will be printed in a separate message.

**DHCP6\_DECLINE\_PROCESS\_IA (1) Processing of IA (IAID: %1) from client %2 started.**

This debug message is printed when the server starts processing an IA\_NA option received in Decline message. It's expected that the option will contain an address that is being declined. Specific information will be printed in a separate message.

**DHCP6\_DHCP4O6\_PACKET\_RECEIVED received DHCPv4o6 packet from DHCPv6 server (type %1) for %2 port %3 on interface %4**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv6 server over inter-process communication.

**DHCP6\_DHCP4O6\_PACKET\_RECEIVED (1) received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 port %3 on**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

**DHCP6\_DHCP4O6\_PACKET\_RECEIVED (2) received DHCPv4o6 packet from DHCPv6 server (type %1) for %2 port %3 on**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv6 server over inter-process communication.

**DHCP6\_DHCP4O6\_PACKET\_RECEIVED (3) received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 port %3 on**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

**DHCP6\_DHCP4O6\_RECEIVE\_FAIL failed to receive DHCPv4o6: %1**

This debug message indicates the inter-process communication with the DHCPv4 server failed. The reason for the error is included in the message.

**DHCP6\_DHCP4O6\_RECEIVE\_FAIL (1) failed to receive DHCPv4o6: %1**

This debug message indicates the inter-process communication with the DHCPv4 server failed. The reason for the error is included in the message.

**DHCP6\_DHCP4O6\_RECEIVING receiving DHCPv4o6 packet from DHCPv4 server**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication socket.

**DHCP6\_DHCP4O6\_RECEIVING (1) receiving DHCPv4o6 packet from DHCPv4 server**

This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication socket.

**DHCP6\_DHCP4O6\_SEND\_FAIL failed to send DHCPv4o6 packet: %1**

This error is output if the IPv6 DHCP server fails to send an assembled DHCPv4o6 message to a client. The reason for the error is included in the message.

**DHCP6\_DHCP4O6\_SEND\_FAIL (1) failed to send DHCPv4o6 packet: %1**

This error is output if the IPv6 DHCP server fails to send an assembled DHCPv4o6 message to a client. The reason for the error is included in the message.

**DHCP6\_DYNAMIC\_RECONFIGURATION initiate server reconfiguration using file: %1, after receiving SIGHUP signal**

This is the info message logged when the DHCPv6 server starts reconfiguration as a result of receiving SIGHUP signal.

**DHCP6\_DYNAMIC\_RECONFIGURATION (1) initiate server reconfiguration using file: %1, after receiving SIGHUP signal**

This is the info message logged when the DHCPv6 server starts reconfiguration as a result of receiving SIGHUP signal.

**DHCP6\_DYNAMIC\_RECONFIGURATION\_FAIL dynamic server reconfiguration failed with file: %1**

This is an error message logged when the dynamic reconfiguration of the DHCP server failed.

**DHCP6\_DYNAMIC\_RECONFIGURATION\_FAIL (1) dynamic server reconfiguration failed with file: %1**

This is an error message logged when the dynamic reconfiguration of the DHCP server failed.

**DHCP6\_FLEX\_ID flexible identifier generated for incoming packet: %1**

This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

---

**DHCP6\_FLEX\_ID (1) flexible identifier generated for incoming packet: %1**

This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

**DHCP6\_HANDLE\_SIGNAL\_EXCEPTION An exception was thrown while handing signal: %1**

This error message is printed when an exception was raised during signal processing. This likely indicates a coding error and should be reported to ISC.

**DHCP6\_HANDLE\_SIGNAL\_EXCEPTION (1) An exception was thrown while handing signal: %1**

This error message is printed when an exception was raised during signal processing. This likely indicates a coding error and should be reported to ISC.

**DHCP6\_HOOKS\_LIBS\_RELOAD\_FAIL reload of hooks libraries failed**

A "libreload" command was issued to reload the hooks libraries but for some reason the reload failed. Other error messages issued from the hooks framework will indicate the nature of the problem.

**DHCP6\_HOOKS\_LIBS\_RELOAD\_FAIL (1) reload of hooks libraries failed**

A "libreload" command was issued to reload the hooks libraries but for some reason the reload failed. Other error messages issued from the hooks framework will indicate the nature of the problem.

**DHCP6\_HOOK\_BUFFER\_RCVD\_DROP received buffer from %1 to %2 over interface %3 was dropped because a callout set**

This debug message is printed when a callout installed on buffer6\_receive hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

**DHCP6\_HOOK\_BUFFER\_RCVD\_DROP (1) received buffer from %1 to %2 over interface %3 was dropped because a callout set**

This debug message is printed when a callout installed on buffer6\_receive hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

**DHCP6\_HOOK\_BUFFER\_RCVD\_SKIP received buffer from %1 to %2 over interface %3 is not parsed because a callout set**

This debug message is printed when a callout installed on buffer6\_receive hook point set the next step status to skip. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

**DHCP6\_HOOK\_BUFFER\_RCVD\_SKIP (1) received buffer from %1 to %2 over interface %3 is not parsed because a callout set**

This debug message is printed when a callout installed on buffer6\_receive hook point set the next step status to skip. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

**DHCP6\_HOOK\_BUFFER\_SEND\_SKIP %1: prepared DHCPv6 response was dropped because a callout set the next step to SKIP**

This debug message is printed when a callout installed on buffer6\_send hook point set the next step to SKIP value. For this particular hook point, the SKIP setting a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be send to the client. The argument includes the client and transaction identification information.

**DHCP6\_HOOK\_BUFFER\_SEND\_SKIP (1) %1: prepared DHCPv6 response was dropped because a callout set the next step to SKIP**

This debug message is printed when a callout installed on buffer6\_send hook point set the next step to SKIP value. For this particular hook point, the SKIP setting a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be send to the client. The argument includes the client and transaction identification information.

**DHCP6\_HOOK\_DECLINE\_DROP During Decline processing (client=%1, interface=%2, addr=%3) hook callout set next step**

This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6\_decline hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

**DHCP6\_HOOK\_DECLINE\_DROP (1) During Decline processing (client=%1, interface=%2, addr=%3) hook callout set next step**

This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6\_decline hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

**DHCP6\_HOOK\_DECLINE\_SKIP During Decline processing (client=%1, interface=%2, addr=%3) hook callout set status to S**

This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6\_decline hook point and one of the callouts set next step status to SKIP. The server will skip the operation of moving the lease to the declined state and will continue processing the packet. In particular, it will send a REPLY message as if the decline actually took place.

**DHCP6\_HOOK\_DECLINE\_SKIP (1) During Decline processing (client=%1, interface=%2, addr=%3) hook callout set status to S**

This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6\_decline hook point and one of the callouts set next step status to SKIP. The server will skip the operation of moving the lease to the declined state and will continue processing the packet. In particular, it will send a REPLY message as if the decline actually took place.

**DHCP6\_HOOK\_LEASE6\_RELEASE\_NA\_SKIP %1: DHCPv6 address lease was not released because a callout set the next step**

This debug message is printed when a callout installed on the lease6\_release hook point set the next step to SKIP. For this particular hook point, this setting by a callout instructs the server to not release a lease. If a client requested the release of multiples leases (by sending multiple IA options), the server will retain this particular lease and proceed with other releases as usual. The argument holds the client and transaction identification information.

**DHCP6\_HOOK\_LEASE6\_RELEASE\_NA\_SKIP (1) %1: DHCPv6 address lease was not released because a callout set the next step**

This debug message is printed when a callout installed on the lease6\_release hook point set the next step to SKIP. For this particular hook point, this setting by a callout instructs the server to not release a lease. If a client requested the release of multiples leases (by sending multiple IA options), the server will retain this particular lease and proceed with other releases as usual. The argument holds the client and transaction identification information.

**DHCP6\_HOOK\_LEASE6\_RELEASE\_PD\_SKIP %1: prefix lease was not released because a callout set the next step to SKIP**

This debug message is printed when a callout installed on lease6\_release hook point set the next step to SKIP value. For this particular hook point, that setting by a callout instructs the server to not release a lease. If client requested release of multiples leases (by sending multiple IA options), the server will retains this particular lease and will proceed with other renewals as usual. The argument holds the client and transaction identification information.

**DHCP6\_HOOK\_LEASE6\_RELEASE\_PD\_SKIP (1) %1: prefix lease was not released because a callout set the next step to SK**

This debug message is printed when a callout installed on lease6\_release hook point set the next step to SKIP value. For this particular hook point, that setting by a callout instructs the server to not release a lease. If client requested release of multiples leases (by sending multiple IA options), the server will retains this particular lease and will proceed with other renewals as usual. The argument holds the client and transaction identification information.

**DHCP6\_HOOK\_LEASES6\_COMMITTED\_DROP %1: packet is dropped, because a callout set the next step to DROP**

This debug message is printed when a callout installed on the leases6\_committed hook point sets the next step to DROP.

**DHCP6\_HOOK\_LEASES6\_COMMITTED\_DROP (1) %1: packet is dropped, because a callout set the next step to DROP**

This debug message is printed when a callout installed on the leases6\_committed hook point sets the next step to DROP.

**DHCP6\_HOOK\_LEASES6\_COMMITTED\_PARK %1: packet is parked, because a callout set the next step to PARK**

This debug message is printed when a callout installed on the lease6\_committed hook point sets the next step to PARK.

**DHCP6\_HOOK\_LEASES6\_COMMITTED\_PARK (1) %1: packet is parked, because a callout set the next step to PARK**

This debug message is printed when a callout installed on the lease6\_committed hook point sets the next step to PARK.

**DHCP6\_HOOK\_PACKET\_RCVD\_SKIP %1: packet is dropped, because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the pkt6\_receive hook point sets the next step to SKIP. For this particular hook point, the value setting instructs the server to drop the packet.

**DHCP6\_HOOK\_PACKET\_RCVD\_SKIP (1) %1: packet is dropped, because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the pkt6\_receive hook point sets the next step to SKIP. For this particular hook point, the value setting instructs the server to drop the packet.

**DHCP6\_HOOK\_PACKET\_SEND\_DROP %1: prepared DHCPv6 response was not sent because a callout set the next step to DROP**

This debug message is printed when a callout installed on the pkt6\_send hook point set the next step to DROP. For this particular hook point, the setting of the value by a callout instructs the server to drop the packet. This effectively means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease). The argument specifies the client and transaction identification information.

**DHCP6\_HOOK\_PACKET\_SEND\_DROP (1) %1: prepared DHCPv6 response was not sent because a callout set the next step to DROP**

This debug message is printed when a callout installed on the pkt6\_send hook point set the next step to DROP. For this particular hook point, the setting of the value by a callout instructs the server to drop the packet. This effectively means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease). The argument specifies the client and transaction identification information.

**DHCP6\_HOOK\_PACKET\_SEND\_SKIP %1: prepared DHCPv6 response is not built because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the pkt6\_send hook point set the next step to SKIP. For this particular hook point, the setting of the value by a callout instructs the server to not build the wire data (pack) because it was already done by the book. The argument specifies the client and transaction identification information.

**DHCP6\_HOOK\_PACKET\_SEND\_SKIP (1) %1: prepared DHCPv6 response is not built because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the pkt6\_send hook point set the next step to SKIP. For this particular hook point, the setting of the value by a callout instructs the server to not build the wire data (pack) because it was already done by the book. The argument specifies the client and transaction identification information.

**DHCP6\_HOOK\_SUBNET6\_SELECT\_DROP %1: packet was dropped because a callout set the drop flag**

This debug message is printed when a callout installed on the subnet6\_select hook point set the drop flag. For this particular hook point, the setting of the flag instructs the server to drop the received packet. The argument holds the client and transaction identification information.

**DHCP6\_HOOK\_SUBNET6\_SELECT\_DROP (1) %1: packet was dropped because a callout set the drop flag**

This debug message is printed when a callout installed on the subnet6\_select hook point set the drop flag. For this particular hook point, the setting of the flag instructs the server to drop the received packet. The argument holds the client and transaction identification information.

**DHCP6\_HOOK\_SUBNET6\_SELECT\_SKIP %1: no subnet was selected because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the subnet6\_select hook point set the next step to SKIP value. For this particular hook point, the setting of this value instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses or prefixes will be assigned. The argument holds the client and transaction identification information.

**DHCP6\_HOOK\_SUBNET6\_SELECT\_SKIP (1) %1: no subnet was selected because a callout set the next step to SKIP**

This debug message is printed when a callout installed on the subnet6\_select hook point set the next step to SKIP value. For this particular hook point, the setting of this value instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses or prefixes will be assigned. The argument holds the client and transaction identification information.

**DHCP6\_INIT\_FAIL failed to initialize Kea server: %1**

The server has failed to establish communication with the rest of Kea, failed to read JSON configuration file or encountered any other critical issue that prevents it from starting up properly. Attached error message provides more details about the issue.

**DHCP6\_INIT\_FAIL (1) failed to initialize Kea server: %1**

The server has failed to establish communication with the rest of Kea, failed to read JSON configuration file or encountered any other critical issue that prevents it from starting up properly. Attached error message provides more details about the issue.

**DHCP6\_LEASE\_ADVERT %1: lease for address %2 and iaid=%3 will be advertised**

This informational message indicates that the server will advertise an address to the client in the ADVERTISE message. The client will request allocation of this address with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

**DHCP6\_LEASE\_ADVERT (1) %1: lease for address %2 and iaid=%3 will be advertised**

This informational message indicates that the server will advertise an address to the client in the ADVERTISE message. The client will request allocation of this address with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

**DHCP6\_LEASE\_ADVERT\_FAIL %1: failed to advertise an address lease for iaid=%2**

This message indicates that in response to a received SOLICIT, the server failed to advertise a non-temporary lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

**DHCP6\_LEASE\_ADVERT\_FAIL (1) %1: failed to advertise an address lease for iaid=%2**

This message indicates that in response to a received SOLICIT, the server failed to advertise a non-temporary lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

**DHCP6\_LEASE\_ALLOC %1: lease for address %2 and iaid=%3 has been allocated**

This informational message indicates that in response to a client's REQUEST message, the server successfully granted a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

**DHCP6\_LEASE\_ALLOC (1) %1: lease for address %2 and iaid=%3 has been allocated**

This informational message indicates that in response to a client's REQUEST message, the server successfully granted a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

**DHCP6\_LEASE\_ALLOC\_FAIL %1: failed to grant an address lease for iaid=%2**

This message indicates that in response to a received REQUEST, the server failed to grant a non-temporary address lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

**DHCP6\_LEASE\_ALLOC\_FAIL (1) %1: failed to grant an address lease for iaid=%2**

This message indicates that in response to a received REQUEST, the server failed to grant a non-temporary address lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

**DHCP6\_LEASE\_DATA %1: detailed lease information for iaid=%2: %3**

This debug message is used to print the detailed information about the allocated lease or a lease which will be advertised to the client. The first argument holds the client and the transaction identification information. The second argument holds the IAID. The third argument holds the detailed lease information.

**DHCP6\_LEASE\_DATA (1) %1: detailed lease information for iaid=%2: %3**

This debug message is used to print the detailed information about the allocated lease or a lease which will be advertised to the client. The first argument holds the client and the transaction identification information. The second argument holds the IAID. The third argument holds the detailed lease information.

**DHCP6\_LEASE\_NA\_WITHOUT\_DUID %1: address lease for address %2 does not have a DUID**

This error message indicates a database consistency problem. The lease database has an entry indicating that the given address is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes the client and transaction identification information. The second argument holds the address to be released.

**DHCP6\_LEASE\_NA\_WITHOUT\_DUID (1) %1: address lease for address %2 does not have a DUID**

This error message indicates a database consistency problem. The lease database has an entry indicating that the given address is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes the client and transaction identification information. The second argument holds the address to be released.

**DHCP6\_LEASE\_PD\_WITHOUT\_DUID %1: lease for prefix %2/%3 does not have a DUID**

This error message indicates a database consistency failure. The lease database has an entry indicating that the given prefix is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes client and transaction identification information. The second and third argument hold the prefix and the prefix length.

**DHCP6\_LEASE\_PD\_WITHOUT\_DUID (1) %1: lease for prefix %2/%3 does not have a DUID**

This error message indicates a database consistency failure. The lease database has an entry indicating that the given prefix is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes client and transaction identification information. The second and third argument hold the prefix and the prefix length.

**DHCP6\_LEASE\_RENEW %1: lease for address %2 and iaid=%3 has been allocated**

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

**DHCP6\_LEASE\_RENEW (1) %1: lease for address %2 and iaid=%3 has been allocated**

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

**DHCP6\_NOT\_RUNNING IPv6 DHCP server is not running**

A warning message is issued when an attempt is made to shut down the IPv6 DHCP server but it is not running.

**DHCP6\_NOT\_RUNNING (1) IPv6 DHCP server is not running**

A warning message is issued when an attempt is made to shut down the IPv6 DHCP server but it is not running.

**DHCP6\_NO\_INTERFACES failed to detect any network interfaces**

During startup the IPv6 DHCP server failed to detect any network interfaces and is therefore shutting down.

**DHCP6\_NO\_INTERFACES (1) failed to detect any network interfaces**

During startup the IPv6 DHCP server failed to detect any network interfaces and is therefore shutting down.

**DHCP6\_NO\_SOCKETS\_OPEN no interface configured to listen to DHCP traffic**

This warning message is issued when current server configuration specifies no interfaces that server should listen on, or specified interfaces are not configured to receive the traffic.

**DHCP6\_NO\_SOCKETS\_OPEN (1) no interface configured to listen to DHCP traffic**

This warning message is issued when current server configuration specifies no interfaces that server should listen on, or specified interfaces are not configured to receive the traffic.

**DHCP6\_OPEN\_SOCKET opening sockets on port %1**

A debug message issued during startup, this indicates that the IPv6 DHCP server is about to open sockets on the specified port.

**DHCP6\_OPEN\_SOCKET (1) opening sockets on port %1**

A debug message issued during startup, this indicates that the IPv6 DHCP server is about to open sockets on the specified port.

**DHCP6\_OPEN\_SOCKET\_FAIL failed to open socket: %1**

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

**DHCP6\_OPEN\_SOCKET\_FAIL (1) failed to open socket: %1**

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

**DHCP6\_PACKET\_DROP\_DHCP\_DISABLED %1: DHCP service is globally disabled**

This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

**DHCP6\_PACKET\_DROP\_DHCP\_DISABLED (1) %1: DHCP service is globally disabled**

This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

**DHCP6\_PACKET\_DROP\_PARSE\_FAIL failed to parse packet from %1 to %2, received over interface %3, reason: %4**

The DHCPv6 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

**DHCP6\_PACKET\_DROP\_PARSE\_FAIL (1) failed to parse packet from %1 to %2, received over interface %3, reason: %4**

The DHCPv6 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

**DHCP6\_PACKET\_DROP\_SERVERID\_MISMATCH %1: dropping packet with server identifier: %2, server is using: %3**

A debug message noting that server has received message with server identifier option that not matching server identifier that server is using.

**DHCP6\_PACKET\_DROP\_SERVERID\_MISMATCH (1) %1: dropping packet with server identifier: %2, server is using: %3**

A debug message noting that server has received message with server identifier option that not matching server identifier that server is using.

**DHCP6\_PACKET\_DROP\_UNICAST %1: dropping unicast %2 packet as this packet should be sent to multicast**

This debug message is issued when the server drops the unicast packet, because packets of this type must be sent to multicast. The first argument specifies the client and transaction identification information, the second argument specifies packet type.

**DHCP6\_PACKET\_DROP\_UNICAST (1) %1: dropping unicast %2 packet as this packet should be sent to multicast**

This debug message is issued when the server drops the unicast packet, because packets of this type must be sent to multicast. The first argument specifies the client and transaction identification information, the second argument specifies packet type.

---



**DHCP6\_PACKET\_OPTIONS\_SKIPPED An error unpacking an option, caused subsequent options to be skipped: %1**

A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will server will still attempt to service the packet.

**DHCP6\_PACKET\_OPTIONS\_SKIPPED (1) An error unpacking an option, caused subsequent options to be skipped: %1**

A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will server will still attempt to service the packet.

**DHCP6\_PACKET\_PROCESS\_EXCEPTION exception occurred during packet processing**

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

**DHCP6\_PACKET\_PROCESS\_EXCEPTION (1) exception occurred during packet processing**

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

**DHCP6\_PACKET\_PROCESS\_FAIL processing of %1 message received from %2 failed: %3**

This is a general catch-all message indicating that the processing of the specified packet type from the indicated address failed. The reason is given in the message. The server will not send a response but will instead ignore the packet.

**DHCP6\_PACKET\_PROCESS\_FAIL (1) processing of %1 message received from %2 failed: %3**

This is a general catch-all message indicating that the processing of the specified packet type from the indicated address failed. The reason is given in the message. The server will not send a response but will instead ignore the packet.

**DHCP6\_PACKET\_PROCESS\_STD\_EXCEPTION exception occurred during packet processing: %1**

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

**DHCP6\_PACKET\_PROCESS\_STD\_EXCEPTION (1) exception occurred during packet processing: %1**

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

**DHCP6\_PACKET\_RECEIVED %1: %2 (type %3) received from %4 to %5 on interface %6**

A debug message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv6 message and its numeric type respectively. The remaining arguments specify the source address, destination IP address and the name of the interface on which the message has been received.

**DHCP6\_PACKET\_RECEIVED (1) %1: %2 (type %3) received from %4 to %5 on interface %6**

A debug message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv6 message and its numeric type respectively. The remaining arguments specify the source address, destination IP address and the name of the interface on which the message has been received.

**DHCP6\_PACKET\_RECEIVE\_FAIL error on attempt to receive packet: %1**

The IPv6 DHCP server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

**DHCP6\_PACKET\_RECEIVE\_FAIL (1) error on attempt to receive packet: %1**

The IPv6 DHCP server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

**DHCP6\_PACKET\_SEND\_FAIL failed to send DHCPv6 packet: %1**

This error is output if the IPv6 DHCP server fails to send an assembled DHCP message to a client. The reason for the error is included in the message.

**DHCP6\_PACKET\_SEND\_FAIL (1) failed to send DHCPv6 packet: %1**

This error is output if the IPv6 DHCP server fails to send an assembled DHCP message to a client. The reason for the error is included in the message.

---

**DHCP6\_PACK\_FAIL failed to assemble response correctly**

This error is output if the server failed to assemble the data to be returned to the client into a valid packet. The reason is most likely to be to a programming error: please raise a bug report.

**DHCP6\_PACK\_FAIL (1) failed to assemble response correctly**

This error is output if the server failed to assemble the data to be returned to the client into a valid packet. The reason is most likely to be to a programming error: please raise a bug report.

**DHCP6\_PARSER\_COMMIT\_EXCEPTION parser failed to commit changes**

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

**DHCP6\_PARSER\_COMMIT\_EXCEPTION (1) parser failed to commit changes**

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

**DHCP6\_PARSER\_COMMIT\_FAIL parser failed to commit changes: %1**

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

**DHCP6\_PARSER\_COMMIT\_FAIL (1) parser failed to commit changes: %1**

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

**DHCP6\_PARSER\_EXCEPTION failed to create or run parser for configuration element %1**

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information.

The most likely cause of this is that the specification file for the server (which details the allowable contents of the configuration) is not correct for this version of Kea. This may be the result of an interrupted installation of an update to Kea.

**DHCP6\_PARSER\_EXCEPTION (1) failed to create or run parser for configuration element %1**

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information.

The most likely cause of this is that the specification file for the server (which details the allowable contents of the configuration) is not correct for this version of Kea. This may be the result of an interrupted installation of an update to Kea.

**DHCP6\_PARSER\_FAIL failed to create or run parser for configuration element %1: %2**

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

**DHCP6\_PARSER\_FAIL (1) failed to create or run parser for configuration element %1: %2**

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

**DHCP6\_PD\_LEASE\_ADVERT %1: lease for prefix %2/%3 and iaid=%4 will be advertised**

This informational message indicates that the server will advertise a prefix to the client in the ADVERTISE message. The client will request allocation of this prefix with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and IAID.

**DHCP6\_PD\_LEASE\_ADVERT (1) %1: lease for prefix %2/%3 and iaid=%4 will be advertised**

This informational message indicates that the server will advertise a prefix to the client in the ADVERTISE message. The client will request allocation of this prefix with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and IAID.

**DHCP6\_PD\_LEASE\_ADVERT\_FAIL %1: failed to advertise a prefix lease for iaid=%2**

This message indicates that in response to a received SOLICIT, the server failed to advertise a prefix lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

**DHCP6\_PD\_LEASE\_ADVERT\_FAIL (1) %1: failed to advertise a prefix lease for iaid=%2**

This message indicates that in response to a received SOLICIT, the server failed to advertise a prefix lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

**DHCP6\_PD\_LEASE\_ALLOC %1: lease for prefix %2/%3 and iaid=%4 has been allocated**

This informational message indicates that in response to a client's REQUEST message, the server successfully granted a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and and IAID.

**DHCP6\_PD\_LEASE\_ALLOC (1) %1: lease for prefix %2/%3 and iaid=%4 has been allocated**

This informational message indicates that in response to a client's REQUEST message, the server successfully granted a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and and IAID.

**DHCP6\_PD\_LEASE\_ALLOC\_FAIL %1: failed to grant a prefix lease for iaid=%2**

This message indicates that in response to a received REQUEST, the server failed to grant a prefix lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

**DHCP6\_PD\_LEASE\_ALLOC\_FAIL (1) %1: failed to grant a prefix lease for iaid=%2**

This message indicates that in response to a received REQUEST, the server failed to grant a prefix lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

**DHCP6\_PD\_LEASE\_RENEW %1: lease for prefix %2/%3 and iaid=%4 has been allocated**

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and and IAID.

**DHCP6\_PD\_LEASE\_RENEW (1) %1: lease for prefix %2/%3 and iaid=%4 has been allocated**

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and and IAID.

**DHCP6\_PROCESS\_IA\_NA\_EXTEND %1: extending lease lifetime for IA\_NA option with iaid=%2**

This message is logged when the server is starting to extend the lifetime of the address lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

**DHCP6\_PROCESS\_IA\_NA\_EXTEND (1) %1: extending lease lifetime for IA\_NA option with iaid=%2**

This message is logged when the server is starting to extend the lifetime of the address lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

**DHCP6\_PROCESS\_IA\_NA\_RELEASE %1: releasing lease for IA\_NA option with iaid=%2**

This message is logged when the server is trying to release the client's as a result of receiving the RELEASE message. The first argument includes the client and transaction identification information. The second argument contains the IAID.

---

**DHCP6\_PROCESS\_IA\_NA\_RELEASE (1) %1: releasing lease for IA\_NA option with iaid=%2**

This message is logged when the server is trying to release the client's as a result of receiving the RELEASE message. The first argument includes the client and transaction identification information. The second argument contains the IAID.

**DHCP6\_PROCESS\_IA\_NA\_REQUEST %1: server is processing IA\_NA option with iaid=%2 and hint=%3**

This is a debug message that indicates the processing of a received IA\_NA option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_NA option. The third argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

**DHCP6\_PROCESS\_IA\_NA\_REQUEST (1) %1: server is processing IA\_NA option with iaid=%2 and hint=%3**

This is a debug message that indicates the processing of a received IA\_NA option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_NA option. The third argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

**DHCP6\_PROCESS\_IA\_PD\_EXTEND %1: extending lease lifetime for IA\_PD option with iaid=%2**

This message is logged when the server is starting to extend the lifetime of the prefix lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

**DHCP6\_PROCESS\_IA\_PD\_EXTEND (1) %1: extending lease lifetime for IA\_PD option with iaid=%2**

This message is logged when the server is starting to extend the lifetime of the prefix lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

**DHCP6\_PROCESS\_IA\_PD\_REQUEST %1: server is processing IA\_PD option with iaid=%2 and hint=%3**

This is a debug message that indicates a processing of received IA\_PD option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_PD option. The third argument may hold the hint for the server about the prefix that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

**DHCP6\_PROCESS\_IA\_PD\_REQUEST (1) %1: server is processing IA\_PD option with iaid=%2 and hint=%3**

This is a debug message that indicates a processing of received IA\_PD option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_PD option. The third argument may hold the hint for the server about the prefix that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

**DHCP6\_QUERY\_DATA %1, packet details: %2**

A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

**DHCP6\_QUERY\_DATA (1) %1, packet details: %2**

A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

**DHCP6\_RAPID\_COMMIT %1: Rapid Commit option received, following 2-way exchange**

This debug message is issued when the server found a Rapid Commit option in the client's message and 2-way exchanges are supported by the server for the subnet on which the client is connected. The argument specifies the client and transaction identification information.

**DHCP6\_RAPID\_COMMIT (1) %1: Rapid Commit option received, following 2-way exchange**

This debug message is issued when the server found a Rapid Commit option in the client's message and 2-way exchanges are supported by the server for the subnet on which the client is connected. The argument specifies the client and transaction identification information.

**DHCP6\_RELEASE\_NA %1: binding for address %2 and iaid=%3 was released properly**

This informational message indicates that an address was released properly. It is a normal operation during client shutdown.

**DHCP6\_RELEASE\_NA (1) %1: binding for address %2 and iaid=%3 was released properly**

This informational message indicates that an address was released properly. It is a normal operation during client shutdown.

**DHCP6\_RELEASE\_NA\_FAIL %1: failed to remove address lease for address %2 and iaid=%3**

This error message indicates that the software failed to remove an address lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument holds the client and transaction identification information. The second and third argument hold the released address and IAID respectively.

**DHCP6\_RELEASE\_NA\_FAIL (1) %1: failed to remove address lease for address %2 and iaid=%3**

This error message indicates that the software failed to remove an address lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument holds the client and transaction identification information. The second and third argument hold the released address and IAID respectively.

**DHCP6\_RELEASE\_NA\_FAIL\_WRONG\_DUID %1: client tried to release address %2, but it belongs to another client using d**

This warning message indicates that a client tried to release an address that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the address will stop using it anyway, there is a good chance that the situation will correct itself.

**DHCP6\_RELEASE\_NA\_FAIL\_WRONG\_DUID (1) %1: client tried to release address %2, but it belongs to another client using**

This warning message indicates that a client tried to release an address that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the address will stop using it anyway, there is a good chance that the situation will correct itself.

**DHCP6\_RELEASE\_NA\_FAIL\_WRONG\_IAID %1: client tried to release address %2, but it used wrong IAID (expected %3, l**

This warning message indicates that client tried to release an address that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple addresses is flawed.

**DHCP6\_RELEASE\_NA\_FAIL\_WRONG\_IAID (1) %1: client tried to release address %2, but it used wrong IAID (expected %**

This warning message indicates that client tried to release an address that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple addresses is flawed.

**DHCP6\_RELEASE\_PD %1: prefix %2/%3 for iaid=%4 was released properly**

This informational message indicates that a prefix was released properly. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument define the prefix and its length. The fourth argument holds IAID.

**DHCP6\_RELEASE\_PD (1) %1: prefix %2/%3 for iaid=%4 was released properly**

This informational message indicates that a prefix was released properly. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument define the prefix and its length. The fourth argument holds IAID.

**DHCP6\_RELEASE\_PD\_FAIL %1: failed to release prefix %2/%3 for iaid=%4**

This error message indicates that the software failed to remove a prefix lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument hold the client and transaction identification information. The second and third argument define the prefix and its length. The fourth argument holds the IAID.

**DHCP6\_RELEASE\_PD\_FAIL (1) %1: failed to release prefix %2/%3 for iaid=%4**

This error message indicates that the software failed to remove a prefix lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument hold the client and transaction identification information. The second and third argument define the prefix and its length. The fourth argument holds the IAID.

**DHCP6\_RELEASE\_PD\_FAIL\_WRONG\_DUID %1: client tried to release prefix %2/%3, but it belongs to another client (duid %4)**

This warning message indicates that client tried to release a prefix that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the prefix will stop using it anyway, there is a good chance that the situation will correct itself. The first argument includes the client and the transaction identification information. The second and third argument include the prefix and prefix length. The last argument holds the DUID of the client holding the lease.

**DHCP6\_RELEASE\_PD\_FAIL\_WRONG\_DUID (1) %1: client tried to release prefix %2/%3, but it belongs to another client (duid %4)**

This warning message indicates that client tried to release a prefix that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the prefix will stop using it anyway, there is a good chance that the situation will correct itself. The first argument includes the client and the transaction identification information. The second and third argument include the prefix and prefix length. The last argument holds the DUID of the client holding the lease.

**DHCP6\_RELEASE\_PD\_FAIL\_WRONG\_IAID %1: client tried to release prefix %2/%3, but it used wrong IAID (expected %4, found %5)**

This warning message indicates that client tried to release a prefix that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple prefixes is flawed. The first argument includes the client and transaction identification information. The second and third argument identify the prefix. The fourth and fifth argument hold the expected IAID and IAID found respectively.

**DHCP6\_RELEASE\_PD\_FAIL\_WRONG\_IAID (1) %1: client tried to release prefix %2/%3, but it used wrong IAID (expected %4, found %5)**

This warning message indicates that client tried to release a prefix that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple prefixes is flawed. The first argument includes the client and transaction identification information. The second and third argument identify the prefix. The fourth and fifth argument hold the expected IAID and IAID found respectively.

**DHCP6\_REQUIRED\_OPTIONS\_CHECK\_FAIL %1 message received from %2 failed the following check: %3**

This message indicates that received DHCPv6 packet is invalid. This may be due to a number of reasons, e.g. the mandatory client-id option is missing, the server-id forbidden in that particular type of message is present, there is more than one instance of client-id or server-id present, etc. The exact reason for rejecting the packet is included in the message.

**DHCP6\_REQUIRED\_OPTIONS\_CHECK\_FAIL (1) %1 message received from %2 failed the following check: %3**

This message indicates that received DHCPv6 packet is invalid. This may be due to a number of reasons, e.g. the mandatory client-id option is missing, the server-id forbidden in that particular type of message is present, there is more than one instance of client-id or server-id present, etc. The exact reason for rejecting the packet is included in the message.

**DHCP6\_RESPONSE\_DATA responding with packet type %1 data is %2**

A debug message listing the data returned to the client.

**DHCP6\_RESPONSE\_DATA (1) responding with packet type %1 data is %2**

A debug message listing the data returned to the client.

**DHCP6\_SERVER\_FAILED server failed: %1**

The IPv6 DHCP server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

**DHCP6\_SERVER\_FAILED (1) server failed: %1**

The IPv6 DHCP server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

**DHCP6\_SHUTDOWN server shutdown**

The IPv6 DHCP server has terminated normally.

**DHCP6\_SHUTDOWN (1) server shutdown**

The IPv6 DHCP server has terminated normally.

**DHCP6\_SHUTDOWN\_REQUEST shutdown of server requested**

This debug message indicates that a shutdown of the IPv6 server has been requested via a call to the 'shutdown' method of the core Dhcpv6Srv object.

**DHCP6\_SHUTDOWN\_REQUEST (1) shutdown of server requested**

This debug message indicates that a shutdown of the IPv6 server has been requested via a call to the 'shutdown' method of the core Dhcpv6Srv object.

**DHCP6\_SOCKET\_UNICAST server is about to open socket on address %1 on interface %2**

This is a debug message that inform that a unicast socket will be opened.

**DHCP6\_SOCKET\_UNICAST (1) server is about to open socket on address %1 on interface %2**

This is a debug message that inform that a unicast socket will be opened.

**DHCP6\_SRV\_CONSTRUCT\_ERROR error creating Dhcpv6Srv object, reason: %1**

This error message indicates that during startup, the construction of a core component within the IPv6 DHCP server (the Dhcpv6 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

**DHCP6\_SRV\_CONSTRUCT\_ERROR (1) error creating Dhcpv6Srv object, reason: %1**

This error message indicates that during startup, the construction of a core component within the IPv6 DHCP server (the Dhcpv6 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

**DHCP6\_SRV\_D2STOP\_ERROR error stopping IO with DHCP\_DDNS during shutdown: %1**

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv6 server and the DHCP\_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

**DHCP6\_SRV\_D2STOP\_ERROR (1) error stopping IO with DHCP\_DDNS during shutdown: %1**

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv6 server and the DHCP\_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

**DHCP6\_STANDALONE skipping message queue, running standalone**

This is a debug message indicating that the IPv6 server is running in standalone mode, not connected to the message queue. Standalone mode is only useful during program development, and should not be used in a production environment.

**DHCP6\_STANDALONE (1) skipping message queue, running standalone**

This is a debug message indicating that the IPv6 server is running in standalone mode, not connected to the message queue. Standalone mode is only useful during program development, and should not be used in a production environment.

**DHCP6\_STARTED Kea DHCPv6 server version %1 started**

This informational message indicates that the IPv6 DHCP server has processed all configuration information and is ready to process DHCPv6 packets. The version is also printed.

**DHCP6\_STARTED (1) Kea DHCPv6 server version %1 started**

This informational message indicates that the IPv6 DHCP server has processed all configuration information and is ready to process DHCPv6 packets. The version is also printed.

**DHCP6\_STARTING Kea DHCPv6 server version %1 starting**

This informational message indicates that the IPv6 DHCP server has processed any command-line switches and is starting. The version is also printed.

**DHCP6\_STARTING (1) Kea DHCPv6 server version %1 starting**

This informational message indicates that the IPv6 DHCP server has processed any command-line switches and is starting. The version is also printed.

**DHCP6\_START\_INFO pid: %1, port: %2, verbose: %3**

This is a debug message issued during the IPv6 DHCP server startup. It lists some information about the parameters with which the server is running.

**DHCP6\_START\_INFO (1) pid: %1, port: %2, verbose: %3**

This is a debug message issued during the IPv6 DHCP server startup. It lists some information about the parameters with which the server is running.

---

**DHCP6\_SUBNET\_DATA %1: the selected subnet details: %2**

This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second argument includes the subnet details.

**DHCP6\_SUBNET\_DATA (1) %1: the selected subnet details: %2**

This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second argument includes the subnet details.

**DHCP6\_SUBNET\_DYNAMICALLY\_CHANGED %1: changed selected subnet %2 to subnet %3 from shared network %4 for**

This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

**DHCP6\_SUBNET\_DYNAMICALLY\_CHANGED (1) %1: changed selected subnet %2 to subnet %3 from shared network %4 for**

This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

**DHCP6\_SUBNET\_SELECTED %1: the subnet with ID %2 was selected for client assignments**

This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

**DHCP6\_SUBNET\_SELECTED (1) %1: the subnet with ID %2 was selected for client assignments**

This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

**DHCP6\_SUBNET\_SELECTION\_FAILED %1: failed to select subnet for the client**

This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The cause is likely due to a misconfiguration of the server. The packet processing will continue, but the response will only contain generic configuration and no addresses or prefixes. The argument includes the client and the transaction identification information.

**DHCP6\_SUBNET\_SELECTION\_FAILED (1) %1: failed to select subnet for the client**

This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The cause is likely due to a misconfiguration of the server. The packet processing will continue, but the response will only contain generic configuration and no addresses or prefixes. The argument includes the client and the transaction identification information.

**DHCP6\_UNKNOWN\_MSG\_RECEIVED received unknown message (type %1) on interface %2**

This debug message is printed when server receives a message of unknown type. That could either mean missing functionality or invalid or broken relay or client. The list of formally defined message types is available here: <http://www.iana.org/assignments/parameters>.

**DHCP6\_UNKNOWN\_MSG\_RECEIVED (1) received unknown message (type %1) on interface %2**

This debug message is printed when server receives a message of unknown type. That could either mean missing functionality or invalid or broken relay or client. The list of formally defined message types is available here: <http://www.iana.org/assignments/parameters>.

**DHCP6\_USING\_SERVERID server is using server-id %1 and stores in the file %2**

This info message is logged when the server reads its server-id from a file or generates it. This message is a notification to the administrator what server-id will be used and where it is persisted. Typically, there is no need to modify the server id. However, it is possible to do it in the Kea configuration file. It is important to understand the implications of such modification. The clients will remember previous server-id, and will use it to extend their leases. As a result, they will have to go through a rebinding phase to re-acquire their leases and associate them with a new server id.



**DHCP6\_USING\_SERVERID (1) server is using server-id %1 and stores in the file %2**

This info message is logged when the server reads its server-id from a file or generates it. This message is a notification to the administrator what server-id will be used and where it is persisted. Typically, there is no need to modify the server id. However, it is possible to do it in the Kea configuration file. It is important to understand the implications of such modification. The clients will remember previous server-id, and will use it to extend their leases. As a result, they will have to go through a rebinding phase to re-acquire their leases and associate them with a new server id.

## DHCP6SRV Module

**DHCP6SRV\_CFGMGR\_ADD\_IFACE listening on interface %1**

An info message issued when a new interface is being added to the collection of interfaces on which the server listens to DHCP messages.

**DHCP6SRV\_CFGMGR\_ADD\_IFACE (1) listening on interface %1**

An info message issued when a new interface is being added to the collection of interfaces on which the server listens to DHCP messages.

**DHCP6SRV\_CFGMGR\_ADD\_SUBNET4 adding subnet %1**

A debug message reported when the DHCP configuration manager is adding the specified IPv4 subnet to its database.

**DHCP6SRV\_CFGMGR\_ADD\_SUBNET4 (1) adding subnet %1**

A debug message reported when the DHCP configuration manager is adding the specified IPv4 subnet to its database.

**DHCP6SRV\_CFGMGR\_ADD\_SUBNET6 adding subnet %1**

A debug message reported when the DHCP configuration manager is adding the specified IPv6 subnet to its database.

**DHCP6SRV\_CFGMGR\_ADD\_SUBNET6 (1) adding subnet %1**

A debug message reported when the DHCP configuration manager is adding the specified IPv6 subnet to its database.

**DHCP6SRV\_CFGMGR\_ALL\_IFACES\_ACTIVE enabling listening on all interfaces**

A debug message issued when the server is being configured to listen on all interfaces.

**DHCP6SRV\_CFGMGR\_ALL\_IFACES\_ACTIVE (1) enabling listening on all interfaces**

A debug message issued when the server is being configured to listen on all interfaces.

**DHCP6SRV\_CFGMGR\_CFG\_DHCP\_DDNS Setting DHCP-DDNS configuration to: %1**

A debug message issued when the server's DHCP-DDNS settings are changed.

**DHCP6SRV\_CFGMGR\_CFG\_DHCP\_DDNS (1) Setting DHCP-DDNS configuration to: %1**

A debug message issued when the server's DHCP-DDNS settings are changed.

**DHCP6SRV\_CFGMGR\_CLEAR\_ACTIVE\_IFACES stop listening on all interfaces**

A debug message issued when configuration manager clears the internal list of active interfaces. This doesn't prevent the server from listening to the DHCP traffic through open sockets, but will rather be used by Interface Manager to select active interfaces when sockets are re-opened.

**DHCP6SRV\_CFGMGR\_CLEAR\_ACTIVE\_IFACES (1) stop listening on all interfaces**

A debug message issued when configuration manager clears the internal list of active interfaces. This doesn't prevent the server from listening to the DHCP traffic through open sockets, but will rather be used by Interface Manager to select active interfaces when sockets are re-opened.

**DHCP6SRV\_CFGMGR\_CONFIGURE\_SERVERID server configuration includes specification of a server identifier**

This warning message is issued when the server specified configuration of a server identifier. If this new configuration overrides an existing server identifier, this will affect existing bindings of the clients. Clients will use old server identifier when they renew their bindings. The server will not respond to those renews, and the clients will eventually transition to rebinding state. The server should reassign existing bindings and the clients will subsequently use new server identifier. It is recommended to not modify the server identifier, unless there is a good reason for it, to avoid increased number of renewals and a need for rebinding (increase of multicast traffic, which may be received by multiple servers).

**DHCPSRV\_CFGMGR\_CONFIGURE\_SERVERID (1) server configuration includes specification of a server identifier**

This warning message is issued when the server specified configuration of a server identifier. If this new configuration overrides an existing server identifier, this will affect existing bindings of the clients. Clients will use old server identifier when they renew their bindings. The server will not respond to those renews, and the clients will eventually transition to rebinding state. The server should reassign existing bindings and the clients will subsequently use new server identifier. It is recommended to not modify the server identifier, unless there is a good reason for it, to avoid increased number of renewals and a need for rebinding (increase of multicast traffic, which may be received by multiple servers).

**DHCPSRV\_CFGMGR\_DEL\_SUBNET4 IPv4 subnet %1 removed**

This debug message is issued when a subnet is successfully removed from the server configuration. The argument identifies the subnet removed.

**DHCPSRV\_CFGMGR\_DEL\_SUBNET4 (1) IPv4 subnet %1 removed**

This debug message is issued when a subnet is successfully removed from the server configuration. The argument identifies the subnet removed.

**DHCPSRV\_CFGMGR\_DEL\_SUBNET6 IPv6 subnet %1 removed**

This debug message is issued when a subnet is successfully removed from the

**DHCPSRV\_CFGMGR\_DEL\_SUBNET6 (1) IPv6 subnet %1 removed**

This debug message is issued when a subnet is successfully removed from the

**DHCPSRV\_CFGMGR\_NEW\_SUBNET4 a new subnet has been added to configuration: %1**

This is an informational message reporting that the configuration has been extended to include the specified IPv4 subnet.

**DHCPSRV\_CFGMGR\_NEW\_SUBNET4 (1) a new subnet has been added to configuration: %1**

This is an informational message reporting that the configuration has been extended to include the specified IPv4 subnet.

**DHCPSRV\_CFGMGR\_NEW\_SUBNET6 a new subnet has been added to configuration: %1**

This is an informational message reporting that the configuration has been extended to include the specified subnet.

**DHCPSRV\_CFGMGR\_NEW\_SUBNET6 (1) a new subnet has been added to configuration: %1**

This is an informational message reporting that the configuration has been extended to include the specified subnet.

**DHCPSRV\_CFGMGR\_NO\_SUBNET4 no suitable subnet is defined for address hint %1**

This debug message is output when the DHCP configuration manager has received a request for an IPv4 subnet for the specified address, but no such subnet exists.

**DHCPSRV\_CFGMGR\_NO\_SUBNET4 (1) no suitable subnet is defined for address hint %1**

This debug message is output when the DHCP configuration manager has received a request for an IPv4 subnet for the specified address, but no such subnet exists.

**DHCPSRV\_CFGMGR\_NO\_SUBNET6 no suitable subnet is defined for address hint %1**

This debug message is output when the DHCP configuration manager has received a request for an IPv6 subnet for the specified address, but no such subnet exists.

**DHCPSRV\_CFGMGR\_NO\_SUBNET6 (1) no suitable subnet is defined for address hint %1**

This debug message is output when the DHCP configuration manager has received a request for an IPv6 subnet for the specified address, but no such subnet exists.

**DHCPSRV\_CFGMGR\_ONLY\_SUBNET4 retrieved subnet %1 for address hint %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet when given the address hint specified because it is the only subnet defined.

**DHCPSRV\_CFGMGR\_ONLY\_SUBNET4 (1) retrieved subnet %1 for address hint %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet when given the address hint specified because it is the only subnet defined.

**DHCPSRV\_CFGMGR\_ONLY\_SUBNET6 retrieved subnet %1 for address hint %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet when given the address hint specified because it is the only subnet defined.

**DHCPSRV\_CFGMGR\_ONLY\_SUBNET6 (1) retrieved subnet %1 for address hint %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet when given the address hint specified because it is the only subnet defined.

**DHCPSRV\_CFGMGR\_OPTION\_DUPLICATE multiple options with the code: %1 added to the subnet: %2**

This warning message is issued on an attempt to configure multiple options with the same option code for the particular subnet. Adding multiple options is uncommon for DHCPv6, but it is not prohibited.

**DHCPSRV\_CFGMGR\_OPTION\_DUPLICATE (1) multiple options with the code: %1 added to the subnet: %2**

This warning message is issued on an attempt to configure multiple options with the same option code for the particular subnet. Adding multiple options is uncommon for DHCPv6, but it is not prohibited.

**DHCPSRV\_CFGMGR\_RELAY\_IP\_ADDRESS\_DEPRECATED "relay" uses "ip-address", which has been deprecated, please**

This is debug message issued when the "relay" element being parse contains "ip-address" rather than its replacement, "ip-addresses". The server will still honor the value but users are encouraged to move to the new list parameter.

**DHCPSRV\_CFGMGR\_RELAY\_IP\_ADDRESS\_DEPRECATED (1) "relay" uses "ip-address", which has been deprecated, please**

This is debug message issued when the "relay" element being parse contains "ip-address" rather than its replacement, "ip-addresses". The server will still honor the value but users are encouraged to move to the new list parameter.

**DHCPSRV\_CFGMGR\_SOCKET\_RAW\_UNSUPPORTED use of raw sockets is unsupported on this OS, UDP sockets will be u**

This warning message is logged when the user specified that the DHCPv4 server should use the raw sockets to receive the DHCP messages and respond to the clients, but the use of raw sockets is not supported on the particular environment. The raw sockets are useful when the server must respond to the directly connected clients which don't have an address yet. If the raw sockets are not supported by Kea on the particular platform, Kea will fall back to use of the IP/UDP sockets. The responses to the directly connected clients will be broadcast. The responses to relayed clients will be unicast as usual.

**DHCPSRV\_CFGMGR\_SOCKET\_RAW\_UNSUPPORTED (1) use of raw sockets is unsupported on this OS, UDP sockets will be u**

This warning message is logged when the user specified that the DHCPv4 server should use the raw sockets to receive the DHCP messages and respond to the clients, but the use of raw sockets is not supported on the particular environment. The raw sockets are useful when the server must respond to the directly connected clients which don't have an address yet. If the raw sockets are not supported by Kea on the particular platform, Kea will fall back to use of the IP/UDP sockets. The responses to the directly connected clients will be broadcast. The responses to relayed clients will be unicast as usual.

**DHCPSRV\_CFGMGR\_SOCKET\_TYPE\_DEFAULT "dhcp-socket-type" not specified , using default socket type %1**

This informational message is logged when the administrator hasn't specified the "dhcp-socket-type" parameter in configuration for interfaces. In such case, the default socket type will be used.

**DHCPSRV\_CFGMGR\_SOCKET\_TYPE\_DEFAULT (1) "dhcp-socket-type" not specified , using default socket type %1**

This informational message is logged when the administrator hasn't specified the "dhcp-socket-type" parameter in configuration for interfaces. In such case, the default socket type will be used.

**DHCPSRV\_CFGMGR\_SOCKET\_TYPE\_SELECT using socket type %1**

This informational message is logged when the DHCPv4 server selects the socket type to be used for all sockets that will be opened on the interfaces. Typically, the socket type is specified by the server administrator. If the socket type hasn't been specified, the raw socket will be selected. If the raw socket has been selected but Kea doesn't support the use of raw sockets on the particular OS, it will use an UDP socket instead.

**DHCPSRV\_CFGMGR\_SOCKET\_TYPE\_SELECT (1) using socket type %1**

This informational message is logged when the DHCPv4 server selects the socket type to be used for all sockets that will be opened on the interfaces. Typically, the socket type is specified by the server administrator. If the socket type hasn't been specified, the raw socket will be selected. If the raw socket has been selected but Kea doesn't support the use of raw sockets on the particular OS, it will use an UDP socket instead.

**DHCPSRV\_CFGMGR\_SUBNET4 retrieved subnet %1 for address hint %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet when given the address hint specified as the address is within the subnet.

---

**DHCPSRV\_CFGMGR\_SUBNET4 (1) retrieved subnet %1 for address hint %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet when given the address hint specified as the address is within the subnet.

**DHCPSRV\_CFGMGR\_SUBNET4\_ADDR selected subnet %1 for packet received by matching address %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a received packet. This particular subnet was selected, because an IPv4 address was matched which belonged to that subnet.

**DHCPSRV\_CFGMGR\_SUBNET4\_ADDR (1) selected subnet %1 for packet received by matching address %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a received packet. This particular subnet was selected, because an IPv4 address was matched which belonged to that subnet.

**DHCPSRV\_CFGMGR\_SUBNET4\_IFACE selected subnet %1 for packet received over interface %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a packet received over the given interface. This particular subnet was selected, because it was specified as being directly reachable over the given interface. (see 'interface' parameter in the subnet4 definition).

**DHCPSRV\_CFGMGR\_SUBNET4\_IFACE (1) selected subnet %1 for packet received over interface %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a packet received over the given interface. This particular subnet was selected, because it was specified as being directly reachable over the given interface. (see 'interface' parameter in the subnet4 definition).

**DHCPSRV\_CFGMGR\_SUBNET4\_RELAY selected subnet %1, because of matching relay addr %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet, because detected relay agent address matches value specified for this subnet.

**DHCPSRV\_CFGMGR\_SUBNET4\_RELAY (1) selected subnet %1, because of matching relay addr %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet, because detected relay agent address matches value specified for this subnet.

**DHCPSRV\_CFGMGR\_SUBNET6 retrieved subnet %1 for address hint %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet when given the address hint specified as the address is within the subnet.

**DHCPSRV\_CFGMGR\_SUBNET6 (1) retrieved subnet %1 for address hint %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet when given the address hint specified as the address is within the subnet.

**DHCPSRV\_CFGMGR\_SUBNET6\_IFACE selected subnet %1 for packet received over interface %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a packet received over given interface. This particular subnet was selected, because it was specified as being directly reachable over given interface. (see 'interface' parameter in the subnet6 definition).

**DHCPSRV\_CFGMGR\_SUBNET6\_IFACE (1) selected subnet %1 for packet received over interface %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a packet received over given interface. This particular subnet was selected, because it was specified as being directly reachable over given interface. (see 'interface' parameter in the subnet6 definition).

**DHCPSRV\_CFGMGR\_SUBNET6\_IFACE\_ID selected subnet %1 (interface-id match) for incoming packet**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a received packet. This particular subnet was selected, because value of interface-id option matched what was configured in the server's interface-id option for that selected subnet6. (see 'interface-id' parameter in the subnet6 definition).

**DHCPSRV\_CFGMGR\_SUBNET6\_IFACE\_ID (1) selected subnet %1 (interface-id match) for incoming packet**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a received packet. This particular subnet was selected, because value of interface-id option matched what was configured in the server's interface-id option for that selected subnet6. (see 'interface-id' parameter in the subnet6 definition).

**DHCPSRV\_CFGMGR\_SUBNET6\_RELAY selected subnet %1, because of matching relay addr %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet, because detected relay agent address matches value specified for this subnet.

**DHCPSRV\_CFGMGR\_SUBNET6\_RELAY (1) selected subnet %1, because of matching relay addr %2**

This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet, because detected relay agent address matches value specified for this subnet.

**DHCPSRV\_CFGMGR\_UNICAST\_LINK\_LOCAL specified link local address %1 for unicast traffic on interface %2**

This warning message is logged when user specified a link-local address to receive unicast traffic. The warning message is issued because it is an uncommon use.

**DHCPSRV\_CFGMGR\_UNICAST\_LINK\_LOCAL (1) specified link local address %1 for unicast traffic on interface %2**

This warning message is logged when user specified a link-local address to receive unicast traffic. The warning message is issued because it is an uncommon use.

**DHCPSRV\_CFGMGR\_USE\_ADDRESS listening on address %1, on interface %2**

A message issued when the server is configured to listen on the explicitly specified IP address on the given interface.

**DHCPSRV\_CFGMGR\_USE\_ADDRESS (1) listening on address %1, on interface %2**

A message issued when the server is configured to listen on the explicitly specified IP address on the given interface.

**DHCPSRV\_CFGMGR\_USE\_UNICAST listening on unicast address %1, on interface %2**

An info message issued when configuring the DHCP server to listen on the unicast address on the specific interface.

**DHCPSRV\_CFGMGR\_USE\_UNICAST (1) listening on unicast address %1, on interface %2**

An info message issued when configuring the DHCP server to listen on the unicast address on the specific interface.

**DHCPSRV\_CLOSE\_DB closing currently open %1 database**

This is a debug message, issued when the DHCP server closes the currently open lease database. It is issued at program shutdown and whenever the database access parameters are changed: in the latter case, the server closes the currently open database, and opens a database using the new parameters.

**DHCPSRV\_CLOSE\_DB (1) closing currently open %1 database**

This is a debug message, issued when the DHCP server closes the currently open lease database. It is issued at program shutdown and whenever the database access parameters are changed: in the latter case, the server closes the currently open database, and opens a database using the new parameters.

**DHCPSRV\_CQL\_ADD\_ADDR4 adding IPv4 lease with address %1**

A debug message issued when the server is about to add an IPv4 lease with the specified address to the Cassandra backend database.

**DHCPSRV\_CQL\_ADD\_ADDR4 (1) adding IPv4 lease with address %1**

A debug message issued when the server is about to add an IPv4 lease with the specified address to the Cassandra backend database.

**DHCPSRV\_CQL\_ADD\_ADDR6 adding IPv6 lease with address %1**

A debug message issued when the server is about to add an IPv6 lease with the specified address to the Cassandra backend database.

**DHCPSRV\_CQL\_ADD\_ADDR6 (1) adding IPv6 lease with address %1**

A debug message issued when the server is about to add an IPv6 lease with the specified address to the Cassandra backend database.

**DHCPSRV\_CQL\_COMMIT committing to Cassandra database.**

A commit call been issued on the server. For Cassandra, this is a no-op.

**DHCPSRV\_CQL\_COMMIT (1) committing to Cassandra database.**

A commit call been issued on the server. For Cassandra, this is a no-op.

**DHCPSRV\_CQL\_CONNECTION\_BEGIN\_TRANSACTION begin transaction on current connection.**

The server has issued a begin transaction call.

**DHCPSRV\_CQL\_CONNECTION\_BEGIN\_TRANSACTION (1) begin transaction on current connection.**

The server has issued a begin transaction call.

**DHCPSRV\_CQL\_CONNECTION\_COMMIT committing to Cassandra database on current connection.**

A commit call been issued on the server. For Cassandra, this is a no-op.

**DHCPSRV\_CQL\_CONNECTION\_COMMIT (1) committing to Cassandra database on current connection.**

A commit call been issued on the server. For Cassandra, this is a no-op.

**DHCPSRV\_CQL\_CONNECTION\_ROLLBACK rolling back Cassandra database on current connection.**

The code has issued a rollback call. For Cassandra, this is a no-op.

**DHCPSRV\_CQL\_CONNECTION\_ROLLBACK (1) rolling back Cassandra database on current connection.**

The code has issued a rollback call. For Cassandra, this is a no-op.

**DHCPSRV\_CQL\_DB opening Cassandra lease database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a Cassandra lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_CQL\_DB (1) opening Cassandra lease database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a Cassandra lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_CQL\_DEALLOC\_ERROR An error occurred while closing the CQL connection: %1**

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing CQL database resources as part of closing its connection to the Cassandra database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

**DHCPSRV\_CQL\_DEALLOC\_ERROR (1) An error occurred while closing the CQL connection: %1**

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing CQL database resources as part of closing its connection to the Cassandra database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

**DHCPSRV\_CQL\_DELETE\_ADDR deleting lease for address %1**

A debug message issued when the server is attempting to delete a lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_DELETE\_ADDR (1) deleting lease for address %1**

A debug message issued when the server is attempting to delete a lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_DELETE\_EXPIRED\_RECLAIMED4 deleting reclaimed IPv4 leases that expired more than %1 seconds ago**

A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_CQL\_DELETE\_EXPIRED\_RECLAIMED4 (1) deleting reclaimed IPv4 leases that expired more than %1 seconds ago**

A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_CQL\_DELETE\_EXPIRED\_RECLAIMED6 deleting reclaimed IPv6 leases that expired more than %1 seconds ago**

A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

---

**DHCPSRV\_CQL\_DELETE\_EXPIRED\_RECLAIMED6 (1) deleting reclaimed IPv6 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_CQL\_GET4 obtaining all IPv4 leases**

A debug message issued when the server is attempting to obtain all IPv4 leases from the Cassandra database.

**DHCPSRV\_CQL\_GET4 (1) obtaining all IPv4 leases**

A debug message issued when the server is attempting to obtain all IPv4 leases from the Cassandra database.

**DHCPSRV\_CQL\_GET\_ADDR4 obtaining IPv4 lease for address %1**

A debug message issued when the server is attempting to obtain an IPv4 lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_GET\_ADDR4 (1) obtaining IPv4 lease for address %1**

A debug message issued when the server is attempting to obtain an IPv4 lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_GET\_ADDR6 obtaining IPv6 lease for address %1 and lease type %2**

A debug message issued when the server is attempting to obtain an IPv6 lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_GET\_ADDR6 (1) obtaining IPv6 lease for address %1 and lease type %2**

A debug message issued when the server is attempting to obtain an IPv6 lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_GET\_CLIENTID obtaining IPv4 leases for client ID %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the Cassandra database for a client with the specified client identification.

**DHCPSRV\_CQL\_GET\_CLIENTID (1) obtaining IPv4 leases for client ID %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the Cassandra database for a client with the specified client identification.

**DHCPSRV\_CQL\_GET\_CLIENTID\_HWADDR\_SUBID obtaining IPv4 lease for client ID %1, hardware address %2 and subnet**

A debug message issued when the server is attempting to obtain an IPv4 lease from the Cassandra database for a client with the specified client ID, hardware address and subnet ID.

**DHCPSRV\_CQL\_GET\_CLIENTID\_HWADDR\_SUBID (1) obtaining IPv4 lease for client ID %1, hardware address %2 and subnet**

A debug message issued when the server is attempting to obtain an IPv4 lease from the Cassandra database for a client with the specified client ID, hardware address and subnet ID.

**DHCPSRV\_CQL\_GET\_EXPIRED4 obtaining maximum %1 of expired IPv4 leases**

A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_CQL\_GET\_EXPIRED4 (1) obtaining maximum %1 of expired IPv4 leases**

A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_CQL\_GET\_EXPIRED6 obtaining maximum %1 of expired IPv6 leases**

A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_CQL\_GET\_EXPIRED6 (1) obtaining maximum %1 of expired IPv6 leases**

A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_CQL\_GET\_HWADDR obtaining IPv4 leases for hardware address %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the Cassandra database for a client with the specified hardware address.

**DHCPSRV\_CQL\_GET\_HWADDR (1) obtaining IPv4 leases for hardware address %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the Cassandra database for a client with the specified hardware address.

**DHCPSRV\_CQL\_GET\_IAID\_DUID obtaining IPv6 leases for IAID %1 and DUID %2 and lease type %3**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the Cassandra database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

**DHCPSRV\_CQL\_GET\_IAID\_DUID (1) obtaining IPv6 leases for IAID %1 and DUID %2 and lease type %3**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the Cassandra database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

**DHCPSRV\_CQL\_GET\_IAID\_SUBID\_DUID obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3 and lease type %4**

A debug message issued when the server is attempting to obtain an IPv6 lease from the Cassandra database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

**DHCPSRV\_CQL\_GET\_IAID\_SUBID\_DUID (1) obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3 and lease type %4**

A debug message issued when the server is attempting to obtain an IPv6 lease from the Cassandra database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

**DHCPSRV\_CQL\_GET\_PAGE4 obtaining at most %1 IPv4 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_CQL\_GET\_PAGE4 (1) obtaining at most %1 IPv4 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_CQL\_GET\_PAGE6 obtaining at most %1 IPv6 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_CQL\_GET\_PAGE6 (1) obtaining at most %1 IPv6 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_CQL\_GET\_SUBID4 obtaining IPv4 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the Cassandra database.

**DHCPSRV\_CQL\_GET\_SUBID4 (1) obtaining IPv4 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the Cassandra database.

**DHCPSRV\_CQL\_GET\_SUBID\_CLIENTID obtaining IPv4 lease for subnet ID %1 and client ID %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the Cassandra database for a client with the specified subnet ID and client ID.

**DHCPSRV\_CQL\_GET\_SUBID\_CLIENTID (1) obtaining IPv4 lease for subnet ID %1 and client ID %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the Cassandra database for a client with the specified subnet ID and client ID.

**DHCPSRV\_CQL\_GET\_SUBID\_HWADDR obtaining IPv4 lease for subnet ID %1 and hardware address %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the Cassandra database for a client with the specified subnet ID and hardware address.

**DHCPSRV\_CQL\_GET\_SUBID\_HWADDR (1) obtaining IPv4 lease for subnet ID %1 and hardware address %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the Cassandra database for a client with the specified subnet ID and hardware address.



**DHCPSRV\_CQL\_GET\_VERSION obtaining schema version information**

A debug message issued when the server is about to obtain schema version information from the Cassandra database.

**DHCPSRV\_CQL\_GET\_VERSION (1) obtaining schema version information**

A debug message issued when the server is about to obtain schema version information from the Cassandra database.

**DHCPSRV\_CQL\_HOST\_ADD Adding host information to the database**

An informational message logged when options belonging to any reservation from a single host are inserted.

**DHCPSRV\_CQL\_HOST\_ADD (1) Adding host information to the database**

An informational message logged when options belonging to any reservation from a single host are inserted.

**DHCPSRV\_CQL\_HOST\_DB Connecting to CQL hosts database: %1**

An informational message logged when the CQL hosts database is about to be connected to. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_CQL\_HOST\_DB (1) Connecting to CQL hosts database: %1**

An informational message logged when the CQL hosts database is about to be connected to. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_CQL\_HOST\_DB\_GET\_VERSION obtaining schema version information for the CQL hosts database**

A debug message issued when the server is about to obtain schema version information from the CQL hosts database.

**DHCPSRV\_CQL\_HOST\_DB\_GET\_VERSION (1) obtaining schema version information for the CQL hosts database**

A debug message issued when the server is about to obtain schema version information from the CQL hosts database.

**DHCPSRV\_CQL\_HOST\_GET4 Retrieving one DHCPv4 host from a CQL database**

An informational message logged when a DHCP server is about to retrieve one host from a CQL database by IPv4 criteria.

**DHCPSRV\_CQL\_HOST\_GET4 (1) Retrieving one DHCPv4 host from a CQL database**

An informational message logged when a DHCP server is about to retrieve one host from a CQL database by IPv4 criteria.

**DHCPSRV\_CQL\_HOST\_GET6 Retrieving one DHCPv6 host from a CQL database**

An informational message logged when a DHCP server is about to retrieve one host from a CQL database by IPv6 criteria.

**DHCPSRV\_CQL\_HOST\_GET6 (1) Retrieving one DHCPv6 host from a CQL database**

An informational message logged when a DHCP server is about to retrieve one host from a CQL database by IPv6 criteria.

**DHCPSRV\_CQL\_HOST\_GET\_ALL Retrieving multiple hosts from a CQL database**

An informational message logged when multiple hosts from a CQL database are retrieved.

**DHCPSRV\_CQL\_HOST\_GET\_ALL (1) Retrieving multiple hosts from a CQL database**

An informational message logged when multiple hosts from a CQL database are retrieved.

**DHCPSRV\_CQL\_LEASE\_EXCEPTION\_THROWN Exception thrown during Cassandra operation: %1****DHCPSRV\_CQL\_LEASE\_EXCEPTION\_THROWN (1) Exception thrown during Cassandra operation: %1****DHCPSRV\_CQL\_ROLLBACK rolling back Cassandra database.**

The code has issued a rollback call. For Cassandra, this is a no-op.

**DHCPSRV\_CQL\_ROLLBACK (1) rolling back Cassandra database.**

The code has issued a rollback call. For Cassandra, this is a no-op.

**DHCPSRV\_CQL\_UPDATE\_ADDR4 updating IPv4 lease for address %1**

A debug message issued when the server is attempting to update IPv4 lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_UPDATE\_ADDR4 (1) updating IPv4 lease for address %1**

A debug message issued when the server is attempting to update IPv4 lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_UPDATE\_ADDR6 updating IPv6 lease for address %1**

A debug message issued when the server is attempting to update IPv6 lease from the Cassandra database for the specified address.

**DHCPSRV\_CQL\_UPDATE\_ADDR6 (1) updating IPv6 lease for address %1**

A debug message issued when the server is attempting to update IPv6 lease from the Cassandra database for the specified address.

**DHCPSRV\_DHCP4O6\_RECEIVED\_BAD\_PACKET received bad DHCPv4o6 packet: %1**

A bad DHCPv4o6 packet was received.

**DHCPSRV\_DHCP4O6\_RECEIVED\_BAD\_PACKET (1) received bad DHCPv4o6 packet: %1**

A bad DHCPv4o6 packet was received.

**DHCPSRV\_DHCP\_DDNS\_ERROR\_EXCEPTION error handler for DHCP\_DDNS IO generated an expected exception: %1**

This is an error message that occurs when an attempt to send a request to kea-dhcp-ddns fails there registered error handler threw an uncaught exception. This is a programmatic error which should not occur. By convention, the error handler should not propagate exceptions. Please report this error.

**DHCPSRV\_DHCP\_DDNS\_ERROR\_EXCEPTION (1) error handler for DHCP\_DDNS IO generated an expected exception: %1**

This is an error message that occurs when an attempt to send a request to kea-dhcp-ddns fails there registered error handler threw an uncaught exception. This is a programmatic error which should not occur. By convention, the error handler should not propagate exceptions. Please report this error.

**DHCPSRV\_DHCP\_DDNS\_HANDLER\_NULL error handler for DHCP\_DDNS IO is not set.**

This is an error message that occurs when an attempt to send a request to kea-dhcp-ddns fails and there is no registered error handler. This is a programmatic error which should never occur and should be reported.

**DHCPSRV\_DHCP\_DDNS\_HANDLER\_NULL (1) error handler for DHCP\_DDNS IO is not set.**

This is an error message that occurs when an attempt to send a request to kea-dhcp-ddns fails and there is no registered error handler. This is a programmatic error which should never occur and should be reported.

**DHCPSRV\_DHCP\_DDNS\_NCR\_REJECTED NameChangeRequest rejected by the sender: %1, ncr: %2**

This is an error message indicating that NameChangeSender used to deliver DDNS update requests to kea-dhcp-ddns rejected the request. This most likely cause is the sender's queue has reached maximum capacity. This would imply that requests are being generated faster than they can be delivered.

**DHCPSRV\_DHCP\_DDNS\_NCR\_REJECTED (1) NameChangeRequest rejected by the sender: %1, ncr: %2**

This is an error message indicating that NameChangeSender used to deliver DDNS update requests to kea-dhcp-ddns rejected the request. This most likely cause is the sender's queue has reached maximum capacity. This would imply that requests are being generated faster than they can be delivered.

**DHCPSRV\_DHCP\_DDNS\_NCR\_SENT NameChangeRequest sent to kea-dhcp-ddns: %1**

A debug message issued when a NameChangeRequest has been successfully sent to kea-dhcp-ddns.

**DHCPSRV\_DHCP\_DDNS\_NCR\_SENT (1) NameChangeRequest sent to kea-dhcp-ddns: %1**

A debug message issued when a NameChangeRequest has been successfully sent to kea-dhcp-ddns.

**DHCPSRV\_DHCP\_DDNS\_SENDER\_STARTED NameChangeRequest sender has been started: %1**

A informational message issued when a communications with kea-dhcp-ddns has been successfully started.

**DHCPSRV\_DHCP\_DDNS\_SENDER\_STARTED (1) NameChangeRequest sender has been started: %1**

A informational message issued when a communications with kea-dhcp-ddns has been successfully started.

**DHCPSRV\_DHCP\_DDNS\_SENDER\_STOPPED NameChangeRequest sender has been stopped.**

A informational message issued when a communications with kea-dhcp-ddns has been stopped. This normally occurs during reconfiguration and as part of normal shutdown. It may occur if kea-dhcp-ddns communications breakdown.

**DHCPSRV\_DHCP\_DDNS\_SENDER\_STOPPED (1) NameChangeRequest sender has been stopped.**

A informational message issued when a communications with kea-dhcp-ddns has been stopped. This normally occurs during reconfiguration and as part of normal shutdown. It may occur if kea-dhcp-ddns communications breakdown.

**DHCPSRV\_DHCP\_DDNS\_SUSPEND\_UPDATES DHCP\_DDNS updates are being suspended.**

This is a warning message indicating the DHCP\_DDNS updates have been turned off. This should only occur if IO errors communicating with kea-dhcp-ddns have been experienced. Any such errors should have preceding entries in the log with details. No further attempts to communicate with kea-dhcp-ddns will be made without intervention.

**DHCPSRV\_DHCP\_DDNS\_SUSPEND\_UPDATES (1) DHCP\_DDNS updates are being suspended.**

This is a warning message indicating the DHCP\_DDNS updates have been turned off. This should only occur if IO errors communicating with kea-dhcp-ddns have been experienced. Any such errors should have preceding entries in the log with details. No further attempts to communicate with kea-dhcp-ddns will be made without intervention.

**DHCPSRV\_HOOK\_LEASE4\_RECOVER\_SKIP DHCPv4 lease %1 was not recovered from the declined state because a callout**

This debug message is printed when a callout installed on lease4\_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

**DHCPSRV\_HOOK\_LEASE4\_RECOVER\_SKIP (1) DHCPv4 lease %1 was not recovered from the declined state because a callout**

This debug message is printed when a callout installed on lease4\_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

**DHCPSRV\_HOOK\_LEASE4\_RENEW\_SKIP DHCPv4 lease was not renewed because a callout set the skip flag.**

This debug message is printed when a callout installed on lease4\_renew hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not renew a lease. The server will use existing lease as it is, without extending its lifetime.

**DHCPSRV\_HOOK\_LEASE4\_RENEW\_SKIP (1) DHCPv4 lease was not renewed because a callout set the skip flag.**

This debug message is printed when a callout installed on lease4\_renew hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not renew a lease. The server will use existing lease as it is, without extending its lifetime.

**DHCPSRV\_HOOK\_LEASE4\_SELECT\_SKIP Lease4 creation was skipped, because of callout skip flag.**

This debug message is printed when a callout installed on lease4\_select hook point sets the skip flag. It means that the server was told that no lease4 should be assigned. The server will not put that lease in its database and the client will get a NAK packet.

**DHCPSRV\_HOOK\_LEASE4\_SELECT\_SKIP (1) Lease4 creation was skipped, because of callout skip flag.**

This debug message is printed when a callout installed on lease4\_select hook point sets the skip flag. It means that the server was told that no lease4 should be assigned. The server will not put that lease in its database and the client will get a NAK packet.

**DHCPSRV\_HOOK\_LEASE6\_EXTEND\_SKIP DHCPv6 lease lifetime was not extended because a callout set the skip flag for m**

This debug message is printed when a callout installed on lease6\_renew or the lease6\_rebind hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not extend the lifetime for a lease. If the client requested renewal of multiple leases (by sending multiple IA options), the server will skip the renewal of the one in question and will proceed with other renewals as usual.

**DHCPSRV\_HOOK\_LEASE6\_EXTEND\_SKIP (1) DHCPv6 lease lifetime was not extended because a callout set the skip flag for f**

This debug message is printed when a callout installed on lease6\_renew or the lease6\_rebind hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not extend the lifetime for a lease. If the client requested renewal of multiple leases (by sending multiple IA options), the server will skip the renewal of the one in question and will proceed with other renewals as usual.

**DHCPSRV\_HOOK\_LEASE6\_RECOVER\_SKIP DHCPv6 lease %1 was not recovered from declined state because a callout se**

This debug message is printed when a callout installed on lease6\_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

**DHCPSRV\_HOOK\_LEASE6\_RECOVER\_SKIP (1) DHCPv6 lease %1 was not recovered from declined state because a callout**

This debug message is printed when a callout installed on lease6\_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

**DHCPSRV\_HOOK\_LEASE6\_SELECT\_SKIP Lease6 (non-temporary) creation was skipped, because of callout skip flag.**

This debug message is printed when a callout installed on lease6\_select hook point sets the skip flag. It means that the server was told that no lease6 should be assigned. The server will not put that lease in its database and the client will get a NoAddrAvail for that IA\_NA option.

**DHCPSRV\_HOOK\_LEASE6\_SELECT\_SKIP (1) Lease6 (non-temporary) creation was skipped, because of callout skip flag.**

This debug message is printed when a callout installed on lease6\_select hook point sets the skip flag. It means that the server was told that no lease6 should be assigned. The server will not put that lease in its database and the client will get a NoAddrAvail for that IA\_NA option.

**DHCPSRV\_INVALID\_ACCESS invalid database access string: %1**

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. The access string in question - which should be of the form 'keyword=value keyword=value...' is included in the message.

**DHCPSRV\_INVALID\_ACCESS (1) invalid database access string: %1**

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. The access string in question - which should be of the form 'keyword=value keyword=value...' is included in the message.

**DHCPSRV\_LEASE\_SANITY\_FAIL The lease %1 with subnet-id %2 failed subnet-id checks.**

This warning message is printed when the lease being loaded does not match the configuration. Due to lease-checks value, the lease will be loaded, but it will most likely be unused by Kea, as there is no subnet that matches the IP address associated with the lease.

**DHCPSRV\_LEASE\_SANITY\_FAIL (1) The lease %1 with subnet-id %2 failed subnet-id checks.**

This warning message is printed when the lease being loaded does not match the configuration. Due to lease-checks value, the lease will be loaded, but it will most likely be unused by Kea, as there is no subnet that matches the IP address associated with the lease.

**DHCPSRV\_LEASE\_SANITY\_FAIL\_DISCARD The lease %1 with subnet-id %2 failed subnet-id checks and was dropped.**

This warning message is printed when a lease was loaded, but Kea was told (by setting lease-checks parameter) to discard leases with inconsistent data. The lease was discarded, because either there is no subnet configured with matching subnet-id or the address of the lease does not belong to the subnet.

**DHCPSRV\_LEASE\_SANITY\_FAIL\_DISCARD (1) The lease %1 with subnet-id %2 failed subnet-id checks and was dropped.**

This warning message is printed when a lease was loaded, but Kea was told (by setting lease-checks parameter) to discard leases with inconsistent data. The lease was discarded, because either there is no subnet configured with matching subnet-id or the address of the lease does not belong to the subnet.

**DHCPSRV\_LEASE\_SANITY\_FIXED The lease %1 with subnet-id %2 failed subnet-id checks, but was corrected to subnet-id**

This informational message is printed when a lease was loaded, but had incorrect subnet-id value. The lease-checks parameter was set to a value that told Kea to try to correct the problem. There is a matching subnet, so Kea updated subnet-id and loaded the lease successfully.

**DHCPSRV\_LEASE\_SANITY\_FIXED (1) The lease %1 with subnet-id %2 failed subnet-id checks, but was corrected to subnet**

This informational message is printed when a lease was loaded, but had incorrect subnet-id value. The lease-checks parameter was set to a value that told Kea to try to correct the problem. There is a matching subnet, so Kea updated subnet-id and loaded the lease successfully.

**DHCPSRV\_MEMFILE\_ADD\_ADDR4 adding IPv4 lease with address %1**

A debug message issued when the server is about to add an IPv4 lease with the specified address to the memory file backend database.

**DHCPSRV\_MEMFILE\_ADD\_ADDR4 (1) adding IPv4 lease with address %1**

A debug message issued when the server is about to add an IPv4 lease with the specified address to the memory file backend database.

**DHCPSRV\_MEMFILE\_ADD\_ADDR6 adding IPv6 lease with address %1**

A debug message issued when the server is about to add an IPv6 lease with the specified address to the memory file backend database.

**DHCPSRV\_MEMFILE\_ADD\_ADDR6 (1) adding IPv6 lease with address %1**

A debug message issued when the server is about to add an IPv6 lease with the specified address to the memory file backend database.

**DHCPSRV\_MEMFILE\_BEGIN\_TRANSACTION committing to memory file database**

The code has issued a begin transaction call. For the memory file database, this is a no-op.

**DHCPSRV\_MEMFILE\_BEGIN\_TRANSACTION (1) committing to memory file database**

The code has issued a begin transaction call. For the memory file database, this is a no-op.

**DHCPSRV\_MEMFILE\_COMMIT committing to memory file database**

The code has issued a commit call. For the memory file database, this is a no-op.

**DHCPSRV\_MEMFILE\_COMMIT (1) committing to memory file database**

The code has issued a commit call. For the memory file database, this is a no-op.

**DHCPSRV\_MEMFILE\_CONVERTING\_LEASE\_FILES running LFC now to convert lease files to the current schema: %1.%2**

A warning message issued when the server has detected lease files that need to be either upgraded or downgraded to match the server's schema, and that the server is automatically running the LFC process to perform the conversion. This should only occur the first time the server is launched following a Kea installation upgrade (or downgrade).

**DHCPSRV\_MEMFILE\_CONVERTING\_LEASE\_FILES (1) running LFC now to convert lease files to the current schema: %1.%2**

A warning message issued when the server has detected lease files that need to be either upgraded or downgraded to match the server's schema, and that the server is automatically running the LFC process to perform the conversion. This should only occur the first time the server is launched following a Kea installation upgrade (or downgrade).

**DHCPSRV\_MEMFILE\_DB opening memory file lease database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a memory file lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_MEMFILE\_DB (1) opening memory file lease database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a memory file lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_MEMFILE\_DELETE\_ADDR deleting lease for address %1**

A debug message issued when the server is attempting to delete a lease for the specified address from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_DELETE\_ADDR (1) deleting lease for address %1**

A debug message issued when the server is attempting to delete a lease for the specified address from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED4 deleting reclaimed IPv4 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED4 (1) deleting reclaimed IPv4 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED6 deleting reclaimed IPv6 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED6 (1) deleting reclaimed IPv6 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED\_START starting deletion of %1 expired-reclaimed leases**

A debug message issued when the server has found expired-reclaimed leases to be removed. The number of leases to be removed is logged in the message.

**DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED\_START (1) starting deletion of %1 expired-reclaimed leases**

A debug message issued when the server has found expired-reclaimed leases to be removed. The number of leases to be removed is logged in the message.

**DHCPSRV\_MEMFILE\_GET4 obtaining all IPv4 leases**

A debug message issued when the server is attempting to obtain all IPv4 leases from the memory file database.

**DHCPSRV\_MEMFILE\_GET4 (1) obtaining all IPv4 leases**

A debug message issued when the server is attempting to obtain all IPv4 leases from the memory file database.

**DHCPSRV\_MEMFILE\_GET6 obtaining all IPv6 leases**

A debug message issued when the server is attempting to obtain all IPv6 leases from the memory file database.

**DHCPSRV\_MEMFILE\_GET6 (1) obtaining all IPv6 leases**

A debug message issued when the server is attempting to obtain all IPv6 leases from the memory file database.

**DHCPSRV\_MEMFILE\_GET6\_DUID obtaining IPv6 leases for DUID %1**

A debug message issued when the server is attempting to obtain IPv6 leases from the memory file database for the DUID.

**DHCPSRV\_MEMFILE\_GET6\_DUID (1) obtaining IPv6 leases for DUID %1**

A debug message issued when the server is attempting to obtain IPv6 leases from the memory file database for the DUID.

**DHCPSRV\_MEMFILE\_GET\_ADDR4 obtaining IPv4 lease for address %1**

A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_GET\_ADDR4 (1) obtaining IPv4 lease for address %1**

A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_GET\_ADDR6 obtaining IPv6 lease for address %1 and lease type %2**

A debug message issued when the server is attempting to obtain an IPv6 lease from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_GET\_ADDR6 (1) obtaining IPv6 lease for address %1 and lease type %2**

A debug message issued when the server is attempting to obtain an IPv6 lease from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_GET\_CLIENTID obtaining IPv4 leases for client ID %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified client identification.

**DHCPSRV\_MEMFILE\_GET\_CLIENTID (1) obtaining IPv4 leases for client ID %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified client identification.

**DHCPSRV\_MEMFILE\_GET\_CLIENTID\_HWADDR\_SUBID obtaining IPv4 lease for client ID %1, hardware address %2 and subnet ID %3**

A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified client ID, hardware address and subnet ID.

**DHCPSRV\_MEMFILE\_GET\_CLIENTID\_HWADDR\_SUBID (1) obtaining IPv4 lease for client ID %1, hardware address %2 and subnet ID %3**

A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified client ID, hardware address and subnet ID.

**DHCPSRV\_MEMFILE\_GET\_EXPIRED4 obtaining maximum %1 of expired IPv4 leases**

A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_MEMFILE\_GET\_EXPIRED4 (1) obtaining maximum %1 of expired IPv4 leases**

A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_MEMFILE\_GET\_EXPIRED6 obtaining maximum %1 of expired IPv6 leases**

A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_MEMFILE\_GET\_EXPIRED6 (1) obtaining maximum %1 of expired IPv6 leases**

A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_MEMFILE\_GET\_HWADDR obtaining IPv4 leases for hardware address %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified hardware address.

**DHCPSRV\_MEMFILE\_GET\_HWADDR (1) obtaining IPv4 leases for hardware address %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified hardware address.

**DHCPSRV\_MEMFILE\_GET\_IAID\_DUID obtaining IPv6 leases for IAID %1 and DUID %2 and lease type %3**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

**DHCPSRV\_MEMFILE\_GET\_IAID\_DUID (1) obtaining IPv6 leases for IAID %1 and DUID %2 and lease type %3**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

**DHCPSRV\_MEMFILE\_GET\_IAID\_SUBID\_DUID obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3 and lease type %4**

A debug message issued when the server is attempting to obtain an IPv6 lease from the memory file database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

**DHCPSRV\_MEMFILE\_GET\_IAID\_SUBID\_DUID (1) obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3 and lease type %4**

A debug message issued when the server is attempting to obtain an IPv6 lease from the memory file database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

**DHCPSRV\_MEMFILE\_GET\_PAGE4 obtaining at most %1 IPv4 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_MEMFILE\_GET\_PAGE4 (1) obtaining at most %1 IPv4 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_MEMFILE\_GET\_PAGE6 obtaining at most %1 IPv6 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_MEMFILE\_GET\_PAGE6 (1) obtaining at most %1 IPv6 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_MEMFILE\_GET\_SUBID4 obtaining IPv4 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the memory file database.

**DHCPSRV\_MEMFILE\_GET\_SUBID4 (1) obtaining IPv4 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the memory file database.

**DHCPSRV\_MEMFILE\_GET\_SUBID6 obtaining IPv6 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the memory file database.

**DHCPSRV\_MEMFILE\_GET\_SUBID6 (1) obtaining IPv6 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the memory file database.

**DHCPSRV\_MEMFILE\_GET\_SUBID\_CLIENTID obtaining IPv4 lease for subnet ID %1 and client ID %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and client ID.

**DHCPSRV\_MEMFILE\_GET\_SUBID\_CLIENTID (1) obtaining IPv4 lease for subnet ID %1 and client ID %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and client ID.

**DHCPSRV\_MEMFILE\_GET\_SUBID\_HWADDR obtaining IPv4 lease for subnet ID %1 and hardware address %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and hardware address.

**DHCPSRV\_MEMFILE\_GET\_SUBID\_HWADDR (1) obtaining IPv4 lease for subnet ID %1 and hardware address %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and hardware address.

**DHCPSRV\_MEMFILE\_GET\_VERSION obtaining schema version information**

A debug message issued when the server is about to obtain schema version information from the memory file database.

**DHCPSRV\_MEMFILE\_GET\_VERSION (1) obtaining schema version information**

A debug message issued when the server is about to obtain schema version information from the memory file database.

**DHCPSRV\_MEMFILE\_LEASE\_FILE\_LOAD loading leases from file %1**

An info message issued when the server is about to start reading DHCP leases from the lease file. All leases currently held in the memory will be replaced by those read from the file.

**DHCPSRV\_MEMFILE\_LEASE\_FILE\_LOAD (1) loading leases from file %1**

An info message issued when the server is about to start reading DHCP leases from the lease file. All leases currently held in the memory will be replaced by those read from the file.

**DHCPSRV\_MEMFILE\_LEASE\_LOAD loading lease %1**

A debug message issued when DHCP lease is being loaded from the file to memory.



**DHCPSRV\_MEMFILE\_LEASE\_LOAD (1) loading lease %1**

A debug message issued when DHCP lease is being loaded from the file to memory.

**DHCPSRV\_MEMFILE\_LEASE\_LOAD\_ROW\_ERROR discarding row %1, error: %2**

An error message issued the the DHCP lease being loaded from the given row of the lease file fails. The log message should contain the specific reason the row was discarded. The server will continue loading the remaining data. This may indicate a corrupt lease file.

**DHCPSRV\_MEMFILE\_LEASE\_LOAD\_ROW\_ERROR (1) discarding row %1, error: %2**

An error message issued the the DHCP lease being loaded from the given row of the lease file fails. The log message should contain the specific reason the row was discarded. The server will continue loading the remaining data. This may indicate a corrupt lease file.

**DHCPSRV\_MEMFILE\_LFC\_EXECUTE executing Lease File Cleanup using: %1**

An informational message issued when the Memfile lease database backend starts a new process to perform Lease File Cleanup.

**DHCPSRV\_MEMFILE\_LFC\_EXECUTE (1) executing Lease File Cleanup using: %1**

An informational message issued when the Memfile lease database backend starts a new process to perform Lease File Cleanup.

**DHCPSRV\_MEMFILE\_LFC\_LEASE\_FILE\_RENAME\_FAIL failed to rename the current lease file %1 to %2, reason: %3**

An error message logged when the Memfile lease database backend fails to move the current lease file to a new file on which the cleanup should be performed. This effectively means that the lease file cleanup will not take place.

**DHCPSRV\_MEMFILE\_LFC\_LEASE\_FILE\_RENAME\_FAIL (1) failed to rename the current lease file %1 to %2, reason: %3**

An error message logged when the Memfile lease database backend fails to move the current lease file to a new file on which the cleanup should be performed. This effectively means that the lease file cleanup will not take place.

**DHCPSRV\_MEMFILE\_LFC\_LEASE\_FILE\_REOPEN\_FAIL failed to reopen lease file %1 after preparing input file for lease**

An error message logged when the Memfile lease database backend failed to re-open or re-create the lease file after renaming the lease file for lease file cleanup. The server will continue to operate but leases will not be persisted to disk.

**DHCPSRV\_MEMFILE\_LFC\_LEASE\_FILE\_REOPEN\_FAIL (1) failed to reopen lease file %1 after preparing input file for lease**

An error message logged when the Memfile lease database backend failed to re-open or re-create the lease file after renaming the lease file for lease file cleanup. The server will continue to operate but leases will not be persisted to disk.

**DHCPSRV\_MEMFILE\_LFC\_SETUP setting up the Lease File Cleanup interval to %1 sec**

An informational message logged when the Memfile lease database backend configures the LFC to be executed periodically. The argument holds the interval in seconds in which the LFC will be executed.

**DHCPSRV\_MEMFILE\_LFC\_SETUP (1) setting up the Lease File Cleanup interval to %1 sec**

An informational message logged when the Memfile lease database backend configures the LFC to be executed periodically. The argument holds the interval in seconds in which the LFC will be executed.

**DHCPSRV\_MEMFILE\_LFC\_SPAWN\_FAIL lease file cleanup failed to run because kea-lfc process couldn't be spawned**

This error message is logged when the Kea server fails to run kea-lfc, the program that cleans up the lease file. The server will try again the next time a lease file cleanup is scheduled. Although this message should not appear and the reason why it did investigated, the occasional failure to start the lease file cleanup will not impact operations. Should the failure persist however, the size of the lease file will increase without bound.

**DHCPSRV\_MEMFILE\_LFC\_SPAWN\_FAIL (1) lease file cleanup failed to run because kea-lfc process couldn't be spawned**

This error message is logged when the Kea server fails to run kea-lfc, the program that cleans up the lease file. The server will try again the next time a lease file cleanup is scheduled. Although this message should not appear and the reason why it did investigated, the occasional failure to start the lease file cleanup will not impact operations. Should the failure persist however, the size of the lease file will increase without bound.

**DHCPSRV\_MEMFILE\_LFC\_START starting Lease File Cleanup**

An informational message issued when the Memfile lease database backend starts the periodic Lease File Cleanup.

**DHCPSRV\_MEMFILE\_LFC\_START (1) starting Lease File Cleanup**

An informational message issued when the Memfile lease database backend starts the periodic Lease File Cleanup.

**DHCPSRV\_MEMFILE\_LFC\_UNREGISTER\_TIMER\_FAILED failed to unregister timer 'memfile-lfc': %1**

This debug message is logged when Memfile backend fails to unregister timer used for lease file cleanup scheduling. There are several reasons why this could occur, although the most likely cause is that the system is being shut down and some other component has unregistered the timer. The message includes the reason for this error.

**DHCPSRV\_MEMFILE\_LFC\_UNREGISTER\_TIMER\_FAILED (1) failed to unregister timer 'memfile-lfc': %1**

This debug message is logged when Memfile backend fails to unregister timer used for lease file cleanup scheduling. There are several reasons why this could occur, although the most likely cause is that the system is being shut down and some other component has unregistered the timer. The message includes the reason for this error.

**DHCPSRV\_MEMFILE\_NEEDS\_DOWNGRADING version of lease file: %1 schema is later than version %2**

A warning message issued when the schema of the lease file loaded by the server is newer than the memfile schema of the server. The server converts the lease data from newer schemas to its schema as it is read, therefore the lease information in use by the server will be correct. Note though, that any data stored in newer schema fields will be dropped. What remains is for the file itself to be rewritten using the current schema.

**DHCPSRV\_MEMFILE\_NEEDS\_DOWNGRADING (1) version of lease file: %1 schema is later than version %2**

A warning message issued when the schema of the lease file loaded by the server is newer than the memfile schema of the server. The server converts the lease data from newer schemas to its schema as it is read, therefore the lease information in use by the server will be correct. Note though, that any data stored in newer schema fields will be dropped. What remains is for the file itself to be rewritten using the current schema.

**DHCPSRV\_MEMFILE\_NEEDS\_UPGRADING version of lease file: %1 schema is earlier than version %2**

A warning message issued when the schema of the lease file loaded by the server pre-dates the memfile schema of the server. Note that the server converts the lease data from older schemas to the current schema as it is read, therefore the lease information in use by the server will be correct. What remains is for the file itself to be rewritten using the current schema.

**DHCPSRV\_MEMFILE\_NEEDS\_UPGRADING (1) version of lease file: %1 schema is earlier than version %2**

A warning message issued when the schema of the lease file loaded by the server pre-dates the memfile schema of the server. Note that the server converts the lease data from older schemas to the current schema as it is read, therefore the lease information in use by the server will be correct. What remains is for the file itself to be rewritten using the current schema.

**DHCPSRV\_MEMFILE\_NO\_STORAGE running in non-persistent mode, leases will be lost after restart**

A warning message issued when writes of leases to disk have been disabled in the configuration. This mode is useful for some kinds of performance testing but should not be enabled in normal circumstances. Non-persistence mode is enabled when 'persist4=no persist6=no' parameters are specified in the database access string.

**DHCPSRV\_MEMFILE\_NO\_STORAGE (1) running in non-persistent mode, leases will be lost after restart**

A warning message issued when writes of leases to disk have been disabled in the configuration. This mode is useful for some kinds of performance testing but should not be enabled in normal circumstances. Non-persistence mode is enabled when 'persist4=no persist6=no' parameters are specified in the database access string.

**DHCPSRV\_MEMFILE\_READ\_HWADDR\_FAIL failed to read hardware address from lease file: %1**

A warning message issued when read attempt of the hardware address stored in a disk file failed. The parameter should provide the exact nature of the failure. The database read will continue, but that particular lease will no longer have hardware address associated with it.

**DHCPSRV\_MEMFILE\_READ\_HWADDR\_FAIL (1) failed to read hardware address from lease file: %1**

A warning message issued when read attempt of the hardware address stored in a disk file failed. The parameter should provide the exact nature of the failure. The database read will continue, but that particular lease will no longer have hardware address associated with it.

**DHCPSRV\_MEMFILE\_ROLLBACK rolling back memory file database**

The code has issued a rollback call. For the memory file database, this is a no-op.

**DHCPSRV\_MEMFILE\_ROLLBACK (1) rolling back memory file database**

The code has issued a rollback call. For the memory file database, this is a no-op.

**DHCPSRV\_MEMFILE\_UPDATE\_ADDR4 updating IPv4 lease for address %1**

A debug message issued when the server is attempting to update IPv4 lease from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_UPDATE\_ADDR4 (1) updating IPv4 lease for address %1**

A debug message issued when the server is attempting to update IPv4 lease from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_UPDATE\_ADDR6 updating IPv6 lease for address %1**

A debug message issued when the server is attempting to update IPv6 lease from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_UPDATE\_ADDR6 (1) updating IPv6 lease for address %1**

A debug message issued when the server is attempting to update IPv6 lease from the memory file database for the specified address.

**DHCPSRV\_MEMFILE\_WIPE\_LEASES4 removing all IPv4 leases from subnet %1**

This informational message is printed when removal of all leases from specified IPv4 subnet is commencing. This is a result of receiving administrative command.

**DHCPSRV\_MEMFILE\_WIPE\_LEASES4 (1) removing all IPv4 leases from subnet %1**

This informational message is printed when removal of all leases from specified IPv4 subnet is commencing. This is a result of receiving administrative command.

**DHCPSRV\_MEMFILE\_WIPE\_LEASES4\_FINISHED removing all IPv4 leases from subnet %1 finished, removed %2 leases**

This informational message is printed when removal of all leases from a specified IPv4 subnet has finished. The number of removed leases is printed.

**DHCPSRV\_MEMFILE\_WIPE\_LEASES4\_FINISHED (1) removing all IPv4 leases from subnet %1 finished, removed %2 leases**

This informational message is printed when removal of all leases from a specified IPv4 subnet has finished. The number of removed leases is printed.

**DHCPSRV\_MEMFILE\_WIPE\_LEASES6 removing all IPv6 leases from subnet %1**

This informational message is printed when removal of all leases from specified IPv6 subnet is commencing. This is a result of receiving administrative command.

**DHCPSRV\_MEMFILE\_WIPE\_LEASES6 (1) removing all IPv6 leases from subnet %1**

This informational message is printed when removal of all leases from specified IPv6 subnet is commencing. This is a result of receiving administrative command.

**DHCPSRV\_MEMFILE\_WIPE\_LEASES6\_FINISHED removing all IPv6 leases from subnet %1 finished, removed %2 leases**

This informational message is printed when removal of all leases from a specified IPv6 subnet has finished. The number of removed leases is printed.

**DHCPSRV\_MEMFILE\_WIPE\_LEASES6\_FINISHED (1) removing all IPv6 leases from subnet %1 finished, removed %2 leases**

This informational message is printed when removal of all leases from a specified IPv6 subnet has finished. The number of removed leases is printed.

**DHCPSRV\_MULTIPLE\_RAW\_SOCKETS\_PER\_IFACE current configuration will result in opening multiple broadcast capabilities**

A warning message issued when the current configuration indicates that multiple sockets, capable of receiving broadcast traffic, will be opened on some of the interfaces. It must be noted that this may lead to receiving and processing the same DHCP message multiple times, as it will be received by each socket individually.

**DHCPSRV\_MULTIPLE\_RAW\_SOCKETS\_PER\_IFACE (1) current configuration will result in opening multiple broadcast ca**

A warning message issued when the current configuration indicates that multiple sockets, capable of receiving broadcast traffic, will be opened on some of the interfaces. It must be noted that this may lead to receiving and processing the same DHCP message multiple times, as it will be received by each socket individually.

**DHCPSRV\_MYSQL\_ADD\_ADDR4 adding IPv4 lease with address %1**

A debug message issued when the server is about to add an IPv4 lease with the specified address to the MySQL backend database.

**DHCPSRV\_MYSQL\_ADD\_ADDR4 (1) adding IPv4 lease with address %1**

A debug message issued when the server is about to add an IPv4 lease with the specified address to the MySQL backend database.

**DHCPSRV\_MYSQL\_ADD\_ADDR6 adding IPv6 lease with address %1, lease type %2**

A debug message issued when the server is about to add an IPv6 lease with the specified address to the MySQL backend database.

**DHCPSRV\_MYSQL\_ADD\_ADDR6 (1) adding IPv6 lease with address %1, lease type %2**

A debug message issued when the server is about to add an IPv6 lease with the specified address to the MySQL backend database.

**DHCPSRV\_MYSQL\_BEGIN\_TRANSACTION committing to MySQL database**

The code has issued a begin transaction call.

**DHCPSRV\_MYSQL\_BEGIN\_TRANSACTION (1) committing to MySQL database**

The code has issued a begin transaction call.

**DHCPSRV\_MYSQL\_COMMIT committing to MySQL database**

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the committal may not include a write to disk.

**DHCPSRV\_MYSQL\_COMMIT (1) committing to MySQL database**

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the committal may not include a write to disk.

**DHCPSRV\_MYSQL\_DB opening MySQL lease database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_MYSQL\_DB (1) opening MySQL lease database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_MYSQL\_DELETED\_EXPIRED\_RECLAIMED deleted %1 reclaimed leases from the database**

A debug message issued when the server has removed a number of reclaimed leases from the database. The number of removed leases is included in the message.

**DHCPSRV\_MYSQL\_DELETED\_EXPIRED\_RECLAIMED (1) deleted %1 reclaimed leases from the database**

A debug message issued when the server has removed a number of reclaimed leases from the database. The number of removed leases is included in the message.

**DHCPSRV\_MYSQL\_DELETE\_ADDR deleting lease for address %1**

A debug message issued when the server is attempting to delete a lease for the specified address from the MySQL database for the specified address.

**DHCPSRV\_MYSQL\_DELETE\_ADDR (1) deleting lease for address %1**

A debug message issued when the server is attempting to delete a lease for the specified address from the MySQL database for the specified address.

**DHCPSRV\_MYSQL\_DELETE\_EXPIRED\_RECLAIMED4 deleting reclaimed IPv4 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_MYSQL\_DELETE\_EXPIRED\_RECLAIMED4 (1) deleting reclaimed IPv4 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_MYSQL\_DELETE\_EXPIRED\_RECLAIMED6 deleting reclaimed IPv6 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_MYSQL\_DELETE\_EXPIRED\_RECLAIMED6 (1) deleting reclaimed IPv6 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_MYSQL\_FATAL\_ERROR Unrecoverable MySQL error occurred: %1 for <%2>, reason: %3 (error code: %4).**

An error message indicating that communication with the MySQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover connectivity. If not the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the MySQL server has gone down.

**DHCPSRV\_MYSQL\_FATAL\_ERROR (1) Unrecoverable MySQL error occurred: %1 for <%2>, reason: %3 (error code: %4).**

An error message indicating that communication with the MySQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover connectivity. If not the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the MySQL server has gone down.

**DHCPSRV\_MYSQL\_GET4 obtaining all IPv4 leases**

A debug message issued when the server is attempting to obtain all IPv4 leases from the MySQL database.

**DHCPSRV\_MYSQL\_GET4 (1) obtaining all IPv4 leases**

A debug message issued when the server is attempting to obtain all IPv4 leases from the MySQL database.

**DHCPSRV\_MYSQL\_GET6 obtaining all IPv6 leases**

A debug message issued when the server is attempting to obtain all IPv6 leases from the MySQL database.

**DHCPSRV\_MYSQL\_GET6 (1) obtaining all IPv6 leases**

A debug message issued when the server is attempting to obtain all IPv6 leases from the MySQL database.

**DHCPSRV\_MYSQL\_GET\_ADDR4 obtaining IPv4 lease for address %1**

A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for the specified address.

**DHCPSRV\_MYSQL\_GET\_ADDR4 (1) obtaining IPv4 lease for address %1**

A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for the specified address.

**DHCPSRV\_MYSQL\_GET\_ADDR6 obtaining IPv6 lease for address %1, lease type %2**

A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified address.

---

**DHCPSRV\_MYSQL\_GET\_ADDR6 (1) obtaining IPv6 lease for address %1, lease type %2**

A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified address.

**DHCPSRV\_MYSQL\_GET\_CLIENTID obtaining IPv4 leases for client ID %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified client identification.

**DHCPSRV\_MYSQL\_GET\_CLIENTID (1) obtaining IPv4 leases for client ID %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified client identification.

**DHCPSRV\_MYSQL\_GET\_DUID obtaining IPv6 lease for duid %1,**

A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified duid.

**DHCPSRV\_MYSQL\_GET\_DUID (1) obtaining IPv6 lease for duid %1,**

A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified duid.

**DHCPSRV\_MYSQL\_GET\_EXPIRED4 obtaining maximum %1 of expired IPv4 leases**

A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_MYSQL\_GET\_EXPIRED4 (1) obtaining maximum %1 of expired IPv4 leases**

A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_MYSQL\_GET\_EXPIRED6 obtaining maximum %1 of expired IPv6 leases**

A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_MYSQL\_GET\_EXPIRED6 (1) obtaining maximum %1 of expired IPv6 leases**

A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_MYSQL\_GET\_HWADDR obtaining IPv4 leases for hardware address %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified hardware address.

**DHCPSRV\_MYSQL\_GET\_HWADDR (1) obtaining IPv4 leases for hardware address %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified hardware address.

**DHCPSRV\_MYSQL\_GET\_IAID\_DUID obtaining IPv6 leases for IAID %1, DUID %2, lease type %3**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

**DHCPSRV\_MYSQL\_GET\_IAID\_DUID (1) obtaining IPv6 leases for IAID %1, DUID %2, lease type %3**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

**DHCPSRV\_MYSQL\_GET\_IAID\_SUBID\_DUID obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3, lease type %4**

A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

**DHCPSRV\_MYSQL\_GET\_IAID\_SUBID\_DUID (1) obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3, lease type %4**

A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

**DHCPSRV\_MYSQL\_GET\_PAGE4 obtaining at most %1 IPv4 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_MYSQL\_GET\_PAGE4 (1) obtaining at most %1 IPv4 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_MYSQL\_GET\_PAGE6 obtaining at most %1 IPv6 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_MYSQL\_GET\_PAGE6 (1) obtaining at most %1 IPv6 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_MYSQL\_GET\_SUBID4 obtaining IPv4 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the MySQL database.

**DHCPSRV\_MYSQL\_GET\_SUBID4 (1) obtaining IPv4 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the MySQL database.

**DHCPSRV\_MYSQL\_GET\_SUBID6 obtaining IPv6 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the MySQL database.

**DHCPSRV\_MYSQL\_GET\_SUBID6 (1) obtaining IPv6 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the MySQL database.

**DHCPSRV\_MYSQL\_GET\_SUBID\_CLIENTID obtaining IPv4 lease for subnet ID %1 and client ID %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and client ID.

**DHCPSRV\_MYSQL\_GET\_SUBID\_CLIENTID (1) obtaining IPv4 lease for subnet ID %1 and client ID %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and client ID.

**DHCPSRV\_MYSQL\_GET\_SUBID\_HWADDR obtaining IPv4 lease for subnet ID %1 and hardware address %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and hardware address.

**DHCPSRV\_MYSQL\_GET\_SUBID\_HWADDR (1) obtaining IPv4 lease for subnet ID %1 and hardware address %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and hardware address.

**DHCPSRV\_MYSQL\_GET\_VERSION obtaining schema version information**

A debug message issued when the server is about to obtain schema version information from the MySQL database.

**DHCPSRV\_MYSQL\_GET\_VERSION (1) obtaining schema version information**

A debug message issued when the server is about to obtain schema version information from the MySQL database.

**DHCPSRV\_MYSQL\_HOST\_DB opening MySQL hosts database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_MYSQL\_HOST\_DB (1) opening MySQL hosts database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_MYSQL\_HOST\_DB\_GET\_VERSION obtaining schema version information for the MySQL hosts database**

A debug message issued when the server is about to obtain schema version information from the MySQL hosts database.

---

**DHCPSRV\_MYSQL\_HOST\_DB\_GET\_VERSION (1) obtaining schema version information for the MySQL hosts database**

A debug message issued when the server is about to obtain schema version information from the MySQL hosts database.

**DHCPSRV\_MYSQL\_HOST\_DB\_READONLY MySQL host database opened for read access only**

This informational message is issued when the user has configured the MySQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

**DHCPSRV\_MYSQL\_HOST\_DB\_READONLY (1) MySQL host database opened for read access only**

This informational message is issued when the user has configured the MySQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

**DHCPSRV\_MYSQL\_ROLLBACK rolling back MySQL database**

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

**DHCPSRV\_MYSQL\_ROLLBACK (1) rolling back MySQL database**

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

**DHCPSRV\_MYSQL\_START\_TRANSACTION starting new MySQL transaction**

A debug message issued when a new MySQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

**DHCPSRV\_MYSQL\_START\_TRANSACTION (1) starting new MySQL transaction**

A debug message issued when a new MySQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

**DHCPSRV\_MYSQL\_UPDATE\_ADDR4 updating IPv4 lease for address %1**

A debug message issued when the server is attempting to update IPv4 lease from the MySQL database for the specified address.

**DHCPSRV\_MYSQL\_UPDATE\_ADDR4 (1) updating IPv4 lease for address %1**

A debug message issued when the server is attempting to update IPv4 lease from the MySQL database for the specified address.

**DHCPSRV\_MYSQL\_UPDATE\_ADDR6 updating IPv6 lease for address %1, lease type %2**

A debug message issued when the server is attempting to update IPv6 lease from the MySQL database for the specified address.

**DHCPSRV\_MYSQL\_UPDATE\_ADDR6 (1) updating IPv6 lease for address %1, lease type %2**

A debug message issued when the server is attempting to update IPv6 lease from the MySQL database for the specified address.

**DHCPSRV\_NOTYPE\_DB no 'type' keyword to determine database backend: %1**

This is an error message, logged when an attempt has been made to access a database backend, but where no 'type' keyword has been included in the access string. The access string (less any passwords) is included in the message.

**DHCPSRV\_NOTYPE\_DB (1) no 'type' keyword to determine database backend: %1**

This is an error message, logged when an attempt has been made to access a database backend, but where no 'type' keyword has been included in the access string. The access string (less any passwords) is included in the message.

**DHCPSRV\_NO\_SOCKETS\_OPEN no interface configured to listen to DHCP traffic**

This warning message is issued when the current server configuration specifies no interfaces that the server should listen on, or when the specified interfaces are not configured to receive the traffic.

**DHCPSRV\_NO\_SOCKETS\_OPEN (1) no interface configured to listen to DHCP traffic**

This warning message is issued when the current server configuration specifies no interfaces that the server should listen on, or when the specified interfaces are not configured to receive the traffic.



**DHCPSRV\_OPEN\_SOCKET\_FAIL failed to open socket: %1**

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

**DHCPSRV\_OPEN\_SOCKET\_FAIL (1) failed to open socket: %1**

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

**DHCPSRV\_PGSQL\_ADD\_ADDR4 adding IPv4 lease with address %1**

A debug message issued when the server is about to add an IPv4 lease with the specified address to the PostgreSQL backend database.

**DHCPSRV\_PGSQL\_ADD\_ADDR4 (1) adding IPv4 lease with address %1**

A debug message issued when the server is about to add an IPv4 lease with the specified address to the PostgreSQL backend database.

**DHCPSRV\_PGSQL\_ADD\_ADDR6 adding IPv6 lease with address %1**

A debug message issued when the server is about to add an IPv6 lease with the specified address to the PostgreSQL backend database.

**DHCPSRV\_PGSQL\_ADD\_ADDR6 (1) adding IPv6 lease with address %1**

A debug message issued when the server is about to add an IPv6 lease with the specified address to the PostgreSQL backend database.

**DHCPSRV\_PGSQL\_BEGIN\_TRANSACTION committing to PostgreSQL database**

The code has issued a begin transaction call.

**DHCPSRV\_PGSQL\_BEGIN\_TRANSACTION (1) committing to PostgreSQL database**

The code has issued a begin transaction call.

**DHCPSRV\_PGSQL\_COMMIT committing to PostgreSQL database**

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the committal may not include a write to disk.

**DHCPSRV\_PGSQL\_COMMIT (1) committing to PostgreSQL database**

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the committal may not include a write to disk.

**DHCPSRV\_PGSQL\_DB opening PostgreSQL lease database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_PGSQL\_DB (1) opening PostgreSQL lease database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_PGSQL\_DEALLOC\_ERROR An error occurred deallocating SQL statements while closing the PostgreSQL lease**

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing database SQL resources as part of closing its connection to the PostgreSQL database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

**DHCPSRV\_PGSQL\_DEALLOC\_ERROR (1) An error occurred deallocating SQL statements while closing the PostgreSQL lease**

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing database SQL resources as part of closing its connection to the PostgreSQL database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

**DHCPSRV\_PGSQL\_DELETE\_ADDR deleting lease for address %1**

A debug message issued when the server is attempting to delete a lease for the specified address from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_DELETE\_ADDR (1) deleting lease for address %1**

A debug message issued when the server is attempting to delete a lease for the specified address from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_DELETE\_EXPIRED\_RECLAIMED4 deleting reclaimed IPv4 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_PGSQL\_DELETE\_EXPIRED\_RECLAIMED4 (1) deleting reclaimed IPv4 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_PGSQL\_DELETE\_EXPIRED\_RECLAIMED6 deleting reclaimed IPv6 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_PGSQL\_DELETE\_EXPIRED\_RECLAIMED6 (1) deleting reclaimed IPv6 leases that expired more than %1 seconds**

A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

**DHCPSRV\_PGSQL\_FATAL\_ERROR Unrecoverable PostgreSQL error occurred: Statement: <%1>, reason: %2 (error code: %3)**

An error message indicating that communication with the PostgreSQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover the connectivity. If not the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the PostgreSQL server has gone down.

**DHCPSRV\_PGSQL\_FATAL\_ERROR (1) Unrecoverable PostgreSQL error occurred: Statement: <%1>, reason: %2 (error code: %3)**

An error message indicating that communication with the PostgreSQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover the connectivity. If not the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the PostgreSQL server has gone down.

**DHCPSRV\_PGSQL\_GET4 obtaining all IPv4 leases**

A debug message issued when the server is attempting to obtain all IPv4 leases from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET4 (1) obtaining all IPv4 leases**

A debug message issued when the server is attempting to obtain all IPv4 leases from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET6 obtaining all IPv6 leases**

A debug message issued when the server is attempting to obtain all IPv6 leases from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET6 (1) obtaining all IPv6 leases**

A debug message issued when the server is attempting to obtain all IPv6 leases from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET\_ADDR4 obtaining IPv4 lease for address %1**

A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_GET\_ADDR4 (1) obtaining IPv4 lease for address %1**

A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_GET\_ADDR6 obtaining IPv6 lease for address %1 (lease type %2)**

A debug message issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_GET\_ADDR6 (1) obtaining IPv6 lease for address %1 (lease type %2)**

A debug message issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_GET\_CLIENTID obtaining IPv4 leases for client ID %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified client identification.

**DHCPSRV\_PGSQL\_GET\_CLIENTID (1) obtaining IPv4 leases for client ID %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified client identification.

**DHCPSRV\_PGSQL\_GET\_DUID obtaining IPv6 leases for DUID %1,**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified DUID (DHCP Unique Identifier).

**DHCPSRV\_PGSQL\_GET\_DUID (1) obtaining IPv6 leases for DUID %1,**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified DUID (DHCP Unique Identifier).

**DHCPSRV\_PGSQL\_GET\_EXPIRED4 obtaining maximum %1 of expired IPv4 leases**

A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_PGSQL\_GET\_EXPIRED4 (1) obtaining maximum %1 of expired IPv4 leases**

A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_PGSQL\_GET\_EXPIRED6 obtaining maximum %1 of expired IPv6 leases**

A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_PGSQL\_GET\_EXPIRED6 (1) obtaining maximum %1 of expired IPv6 leases**

A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

**DHCPSRV\_PGSQL\_GET\_HWADDR obtaining IPv4 leases for hardware address %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified hardware address.

**DHCPSRV\_PGSQL\_GET\_HWADDR (1) obtaining IPv4 leases for hardware address %1**

A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified hardware address.

**DHCPSRV\_PGSQL\_GET\_IAID\_DUID obtaining IPv4 leases for IAID %1 and DUID %2, lease type %3**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

**DHCPSRV\_PGSQL\_GET\_IAID\_DUID (1) obtaining IPv4 leases for IAID %1 and DUID %2, lease type %3**

A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

**DHCPSRV\_PGSQL\_GET\_IAID\_SUBID\_DUID obtaining IPv4 leases for IAID %1, Subnet ID %2, DUID %3, and lease type %4**

A debug message issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

**DHCPSRV\_PGSQL\_GET\_IAID\_SUBID\_DUID (1) obtaining IPv4 leases for IAID %1, Subnet ID %2, DUID %3, and lease type %4**

A debug message issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

**DHCPSRV\_PGSQL\_GET\_PAGE4 obtaining at most %1 IPv4 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_PGSQL\_GET\_PAGE4 (1) obtaining at most %1 IPv4 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_PGSQL\_GET\_PAGE6 obtaining at most %1 IPv6 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_PGSQL\_GET\_PAGE6 (1) obtaining at most %1 IPv6 leases starting from address %2**

A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

**DHCPSRV\_PGSQL\_GET\_SUBID4 obtaining IPv4 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET\_SUBID4 (1) obtaining IPv4 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET\_SUBID6 obtaining IPv6 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET\_SUBID6 (1) obtaining IPv6 leases for subnet ID %1**

A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET\_SUBID\_CLIENTID obtaining IPv4 lease for subnet ID %1 and client ID %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and client ID.

**DHCPSRV\_PGSQL\_GET\_SUBID\_CLIENTID (1) obtaining IPv4 lease for subnet ID %1 and client ID %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and client ID.

**DHCPSRV\_PGSQL\_GET\_SUBID\_HWADDR obtaining IPv4 lease for subnet ID %1 and hardware address %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and hardware address.

**DHCPSRV\_PGSQL\_GET\_SUBID\_HWADDR (1) obtaining IPv4 lease for subnet ID %1 and hardware address %2**

A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and hardware address.

**DHCPSRV\_PGSQL\_GET\_VERSION obtaining schema version information**

A debug message issued when the server is about to obtain schema version information from the PostgreSQL database.

**DHCPSRV\_PGSQL\_GET\_VERSION (1) obtaining schema version information**

A debug message issued when the server is about to obtain schema version information from the PostgreSQL database.

**DHCPSRV\_PGSQL\_HOST\_DB opening PostgreSQL hosts database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_PGSQL\_HOST\_DB (1) opening PostgreSQL hosts database: %1**

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

**DHCPSRV\_PGSQL\_HOST\_DB\_GET\_VERSION obtaining schema version information for the PostgreSQL hosts database**

A debug message issued when the server is about to obtain schema version information from the PostgreSQL hosts database.

**DHCPSRV\_PGSQL\_HOST\_DB\_GET\_VERSION (1) obtaining schema version information for the PostgreSQL hosts database**

A debug message issued when the server is about to obtain schema version information from the PostgreSQL hosts database.

**DHCPSRV\_PGSQL\_HOST\_DB\_READONLY PostgreSQL host database opened for read access only**

This informational message is issued when the user has configured the PostgreSQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

**DHCPSRV\_PGSQL\_HOST\_DB\_READONLY (1) PostgreSQL host database opened for read access only**

This informational message is issued when the user has configured the PostgreSQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

**DHCPSRV\_PGSQL\_ROLLBACK rolling back PostgreSQL database**

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

**DHCPSRV\_PGSQL\_ROLLBACK (1) rolling back PostgreSQL database**

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

**DHCPSRV\_PGSQL\_START\_TRANSACTION starting a new PostgreSQL transaction**

A debug message issued when a new PostgreSQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

**DHCPSRV\_PGSQL\_START\_TRANSACTION (1) starting a new PostgreSQL transaction**

A debug message issued when a new PostgreSQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

**DHCPSRV\_PGSQL\_UPDATE\_ADDR4 updating IPv4 lease for address %1**

A debug message issued when the server is attempting to update IPv4 lease from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_UPDATE\_ADDR4 (1) updating IPv4 lease for address %1**

A debug message issued when the server is attempting to update IPv4 lease from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_UPDATE\_ADDR6 updating IPv6 lease for address %1**

A debug message issued when the server is attempting to update IPv6 lease from the PostgreSQL database for the specified address.

**DHCPSRV\_PGSQL\_UPDATE\_ADDR6 (1) updating IPv6 lease for address %1**

A debug message issued when the server is attempting to update IPv6 lease from the PostgreSQL database for the specified address.

**DHCPSRV\_QUEUE\_NCR %1: name change request to %2 DNS entry queued: %3**

A debug message which is logged when the NameChangeRequest to add or remove a DNS entries for a particular lease has been queued. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument carries the details of the NameChangeRequest.

**DHCPSRV\_QUEUE\_NCR (1) %1: name change request to %2 DNS entry queued: %3**

A debug message which is logged when the NameChangeRequest to add or remove a DNS entries for a particular lease has been queued. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument carries the details of the NameChangeRequest.

**DHCPSRV\_QUEUE\_NCR\_FAILED %1: queuing %2 name change request failed for lease %3: %4**

This error message is logged when sending a name change request to DHCP DDNS failed. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument specifies the leased address. The last argument provides the reason for failure.

**DHCPSRV\_QUEUE\_NCR\_FAILED (1) %1: queuing %2 name change request failed for lease %3: %4**

This error message is logged when sending a name change request to DHCP DDNS failed. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument specifies the leased address. The last argument provides the reason for failure.

**DHCPSRV\_QUEUE\_NCR\_SKIP %1: skip queuing name change request for lease: %2**

This debug message is issued when the server decides to not queue the name change request because the lease doesn't include the FQDN, the forward and reverse update is disabled for this lease or the DNS updates are disabled in the configuration. The first argument includes the client identification information. The second argument includes the leased address.

**DHCPSRV\_QUEUE\_NCR\_SKIP (1) %1: skip queuing name change request for lease: %2**

This debug message is issued when the server decides to not queue the name change request because the lease doesn't include the FQDN, the forward and reverse update is disabled for this lease or the DNS updates are disabled in the configuration. The first argument includes the client identification information. The second argument includes the leased address.

**DHCPSRV\_TIMERMGR\_CALLBACK\_FAILED running handler for timer %1 caused exception: %2**

This error message is emitted when the timer elapsed and the operation associated with this timer has thrown an exception. The timer name and the reason for exception is logged.

**DHCPSRV\_TIMERMGR\_CALLBACK\_FAILED (1) running handler for timer %1 caused exception: %2**

This error message is emitted when the timer elapsed and the operation associated with this timer has thrown an exception. The timer name and the reason for exception is logged.

**DHCPSRV\_TIMERMGR\_REGISTER\_TIMER registering timer: %1, using interval: %2 ms**

A debug message issued when the new interval timer is registered in the Timer Manager. This timer will have a callback function associated with it, and this function will be executed according to the interval specified. The unique name of the timer and the interval at which the callback function will be executed is included in the message.

**DHCPSRV\_TIMERMGR\_REGISTER\_TIMER (1) registering timer: %1, using interval: %2 ms**

A debug message issued when the new interval timer is registered in the Timer Manager. This timer will have a callback function associated with it, and this function will be executed according to the interval specified. The unique name of the timer and the interval at which the callback function will be executed is included in the message.

**DHCPSRV\_TIMERMGR\_RUN\_TIMER\_OPERATION running operation for timer: %1**

A debug message issued when the Timer Manager is about to run a periodic operation associated with the given timer. An example of such operation is a periodic cleanup of expired leases. The name of the timer is included in the message.

**DHCPSRV\_TIMERMGR\_RUN\_TIMER\_OPERATION (1) running operation for timer: %1**

A debug message issued when the Timer Manager is about to run a periodic operation associated with the given timer. An example of such operation is a periodic cleanup of expired leases. The name of the timer is included in the message.

**DHCPSRV\_TIMERMGR\_START\_TIMER starting timer: %1**

A debug message issued when the registered interval timer is being started. If this operation is successful the timer will periodically execute the operation associated with it. The name of the started timer is included in the message.

**DHCPSRV\_TIMERMGR\_START\_TIMER (1) starting timer: %1**

A debug message issued when the registered interval timer is being started. If this operation is successful the timer will periodically execute the operation associated with it. The name of the started timer is included in the message.

**DHCPSRV\_TIMERMGR\_STOP\_TIMER stopping timer: %1**

A debug message issued when the registered interval timer is being stopped. The timer remains registered and can be restarted if necessary. The name of the timer is included in the message.

**DHCPSRV\_TIMERMGR\_STOP\_TIMER (1) stopping timer: %1**

A debug message issued when the registered interval timer is being stopped. The timer remains registered and can be restarted if necessary. The name of the timer is included in the message.

**DHCPSRV\_TIMERMGR\_UNREGISTER\_ALL\_TIMERS unregistering all timers**

A debug message issued when all registered interval timers are being unregistered from the Timer Manager.

**DHCPSRV\_TIMERMGR\_UNREGISTER\_ALL\_TIMERS (1) unregistering all timers**

A debug message issued when all registered interval timers are being unregistered from the Timer Manager.

**DHCPSRV\_TIMERMGR\_UNREGISTER\_TIMER unregistering timer: %1**

A debug message issued when one of the registered interval timers is unregistered from the Timer Manager. The name of the timer is included in the message.

**DHCPSRV\_TIMERMGR\_UNREGISTER\_TIMER (1) unregistering timer: %1**

A debug message issued when one of the registered interval timers is unregistered from the Timer Manager. The name of the timer is included in the message.

**DHCPSRV\_UNEXPECTED\_NAME database access parameters passed through '%1', expected 'lease-database'**

The parameters for access the lease database were passed to the server through the named configuration parameter, but the code was expecting them to be passed via the parameter named "lease-database". If the database opens successfully, there is no impact on server operation. However, as this does indicate an error in the source code, please submit a bug report.

**DHCPSRV\_UNEXPECTED\_NAME (1) database access parameters passed through '%1', expected 'lease-database'**

The parameters for access the lease database were passed to the server through the named configuration parameter, but the code was expecting them to be passed via the parameter named "lease-database". If the database opens successfully, there is no impact on server operation. However, as this does indicate an error in the source code, please submit a bug report.

**DHCPSRV\_UNKNOWN\_DB unknown database type: %1**

The database access string specified a database type (given in the message) that is unknown to the software. This is a configuration error.

**DHCPSRV\_UNKNOWN\_DB (1) unknown database type: %1**

The database access string specified a database type (given in the message) that is unknown to the software. This is a configuration error.

## DHCP Module

**DHCP\_DDNS\_ADD\_FAILED DHCP\_DDNS Request ID %1: Transaction outcome %2**

This is an error message issued after DHCP\_DDNS attempts to submit DNS mapping entry additions have failed. The precise reason for the failure should be documented in preceding log entries.

**DHCP\_DDNS\_ADD\_FAILED (1) DHCP\_DDNS Request ID %1: Transaction outcome %2**

This is an error message issued after DHCP\_DDNS attempts to submit DNS mapping entry additions have failed. The precise reason for the failure should be documented in preceding log entries.

**DHCP\_DDNS\_ADD\_SUCCEEDED DHCP\_DDNS Request ID %1: successfully added the DNS mapping addition for this request**

This is an informational message issued after DHCP\_DDNS has submitted DNS mapping additions which were received and accepted by an appropriate DNS server.

**DHCP\_DDNS\_ADD\_SUCCEEDED (1) DHCP\_DDNS Request ID %1: successfully added the DNS mapping addition for this request**

This is an informational message issued after DHCP\_DDNS has submitted DNS mapping additions which were received and accepted by an appropriate DNS server.

---

**DHCP\_DDNS\_ALREADY\_RUNNING %1 already running? %2**

This is an error message that occurs when DHCP\_DDNS encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of DHCP\_DDNS using the same configuration file. It is possible, though unlikely, that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than DHCP\_DDNS. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCP\_DDNS process name, the second contains the PID and PID file.

**DHCP\_DDNS\_ALREADY\_RUNNING (1) %1 already running? %2**

This is an error message that occurs when DHCP\_DDNS encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of DHCP\_DDNS using the same configuration file. It is possible, though unlikely, that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than DHCP\_DDNS. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCP\_DDNS process name, the second contains the PID and PID file.

**DHCP\_DDNS\_AT\_MAX\_TRANSACTIONS application has %1 queued requests but has reached maximum number of %2 co**

This is a debug message that indicates that the application has DHCP\_DDNS requests in the queue but is working as many concurrent requests as allowed.

**DHCP\_DDNS\_AT\_MAX\_TRANSACTIONS (1) application has %1 queued requests but has reached maximum number of %2**

This is a debug message that indicates that the application has DHCP\_DDNS requests in the queue but is working as many concurrent requests as allowed.

**DHCP\_DDNS\_CLEARED\_FOR\_SHUTDOWN application has met shutdown criteria for shutdown type: %1**

This is a debug message issued when the application has been instructed to shutdown and has met the required criteria to exit.

**DHCP\_DDNS\_CLEARED\_FOR\_SHUTDOWN (1) application has met shutdown criteria for shutdown type: %1**

This is a debug message issued when the application has been instructed to shutdown and has met the required criteria to exit.

**DHCP\_DDNS\_COMMAND command directive received, command: %1 - args: %2**

This is a debug message issued when the DHCP-DDNS application command method has been invoked.

**DHCP\_DDNS\_COMMAND (1) command directive received, command: %1 - args: %2**

This is a debug message issued when the DHCP-DDNS application command method has been invoked.

**DHCP\_DDNS\_CONFIGURE configuration %1 received: %2**

This is a debug message issued when the DHCP-DDNS application configure method has been invoked.

**DHCP\_DDNS\_CONFIGURE (1) configuration %1 received: %2**

This is a debug message issued when the DHCP-DDNS application configure method has been invoked.

**DHCP\_DDNS\_CONFIG\_CHECK\_FAIL DHCP-DDNS server configuration check failed: %1**

This error message indicates that the DHCP-DDNS had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**DHCP\_DDNS\_CONFIG\_CHECK\_FAIL (1) DHCP-DDNS server configuration check failed: %1**

This error message indicates that the DHCP-DDNS had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**DHCP\_DDNS\_CONFIG\_FAIL DHCP-DDNS server configuration failed: %1**

This error message indicates that the DHCP-DDNS had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**DHCP\_DDNS\_CONFIG\_FAIL (1) DHCP-DDNS server configuration failed: %1**

This error message indicates that the DHCP-DDNS had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.



**DHCP\_DDNS\_FAILED application experienced a fatal error: %1**

This is a debug message issued when the DHCP-DDNS application encounters an unrecoverable error from within the event loop.

**DHCP\_DDNS\_FAILED (1) application experienced a fatal error: %1**

This is a debug message issued when the DHCP-DDNS application encounters an unrecoverable error from within the event loop.

**DHCP\_DDNS\_FORWARD\_ADD\_BAD\_DNSCLIENT\_STATUS DHCP\_DDNS Request ID %1: received an unknown DNSClient**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was adding a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_FORWARD\_ADD\_BAD\_DNSCLIENT\_STATUS (1) DHCP\_DDNS Request ID %1: received an unknown DNSClient**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was adding a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_FORWARD\_ADD\_BUILD\_FAILURE DNS Request ID %1: update message to add a forward DNS entry could not be built**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address addition. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_FORWARD\_ADD\_BUILD\_FAILURE (1) DNS Request ID %1: update message to add a forward DNS entry could not be built**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address addition. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_FORWARD\_ADD\_IO\_ERROR DHCP\_DDNS Request ID %1: encountered an IO error sending a forward map**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address update. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_ADD\_IO\_ERROR (1) DHCP\_DDNS Request ID %1: encountered an IO error sending a forward map**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address update. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_ADD\_REJECTED DNS Request ID %1: Server, %2, rejected a DNS update request to add the address**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_FORWARD\_ADD\_REJECTED (1) DNS Request ID %1: Server, %2, rejected a DNS update request to add the address**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_FORWARD\_ADD\_RESP\_CORRUPT DHCP\_DDNS Request ID %1: received a corrupt response from the DNS server**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to add a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_ADD\_RESP\_CORRUPT (1) DHCP\_DDNS Request ID %1: received a corrupt response from the DNS server**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to add a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_BAD\_DNSCLIENT\_STATUS DHCP\_DDNS Request ID %1: received an unknown status**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_BAD\_DNSCLIENT\_STATUS (1) DHCP\_DDNS Request ID %1: received an unknown status**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_BUILD\_FAILURE DNS Request ID %1: update message to remove a forward address failed**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address (A or AAAA) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue. /\*sar\*/

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_BUILD\_FAILURE (1) DNS Request ID %1: update message to remove a forward address failed**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address (A or AAAA) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue. /\*sar\*/

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_IO\_ERROR DHCP\_DDNS Request ID %1: encountered an IO error sending update message**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address remove. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_IO\_ERROR (1) DHCP\_DDNS Request ID %1: encountered an IO error sending update message**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address remove. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_REJECTED DNS Request ID %1: Server, %2, rejected a DNS update request**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_REJECTED (1) DNS Request ID %1: Server, %2, rejected a DNS update request**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_RESP\_CORRUPT DHCP\_DDNS Request ID %1: received a corrupt response**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_RESP\_CORRUPT (1) DHCP\_DDNS Request ID %1: received a corrupt response**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_BAD\_DNSCLIENT\_STATUS DHCP\_DDNS Request ID %1: received an unknown status**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing forward RRs. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_BAD\_DNSCLIENT\_STATUS (1) DHCP\_DDNS Request ID %1: received an unknown status**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing forward RRs. The request will be aborted. This is most likely a programmatic issue and should be reported.

---

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_BUILD\_FAILURE DNS Request ID %1: update message to remove forward DNS**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting forward RR (DHCID RR) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_BUILD\_FAILURE (1) DNS Request ID %1: update message to remove forward DNS**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting forward RR (DHCID RR) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_IO\_ERROR DHCP\_DDNS Request ID %1: encountered an IO error sending a f**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward RR remove. The application will retry against the same server.

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_IO\_ERROR (1) DHCP\_DDNS Request ID %1: encountered an IO error sending**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward RR remove. The application will retry against the same server.

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_REJECTED DNS Request ID %1: Server, %2, rejected a DNS update request to**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_REJECTED (1) DNS Request ID %1: Server, %2, rejected a DNS update request**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_RESP\_CORRUPT DHCP\_DDNS Request ID %1: received a corrupt response fr**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove forward RRs mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.  
/\*sar\*/

**DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_RESP\_CORRUPT (1) DHCP\_DDNS Request ID %1: received a corrupt respons**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove forward RRs mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.  
/\*sar\*/

**DHCP\_DDNS\_FORWARD\_REPLACE\_BAD\_DNSCLIENT\_STATUS DHCP\_DDNS Request ID %1: received an unknown D**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was replacing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_FORWARD\_REPLACE\_BAD\_DNSCLIENT\_STATUS (1) DHCP\_DDNS Request ID %1: received an unknown**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was replacing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_FORWARD\_REPLACE\_BUILD\_FAILURE DNS Request ID %1: update message to replace a forward DNS en**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

---

**DHCP\_DDNS\_FORWARD\_REPLACE\_BUILD\_FAILURE (1) DNS Request ID %1: update message to replace a forward DNS**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_FORWARD\_REPLACE\_IO\_ERROR DHCP\_DDNS Request ID %1: encountered an IO error sending a forward**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address update. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_REPLACE\_IO\_ERROR (1) DHCP\_DDNS Request ID %1: encountered an IO error sending a forward**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address update. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_REPLACE\_REJECTED DNS Request ID %1: Server, %2, rejected a DNS update request to repla**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_FORWARD\_REPLACE\_REJECTED (1) DNS Request ID %1: Server, %2, rejected a DNS update request to re**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_FORWARD\_REPLACE\_RESP\_CORRUPT DHCP\_DDNS Request ID %1: received a corrupt response from th**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to replace a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FORWARD\_REPLACE\_RESP\_CORRUPT (1) DHCP\_DDNS Request ID %1: received a corrupt response from**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to replace a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_FWD\_REQUEST\_IGNORED Request ID %1: Forward updates are disabled, the forward portion of request w**

This is a debug message issued when forward DNS updates are disabled and DHCP\_DDNS receives an update request containing a forward DNS update. The forward update will not performed.

**DHCP\_DDNS\_FWD\_REQUEST\_IGNORED (1) Request ID %1: Forward updates are disabled, the forward portion of reques**

This is a debug message issued when forward DNS updates are disabled and DHCP\_DDNS receives an update request containing a forward DNS update. The forward update will not performed.

**DHCP\_DDNS\_INVALID\_NCR application received an invalid DNS update request: %1**

This is an error message that indicates that an invalid request to update a DNS entry was received by the application. Either the format or the content of the request is incorrect. The request will be ignored.

**DHCP\_DDNS\_INVALID\_NCR (1) application received an invalid DNS update request: %1**

This is an error message that indicates that an invalid request to update a DNS entry was received by the application. Either the format or the content of the request is incorrect. The request will be ignored.

**DHCP\_DDNS\_INVALID\_RESPONSE received response to DNS Update message is malformed: %1**

This is a debug message issued when the DHCP-DDNS application encountered an error while decoding a response to DNS Update message. Typically, this error will be encountered when a response message is malformed.

**DHCP\_DDNS\_INVALID\_RESPONSE (1) received response to DNS Update message is malformed: %1**

This is a debug message issued when the DHCP-DDNS application encountered an error while decoding a response to DNS Update message. Typically, this error will be encountered when a response message is malformed.

**DHCP\_DDNS\_NCR\_FLUSH\_IO\_ERROR DHCP-DDNS Last send before stopping did not complete successfully: %1**

This is an error message that indicates the DHCP-DDNS client was unable to complete the last send prior to exiting send mode. This is a programmatic error, highly unlikely to occur, and should not impair the application's ability to process requests.

**DHCP\_DDNS\_NCR\_FLUSH\_IO\_ERROR (1) DHCP-DDNS Last send before stopping did not complete successfully: %1**

This is an error message that indicates the DHCP-DDNS client was unable to complete the last send prior to exiting send mode. This is a programmatic error, highly unlikely to occur, and should not impair the application's ability to process requests.

**DHCP\_DDNS\_NCR\_LISTEN\_CLOSE\_ERROR application encountered an error while closing the listener used to receive Name**

This is an error message that indicates the application was unable to close the listener connection used to receive NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the application's ability to process requests but it should be reported for analysis.

**DHCP\_DDNS\_NCR\_LISTEN\_CLOSE\_ERROR (1) application encountered an error while closing the listener used to receive**

This is an error message that indicates the application was unable to close the listener connection used to receive NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the application's ability to process requests but it should be reported for analysis.

**DHCP\_DDNS\_NCR\_RECV\_NEXT\_ERROR application could not initiate the next read following a request receive.**

This is a error message indicating that NameChangeRequest listener could not start another read after receiving a request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

**DHCP\_DDNS\_NCR\_RECV\_NEXT\_ERROR (1) application could not initiate the next read following a request receive.**

This is a error message indicating that NameChangeRequest listener could not start another read after receiving a request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

**DHCP\_DDNS\_NCR\_SEND\_CLOSE\_ERROR DHCP-DDNS client encountered an error while closing the sender connection us**

This is an error message that indicates the DHCP-DDNS client was unable to close the connection used to send NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the client's ability to send requests but it should be reported for analysis.

**DHCP\_DDNS\_NCR\_SEND\_CLOSE\_ERROR (1) DHCP-DDNS client encountered an error while closing the sender connectio**

This is an error message that indicates the DHCP-DDNS client was unable to close the connection used to send NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the client's ability to send requests but it should be reported for analysis.

**DHCP\_DDNS\_NCR\_SEND\_NEXT\_ERROR DHCP-DDNS client could not initiate the next request send following send comple**

This is a error message indicating that NameChangeRequest sender could not start another send after completing the send of the previous request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

**DHCP\_DDNS\_NCR\_SEND\_NEXT\_ERROR (1) DHCP-DDNS client could not initiate the next request send following send con**

This is a error message indicating that NameChangeRequest sender could not start another send after completing the send of the previous request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

**DHCP\_DDNS\_NCR\_UDP\_CLEAR\_READY\_ERROR NCR UDP watch socket failed to clear: %1**

This is an error message that indicates the application was unable to reset the UDP NCR sender ready status after completing a send. This is programmatic error that should be reported. The application may or may not continue to operate correctly.

**DHCP\_DDNS\_NCR\_UDP\_CLEAR\_READY\_ERROR (1) NCR UDP watch socket failed to clear: %1**

This is an error message that indicates the application was unable to reset the UDP NCR sender ready status after completing a send. This is programmatic error that should be reported. The application may or may not continue to operate correctly.

**DHCP\_DDNS\_NCR\_UDP\_RECV\_CANCELED UDP socket receive was canceled while listening for DNS Update requests**

This is a debug message indicating that the listening on a UDP socket for DNS update requests has been canceled. This is a normal part of suspending listening operations.

**DHCP\_DDNS\_NCR\_UDP\_RECV\_CANCELED (1) UDP socket receive was canceled while listening for DNS Update requests**

This is a debug message indicating that the listening on a UDP socket for DNS update requests has been canceled. This is a normal part of suspending listening operations.

**DHCP\_DDNS\_NCR\_UDP\_RECV\_ERROR UDP socket receive error while listening for DNS Update requests: %1**

This is an error message indicating that an I/O error occurred while listening over a UDP socket for DNS update requests. This could indicate a network connectivity or system resource issue.

**DHCP\_DDNS\_NCR\_UDP\_RECV\_ERROR (1) UDP socket receive error while listening for DNS Update requests: %1**

This is an error message indicating that an I/O error occurred while listening over a UDP socket for DNS update requests. This could indicate a network connectivity or system resource issue.

**DHCP\_DDNS\_NCR\_UDP\_SEND\_CANCELED UDP socket send was canceled while sending a DNS Update request to DHCP**

This is an informational message indicating that sending requests via UDP socket to DHCP\_DDNS has been interrupted. This is a normal part of suspending send operations.

**DHCP\_DDNS\_NCR\_UDP\_SEND\_CANCELED (1) UDP socket send was canceled while sending a DNS Update request to DHCP**

This is an informational message indicating that sending requests via UDP socket to DHCP\_DDNS has been interrupted. This is a normal part of suspending send operations.

**DHCP\_DDNS\_NCR\_UDP\_SEND\_ERROR UDP socket send error while sending a DNS Update request: %1**

This is an error message indicating that an IO error occurred while sending a DNS update request to DHCP\_DDNS over a UDP socket. This could indicate a network connectivity or system resource issue.

**DHCP\_DDNS\_NCR\_UDP\_SEND\_ERROR (1) UDP socket send error while sending a DNS Update request: %1**

This is an error message indicating that an IO error occurred while sending a DNS update request to DHCP\_DDNS over a UDP socket. This could indicate a network connectivity or system resource issue.

**DHCP\_DDNS\_NOT\_ON\_LOOPBACK the DHCP-DDNS server has been configured to listen on %1 which is not the local loopback**

This is a warning message issued when the DHCP-DDNS server is configured to listen at an address other than the loopback address (127.0.0.1 or ::1). It is possible for a malicious attacker to send bogus NameChangeRequests to it and change entries in the DNS. For this reason, addresses other than the IPv4 or IPv6 loopback addresses should only be used for testing purposes. A future version of Kea will implement authentication to guard against such attacks.

**DHCP\_DDNS\_NOT\_ON\_LOOPBACK (1) the DHCP-DDNS server has been configured to listen on %1 which is not the local loopback**

This is a warning message issued when the DHCP-DDNS server is configured to listen at an address other than the loopback address (127.0.0.1 or ::1). It is possible for a malicious attacker to send bogus NameChangeRequests to it and change entries in the DNS. For this reason, addresses other than the IPv4 or IPv6 loopback addresses should only be used for testing purposes. A future version of Kea will implement authentication to guard against such attacks.

**DHCP\_DDNS\_NO\_ELIGIBLE\_JOBS although there are queued requests, there are pending transactions for each, Queue count is %1**

This is a debug message issued when all of the queued requests represent clients for which there is an update already in progress. This may occur under normal operations but should be a temporary situation.

**DHCP\_DDNS\_NO\_ELIGIBLE\_JOBS (1) although there are queued requests, there are pending transactions for each, Queue o**

This is a debug message issued when all of the queued requests represent clients for which there is an update already in progress. This may occur under normal operations but should be a temporary situation.

**DHCP\_DDNS\_NO\_FWD\_MATCH\_ERROR Request ID %1: the configured list of forward DDNS domains does not contain a**

This is an error message that indicates that DHCP\_DDNS received a request to update the forward DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP\_DDNS configuration. Either the DHCP\_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

**DHCP\_DDNS\_NO\_FWD\_MATCH\_ERROR (1) Request ID %1: the configured list of forward DDNS domains does not contain a**

This is an error message that indicates that DHCP\_DDNS received a request to update the forward DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP\_DDNS configuration. Either the DHCP\_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

**DHCP\_DDNS\_NO\_MATCH No DNS servers match FQDN %1**

This is a warning message issued when there are no domains in the configuration which match the cited fully qualified domain name (FQDN). The DNS Update request for the FQDN cannot be processed.

**DHCP\_DDNS\_NO\_MATCH (1) No DNS servers match FQDN %1**

This is a warning message issued when there are no domains in the configuration which match the cited fully qualified domain name (FQDN). The DNS Update request for the FQDN cannot be processed.

**DHCP\_DDNS\_NO\_REV\_MATCH\_ERROR Request ID %1: the configured list of reverse DDNS domains does not contain a m**

This is an error message that indicates that DHCP\_DDNS received a request to update the reverse DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP\_DDNS configuration. Either the DHCP\_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

**DHCP\_DDNS\_NO\_REV\_MATCH\_ERROR (1) Request ID %1: the configured list of reverse DDNS domains does not contain a m**

This is an error message that indicates that DHCP\_DDNS received a request to update the reverse DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP\_DDNS configuration. Either the DHCP\_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

**DHCP\_DDNS\_PROCESS\_INIT application init invoked**

This is a debug message issued when the DHCP-DDNS application enters its initialization method.

**DHCP\_DDNS\_PROCESS\_INIT (1) application init invoked**

This is a debug message issued when the DHCP-DDNS application enters its initialization method.

**DHCP\_DDNS\_QUEUE\_MGR\_QUEUE\_FULL application request queue has reached maximum number of entries %1**

This is an error message indicating that DHCP-DDNS is receiving DNS update requests faster than they can be processed. This may mean the maximum queue needs to be increased, the DHCP-DDNS clients are simply generating too many requests too quickly, or perhaps upstream DNS servers are experiencing load issues.

**DHCP\_DDNS\_QUEUE\_MGR\_QUEUE\_FULL (1) application request queue has reached maximum number of entries %1**

This is an error message indicating that DHCP-DDNS is receiving DNS update requests faster than they can be processed. This may mean the maximum queue needs to be increased, the DHCP-DDNS clients are simply generating too many requests too quickly, or perhaps upstream DNS servers are experiencing load issues.

**DHCP\_DDNS\_QUEUE\_MGR\_QUEUE\_RECEIVE Request ID %1: received and queued a request.**

This is an informational message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive a request has received a request and queued it for further processing.

**DHCP\_DDNS\_QUEUE\_MGR\_QUEUE\_RECEIVE (1) Request ID %1: received and queued a request.**

This is an informational message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive a request has received a request and queued it for further processing.

---

**DHCP\_DDNS\_QUEUE\_MGR\_RECONFIGURING application is reconfiguring the queue manager**

This is an informational message indicating that DHCP\_DDNS is reconfiguring the queue manager as part of normal startup or in response to a new configuration.

**DHCP\_DDNS\_QUEUE\_MGR\_RECONFIGURING (1) application is reconfiguring the queue manager**

This is an informational message indicating that DHCP\_DDNS is reconfiguring the queue manager as part of normal startup or in response to a new configuration.

**DHCP\_DDNS\_QUEUE\_MGR\_RECOVERING application is attempting to recover from a queue manager IO error**

This is an informational message indicating that DHCP\_DDNS is attempting to restart the queue manager after it suffered an IO error while receiving requests.

**DHCP\_DDNS\_QUEUE\_MGR\_RECOVERING (1) application is attempting to recover from a queue manager IO error**

This is an informational message indicating that DHCP\_DDNS is attempting to restart the queue manager after it suffered an IO error while receiving requests.

**DHCP\_DDNS\_QUEUE\_MGR\_RECV\_ERROR application's queue manager was notified of a request receive error by its listener**

This is an error message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive requests encountered an IO error. There should be corresponding log messages from the listener layer with more details. This may indicate a network connectivity or system resource issue.

**DHCP\_DDNS\_QUEUE\_MGR\_RECV\_ERROR (1) application's queue manager was notified of a request receive error by its listener**

This is an error message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive requests encountered an IO error. There should be corresponding log messages from the listener layer with more details. This may indicate a network connectivity or system resource issue.

**DHCP\_DDNS\_QUEUE\_MGR\_RESUME\_ERROR application could not restart the queue manager, reason: %1**

This is an error message indicating that DHCP\_DDNS's Queue Manager could not be restarted after stopping due to a full receive queue. This means that the application cannot receive requests. This is most likely due to DHCP\_DDNS configuration parameters referring to resources such as an IP address or port, that is no longer unavailable. DHCP\_DDNS will attempt to restart the queue manager if given a new configuration.

**DHCP\_DDNS\_QUEUE\_MGR\_RESUME\_ERROR (1) application could not restart the queue manager, reason: %1**

This is an error message indicating that DHCP\_DDNS's Queue Manager could not be restarted after stopping due to a full receive queue. This means that the application cannot receive requests. This is most likely due to DHCP\_DDNS configuration parameters referring to resources such as an IP address or port, that is no longer unavailable. DHCP\_DDNS will attempt to restart the queue manager if given a new configuration.

**DHCP\_DDNS\_QUEUE\_MGR\_RESUMING application is resuming listening for requests now that the request queue size has**

This is an informational message indicating that DHCP\_DDNS, which had stopped accepting new requests, has processed enough entries from the receive queue to resume accepting requests.

**DHCP\_DDNS\_QUEUE\_MGR\_RESUMING (1) application is resuming listening for requests now that the request queue size has**

This is an informational message indicating that DHCP\_DDNS, which had stopped accepting new requests, has processed enough entries from the receive queue to resume accepting requests.

**DHCP\_DDNS\_QUEUE\_MGR\_STARTED application's queue manager has begun listening for requests.**

This is a debug message indicating that DHCP\_DDNS's Queue Manager has successfully started and is now listening for NameChangeRequests.

**DHCP\_DDNS\_QUEUE\_MGR\_STARTED (1) application's queue manager has begun listening for requests.**

This is a debug message indicating that DHCP\_DDNS's Queue Manager has successfully started and is now listening for NameChangeRequests.

---



**DHCP\_DDNS\_QUEUE\_MGR\_START\_ERROR application could not start the queue manager, reason: %1**

This is an error message indicating that DHCP\_DDNS's Queue Manager could not be started. This means that the application cannot receive requests. This is most likely due to DHCP\_DDNS configuration parameters referring to resources such as an IP address or port, that are unavailable. DHCP\_DDNS will attempt to restart the queue manager if given a new configuration.

**DHCP\_DDNS\_QUEUE\_MGR\_START\_ERROR (1) application could not start the queue manager, reason: %1**

This is an error message indicating that DHCP\_DDNS's Queue Manager could not be started. This means that the application cannot receive requests. This is most likely due to DHCP\_DDNS configuration parameters referring to resources such as an IP address or port, that are unavailable. DHCP\_DDNS will attempt to restart the queue manager if given a new configuration.

**DHCP\_DDNS\_QUEUE\_MGR\_STOPPED application's queue manager has stopped listening for requests.**

This is a debug message indicating that DHCP\_DDNS's Queue Manager has stopped listening for NameChangeRequests. This may be because of normal event such as reconfiguration or as a result of an error. There should be log messages preceding this one to indicate why it has stopped.

**DHCP\_DDNS\_QUEUE\_MGR\_STOPPED (1) application's queue manager has stopped listening for requests.**

This is a debug message indicating that DHCP\_DDNS's Queue Manager has stopped listening for NameChangeRequests. This may be because of normal event such as reconfiguration or as a result of an error. There should be log messages preceding this one to indicate why it has stopped.

**DHCP\_DDNS\_QUEUE\_MGR\_STOPPING application is stopping the queue manager for %1**

This is an informational message indicating that DHCP\_DDNS is stopping the queue manager either to reconfigure it or as part of application shutdown.

**DHCP\_DDNS\_QUEUE\_MGR\_STOPPING (1) application is stopping the queue manager for %1**

This is an informational message indicating that DHCP\_DDNS is stopping the queue manager either to reconfigure it or as part of application shutdown.

**DHCP\_DDNS\_QUEUE\_MGR\_STOP\_ERROR application encountered an error stopping the queue manager: %1**

This is an error message indicating that DHCP\_DDNS encountered an error while trying to stop the queue manager. This error is unlikely to occur or to impair the application's ability to function but it should be reported for analysis.

**DHCP\_DDNS\_QUEUE\_MGR\_STOP\_ERROR (1) application encountered an error stopping the queue manager: %1**

This is an error message indicating that DHCP\_DDNS encountered an error while trying to stop the queue manager. This error is unlikely to occur or to impair the application's ability to function but it should be reported for analysis.

**DHCP\_DDNS\_QUEUE\_MGR\_UNEXPECTED\_HANDLER\_ERROR application's queue manager request receive handler error**

This is an error message indicating that an unexpected error occurred within the DHCP\_DDNS's Queue Manager request receive completion handler. This is most likely a programmatic issue that should be reported. The application may recover on its own.

**DHCP\_DDNS\_QUEUE\_MGR\_UNEXPECTED\_HANDLER\_ERROR (1) application's queue manager request receive handler error**

This is an error message indicating that an unexpected error occurred within the DHCP\_DDNS's Queue Manager request receive completion handler. This is most likely a programmatic issue that should be reported. The application may recover on its own.

**DHCP\_DDNS\_QUEUE\_MGR\_UNEXPECTED\_STOP application's queue manager receive was**

aborted unexpectedly while queue manager state is: %1 This is an error message indicating that DHCP\_DDNS's Queue Manager request receive was unexpected interrupted. Normally, the read is receive is only interrupted as a normal part of stopping the queue manager. This is most likely a programmatic issue that should be reported.

**DHCP\_DDNS\_QUEUE\_MGR\_UNEXPECTED\_STOP (1) application's queue manager receive was**

aborted unexpectedly while queue manager state is: %1 This is an error message indicating that DHCP\_DDNS's Queue Manager request receive was unexpected interrupted. Normally, the read is receive is only interrupted as a normal part of stopping the queue manager. This is most likely a programmatic issue that should be reported.

**DHCP\_DDNS\_REMOVE\_FAILED DHCP\_DDNS Request ID %1: Transaction outcome: %2**

This is an error message issued after DHCP\_DDNS attempts to submit DNS mapping entry removals have failed. The precise reason for the failure should be documented in preceding log entries.

**DHCP\_DDNS\_REMOVE\_FAILED (1) DHCP\_DDNS Request ID %1: Transaction outcome: %2**

This is an error message issued after DHCP\_DDNS attempts to submit DNS mapping entry removals have failed. The precise reason for the failure should be documented in preceding log entries.

**DHCP\_DDNS\_REMOVE\_SUCCEEDED DHCP\_DDNS Request ID %1: successfully removed the DNS mapping addition for t**

This is an informational message issued after DHCP\_DDNS has submitted DNS mapping removals which were received and accepted by an appropriate DNS server.

**DHCP\_DDNS\_REMOVE\_SUCCEEDED (1) DHCP\_DDNS Request ID %1: successfully removed the DNS mapping addition f**

This is an informational message issued after DHCP\_DDNS has submitted DNS mapping removals which were received and accepted by an appropriate DNS server.

**DHCP\_DDNS\_REQUEST\_DROPPED Request ID %1: Request contains no enabled update requests and will be dropped: %2**

This is a debug message issued when DHCP\_DDNS receives a request which does not contain updates in a direction that is enabled. In other words, if only forward updates are enabled and request is received that asks only for reverse updates then the request is dropped.

**DHCP\_DDNS\_REQUEST\_DROPPED (1) Request ID %1: Request contains no enabled update requests and will be dropped:**

This is a debug message issued when DHCP\_DDNS receives a request which does not contain updates in a direction that is enabled. In other words, if only forward updates are enabled and request is received that asks only for reverse updates then the request is dropped.

**DHCP\_DDNS\_REVERSE\_REMOVE\_BAD\_DNSCLIENT\_STATUS DHCP\_DDNS Request ID %1: received an unknown DNS**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_REVERSE\_REMOVE\_BAD\_DNSCLIENT\_STATUS (1) DHCP\_DDNS Request ID %1: received an unknown I**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_REVERSE\_REMOVE\_BUILD\_FAILURE DNS Request ID %1: update message to remove a reverse DNS entry**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_REVERSE\_REMOVE\_BUILD\_FAILURE (1) DNS Request ID %1: update message to remove a reverse DNS e**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_REVERSE\_REMOVE\_IO\_ERROR DHCP\_DDNS Request ID %1: encountered an IO error sending a reverse**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a reverse address update. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_REVERSE\_REMOVE\_IO\_ERROR (1) DHCP\_DDNS Request ID %1: encountered an IO error sending a reve**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a reverse address update. The application will retry against the same server or others as appropriate.

---

**DHCP\_DDNS\_REVERSE\_REMOVE\_REJECTED DNS Request ID %1: Server, %2, rejected a DNS update request to remove**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_REVERSE\_REMOVE\_REJECTED (1) DNS Request ID %1: Server, %2, rejected a DNS update request to remove**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_REVERSE\_REMOVE\_RESP\_CORRUPT DHCP\_DDNS Request ID %1: received a corrupt response from the**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_REVERSE\_REMOVE\_RESP\_CORRUPT (1) DHCP\_DDNS Request ID %1: received a corrupt response from**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_REVERSE\_REPLACE\_BAD\_DNSCLIENT\_STATUS DHCP\_DDNS Request ID %1: received an unknown DN**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was replacing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_REVERSE\_REPLACE\_BAD\_DNSCLIENT\_STATUS (1) DHCP\_DDNS Request ID %1: received an unknown**

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was replacing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

**DHCP\_DDNS\_REVERSE\_REPLACE\_BUILD\_FAILURE DNS Request ID %1: update message to replace a reverse DNS entr**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_REVERSE\_REPLACE\_BUILD\_FAILURE (1) DNS Request ID %1: update message to replace a reverse DNS e**

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

**DHCP\_DDNS\_REVERSE\_REPLACE\_IO\_ERROR DHCP\_DDNS Request ID %1: encountered an IO error sending a reverse**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a reverse address update. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_REVERSE\_REPLACE\_IO\_ERROR (1) DHCP\_DDNS Request ID %1: encountered an IO error sending a reve**

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a reverse address update. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_REVERSE\_REPLACE\_REJECTED DNS Request ID %1: Server, %2, rejected a DNS update request to replac**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

**DHCP\_DDNS\_REVERSE\_REPLACE\_REJECTED (1) DNS Request ID %1: Server, %2, rejected a DNS update request to rep**

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

---

**DHCP\_DDNS\_REVERSE\_REPLACE\_RESP\_CORRUPT DHCP\_DDNS Request ID %1: received a corrupt response from the server**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to replace a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_REVERSE\_REPLACE\_RESP\_CORRUPT (1) DHCP\_DDNS Request ID %1: received a corrupt response from the server**

This is an error message issued when the response received by DHCP\_DDNS, to a update request to replace a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

**DHCP\_DDNS\_REV\_REQUEST\_IGNORED Request ID %1: Reverse updates are disabled, the reverse portion of request will be ignored**

This is a debug message issued when reverse DNS updates are disabled and DHCP\_DDNS receives an update request containing a reverse DNS update. The reverse update will not be performed.

**DHCP\_DDNS\_REV\_REQUEST\_IGNORED (1) Request ID %1: Reverse updates are disabled, the reverse portion of request will be ignored**

This is a debug message issued when reverse DNS updates are disabled and DHCP\_DDNS receives an update request containing a reverse DNS update. The reverse update will not be performed.

**DHCP\_DDNS\_RUN\_EXIT application is exiting the event loop**

This is a debug message issued when the DHCP-DDNS server exits its event loop.

**DHCP\_DDNS\_RUN\_EXIT (1) application is exiting the event loop**

This is a debug message issued when the DHCP-DDNS server exits its event loop.

**DHCP\_DDNS\_SHUTDOWN\_COMMAND application received shutdown command with args: %1**

This is a debug message issued when the application has been instructed to shut down by the controller.

**DHCP\_DDNS\_SHUTDOWN\_COMMAND (1) application received shutdown command with args: %1**

This is a debug message issued when the application has been instructed to shut down by the controller.

**DHCP\_DDNS\_STARTED Kea DHCP-DDNS server version %1 started**

This informational message indicates that the DHCP-DDNS server has processed all configuration information and is ready to begin processing. The version is also printed.

**DHCP\_DDNS\_STARTED (1) Kea DHCP-DDNS server version %1 started**

This informational message indicates that the DHCP-DDNS server has processed all configuration information and is ready to begin processing. The version is also printed.

**DHCP\_DDNS\_STARTING\_TRANSACTION Request ID %1:**

This is a debug message issued when DHCP-DDNS has begun a transaction for a given request.

**DHCP\_DDNS\_STARTING\_TRANSACTION (1) Request ID %1:**

This is a debug message issued when DHCP-DDNS has begun a transaction for a given request.

**DHCP\_DDNS\_STATE\_MODEL\_UNEXPECTED\_ERROR Request ID %1: application encountered an unexpected error while processing request**

This is error message issued when the application fails to process a NameChangeRequest correctly. Some or all of the DNS updates requested as part of this update did not succeed. This is a programmatic error and should be reported.

**DHCP\_DDNS\_STATE\_MODEL\_UNEXPECTED\_ERROR (1) Request ID %1: application encountered an unexpected error while processing request**

This is error message issued when the application fails to process a NameChangeRequest correctly. Some or all of the DNS updates requested as part of this update did not succeed. This is a programmatic error and should be reported.

**DHCP\_DDNS\_TRANS\_SEND\_ERROR Request ID %1: application encountered an unexpected error while attempting to send update**

This is error message issued when the application is able to construct an update message but the attempt to send it suffered an unexpected error. This is most likely a programmatic error, rather than a communications issue. Some or all of the DNS updates requested as part of this request did not succeed.

**DHCP\_DDNS\_TRANS\_SEND\_ERROR (1) Request ID %1: application encountered an unexpected error while attempting to**

This is error message issued when the application is able to construct an update message but the attempt to send it suffered an unexpected error. This is most likely a programmatic error, rather than a communications issue. Some or all of the DNS updates requested as part of this request did not succeed.

**DHCP\_DDNS\_UDP\_SENDER\_WATCH\_SOCKET\_CLOSE\_ERROR watch socket failed to close: %1**

This is an error message that indicates the application was unable to close the inbound or outbound side of a NCR sender's watch socket. While technically possible the error is highly unlikely to occur and should not impair the application's ability to process requests.

**DHCP\_DDNS\_UDP\_SENDER\_WATCH\_SOCKET\_CLOSE\_ERROR (1) watch socket failed to close: %1**

This is an error message that indicates the application was unable to close the inbound or outbound side of a NCR sender's watch socket. While technically possible the error is highly unlikely to occur and should not impair the application's ability to process requests.

**DHCP\_DDNS\_UNCAUGHT\_NCR\_RECV\_HANDLER\_ERROR unexpected exception thrown from the application receive**

This is an error message that indicates that an exception was thrown but not caught in the application's request receive completion handler. This is a programmatic error that needs to be reported. Dependent upon the nature of the error the application may or may not continue operating normally.

**DHCP\_DDNS\_UNCAUGHT\_NCR\_RECV\_HANDLER\_ERROR (1) unexpected exception thrown from the application receive**

This is an error message that indicates that an exception was thrown but not caught in the application's request receive completion handler. This is a programmatic error that needs to be reported. Dependent upon the nature of the error the application may or may not continue operating normally.

**DHCP\_DDNS\_UNCAUGHT\_NCR\_SEND\_HANDLER\_ERROR unexpected exception thrown from the DHCP-DDNS client se**

This is an error message that indicates that an exception was thrown but not caught in the application's send completion handler. This is a programmatic error that needs to be reported. Dependent upon the nature of the error the client may or may not continue operating normally.

**DHCP\_DDNS\_UNCAUGHT\_NCR\_SEND\_HANDLER\_ERROR (1) unexpected exception thrown from the DHCP-DDNS client**

This is an error message that indicates that an exception was thrown but not caught in the application's send completion handler. This is a programmatic error that needs to be reported. Dependent upon the nature of the error the client may or may not continue operating normally.

**DHCP\_DDNS\_UPDATE\_REQUEST\_SENT Request ID %1: %2 to server: %3**

This is a debug message issued when DHCP\_DDNS sends a DNS request to a DNS server.

**DHCP\_DDNS\_UPDATE\_REQUEST\_SENT (1) Request ID %1: %2 to server: %3**

This is a debug message issued when DHCP\_DDNS sends a DNS request to a DNS server.

**DHCP\_DDNS\_UPDATE\_RESPONSE\_RECEIVED Request ID %1: to server: %2 status: %3**

This is a debug message issued when DHCP\_DDNS receives sends a DNS update response from a DNS server.

**DHCP\_DDNS\_UPDATE\_RESPONSE\_RECEIVED (1) Request ID %1: to server: %2 status: %3**

This is a debug message issued when DHCP\_DDNS receives sends a DNS update response from a DNS server.

## EVAL Module

**EVAL\_DEBUG\_AND Popping %1 and %2 pushing %3**

This debug message indicates that two values are popped from the value stack. Then are then combined via logical and and the result is pushed onto the value stack.

---

**EVAL\_DEBUG\_AND (1) Popping %1 and %2 pushing %3**

This debug message indicates that two values are popped from the value stack. They are then combined via logical and and the result is pushed onto the value stack.

**EVAL\_DEBUG\_CONCAT Popping %1 and %2 pushing %3**

This debug message indicates that the two strings are being popped off of the stack. They are then concatenated and the resulting string is pushed onto the stack. The strings are displayed in hex.

**EVAL\_DEBUG\_CONCAT (1) Popping %1 and %2 pushing %3**

This debug message indicates that the two strings are being popped off of the stack. They are then concatenated and the resulting string is pushed onto the stack. The strings are displayed in hex.

**EVAL\_DEBUG\_EQUAL Popping %1 and %2 pushing result %3**

This debug message indicates that the two strings are being popped off of the value stack and the result of comparing them is being pushed onto the value stack. The strings are displayed in hex.

**EVAL\_DEBUG\_EQUAL (1) Popping %1 and %2 pushing result %3**

This debug message indicates that the two strings are being popped off of the value stack and the result of comparing them is being pushed onto the value stack. The strings are displayed in hex.

**EVAL\_DEBUG\_HEXSTRING Pushing hex string %1**

This debug message indicates that the given binary string is being pushed onto the value stack. The string is displayed in hex.

**EVAL\_DEBUG\_HEXSTRING (1) Pushing hex string %1**

This debug message indicates that the given binary string is being pushed onto the value stack. The string is displayed in hex.

**EVAL\_DEBUG\_IFELSE\_FALSE Popping %1 (false) and %2, leaving %3**

This debug message indicates that the condition is false so the iftrue branch value is removed and the ifelse branch value is left on the value stack.

**EVAL\_DEBUG\_IFELSE\_FALSE (1) Popping %1 (false) and %2, leaving %3**

This debug message indicates that the condition is false so the iftrue branch value is removed and the ifelse branch value is left on the value stack.

**EVAL\_DEBUG\_IFELSE\_TRUE Popping %1 (true) and %2, leaving %3**

This debug message indicates that the condition is true so the ifelse branch value is removed and the iftrue branch value is left on the value stack.

**EVAL\_DEBUG\_IFELSE\_TRUE (1) Popping %1 (true) and %2, leaving %3**

This debug message indicates that the condition is true so the ifelse branch value is removed and the iftrue branch value is left on the value stack.

**EVAL\_DEBUG\_IPADDRESS Pushing IPAddress %1**

This debug message indicates that the given binary string is being pushed onto the value stack. This represents either an IPv4 or IPv6 address. The string is displayed in hex.

**EVAL\_DEBUG\_IPADDRESS (1) Pushing IPAddress %1**

This debug message indicates that the given binary string is being pushed onto the value stack. This represents either an IPv4 or IPv6 address. The string is displayed in hex.

**EVAL\_DEBUG\_MEMBER Checking membership of '%1', pushing result %2**

This debug message indicates that the membership of the packet for the client class was checked.

**EVAL\_DEBUG\_MEMBER (1) Checking membership of '%1', pushing result %2**

This debug message indicates that the membership of the packet for the client class was checked.

**EVAL\_DEBUG\_NOT Popping %1 pushing %2**

This debug message indicates that the first value is popped from the value stack, negated and then pushed onto the value stack. The string is displayed in text.

**EVAL\_DEBUG\_NOT (1) Popping %1 pushing %2**

This debug message indicates that the first value is popped from the value stack, negated and then pushed onto the value stack. The string is displayed in text.

**EVAL\_DEBUG\_OPTION Pushing option %1 with value %2**

This debug message indicates that the given string representing the value of the requested option is being pushed onto the value stack. The string may be the text or binary value of the string based on the representation type requested (.text or .hex) or "true" or "false" if the requested type is .exists. The option code may be for either an option or a sub-option as requested in the classification statement.

**EVAL\_DEBUG\_OPTION (1) Pushing option %1 with value %2**

This debug message indicates that the given string representing the value of the requested option is being pushed onto the value stack. The string may be the text or binary value of the string based on the representation type requested (.text or .hex) or "true" or "false" if the requested type is .exists. The option code may be for either an option or a sub-option as requested in the classification statement.

**EVAL\_DEBUG\_OR Popping %1 and %2 pushing %3**

This debug message indicates that two values are popped from the value stack. Then are then combined via logical or and the result is pushed onto the value stack. The string is displayed in text.

**EVAL\_DEBUG\_OR (1) Popping %1 and %2 pushing %3**

This debug message indicates that two values are popped from the value stack. Then are then combined via logical or and the result is pushed onto the value stack. The string is displayed in text.

**EVAL\_DEBUG\_PKT Pushing PKT meta data %1 with value %2**

This debug message indicates that the given binary string representing the value of the requested meta data is being pushed onto the value stack. The string is displayed in hex at the exception of interface name.

**EVAL\_DEBUG\_PKT (1) Pushing PKT meta data %1 with value %2**

This debug message indicates that the given binary string representing the value of the requested meta data is being pushed onto the value stack. The string is displayed in hex at the exception of interface name.

**EVAL\_DEBUG\_PKT4 Pushing PKT4 field %1 with value %2**

This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

**EVAL\_DEBUG\_PKT4 (1) Pushing PKT4 field %1 with value %2**

This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

**EVAL\_DEBUG\_PKT6 Pushing PKT6 field %1 with value %2**

This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

**EVAL\_DEBUG\_PKT6 (1) Pushing PKT6 field %1 with value %2**

This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

**EVAL\_DEBUG\_RELAY6 Pushing PKT6 relay field %1 nest %2 with value %3**

This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

**EVAL\_DEBUG\_RELAY6 (1) Pushing PKT6 relay field %1 nest %2 with value %3**

This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

**EVAL\_DEBUG\_RELAY6\_RANGE Pushing PKT6 relay field %1 nest %2 with value %3**

This debug message is generated if the nest field is out of range. The empty string will always be the value pushed onto the stack.

**EVAL\_DEBUG\_RELAY6\_RANGE (1) Pushing PKT6 relay field %1 nest %2 with value %3**

This debug message is generated if the nest field is out of range. The empty string will always be the value pushed onto the stack.

---

**EVAL\_DEBUG\_STRING Pushing text string %1**

This debug message indicates that the given text string is being pushed onto the value stack. The string is displayed in text.

**EVAL\_DEBUG\_STRING (1) Pushing text string %1**

This debug message indicates that the given text string is being pushed onto the value stack. The string is displayed in text.

**EVAL\_DEBUG\_SUBSTRING Popping length %1, start %2, string %3 pushing result %4**

This debug message indicates that three values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the starting point and length of a substring to extract from the given string. The resulting string is pushed onto the stack. The strings are displayed in hex.

**EVAL\_DEBUG\_SUBSTRING (1) Popping length %1, start %2, string %3 pushing result %4**

This debug message indicates that three values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the starting point and length of a substring to extract from the given string. The resulting string is pushed onto the stack. The strings are displayed in hex.

**EVAL\_DEBUG\_SUBSTRING\_EMPTY Popping length %1, start %2, string %3 pushing result %4**

This debug message indicates that the string popped from the stack was empty and so the result will also be empty. The start, length and string are still popped from the stack and the result is still pushed.

**EVAL\_DEBUG\_SUBSTRING\_EMPTY (1) Popping length %1, start %2, string %3 pushing result %4**

This debug message indicates that the string popped from the stack was empty and so the result will also be empty. The start, length and string are still popped from the stack and the result is still pushed.

**EVAL\_DEBUG\_SUBSTRING\_RANGE Popping length %1, start %2, string %3 pushing result %4**

This debug message indicates that the value of start is outside of the string and an empty result will be pushed onto the stack. The start, length and string are still popped from the stack and the result is still pushed. The strings are displayed in hex.

**EVAL\_DEBUG\_SUBSTRING\_RANGE (1) Popping length %1, start %2, string %3 pushing result %4**

This debug message indicates that the value of start is outside of the string and an empty result will be pushed onto the stack. The start, length and string are still popped from the stack and the result is still pushed. The strings are displayed in hex.

**EVAL\_DEBUG\_TOHEXSTRING Popping binary value %1 and separator %2, pushing result %3**

This debug message indicates that two values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the binary value to convert and the separator. The binary value is converted to its hexadecimal string representation and pushed onto the stack. The binary value is displayed in hex.

**EVAL\_DEBUG\_TOHEXSTRING (1) Popping binary value %1 and separator %2, pushing result %3**

This debug message indicates that two values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the binary value to convert and the separator. The binary value is converted to its hexadecimal string representation and pushed onto the stack. The binary value is displayed in hex.

**EVAL\_DEBUG\_VENDOR\_CLASS\_DATA Data %1 (out of %2 received) in vendor class found, pushing result %3**

This debug message indicates that vendor class option was found and passed enterprise-id checks and has sufficient number of data chunks. The total number of chunks and value pushed are reported as debugging aid.

**EVAL\_DEBUG\_VENDOR\_CLASS\_DATA (1) Data %1 (out of %2 received) in vendor class found, pushing result %3**

This debug message indicates that vendor class option was found and passed enterprise-id checks and has sufficient number of data chunks. The total number of chunks and value pushed are reported as debugging aid.

**EVAL\_DEBUG\_VENDOR\_CLASS\_DATA\_NOT\_FOUND Requested data index %1, but option with enterprise-id %2 has onl**

This debug message indicates that vendor class option was found and passed enterprise-id checks, but does not have sufficient number of data chunks. Note that the index starts at 0, so there has to be at least (index + 1) data chunks.

**EVAL\_DEBUG\_VENDOR\_CLASS\_DATA\_NOT\_FOUND (1) Requested data index %1, but option with enterprise-id %2 has**

This debug message indicates that vendor class option was found and passed enterprise-id checks, but does not have sufficient number of data chunks. Note that the index starts at 0, so there has to be at least (index + 1) data chunks.

---



**EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID Pushing enterprise-id %1 as result 0x%2**

This debug message indicates that the expression has been evaluated and vendor class option was found and its enterprise-id is being reported.

**EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID (1) Pushing enterprise-id %1 as result 0x%2**

This debug message indicates that the expression has been evaluated and vendor class option was found and its enterprise-id is being reported.

**EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID\_MISMATCH Was looking for %1, option had %2, pushing result %3**

This debug message indicates that the expression has been evaluated and vendor class option was found, but has different enterprise-id than specified in the expression.

**EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID\_MISMATCH (1) Was looking for %1, option had %2, pushing result %3**

This debug message indicates that the expression has been evaluated and vendor class option was found, but has different enterprise-id than specified in the expression.

**EVAL\_DEBUG\_VENDOR\_CLASS\_EXISTS Option with enterprise-id %1 found, pushing result %2**

This debug message indicates that the expression has been evaluated and vendor class option was found.

**EVAL\_DEBUG\_VENDOR\_CLASS\_EXISTS (1) Option with enterprise-id %1 found, pushing result %2**

This debug message indicates that the expression has been evaluated and vendor class option was found.

**EVAL\_DEBUG\_VENDOR\_CLASS\_NO\_OPTION Option with code %1 missing, pushing result %2**

This debug message indicates that the expression has been evaluated and vendor class option was not found.

**EVAL\_DEBUG\_VENDOR\_CLASS\_NO\_OPTION (1) Option with code %1 missing, pushing result %2**

This debug message indicates that the expression has been evaluated and vendor class option was not found.

**EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID Pushing enterprise-id %1 as result 0x%2**

This debug message indicates that the expression has been evaluated and vendor option was found and its enterprise-id is being reported.

**EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID (1) Pushing enterprise-id %1 as result 0x%2**

This debug message indicates that the expression has been evaluated and vendor option was found and its enterprise-id is being reported.

**EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID\_MISMATCH Was looking for %1, option had %2, pushing result %3**

This debug message indicates that the expression has been evaluated and vendor option was found, but has different enterprise-id than specified in the expression.

**EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID\_MISMATCH (1) Was looking for %1, option had %2, pushing result %3**

This debug message indicates that the expression has been evaluated and vendor option was found, but has different enterprise-id than specified in the expression.

**EVAL\_DEBUG\_VENDOR\_EXISTS Option with enterprise-id %1 found, pushing result %2**

This debug message indicates that the expression has been evaluated and vendor option was found.

**EVAL\_DEBUG\_VENDOR\_EXISTS (1) Option with enterprise-id %1 found, pushing result %2**

This debug message indicates that the expression has been evaluated and vendor option was found.

**EVAL\_DEBUG\_VENDOR\_NO\_OPTION Option with code %1 missing, pushing result %2**

This debug message indicates that the expression has been evaluated and vendor option was not found.

**EVAL\_DEBUG\_VENDOR\_NO\_OPTION (1) Option with code %1 missing, pushing result %2**

This debug message indicates that the expression has been evaluated and vendor option was not found.

**EVAL\_RESULT Expression %1 evaluated to %2**

This debug message indicates that the expression has been evaluated to said value. This message is mostly useful during debugging of the client classification expressions.

**EVAL\_RESULT (1) Expression %1 evaluated to %2**

This debug message indicates that the expression has been evaluated to said value. This message is mostly useful during debugging of the client classification expressions.

## HA Module

**HA\_BUFFER4\_RECEIVE\_FAILED buffer4\_receive callout failed: %1**

This error message is issued when the callout for the buffer4\_receive hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

**HA\_BUFFER4\_RECEIVE\_FAILED (1) buffer4\_receive callout failed: %1**

This error message is issued when the callout for the buffer4\_receive hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

**HA\_BUFFER4\_RECEIVE\_NOT\_FOR\_US %1: dropping query to be processed by another server**

This debug message is issued when the received DHCPv4 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

**HA\_BUFFER4\_RECEIVE\_NOT\_FOR\_US (1) %1: dropping query to be processed by another server**

This debug message is issued when the received DHCPv4 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

**HA\_BUFFER4\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED an error unpacking an option, caused subsequent options to be skipped**

A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv4 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

**HA\_BUFFER4\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED (1) an error unpacking an option, caused subsequent options to be skipped**

A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv4 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

**HA\_BUFFER4\_RECEIVE\_UNPACK\_FAILED failed to parse query from %1 to %2, received over interface %3, reason: %4**

This debug message is issued when received DHCPv4 query is malformed and can't be parsed by the buffer4\_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

**HA\_BUFFER4\_RECEIVE\_UNPACK\_FAILED (1) failed to parse query from %1 to %2, received over interface %3, reason: %4**

This debug message is issued when received DHCPv4 query is malformed and can't be parsed by the buffer4\_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

**HA\_BUFFER6\_RECEIVE\_FAILED buffer6\_receive callout failed: %1**

This error message is issued when the callout for the buffer6\_receive hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

**HA\_BUFFER6\_RECEIVE\_FAILED (1) buffer6\_receive callout failed: %1**

This error message is issued when the callout for the buffer6\_receive hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

**HA\_BUFFER6\_RECEIVE\_NOT\_FOR\_US %1: dropping query to be processed by another server**

This debug message is issued when the received DHCPv6 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

**HA\_BUFFER6\_RECEIVE\_NOT\_FOR\_US (1) %1: dropping query to be processed by another server**

This debug message is issued when the received DHCPv6 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

**HA\_BUFFER6\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED an error unpacking an option, caused subsequent options to be skip**

A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv6 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

**HA\_BUFFER6\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED (1) an error unpacking an option, caused subsequent options to be**

A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv6 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

**HA\_BUFFER6\_RECEIVE\_UNPACK\_FAILED failed to parse query from %1 to %2, received over interface %3, reason: %4**

This debug message is issued when received DHCPv6 query is malformed and can't be parsed by the buffer6\_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

**HA\_BUFFER6\_RECEIVE\_UNPACK\_FAILED (1) failed to parse query from %1 to %2, received over interface %3, reason: %4**

This debug message is issued when received DHCPv6 query is malformed and can't be parsed by the buffer6\_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

**HA\_COMMAND\_PROCESSED\_FAILED command\_processed callout failed: %1**

This error message is issued when the callout for the command\_processed hook point failed. The argument contains a reason for the error.

**HA\_COMMAND\_PROCESSED\_FAILED (1) command\_processed callout failed: %1**

This error message is issued when the callout for the command\_processed hook point failed. The argument contains a reason for the error.

**HA\_CONFIGURATION\_FAILED failed to configure High Availability hooks library: %1**

This error message is issued when there is an error configuring the HA hooks library. The argument provides the detailed error message.

**HA\_CONFIGURATION\_FAILED (1) failed to configure High Availability hooks library: %1**

This error message is issued when there is an error configuring the HA hooks library. The argument provides the detailed error message.

**HA\_CONFIGURATION\_SUCCESSFUL HA hook library has been successfully configured**

This informational message is issued when the HA hook library configuration parser successfully parses and validates the new configuration.

**HA\_CONFIGURATION\_SUCCESSFUL (1) HA hook library has been successfully configured**

This informational message is issued when the HA hook library configuration parser successfully parses and validates the new configuration.

---

**HA\_CONFIG\_AUTO\_FAILOVER\_DISABLED auto-failover disabled for %1**

This warning message is issued to indicate that the 'auto-failover' parameter was administratively disabled for the specified server. The server will not automatically start serving partner's scope when the partner failure is detected. The server administrator will need to enable this scope manually by sending appropriate ha-scopes command.

**HA\_CONFIG\_AUTO\_FAILOVER\_DISABLED (1) auto-failover disabled for %1**

This warning message is issued to indicate that the 'auto-failover' parameter was administratively disabled for the specified server. The server will not automatically start serving partner's scope when the partner failure is detected. The server administrator will need to enable this scope manually by sending appropriate ha-scopes command.

**HA\_CONFIG\_LEASE\_SYNCING\_DISABLED lease database synchronization between HA servers is disabled**

This warning message is issued when the lease database synchronization is administratively disabled. This is valid configuration if the leases are replicated between lease databases via some other mechanism, e.g. SQL database replication.

**HA\_CONFIG\_LEASE\_SYNCING\_DISABLED (1) lease database synchronization between HA servers is disabled**

This warning message is issued when the lease database synchronization is administratively disabled. This is valid configuration if the leases are replicated between lease databases via some other mechanism, e.g. SQL database replication.

**HA\_CONFIG\_LEASE\_SYNCING\_DISABLED\_REMINDER bypassing SYNCING state because lease database synchronization is disabled**

This informational message is issued as a reminder that lease database synchronization is administratively disabled and therefore the server transitions directly from the "waiting" to "ready" state.

**HA\_CONFIG\_LEASE\_SYNCING\_DISABLED\_REMINDER (1) bypassing SYNCING state because lease database synchronization is disabled**

This informational message is issued as a reminder that lease database synchronization is administratively disabled and therefore the server transitions directly from the "waiting" to "ready" state.

**HA\_CONFIG\_LEASE\_UPDATES\_AND\_SYNCING\_DIFFER unusual configuration where "send-lease-updates": %1 and "sync-leases": %2**

This warning message is issued when the configuration values of the send-lease-updates and sync-leases parameters differ. This may be a valid configuration but is unusual. Normally, if the lease database with replication is in use, both values are set to false. If a lease database without replication is in use (e.g. memfile), both values are set to true. Providing different values for those parameters means that an administrator either wants the server to not synchronize leases upon startup but later send lease updates to the partner, or the lease database should be synchronized upon startup, but no lease updates are later sent as a result of leases allocation.

**HA\_CONFIG\_LEASE\_UPDATES\_AND\_SYNCING\_DIFFER (1) unusual configuration where "send-lease-updates": %1 and "sync-leases": %2**

This warning message is issued when the configuration values of the send-lease-updates and sync-leases parameters differ. This may be a valid configuration but is unusual. Normally, if the lease database with replication is in use, both values are set to false. If a lease database without replication is in use (e.g. memfile), both values are set to true. Providing different values for those parameters means that an administrator either wants the server to not synchronize leases upon startup but later send lease updates to the partner, or the lease database should be synchronized upon startup, but no lease updates are later sent as a result of leases allocation.

**HA\_CONFIG\_LEASE\_UPDATES\_DISABLED lease updates will not be generated**

This warning message is issued when the lease updates are administratively disabled. This is valid configuration if the leases are replicated to the partner's database via some other mechanism, e.g. SQL database replication.

**HA\_CONFIG\_LEASE\_UPDATES\_DISABLED (1) lease updates will not be generated**

This warning message is issued when the lease updates are administratively disabled. This is valid configuration if the leases are replicated to the partner's database via some other mechanism, e.g. SQL database replication.

**HA\_CONFIG\_LEASE\_UPDATES\_DISABLED\_REMINDER lease updates are administratively disabled and will not be generated**

This informational message is issued as a reminder that the lease updates are administratively disabled and will not be issued in the HA state to which the server has transitioned. The sole argument specifies the state into which the server has transitioned.

**HA\_CONFIG\_LEASE\_UPDATES\_DISABLED\_REMINDER (1) lease updates are administratively disabled and will not be ge**

This informational message is issued as a reminder that the lease updates are administratively disabled and will not be issued in the HA state to which the server has transitioned. The sole argument specifies the state into which the server has transitioned.

**HA\_CONTINUE\_HANDLER\_FAILED ha-continue command failed: %1**

This error message is issued to indicate that the ha-continue command handler failed while processing the command. The argument provides the reason for failure.

**HA\_CONTINUE\_HANDLER\_FAILED (1) ha-continue command failed: %1**

This error message is issued to indicate that the ha-continue command handler failed while processing the command. The argument provides the reason for failure.

**HA\_DEINIT\_OK unloading High Availability hooks library successful**

This informational message indicates that the High Availability hooks library has been unloaded successfully.

**HA\_DEINIT\_OK (1) unloading High Availability hooks library successful**

This informational message indicates that the High Availability hooks library has been unloaded successfully.

**HA\_DHCP4\_START\_SERVICE\_FAILED failed to start DHCPv4 HA service in dhcp4\_srv\_configured callout: %1**

This error message is issued when an attempt to start High Availability service for the DHCPv4 server failed in the dhcp4\_srv\_configured callout. This is internal server error and a bug report should be created.

**HA\_DHCP4\_START\_SERVICE\_FAILED (1) failed to start DHCPv4 HA service in dhcp4\_srv\_configured callout: %1**

This error message is issued when an attempt to start High Availability service for the DHCPv4 server failed in the dhcp4\_srv\_configured callout. This is internal server error and a bug report should be created.

**HA\_DHCP6\_START\_SERVICE\_FAILED failed to start DHCPv4 HA service in dhcp6\_srv\_configured callout: %1**

This error message is issued when an attempt to start High Availability service for the DHCPv4 server failed in the dhcp4\_srv\_configured callout. This is internal server error and a bug report should be created.

**HA\_DHCP6\_START\_SERVICE\_FAILED (1) failed to start DHCPv4 HA service in dhcp6\_srv\_configured callout: %1**

This error message is issued when an attempt to start High Availability service for the DHCPv4 server failed in the dhcp4\_srv\_configured callout. This is internal server error and a bug report should be created.

**HA\_DHCP\_DISABLE\_COMMUNICATIONS\_FAILED failed to send request to disable DHCP service of %1: %2**

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-disable command. The first argument provides the remote server's name. The second argument provides a reason for failure.

**HA\_DHCP\_DISABLE\_COMMUNICATIONS\_FAILED (1) failed to send request to disable DHCP service of %1: %2**

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-disable command. The first argument provides the remote server's name. The second argument provides a reason for failure.

**HA\_DHCP\_DISABLE\_FAILED failed to disable DHCP service of %1: %2**

This warning message indicates that a peer returned an error status code in response to a dhcp-disable command. The first argument provides the remote server's name. The second argument provides a reason for failure.

**HA\_DHCP\_DISABLE\_FAILED (1) failed to disable DHCP service of %1: %2**

This warning message indicates that a peer returned an error status code in response to a dhcp-disable command. The first argument provides the remote server's name. The second argument provides a reason for failure.

**HA\_DHCP\_ENABLE\_COMMUNICATIONS\_FAILED failed to send request to enable DHCP service of %1: %2**

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-enable command. The first argument provides the remote server's name. The second argument provides a reason for failure.

**HA\_DHCP\_ENABLE\_COMMUNICATIONS\_FAILED (1) failed to send request to enable DHCP service of %1: %2**

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-enable command. The first argument provides the remote server's name. The second argument provides a reason for failure.

**HA\_DHCP\_ENABLE\_FAILED failed to enable DHCP service of %1: %2**

This warning message indicates that a peer returned an error status code in response to a dhcp-enable command. The first argument provides the remote server's name. The second argument provides a reason for failure.

**HA\_DHCP\_ENABLE\_FAILED (1) failed to enable DHCP service of %1: %2**

This warning message indicates that a peer returned an error status code in response to a dhcp-enable command. The first argument provides the remote server's name. The second argument provides a reason for failure.

**HA\_HEARTBEAT\_COMMUNICATIONS\_FAILED failed to send heartbeat to %1: %2**

This warning message indicates that there was a problem in communication with a HA peer while sending a heartbeat. This is a first sign that the peer may be down. The server will keep trying to send heartbeats until it considers that communication is interrupted.

**HA\_HEARTBEAT\_COMMUNICATIONS\_FAILED (1) failed to send heartbeat to %1: %2**

This warning message indicates that there was a problem in communication with a HA peer while sending a heartbeat. This is a first sign that the peer may be down. The server will keep trying to send heartbeats until it considers that communication is interrupted.

**HA\_HEARTBEAT\_FAILED heartbeat to %1 failed: %2**

This warning message indicates that a peer returned an error status code in response to a heartbeat. This is the sign that the peer may not function properly. The server will keep trying to send heartbeats until it considers that communication is interrupted.

**HA\_HEARTBEAT\_FAILED (1) heartbeat to %1 failed: %2**

This warning message indicates that a peer returned an error status code in response to a heartbeat. This is the sign that the peer may not function properly. The server will keep trying to send heartbeats until it considers that communication is interrupted.

**HA\_HEARTBEAT\_HANDLER\_FAILED heartbeat command failed: %1**

This error message is issued to indicate that the heartbeat command handler failed while processing the command. The argument provides the reason for failure.

**HA\_HEARTBEAT\_HANDLER\_FAILED (1) heartbeat command failed: %1**

This error message is issued to indicate that the heartbeat command handler failed while processing the command. The argument provides the reason for failure.

**HA\_HIGH\_CLOCK\_SKEW partner's clock is %1, please synchronize clocks!**

This warning message is issued when the clock skew between the active servers exceeds 30 seconds. The HA service continues to operate but may not function properly, especially for low lease lifetimes. The administrator should synchronize the clocks, e.g. using NTP. If the clock skew exceeds 60 seconds, the HA service will terminate.

**HA\_HIGH\_CLOCK\_SKEW (1) partner's clock is %1, please synchronize clocks!**

This warning message is issued when the clock skew between the active servers exceeds 30 seconds. The HA service continues to operate but may not function properly, especially for low lease lifetimes. The administrator should synchronize the clocks, e.g. using NTP. If the clock skew exceeds 60 seconds, the HA service will terminate.

**HA\_HIGH\_CLOCK\_SKEW\_CAUSES\_TERMINATION partner's clock is %1, causing HA service to terminate**

This warning message is issued when the clock skew between the active servers exceeds 60 seconds. The HA service stops. The servers will continue to respond to the DHCP queries but won't exchange lease updates or send heartbeats. The administrator is required to synchronize the clocks and then restart the servers to resume the HA service.

**HA\_HIGH\_CLOCK\_SKEW\_CAUSES\_TERMINATION (1) partner's clock is %1, causing HA service to terminate**

This warning message is issued when the clock skew between the active servers exceeds 60 seconds. The HA service stops. The servers will continue to respond to the DHCP queries but won't exchange lease updates or send heartbeats. The administrator is required to synchronize the clocks and then restart the servers to resume the HA service.

**HA\_INIT\_OK loading High Availability hooks library successful**

This informational message indicates that the High Availability hooks library has been loaded successfully.

**HA\_INIT\_OK (1) loading High Availability hooks library successful**

This informational message indicates that the High Availability hooks library has been loaded successfully.

**HA\_LEASES4\_COMMITTED\_FAILED leases4\_committed callout failed: %1**

This error message is issued when the callout for the leases4\_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

**HA\_LEASES4\_COMMITTED\_FAILED (1) leases4\_committed callout failed: %1**

This error message is issued when the callout for the leases4\_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

**HA\_LEASES4\_COMMITTED\_NOTHING\_TO\_UPDATE %1: leases4\_committed callout was invoked without any leases**

This debug message is issued when the "leases4\_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

**HA\_LEASES4\_COMMITTED\_NOTHING\_TO\_UPDATE (1) %1: leases4\_committed callout was invoked without any leases**

This debug message is issued when the "leases4\_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

**HA\_LEASES6\_COMMITTED\_FAILED leases6\_committed callout failed: %1**

This error message is issued when the callout for the leases6\_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

**HA\_LEASES6\_COMMITTED\_FAILED (1) leases6\_committed callout failed: %1**

This error message is issued when the callout for the leases6\_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

**HA\_LEASES6\_COMMITTED\_NOTHING\_TO\_UPDATE %1: leases6\_committed callout was invoked without any leases**

This debug message is issued when the "leases6\_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

**HA\_LEASES6\_COMMITTED\_NOTHING\_TO\_UPDATE (1) %1: leases6\_committed callout was invoked without any leases**

This debug message is issued when the "leases6\_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

**HA\_LEASES\_SYNC\_COMMUNICATIONS\_FAILED failed to communicate with %1 while syncing leases: %2**

This error message is issued to indicate that there was a communication error with a partner server while trying to fetch leases from its lease database. The argument contains a reason for the error.

**HA\_LEASES\_SYNC\_COMMUNICATIONS\_FAILED (1) failed to communicate with %1 while syncing leases: %2**

This error message is issued to indicate that there was a communication error with a partner server while trying to fetch leases from its lease database. The argument contains a reason for the error.

**HA\_LEASES\_SYNC\_FAILED failed to synchronize leases with %1: %2**

This error message is issued to indicate that there was a problem while parsing a response from the server from which leases have been fetched for local database synchronization. The argument contains a reason for the error.

**HA\_LEASES\_SYNC\_FAILED (1) failed to synchronize leases with %1: %2**

This error message is issued to indicate that there was a problem while parsing a response from the server from which leases have been fetched for local database synchronization. The argument contains a reason for the error.

**HA\_LEASES\_SYNC\_LEASE\_PAGE\_RECEIVED received %1 leases from %2**

This informational message is issued during lease database synchronization to indicate that a bulk of leases have been received. The first argument holds the count of leases received. The second argument specifies the partner server name.

**HA\_LEASES\_SYNC\_LEASE\_PAGE\_RECEIVED (1) received %1 leases from %2**

This informational message is issued during lease database synchronization to indicate that a bulk of leases have been received. The first argument holds the count of leases received. The second argument specifies the partner server name.

**HA\_LEASE\_SYNC\_FAILED synchronization failed for lease: %1, reason: %2**

This warning message is issued when creating or updating a lease in the local lease database fails. The lease information in the JSON format is provided as a first argument. The second argument provides a reason for the failure.

**HA\_LEASE\_SYNC\_FAILED (1) synchronization failed for lease: %1, reason: %2**

This warning message is issued when creating or updating a lease in the local lease database fails. The lease information in the JSON format is provided as a first argument. The second argument provides a reason for the failure.

**HA\_LEASE\_SYNC\_STALE\_LEASE4\_SKIP skipping stale lease %1 in subnet %2**

This debug message is issued during lease database synchronization, when fetched IPv4 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies leased address. The second argument specifies a subnet to which the lease belongs.

**HA\_LEASE\_SYNC\_STALE\_LEASE4\_SKIP (1) skipping stale lease %1 in subnet %2**

This debug message is issued during lease database synchronization, when fetched IPv4 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies leased address. The second argument specifies a subnet to which the lease belongs.

**HA\_LEASE\_SYNC\_STALE\_LEASE6\_SKIP skipping stale lease %1 in subnet %2**

This debug message is issued during lease database synchronization, when fetched IPv6 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies leased address. The second argument specifies a subnet to which the lease belongs.

**HA\_LEASE\_SYNC\_STALE\_LEASE6\_SKIP (1) skipping stale lease %1 in subnet %2**

This debug message is issued during lease database synchronization, when fetched IPv6 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies leased address. The second argument specifies a subnet to which the lease belongs.

**HA\_LEASE\_UPDATES\_DISABLED lease updates will not be sent to the partner while in %1 state**

This informational message is issued to indicate that lease updates will not be sent to the partner while the server is in the current state. The argument specifies the server's current state name. The lease updates are still sent to the backup servers if they are configured but any possible errors in communication with the backup servers are ignored.

**HA\_LEASE\_UPDATES\_DISABLED (1) lease updates will not be sent to the partner while in %1 state**

This informational message is issued to indicate that lease updates will not be sent to the partner while the server is in the current state. The argument specifies the server's current state name. The lease updates are still sent to the backup servers if they are configured but any possible errors in communication with the backup servers are ignored.

**HA\_LEASE\_UPDATES\_ENABLED lease updates will be sent to the partner while in %1 state**

This informational message is issued to indicate that lease updates will be sent to the partner while the server is in the current state. The argument specifies the server's current state name.

**HA\_LEASE\_UPDATES\_ENABLED (1) lease updates will be sent to the partner while in %1 state**

This informational message is issued to indicate that lease updates will be sent to the partner while the server is in the current state. The argument specifies the server's current state name.

**HA\_LEASE\_UPDATE\_COMMUNICATIONS\_FAILED %1: failed to communicate with %2: %3**

This warning message indicates that there was a problem in communication with a HA peer while processing a DHCP client query and sending lease update. The client's DHCP message will be dropped.

**HA\_LEASE\_UPDATE\_COMMUNICATIONS\_FAILED (1) %1: failed to communicate with %2: %3**

This warning message indicates that there was a problem in communication with a HA peer while processing a DHCP client query and sending lease update. The client's DHCP message will be dropped.

**HA\_LEASE\_UPDATE\_FAILED %1: lease update to %2 failed: %3**

This warning message indicates that a peer returned an error status code in response to a lease update. The client's DHCP message will be dropped.

**HA\_LEASE\_UPDATE\_FAILED (1) %1: lease update to %2 failed: %3**

This warning message indicates that a peer returned an error status code in response to a lease update. The client's DHCP message will be dropped.



**HA\_LOAD\_BALANCING\_DUID\_MISSING load balancing failed for the DHCPv6 message (transaction id: %1) because DUID is missing**

This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv6 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

**HA\_LOAD\_BALANCING\_DUID\_MISSING (1) load balancing failed for the DHCPv6 message (transaction id: %1) because DUID is missing**

This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv6 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

**HA\_LOAD\_BALANCING\_IDENTIFIER\_MISSING load balancing failed for the DHCPv4 message (transaction id: %1) because identifier is missing**

This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv4 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

**HA\_LOAD\_BALANCING\_IDENTIFIER\_MISSING (1) load balancing failed for the DHCPv4 message (transaction id: %1) because identifier is missing**

This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv4 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

**HA\_LOCAL\_DHCP\_DISABLE local DHCP service is disabled while the %1 is in the %2 state**

This informational message is issued to indicate that the local DHCP service is disabled because the server remains in a state in which the server should not respond to DHCP clients, e.g. the server hasn't synchronized its lease database. The first argument specifies server name. The second argument specifies server's state.

**HA\_LOCAL\_DHCP\_DISABLE (1) local DHCP service is disabled while the %1 is in the %2 state**

This informational message is issued to indicate that the local DHCP service is disabled because the server remains in a state in which the server should not respond to DHCP clients, e.g. the server hasn't synchronized its lease database. The first argument specifies server name. The second argument specifies server's state.

**HA\_LOCAL\_DHCP\_ENABLE local DHCP service is enabled while the %1 is in the %2 state**

This informational message is issued to indicate that the local DHCP service is enabled because the server remains in a state in which it should respond to the DHCP clients. The first argument specifies server name. The second argument specifies server's state.

**HA\_LOCAL\_DHCP\_ENABLE (1) local DHCP service is enabled while the %1 is in the %2 state**

This informational message is issued to indicate that the local DHCP service is enabled because the server remains in a state in which it should respond to the DHCP clients. The first argument specifies server name. The second argument specifies server's state.

**HA\_MISSING\_CONFIGURATION high-availability parameter not specified for High Availability hooks library**

This error message is issued to indicate that the configuration for the High Availability hooks library hasn't been specified. The 'high-availability' parameter must be specified for the hooks library to load properly.

**HA\_MISSING\_CONFIGURATION (1) high-availability parameter not specified for High Availability hooks library**

This error message is issued to indicate that the configuration for the High Availability hooks library hasn't been specified. The 'high-availability' parameter must be specified for the hooks library to load properly.

**HA\_SCOPES\_HANDLER\_FAILED ha-scopes command failed: %1**

This error message is issued to indicate that the ha-scopes command handler failed while processing the command. The argument provides reason for the failure.

**HA\_SCOPES\_HANDLER\_FAILED (1) ha-scopes command failed: %1**

This error message is issued to indicate that the ha-scopes command handler failed while processing the command. The argument provides reason for the failure.

---

**HA\_SERVICE\_STARTED started high availability service in %1 mode as %2 server**

This informational message is issued when the HA service is started as a result of server startup or reconfiguration. The first argument provides the HA mode. The second argument specifies the role of this server instance in this configuration.

**HA\_SERVICE\_STARTED (1) started high availability service in %1 mode as %2 server**

This informational message is issued when the HA service is started as a result of server startup or reconfiguration. The first argument provides the HA mode. The second argument specifies the role of this server instance in this configuration.

**HA\_STATE\_MACHINE\_CONTINUED state machine is un-paused**

This informational message is issued when the HA state machine is un-paused. This unlocks the server from the current state. It may transition to any other state if it needs to do so, e.g. 'partner-down' if its partner appears to be offline. The server may also remain in the current state if the HA setup state warrants such behavior.

**HA\_STATE\_MACHINE\_CONTINUED (1) state machine is un-paused**

This informational message is issued when the HA state machine is un-paused. This unlocks the server from the current state. It may transition to any other state if it needs to do so, e.g. 'partner-down' if its partner appears to be offline. The server may also remain in the current state if the HA setup state warrants such behavior.

**HA\_STATE\_MACHINE\_PAUSED state machine paused in state %1**

This informational message is issued when the HA state machine is paused. HA state machine may be paused in certain states specified in the HA hooks library configuration. When the state machine is paused, the server remains in the given state until it is explicitly unpaused (via ha-continue command). If the state machine is paused, the server operates normally but can't transition to any other state.

**HA\_STATE\_MACHINE\_PAUSED (1) state machine paused in state %1**

This informational message is issued when the HA state machine is paused. HA state machine may be paused in certain states specified in the HA hooks library configuration. When the state machine is paused, the server remains in the given state until it is explicitly unpaused (via ha-continue command). If the state machine is paused, the server operates normally but can't transition to any other state.

**HA\_STATE\_TRANSITION server transitions from %1 to %2 state, partner state is %3**

This informational message is issued when the server transitions to a new state as a result of some interaction (or lack of thereof) with its partner. The arguments specify initial server state, new server state and the partner's state.

**HA\_STATE\_TRANSITION (1) server transitions from %1 to %2 state, partner state is %3**

This informational message is issued when the server transitions to a new state as a result of some interaction (or lack of thereof) with its partner. The arguments specify initial server state, new server state and the partner's state.

**HA\_SYNC\_FAILED lease database synchronization with %1 failed: %2**

This error message is issued to indicate that the lease database synchronization failed. The first argument provides partner server's name. The second argument provides a reason for the failure.

**HA\_SYNC\_FAILED (1) lease database synchronization with %1 failed: %2**

This error message is issued to indicate that the lease database synchronization failed. The first argument provides partner server's name. The second argument provides a reason for the failure.

**HA\_SYNC\_HANDLER\_FAILED ha-sync command failed: %1**

This error message is issued to indicate that the ha-sync command handler failed while processing the command. The argument provides the reason for failure.

**HA\_SYNC\_HANDLER\_FAILED (1) ha-sync command failed: %1**

This error message is issued to indicate that the ha-sync command handler failed while processing the command. The argument provides the reason for failure.

**HA\_SYNC\_START starting lease database synchronization with %1**

This informational message is issued when the server starts lease database synchronization with a partner. The name of the partner is specified with the sole argument.

**HA\_SYNC\_START (1) starting lease database synchronization with %1**

This informational message is issued when the server starts lease database synchronization with a partner. The name of the partner is specified with the sole argument.

**HA\_SYNC\_SUCCESSFUL lease database synchronization with %1 completed successfully in %2**

This informational message is issued when the server successfully completed lease database synchronization with the partner. The first argument specifies the name of the partner server. The second argument specifies the duration of the synchronization.

**HA\_SYNC\_SUCCESSFUL (1) lease database synchronization with %1 completed successfully in %2**

This informational message is issued when the server successfully completed lease database synchronization with the partner. The first argument specifies the name of the partner server. The second argument specifies the duration of the synchronization.

**HA\_TERMINATED HA service terminated because of the unacceptable clock skew; fix the problem and restart!**

This error message is issued to indicate that the HA service has been stopped due to unacceptable clock skew. The error can be fixed by synchronizing the clocks on the active servers and restarting Kea.

**HA\_TERMINATED (1) HA service terminated because of the unacceptable clock skew; fix the problem and restart!**

This error message is issued to indicate that the HA service has been stopped due to unacceptable clock skew. The error can be fixed by synchronizing the clocks on the active servers and restarting Kea.

## HOOKS Module

**HOOKS\_ALL\_CALLOUTS\_DEREGISTERED hook library at index %1 removed all callouts on hook %2**

A debug message issued when all callouts on the specified hook registered by the library with the given index were removed. This is similar to the HOOKS\_CALLOUTS\_REMOVED message (and the two are likely to be seen together), but is issued at a lower-level in the hook framework.

**HOOKS\_ALL\_CALLOUTS\_DEREGISTERED (1) hook library at index %1 removed all callouts on hook %2**

A debug message issued when all callouts on the specified hook registered by the library with the given index were removed. This is similar to the HOOKS\_CALLOUTS\_REMOVED message (and the two are likely to be seen together), but is issued at a lower-level in the hook framework.

**HOOKS\_CALLOUTS\_BEGIN begin all callouts for hook %1**

This debug message is issued when callout manager begins to invoke callouts for the hook. The argument specifies the hook name.

**HOOKS\_CALLOUTS\_BEGIN (1) begin all callouts for hook %1**

This debug message is issued when callout manager begins to invoke callouts for the hook. The argument specifies the hook name.

**HOOKS\_CALLOUTS\_COMPLETE completed callouts for hook %1 (total callouts duration: %2)**

This debug message is issued when callout manager has completed execution of all callouts for the particular hook. The arguments specify the hook name and total execution time for all callouts in milliseconds.

**HOOKS\_CALLOUTS\_COMPLETE (1) completed callouts for hook %1 (total callouts duration: %2)**

This debug message is issued when callout manager has completed execution of all callouts for the particular hook. The arguments specify the hook name and total execution time for all callouts in milliseconds.

**HOOKS\_CALLOUTS\_REMOVED callouts removed from hook %1 for library %2**

This is a debug message issued during library unloading. It notes that one of more callouts registered by that library have been removed from the specified hook. This is similar to the HOOKS\_DEREGISTER\_ALL\_CALLOUTS message (and the two are likely to be seen together), but is issued at a higher-level in the hook framework.

**HOOKS\_CALLOUTS\_REMOVED (1) callouts removed from hook %1 for library %2**

This is a debug message issued during library unloading. It notes that one of more callouts registered by that library have been removed from the specified hook. This is similar to the HOOKS\_DEREGISTER\_ALL\_CALLOUTS message (and the two are likely to be seen together), but is issued at a higher-level in the hook framework.

---

**HOOKS\_CALLOUT\_CALLED hooks library with index %1 has called a callout on hook %2 that has address %3 (callout duration %4)**

Only output at a high debugging level, this message indicates that a callout on the named hook registered by the library with the given index (in the list of loaded libraries) has been called and returned a success state. The address of the callout is given in the message. The message includes the callout execution time in milliseconds.

**HOOKS\_CALLOUT\_CALLED (1) hooks library with index %1 has called a callout on hook %2 that has address %3 (callout duration %4)**

Only output at a high debugging level, this message indicates that a callout on the named hook registered by the library with the given index (in the list of loaded libraries) has been called and returned a success state. The address of the callout is given in the message. The message includes the callout execution time in milliseconds.

**HOOKS\_CALLOUT\_DEREGISTERED hook library at index %1 deregistered a callout on hook %2**

A debug message issued when all instances of a particular callouts on the hook identified in the message that were registered by the library with the given index have been removed.

**HOOKS\_CALLOUT\_DEREGISTERED (1) hook library at index %1 deregistered a callout on hook %2**

A debug message issued when all instances of a particular callouts on the hook identified in the message that were registered by the library with the given index have been removed.

**HOOKS\_CALLOUT\_ERROR error returned by callout on hook %1 registered by library with index %2 (callout address %3)**

If a callout returns an error status when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

**HOOKS\_CALLOUT\_ERROR (1) error returned by callout on hook %1 registered by library with index %2 (callout address %3)**

If a callout returns an error status when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

**HOOKS\_CALLOUT\_EXCEPTION exception thrown by callout on hook %1 registered by library with index %2 (callout address %3)**

If a callout throws an exception when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

**HOOKS\_CALLOUT\_EXCEPTION (1) exception thrown by callout on hook %1 registered by library with index %2 (callout address %3)**

If a callout throws an exception when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

**HOOKS\_CALLOUT\_REGISTRATION hooks library with index %1 registering callout for hook '%2'**

This is a debug message, output when a library (whose index in the list of libraries (being) loaded is given) registers a callout.

**HOOKS\_CALLOUT\_REGISTRATION (1) hooks library with index %1 registering callout for hook '%2'**

This is a debug message, output when a library (whose index in the list of libraries (being) loaded is given) registers a callout.

**HOOKS\_CLOSE\_ERROR failed to close hook library %1: %2**

Kea has failed to close the named hook library for the stated reason. Although this is an error, this should not affect the running system other than as a loss of resources. If this error persists, you should restart Kea.

**HOOKS\_CLOSE\_ERROR (1) failed to close hook library %1: %2**

Kea has failed to close the named hook library for the stated reason. Although this is an error, this should not affect the running system other than as a loss of resources. If this error persists, you should restart Kea.

**HOOKS\_HOOK\_LIST\_RESET the list of hooks has been reset**

This is a message indicating that the list of hooks has been reset. While this is usual when running the Kea test suite, it should not be seen when running Kea in a production environment. If this appears, please report a bug through the usual channels.

**HOOKS\_HOOK\_LIST\_RESET (1) the list of hooks has been reset**

This is a message indicating that the list of hooks has been reset. While this is usual when running the Kea test suite, it should not be seen when running Kea in a production environment. If this appears, please report a bug through the usual channels.

**HOOKS\_INCORRECT\_VERSION hook library %1 is at version %2, require version %3**

Kea has detected that the named hook library has been built against a version of Kea that is incompatible with the version of Kea running on your system. It has not loaded the library.

This is most likely due to the installation of a new version of Kea without rebuilding the hook library. A rebuild and re-install of the library should fix the problem in most cases.

**HOOKS\_INCORRECT\_VERSION (1) hook library %1 is at version %2, require version %3**

Kea has detected that the named hook library has been built against a version of Kea that is incompatible with the version of Kea running on your system. It has not loaded the library.

This is most likely due to the installation of a new version of Kea without rebuilding the hook library. A rebuild and re-install of the library should fix the problem in most cases.

**HOOKS\_LIBRARY\_LOADED hooks library %1 successfully loaded**

This information message is issued when a user-supplied hooks library has been successfully loaded.

**HOOKS\_LIBRARY\_LOADED (1) hooks library %1 successfully loaded**

This information message is issued when a user-supplied hooks library has been successfully loaded.

**HOOKS\_LIBRARY\_LOADING loading hooks library %1**

This is a debug message output just before the specified library is loaded. If the action is successful, it will be followed by the HOOKS\_LIBRARY\_LOADED informational message.

**HOOKS\_LIBRARY\_LOADING (1) loading hooks library %1**

This is a debug message output just before the specified library is loaded. If the action is successful, it will be followed by the HOOKS\_LIBRARY\_LOADED informational message.

**HOOKS\_LIBRARY\_UNLOADED hooks library %1 successfully unloaded**

This information message is issued when a user-supplied hooks library has been successfully unloaded.

**HOOKS\_LIBRARY\_UNLOADED (1) hooks library %1 successfully unloaded**

This information message is issued when a user-supplied hooks library has been successfully unloaded.

**HOOKS\_LIBRARY\_UNLOADING unloading library %1**

This is a debug message called when the specified library is being unloaded. If all is successful, it will be followed by the HOOKS\_LIBRARY\_UNLOADED informational message.

**HOOKS\_LIBRARY\_UNLOADING (1) unloading library %1**

This is a debug message called when the specified library is being unloaded. If all is successful, it will be followed by the HOOKS\_LIBRARY\_UNLOADED informational message.

**HOOKS\_LIBRARY\_VERSION hooks library %1 reports its version as %2**

A debug message issued when the version check on the hooks library has succeeded.

**HOOKS\_LIBRARY\_VERSION (1) hooks library %1 reports its version as %2**

A debug message issued when the version check on the hooks library has succeeded.

**HOOKS\_LOAD\_ERROR 'load' function in hook library %1 returned error %2**

A "load" function was found in the library named in the message and was called. The function returned a non-zero status (also given in the message) which was interpreted as an error. The library has been unloaded and no callouts from it will be installed.

**HOOKS\_LOAD\_ERROR (1) 'load' function in hook library %1 returned error %2**

A "load" function was found in the library named in the message and was called. The function returned a non-zero status (also given in the message) which was interpreted as an error. The library has been unloaded and no callouts from it will be installed.

**HOOKS\_LOAD\_EXCEPTION 'load' function in hook library %1 threw an exception**

A "load" function was found in the library named in the message and was called. The function threw an exception (an error indication) during execution, which is an error condition. The library has been unloaded and no callouts from it will be installed.

**HOOKS\_LOAD\_EXCEPTION (1) 'load' function in hook library %1 threw an exception**

A "load" function was found in the library named in the message and was called. The function threw an exception (an error indication) during execution, which is an error condition. The library has been unloaded and no callouts from it will be installed.

**HOOKS\_LOAD\_FRAMEWORK\_EXCEPTION 'load' function in hook library %1 threw an exception: reason %2**

A "load" function was found in the library named in the message and was called. Either the hooks framework or the function threw an exception (an error indication) during execution, which is an error condition; the cause of the exception is recorded in the message. The library has been unloaded and no callouts from it will be installed.

**HOOKS\_LOAD\_FRAMEWORK\_EXCEPTION (1) 'load' function in hook library %1 threw an exception: reason %2**

A "load" function was found in the library named in the message and was called. Either the hooks framework or the function threw an exception (an error indication) during execution, which is an error condition; the cause of the exception is recorded in the message. The library has been unloaded and no callouts from it will be installed.

**HOOKS\_LOAD\_SUCCESS 'load' function in hook library %1 returned success**

This is a debug message issued when the "load" function has been found in a hook library and has been successfully called.

**HOOKS\_LOAD\_SUCCESS (1) 'load' function in hook library %1 returned success**

This is a debug message issued when the "load" function has been found in a hook library and has been successfully called.

**HOOKS\_NO\_LOAD no 'load' function found in hook library %1**

This is a debug message saying that the specified library was loaded but no function called "load" was found in it. Providing the library contained some "standard" functions (i.e. functions with the names of the hooks for the given server), this is not an issue.

**HOOKS\_NO\_LOAD (1) no 'load' function found in hook library %1**

This is a debug message saying that the specified library was loaded but no function called "load" was found in it. Providing the library contained some "standard" functions (i.e. functions with the names of the hooks for the given server), this is not an issue.

**HOOKS\_NO\_UNLOAD no 'unload' function found in hook library %1**

This is a debug message issued when the library is being unloaded. It merely states that the library did not contain an "unload" function.

**HOOKS\_NO\_UNLOAD (1) no 'unload' function found in hook library %1**

This is a debug message issued when the library is being unloaded. It merely states that the library did not contain an "unload" function.

**HOOKS\_NO\_VERSION no 'version' function found in hook library %1**

The shared library named in the message was found and successfully loaded, but Kea did not find a function named "version" in it. This function is required and should return the version of Kea against which the library was built. The value is used to check that the library was built against a compatible version of Kea. The library has not been loaded.

**HOOKS\_NO\_VERSION (1) no 'version' function found in hook library %1**

The shared library named in the message was found and successfully loaded, but Kea did not find a function named "version" in it. This function is required and should return the version of Kea against which the library was built. The value is used to check that the library was built against a compatible version of Kea. The library has not been loaded.

**HOOKS\_OPEN\_ERROR failed to open hook library %1: %2**

Kea failed to open the specified hook library for the stated reason. The library has not been loaded. Kea will continue to function, but without the services offered by the library.

**HOOKS\_OPEN\_ERROR (1) failed to open hook library %1: %2**

Kea failed to open the specified hook library for the stated reason. The library has not been loaded. Kea will continue to function, but without the services offered by the library.

**HOOKS\_STD\_CALLOUT\_REGISTERED hooks library %1 registered standard callout for hook %2 at address %3**

This is a debug message, output when the library loading function has located a standard callout (a callout with the same name as a hook point) and registered it. The address of the callout is indicated.

**HOOKS\_STD\_CALLOUT\_REGISTERED (1) hooks library %1 registered standard callout for hook %2 at address %3**

This is a debug message, output when the library loading function has located a standard callout (a callout with the same name as a hook point) and registered it. The address of the callout is indicated.

**HOOKS\_UNLOAD\_ERROR 'unload' function in hook library %1 returned error %2**

During the unloading of a library, an "unload" function was found. It was called, but returned an error (non-zero) status, resulting in the issuing of this message. The unload process continued after this message and the library has been unloaded.

**HOOKS\_UNLOAD\_ERROR (1) 'unload' function in hook library %1 returned error %2**

During the unloading of a library, an "unload" function was found. It was called, but returned an error (non-zero) status, resulting in the issuing of this message. The unload process continued after this message and the library has been unloaded.

**HOOKS\_UNLOAD\_EXCEPTION 'unload' function in hook library %1 threw an exception**

During the unloading of a library, an "unload" function was found. It was called, but in the process generated an exception (an error indication). The unload process continued after this message and the library has been unloaded.

**HOOKS\_UNLOAD\_EXCEPTION (1) 'unload' function in hook library %1 threw an exception**

During the unloading of a library, an "unload" function was found. It was called, but in the process generated an exception (an error indication). The unload process continued after this message and the library has been unloaded.

**HOOKS\_UNLOAD\_FRAMEWORK\_EXCEPTION 'unload' function in hook library %1 threw an exception, reason %2**

During the unloading of a library, an "unload" function was found. It was called, but in the process either it or the hooks framework generated an exception (an error indication); the cause of the error is recorded in the message. The unload process continued after this message and the library has been unloaded.

**HOOKS\_UNLOAD\_FRAMEWORK\_EXCEPTION (1) 'unload' function in hook library %1 threw an exception, reason %2**

During the unloading of a library, an "unload" function was found. It was called, but in the process either it or the hooks framework generated an exception (an error indication); the cause of the error is recorded in the message. The unload process continued after this message and the library has been unloaded.

**HOOKS\_UNLOAD\_SUCCESS 'unload' function in hook library %1 returned success**

This is a debug message issued when an "unload" function has been found in a hook library during the unload process, called, and returned success.

**HOOKS\_UNLOAD\_SUCCESS (1) 'unload' function in hook library %1 returned success**

This is a debug message issued when an "unload" function has been found in a hook library during the unload process, called, and returned success.

**HOOKS\_VERSION\_EXCEPTION 'version' function in hook library %1 threw an exception**

This error message is issued if the version() function in the specified hooks library was called and generated an exception. The library is considered unusable and will not be loaded.

**HOOKS\_VERSION\_EXCEPTION (1) 'version' function in hook library %1 threw an exception**

This error message is issued if the version() function in the specified hooks library was called and generated an exception. The library is considered unusable and will not be loaded.

## HOSTS Module

**HOSTS\_BACKENDS\_REGISTERED the following host backend types are available: %1**

This informational message lists all possible host backends that could be used in hosts-database[s].

**HOSTS\_BACKENDS\_REGISTERED (1) the following host backend types are available: %1**

This informational message lists all possible host backends that could be used in hosts-database[s].

**HOSTS\_BACKEND\_DEREGISTER deregistered host backend type: %1**

This debug message is issued when a backend factory was deregistered. It is no longer possible to use host backend of this type.

**HOSTS\_BACKEND\_DEREGISTER (1) deregistered host backend type: %1**

This debug message is issued when a backend factory was deregistered. It is no longer possible to use host backend of this type.

**HOSTS\_BACKEND\_REGISTER registered host backend type: %1**

This debug message is issued when a backend factory was successfully registered. It is now possible to use host backend of this type.

**HOSTS\_BACKEND\_REGISTER (1) registered host backend type: %1**

This debug message is issued when a backend factory was successfully registered. It is now possible to use host backend of this type.

**HOSTS\_CFG\_ADD\_HOST add the host for reservations: %1**

This debug message is issued when new host (with reservations) is added to the server's configuration. The argument describes the host and its reservations in detail.

**HOSTS\_CFG\_ADD\_HOST (1) add the host for reservations: %1**

This debug message is issued when new host (with reservations) is added to the server's configuration. The argument describes the host and its reservations in detail.

**HOSTS\_CFG\_CACHE\_HOST\_DATA\_SOURCE get host cache data source: %1**

This informational message is issued when a host cache data source is detected by the host manager.

**HOSTS\_CFG\_CACHE\_HOST\_DATA\_SOURCE (1) get host cache data source: %1**

This informational message is issued when a host cache data source is detected by the host manager.

**HOSTS\_CFG\_CLOSE\_HOST\_DATA\_SOURCE Closing host data source: %1**

This is a normal message being printed when the server closes host data source connection.

**HOSTS\_CFG\_CLOSE\_HOST\_DATA\_SOURCE (1) Closing host data source: %1**

This is a normal message being printed when the server closes host data source connection.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS4 get all hosts with reservations for IPv4 address %1**

This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv4 address, from the configuration. The argument specifies the IPv4 address used to search the hosts.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS4 (1) get all hosts with reservations for IPv4 address %1**

This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv4 address, from the configuration. The argument specifies the IPv4 address used to search the hosts.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_COUNT using address %1, found %2 host(s)**

This debug message logs the number of hosts found using the specified IPv4 address. The arguments specify the IPv4 address used and the number of hosts found respectively.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_COUNT (1) using address %1, found %2 host(s)**

This debug message logs the number of hosts found using the specified IPv4 address. The arguments specify the IPv4 address used and the number of hosts found respectively.

---



**HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_HOST using address %1 found host: %2**

This debug message is issued when found host with the reservation for the specified IPv4 address. The arguments specify the IPv4 address and the detailed description of the host found.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_HOST (1) using address %1 found host: %2**

This debug message is issued when found host with the reservation for the specified IPv4 address. The arguments specify the IPv4 address and the detailed description of the host found.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS6 get all hosts with reservations for IPv6 address %1**

This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv6 address, from the configuration. The argument specifies the IPv6 address used to search the hosts.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS6 (1) get all hosts with reservations for IPv6 address %1**

This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv6 address, from the configuration. The argument specifies the IPv6 address used to search the hosts.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_COUNT using address %1, found %2 host(s)**

This debug message logs the number of hosts found using the specified IPv6 address. The arguments specify the IPv6 address used and the number of hosts found respectively.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_COUNT (1) using address %1, found %2 host(s)**

This debug message logs the number of hosts found using the specified IPv6 address. The arguments specify the IPv6 address used and the number of hosts found respectively.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_HOST using address %1 found host: %2**

This debug message is issued when found host with the reservation for the specified IPv6 address. The arguments specify the IPv6 address and the detailed description of the host found.

**HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_HOST (1) using address %1 found host: %2**

This debug message is issued when found host with the reservation for the specified IPv6 address. The arguments specify the IPv6 address and the detailed description of the host found.

**HOSTS\_CFG\_GET\_ALL\_IDENTIFIER get all hosts with reservations using identifier: %1**

This debug message is issued when starting to retrieve reservations for all hosts identified by HW address or DUID. The argument holds both the identifier type and the value.

**HOSTS\_CFG\_GET\_ALL\_IDENTIFIER (1) get all hosts with reservations using identifier: %1**

This debug message is issued when starting to retrieve reservations for all hosts identified by HW address or DUID. The argument holds both the identifier type and the value.

**HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_COUNT using identifier %1, found %2 host(s)**

This debug message logs the number of hosts found using the specified identifier. The arguments specify the identifier used and the number of hosts found respectively.

**HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_COUNT (1) using identifier %1, found %2 host(s)**

This debug message logs the number of hosts found using the specified identifier. The arguments specify the identifier used and the number of hosts found respectively.

**HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_HOST using identifier: %1, found host: %2**

This debug message is issued when found host identified by the specific identifier. The arguments specify the identifier and the detailed description of the host found.

**HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_HOST (1) using identifier: %1, found host: %2**

This debug message is issued when found host identified by the specific identifier. The arguments specify the identifier and the detailed description of the host found.

**HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6 get all hosts with reservations for subnet id %1 and IPv6 address %2**

This debug message is issued when starting to retrieve all hosts connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

**HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6 (1) get all hosts with reservations for subnet id %1 and IPv6 address %2**

This debug message is issued when starting to retrieve all hosts connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

**HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_COUNT using subnet id %1 and address %2, found %3 host(s)**

This debug message include the details of the host found using the subnet id and address. The arguments specify subnet id, address and found host details respectively.

**HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_COUNT (1) using subnet id %1 and address %2, found %3 host(s)**

This debug message include the details of the host found using the subnet id and address. The arguments specify subnet id, address and found host details respectively.

**HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_HOST using subnet id %1 and address %2, found host: %3**

This debug message includes the details of the host found using the subnet id and address. The arguments specify subnet id, address and found host details respectively.

**HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_HOST (1) using subnet id %1 and address %2, found host: %3**

This debug message includes the details of the host found using the subnet id and address. The arguments specify subnet id, address and found host details respectively.

**HOSTS\_CFG\_GET\_ONE\_PREFIX get one host with reservation for prefix %1/%2**

This debug message is issued when starting to retrieve a host having a reservation for a specified prefix. The arguments specify a prefix and prefix length.

**HOSTS\_CFG\_GET\_ONE\_PREFIX (1) get one host with reservation for prefix %1/%2**

This debug message is issued when starting to retrieve a host having a reservation for a specified prefix. The arguments specify a prefix and prefix length.

**HOSTS\_CFG\_GET\_ONE\_PREFIX\_HOST using prefix %1/%2, found host: %3**

This debug message includes the details of the host found using the specific prefix/prefix length. The arguments specify prefix, prefix length and host details respectively.

**HOSTS\_CFG\_GET\_ONE\_PREFIX\_HOST (1) using prefix %1/%2, found host: %3**

This debug message includes the details of the host found using the specific prefix/prefix length. The arguments specify prefix, prefix length and host details respectively.

**HOSTS\_CFG\_GET\_ONE\_PREFIX\_NULL host not found using prefix %1/%2**

This debug message is issued when no host was found for a specified prefix and prefix length.

**HOSTS\_CFG\_GET\_ONE\_PREFIX\_NULL (1) host not found using prefix %1/%2**

This debug message is issued when no host was found for a specified prefix and prefix length.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4 get one host with reservation for subnet id %1 and IPv4 address %2**

This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv4 address reserved. The arguments specify subnet id and IPv4 address respectively.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4 (1) get one host with reservation for subnet id %1 and IPv4 address %2**

This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv4 address reserved. The arguments specify subnet id and IPv4 address respectively.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_HOST using subnet id %1 and address %2, found host: %3**

This debug message logs the details of the host found using the subnet id and IPv4 address.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_HOST (1) using subnet id %1 and address %2, found host: %3**

This debug message logs the details of the host found using the subnet id and IPv4 address.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_NULL host not found using subnet id %1 and address %2**

This debug message is issued when no host was found for the specified subnet id and IPv4 address.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_NULL (1) host not found using subnet id %1 and address %2**

This debug message is issued when no host was found for the specified subnet id and IPv4 address.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6 get one host with reservation for subnet id %1 and including IPv6 address %2**

This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6 (1) get one host with reservation for subnet id %1 and including IPv6 address %2**

This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_HOST using subnet id %1 and address %2, found host: %3**

This debug message logs the details of the host found using the subnet id and IPv6 address.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_HOST (1) using subnet id %1 and address %2, found host: %3**

This debug message logs the details of the host found using the subnet id and IPv6 address.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_NULL host not found using subnet id %1 and address %2**

This debug message is issued when no host was found using the specified subnet id and IPv6 address.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_NULL (1) host not found using subnet id %1 and address %2**

This debug message is issued when no host was found using the specified subnet id and IPv6 address.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER get one host with %1 reservation for subnet id %2, identified by %3**

This debug message is issued when starting to retrieve a host holding IPv4 or IPv6 reservations, which is connected to a specific subnet and is identified by a specific unique identifier. The first argument identifies if the IPv4 or IPv6 reservation is desired.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER (1) get one host with %1 reservation for subnet id %2, identified by %3**

This debug message is issued when starting to retrieve a host holding IPv4 or IPv6 reservations, which is connected to a specific subnet and is identified by a specific unique identifier. The first argument identifies if the IPv4 or IPv6 reservation is desired.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_HOST using subnet id %1 and identifier %2, found host: %3**

This debug message includes the details of a host found using a subnet id and specific host identifier.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_HOST (1) using subnet id %1 and identifier %2, found host: %3**

This debug message includes the details of a host found using a subnet id and specific host identifier.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_NULL host not found using subnet id %1 and identifier %2**

This debug message is issued when no host was found using the specified subnet id and host identifier.

**HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_NULL (1) host not found using subnet id %1 and identifier %2**

This debug message is issued when no host was found using the specified subnet id and host identifier.

**HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_ADDRESS4 trying alternate sources for host using subnet id %1 and address %2**

This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specific IPv4 address, and it is starting to search for this host in alternate host data sources.

**HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_ADDRESS4 (1) trying alternate sources for host using subnet id %1 and address %2**

This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specific IPv4 address, and it is starting to search for this host in alternate host data sources.

**HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER** get one host with IPv4 reservation for subnet id %1, identifier %2

This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

**HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER (1)** get one host with IPv4 reservation for subnet id %1, identifier %2

This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

**HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_HOST** using subnet id %1 and identifier %2, found in %3

This debug message includes the details of a host returned by an alternate hosts data source using a subnet id and specific host identifier.

**HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_HOST (1)** using subnet id %1 and identifier %2, found in %3

This debug message includes the details of a host returned by an alternate hosts data source using a subnet id and specific host identifier.

**HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_NULL** host not found using subnet id %1 and identifier %2

This debug message is issued when no host was found using the specified subnet id and host identifier.

**HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_NULL (1)** host not found using subnet id %1 and identifier %2

This debug message is issued when no host was found using the specified subnet id and host identifier.

**HOSTS\_MGR\_ALTERNATE\_GET6\_PREFIX** trying alternate sources for host using prefix %1/%2

This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified prefix, and it is starting to search for this host in alternate host data sources.

**HOSTS\_MGR\_ALTERNATE\_GET6\_PREFIX (1)** trying alternate sources for host using prefix %1/%2

This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified prefix, and it is starting to search for this host in alternate host data sources.

**HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_ADDRESS6** trying alternate sources for host using subnet id %1 and IPv6 address %2

This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified IPv6 address, and it is starting to search for this host in alternate host data sources.

**HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_ADDRESS6 (1)** trying alternate sources for host using subnet id %1 and IPv6 address %2

This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified IPv6 address, and it is starting to search for this host in alternate host data sources.

**HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER** get one host with IPv6 reservation for subnet id %1, identifier %2

This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

**HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER (1)** get one host with IPv6 reservation for subnet id %1, identifier %2

This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

**HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_HOST** using subnet id %1 and identifier %2, found in %3

This debug message includes the details of a host returned by an alternate host data source using a subnet id and specific host identifier.

---

**HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_HOST (1) using subnet id %1 and identifier %2, found in %2**

This debug message includes the details of a host returned by an alternate host data source using a subnet id and specific host identifier.

**HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_NULL host not found using subnet id %1 and identifier %2**

This debug message is issued when no host was found using the specified subnet id and host identifier.

**HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_NULL (1) host not found using subnet id %1 and identifier %2**

This debug message is issued when no host was found using the specified subnet id and host identifier.

## HTTP Module

**HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED bad request received from %1: %2**

This debug message is issued when an HTTP client sends malformed request to the server. This includes HTTP requests using unexpected content types, including malformed JSON etc. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a detailed error message.

**HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED (1) bad request received from %1: %2**

This debug message is issued when an HTTP client sends malformed request to the server. This includes HTTP requests using unexpected content types, including malformed JSON etc. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a detailed error message.

**HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED\_DETAILS detailed information about bad request received from %1:\n%2**

This debug message is issued when an HTTP client sends malformed request to the server. It includes detailed information about the received request rejected by the server. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a request in the textual format. The request is truncated by the logger if it is too large to be printed.

**HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED\_DETAILS (1) detailed information about bad request received from %1:\n%2**

This debug message is issued when an HTTP client sends malformed request to the server. It includes detailed information about the received request rejected by the server. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a request in the textual format. The request is truncated by the logger if it is too large to be printed.

**HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED bad response received when communicating with %1: %2**

This debug message is issued when an HTTP client fails to receive a response from the server or when this response is malformed. The first argument specifies the server URL. The second argument provides a detailed error message.

**HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED (1) bad response received when communicating with %1: %2**

This debug message is issued when an HTTP client fails to receive a response from the server or when this response is malformed. The first argument specifies the server URL. The second argument provides a detailed error message.

**HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED\_DETAILS detailed information about bad response received from %1:\n%2**

This debug message is issued when an HTTP client receives malformed response from the server. The first argument specifies an URL of the server. The second argument provides a response in the textual format. The request is truncated by the logger if it is too large to be printed.

**HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED\_DETAILS (1) detailed information about bad response received from %1:\n%2**

This debug message is issued when an HTTP client receives malformed response from the server. The first argument specifies an URL of the server. The second argument provides a response in the textual format. The request is truncated by the logger if it is too large to be printed.

---

**HTTP\_CLIENT\_REQUEST\_RECEIVED received HTTP request from %1**

This debug message is issued when the server finished receiving a HTTP request from the remote endpoint. The address of the remote endpoint is specified as an argument.

**HTTP\_CLIENT\_REQUEST\_RECEIVED (1) received HTTP request from %1**

This debug message is issued when the server finished receiving a HTTP request from the remote endpoint. The address of the remote endpoint is specified as an argument.

**HTTP\_CLIENT\_REQUEST\_RECEIVED\_DETAILS detailed information about well formed request received from %1:\n%2**

This debug message is issued when the HTTP server receives a well formed request. It includes detailed information about the received request. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides the request in the textual format. The request is truncated by the logger if it is too large to be printed.

**HTTP\_CLIENT\_REQUEST\_RECEIVED\_DETAILS (1) detailed information about well formed request received from %1:\n%2**

This debug message is issued when the HTTP server receives a well formed request. It includes detailed information about the received request. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides the request in the textual format. The request is truncated by the logger if it is too large to be printed.

**HTTP\_CLIENT\_REQUEST\_SEND sending HTTP request %1 to %2**

This debug message is issued when the client is starting to send a HTTP request to a server. The first argument holds basic information about the request (HTTP version number and status code). The second argument specifies a URL of the server.

**HTTP\_CLIENT\_REQUEST\_SEND (1) sending HTTP request %1 to %2**

This debug message is issued when the client is starting to send a HTTP request to a server. The first argument holds basic information about the request (HTTP version number and status code). The second argument specifies a URL of the server.

**HTTP\_CLIENT\_REQUEST\_SEND\_DETAILS detailed information about request sent to %1:\n%2**

This debug message is issued right before the client sends an HTTP request to the server. It includes detailed information about the request. The first argument specifies an URL of the server to which the request is being sent. The second argument provides the request in the textual form. The request is truncated by the logger if it is too large to be printed.

**HTTP\_CLIENT\_REQUEST\_SEND\_DETAILS (1) detailed information about request sent to %1:\n%2**

This debug message is issued right before the client sends an HTTP request to the server. It includes detailed information about the request. The first argument specifies an URL of the server to which the request is being sent. The second argument provides the request in the textual form. The request is truncated by the logger if it is too large to be printed.

**HTTP\_CLIENT\_REQUEST\_TIMEOUT\_OCCURRED HTTP request timeout occurred when communicating with %1**

This debug message is issued when the HTTP request timeout has occurred and the server is going to send a response with Http Request timeout status code.

**HTTP\_CLIENT\_REQUEST\_TIMEOUT\_OCCURRED (1) HTTP request timeout occurred when communicating with %1**

This debug message is issued when the HTTP request timeout has occurred and the server is going to send a response with Http Request timeout status code.

**HTTP\_CONNECTION\_STOP stopping HTTP connection from %1**

This debug message is issued when one of the HTTP connections is stopped. The connection can be stopped as a result of an error or after the successful message exchange with a client.

**HTTP\_CONNECTION\_STOP (1) stopping HTTP connection from %1**

This debug message is issued when one of the HTTP connections is stopped. The connection can be stopped as a result of an error or after the successful message exchange with a client.

**HTTP\_CONNECTION\_STOP\_FAILED stopping HTTP connection failed**

This error message is issued when an error occurred during closing a HTTP connection with a client.

---

**HTTP\_CONNECTION\_STOP\_FAILED (1) stopping HTTP connection failed**

This error message is issued when an error occurred during closing a HTTP connection with a client.

**HTTP\_DATA\_RECEIVED received %1 bytes from %2**

This debug message is issued when the server receives a chunk of data from the remote endpoint. This may include the whole request or only a part of the request. The first argument specifies the amount of received data. The second argument specifies an address of the remote endpoint which produced the data.

**HTTP\_DATA\_RECEIVED (1) received %1 bytes from %2**

This debug message is issued when the server receives a chunk of data from the remote endpoint. This may include the whole request or only a part of the request. The first argument specifies the amount of received data. The second argument specifies an address of the remote endpoint which produced the data.

**HTTP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED closing persistent connection with %1 as a result of a timeout**

This debug message is issued when the persistent HTTP connection is being closed as a result of being idle.

**HTTP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED (1) closing persistent connection with %1 as a result of a timeout**

This debug message is issued when the persistent HTTP connection is being closed as a result of being idle.

**HTTP\_REQUEST\_RECEIVE\_START start receiving request from %1 with timeout %2**

This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

**HTTP\_REQUEST\_RECEIVE\_START (1) start receiving request from %1 with timeout %2**

This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

**HTTP\_SERVER\_RESPONSE\_RECEIVED received HTTP response from %1**

This debug message is issued when the client finished receiving an HTTP response from the server. The URL of the server is specified as an argument.

**HTTP\_SERVER\_RESPONSE\_RECEIVED (1) received HTTP response from %1**

This debug message is issued when the client finished receiving an HTTP response from the server. The URL of the server is specified as an argument.

**HTTP\_SERVER\_RESPONSE\_RECEIVED\_DETAILS detailed information about well formed response received from %1:\n%**

This debug message is issued when the HTTP client receives a well formed response from the server. It includes detailed information about the received response. The first argument specifies a URL of the server which sent the response. The second argument provides the response in the textual format. The response is truncated by the logger if it is too large to be printed.

**HTTP\_SERVER\_RESPONSE\_RECEIVED\_DETAILS (1) detailed information about well formed response received from %1:**

This debug message is issued when the HTTP client receives a well formed response from the server. It includes detailed information about the received response. The first argument specifies a URL of the server which sent the response. The second argument provides the response in the textual format. The response is truncated by the logger if it is too large to be printed.

**HTTP\_SERVER\_RESPONSE\_SEND sending HTTP response %1 to %2**

This debug message is issued when the server is starting to send a HTTP response to a remote endpoint. The first argument holds basic information about the response (HTTP version number and status code). The second argument specifies an address of the remote endpoint.

**HTTP\_SERVER\_RESPONSE\_SEND (1) sending HTTP response %1 to %2**

This debug message is issued when the server is starting to send a HTTP response to a remote endpoint. The first argument holds basic information about the response (HTTP version number and status code). The second argument specifies an address of the remote endpoint.

---

**HTTP\_SERVER\_RESPONSE\_SEND\_DETAILS detailed information about response sent to %1:\n%2**

This debug message is issued right before the server sends a HTTP response to the client. It includes detailed information about the response. The first argument specifies an address of the remote endpoint to which the response is being sent. The second argument provides a response in the textual form. The response is truncated by the logger if it is too large to be printed.

**HTTP\_SERVER\_RESPONSE\_SEND\_DETAILS (1) detailed information about response sent to %1:\n%2**

This debug message is issued right before the server sends a HTTP response to the client. It includes detailed information about the response. The first argument specifies an address of the remote endpoint to which the response is being sent. The second argument provides a response in the textual form. The response is truncated by the logger if it is too large to be printed.

## LEASE Module

**LEASE\_CMDS\_ADD4 lease4-add command successful (parameters: %1)**

The lease4-add command has been successful. Parameters of the host added are logged.

**LEASE\_CMDS\_ADD4 (1) lease4-add command successful (parameters: %1)**

The lease4-add command has been successful. Parameters of the host added are logged.

**LEASE\_CMDS\_ADD4\_FAILED lease4-add command failed (parameters: %1, reason: %2)**

The lease4-add command has failed. Both the reason as well as the parameters passed are logged.

**LEASE\_CMDS\_ADD4\_FAILED (1) lease4-add command failed (parameters: %1, reason: %2)**

The lease4-add command has failed. Both the reason as well as the parameters passed are logged.

**LEASE\_CMDS\_ADD6 lease6-add command successful (parameters: %1)**

The lease6-add command has been successful. Parameters of the host added are logged.

**LEASE\_CMDS\_ADD6 (1) lease6-add command successful (parameters: %1)**

The lease6-add command has been successful. Parameters of the host added are logged.

**LEASE\_CMDS\_ADD6\_FAILED Lease6-add command failed (parameters: %1, reason: %2)**

The lease6-add command has failed. Both the reason as well as the parameters passed are logged.

**LEASE\_CMDS\_ADD6\_FAILED (1) Lease6-add command failed (parameters: %1, reason: %2)**

The lease6-add command has failed. Both the reason as well as the parameters passed are logged.

**LEASE\_CMDS\_DEINIT\_FAILED unloading Lease Commands hooks library failed: %1**

This error message indicates an error during unloading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

**LEASE\_CMDS\_DEINIT\_FAILED (1) unloading Lease Commands hooks library failed: %1**

This error message indicates an error during unloading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

**LEASE\_CMDS\_DEINIT\_OK unloading Lease Commands hooks library successful**

This info message indicates that the Lease Commands hooks library has been removed successfully.

**LEASE\_CMDS\_DEINIT\_OK (1) unloading Lease Commands hooks library successful**

This info message indicates that the Lease Commands hooks library has been removed successfully.

**LEASE\_CMDS\_DEL4 lease4-del command successful (parameters: %1)**

The attempt to delete an IPv4 lease (lease4-del command) has been successful. Parameters of the host removed are logged.

**LEASE\_CMDS\_DEL4 (1) lease4-del command successful (parameters: %1)**

The attempt to delete an IPv4 lease (lease4-del command) has been successful. Parameters of the host removed are logged.

**LEASE\_CMDS\_DEL4\_FAILED lease4-del command failed (parameters: %1, reason: %2)**

The attempt to delete an IPv4 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.



**LEASE\_CMDS\_DEL4\_FAILED (1) lease4-del command failed (parameters: %1, reason: %2)**

The attempt to delete an IPv4 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

**LEASE\_CMDS\_DEL6 lease4-del command successful (parameters: %1)**

The attempt to delete an IPv4 lease (lease4-del command) has been successful. Parameters of the host removed are logged.

**LEASE\_CMDS\_DEL6 (1) lease4-del command successful (parameters: %1)**

The attempt to delete an IPv4 lease (lease4-del command) has been successful. Parameters of the host removed are logged.

**LEASE\_CMDS\_DEL6\_FAILED lease6-del command failed (parameters: %1, reason: %2)**

The attempt to delete an IPv6 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

**LEASE\_CMDS\_DEL6\_FAILED (1) lease6-del command failed (parameters: %1, reason: %2)**

The attempt to delete an IPv6 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

**LEASE\_CMDS\_INIT\_FAILED loading Lease Commands hooks library failed: %1**

This error message indicates an error during loading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

**LEASE\_CMDS\_INIT\_FAILED (1) loading Lease Commands hooks library failed: %1**

This error message indicates an error during loading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

**LEASE\_CMDS\_INIT\_OK loading Lease Commands hooks library successful**

This info message indicates that the Lease Commands hooks library has been loaded successfully. Enjoy!

**LEASE\_CMDS\_INIT\_OK (1) loading Lease Commands hooks library successful**

This info message indicates that the Lease Commands hooks library has been loaded successfully. Enjoy!

## LFC Module

**LFC\_FAIL\_PID\_CREATE : %1**

This message is issued if LFC detected a failure when trying to create the PID file. It includes a more specific error string.

**LFC\_FAIL\_PID\_CREATE (1) : %1**

This message is issued if LFC detected a failure when trying to create the PID file. It includes a more specific error string.

**LFC\_FAIL\_PID\_DEL : %1**

This message is issued if LFC detected a failure when trying to delete the PID file. It includes a more specific error string.

**LFC\_FAIL\_PID\_DEL (1) : %1**

This message is issued if LFC detected a failure when trying to delete the PID file. It includes a more specific error string.

**LFC\_FAIL\_PROCESS : %1**

This message is issued if LFC detected a failure when trying to process the files. It includes a more specific error string.

**LFC\_FAIL\_PROCESS (1) : %1**

This message is issued if LFC detected a failure when trying to process the files. It includes a more specific error string.

**LFC\_FAIL\_ROTATE : %1**

This message is issued if LFC detected a failure when trying to rotate the files. It includes a more specific error string.

**LFC\_FAIL\_ROTATE (1) : %1**

This message is issued if LFC detected a failure when trying to rotate the files. It includes a more specific error string.

**LFC\_PROCESSING Previous file: %1, copy file: %2**

This message is issued just before LFC starts processing the lease files.

---

**LFC\_PROCESSING (1) Previous file: %1, copy file: %2**

This message is issued just before LFC starts processing the lease files.

**LFC\_READ\_STATS Leases: %1, attempts: %2, errors: %3.**

This message prints out the number of leases that were read, the number of attempts to read leases and the number of errors encountered while reading.

**LFC\_READ\_STATS (1) Leases: %1, attempts: %2, errors: %3.**

This message prints out the number of leases that were read, the number of attempts to read leases and the number of errors encountered while reading.

**LFC\_ROTATING LFC rotating files**

This message is issued just before LFC starts rotating the lease files - removing the old and replacing them with the new.

**LFC\_ROTATING (1) LFC rotating files**

This message is issued just before LFC starts rotating the lease files - removing the old and replacing them with the new.

**LFC\_RUNNING LFC instance already running**

This message is issued if LFC detects that a previous copy of LFC may still be running via the PID check.

**LFC\_RUNNING (1) LFC instance already running**

This message is issued if LFC detects that a previous copy of LFC may still be running via the PID check.

**LFC\_START Starting lease file cleanup**

This message is issued as the LFC process starts.

**LFC\_START (1) Starting lease file cleanup**

This message is issued as the LFC process starts.

**LFC\_TERMINATE LFC finished processing**

This message is issued when the LFC process completes. It does not indicate that the process was successful only that it has finished.

**LFC\_TERMINATE (1) LFC finished processing**

This message is issued when the LFC process completes. It does not indicate that the process was successful only that it has finished.

**LFC\_WRITE\_STATS Leases: %1, attempts: %2, errors: %3.**

This message prints out the number of leases that were written, the number of attempts to write leases and the number of errors encountered while writing.

**LFC\_WRITE\_STATS (1) Leases: %1, attempts: %2, errors: %3.**

This message prints out the number of leases that were written, the number of attempts to write leases and the number of errors encountered while writing.

## LOGIMPL Module

**LOGIMPL\_ABOVE\_MAX\_DEBUG debug level of %1 is too high and will be set to the maximum of %2**

A message from the interface to the underlying logger implementation reporting that the debug level (as set by an internally-created string DEBUGn, where n is an integer, e.g. DEBUG22) is above the maximum allowed value and has been reduced to that value. The appearance of this message may indicate a programming error - please submit a bug report.

**LOGIMPL\_ABOVE\_MAX\_DEBUG (1) debug level of %1 is too high and will be set to the maximum of %2**

A message from the interface to the underlying logger implementation reporting that the debug level (as set by an internally-created string DEBUGn, where n is an integer, e.g. DEBUG22) is above the maximum allowed value and has been reduced to that value. The appearance of this message may indicate a programming error - please submit a bug report.

**LOGIMPL\_BAD\_DEBUG\_STRING debug string '%1' has invalid format**

A message from the interface to the underlying logger implementation reporting that an internally-created string used to set the debug level is not of the correct format (it should be of the form DEBUGn, where n is an integer, e.g. DEBUG22). The appearance of this message indicates a programming error - please submit a bug report.

---

**LOGIMPL\_BAD\_DEBUG\_STRING (1) debug string '%1' has invalid format**

A message from the interface to the underlying logger implementation reporting that an internally-created string used to set the debug level is not of the correct format (it should be of the form DEBUGn, where n is an integer, e.g. DEBUG22). The appearance of this message indicates a programming error - please submit a bug report.

**LOGIMPL\_BELOW\_MIN\_DEBUG debug level of %1 is too low and will be set to the minimum of %2**

A message from the interface to the underlying logger implementation reporting that the debug level (as set by an internally-created string DEBUGn, where n is an integer, e.g. DEBUG22) is below the minimum allowed value and has been increased to that value. The appearance of this message may indicate a programming error - please submit a bug report.

**LOGIMPL\_BELOW\_MIN\_DEBUG (1) debug level of %1 is too low and will be set to the minimum of %2**

A message from the interface to the underlying logger implementation reporting that the debug level (as set by an internally-created string DEBUGn, where n is an integer, e.g. DEBUG22) is below the minimum allowed value and has been increased to that value. The appearance of this message may indicate a programming error - please submit a bug report.

## LOG Module

**LOG\_BAD\_DESTINATION unrecognized log destination: %1**

A logger destination value was given that was not recognized. The destination should be one of "console", "file", or "syslog".

**LOG\_BAD\_DESTINATION (1) unrecognized log destination: %1**

A logger destination value was given that was not recognized. The destination should be one of "console", "file", or "syslog".

**LOG\_BAD\_SEVERITY unrecognized log severity: %1**

A logger severity value was given that was not recognized. The severity should be one of "DEBUG", "INFO", "WARN", "ERROR", "FATAL" or "NONE".

**LOG\_BAD\_SEVERITY (1) unrecognized log severity: %1**

A logger severity value was given that was not recognized. The severity should be one of "DEBUG", "INFO", "WARN", "ERROR", "FATAL" or "NONE".

**LOG\_BAD\_STREAM bad log console output stream: %1**

Logging has been configured so that output is written to the terminal (console) but the stream on which it is to be written is not recognized. Allowed values are "stdout" and "stderr".

**LOG\_BAD\_STREAM (1) bad log console output stream: %1**

Logging has been configured so that output is written to the terminal (console) but the stream on which it is to be written is not recognized. Allowed values are "stdout" and "stderr".

**LOG\_DUPLICATE\_MESSAGE\_ID duplicate message ID (%1) in compiled code**

During start-up, Kea detected that the given message identification had been defined multiple times in the Kea code. This indicates a programming error; please submit a bug report.

**LOG\_DUPLICATE\_MESSAGE\_ID (1) duplicate message ID (%1) in compiled code**

During start-up, Kea detected that the given message identification had been defined multiple times in the Kea code. This indicates a programming error; please submit a bug report.

**LOG\_DUPLICATE\_NAMESPACE line %1: duplicate \$NAMESPACE directive found**

When reading a message file, more than one \$NAMESPACE directive was found. (This directive is used to set a C++ namespace when generating header files during software development.) Such a condition is regarded as an error and the read will be abandoned.

**LOG\_DUPLICATE\_NAMESPACE (1) line %1: duplicate \$NAMESPACE directive found**

When reading a message file, more than one \$NAMESPACE directive was found. (This directive is used to set a C++ namespace when generating header files during software development.) Such a condition is regarded as an error and the read will be abandoned.

---

**LOG\_INPUT\_OPEN\_FAIL unable to open message file %1 for input: %2**

The program was not able to open the specified input message file for the reason given.

**LOG\_INPUT\_OPEN\_FAIL (1) unable to open message file %1 for input: %2**

The program was not able to open the specified input message file for the reason given.

**LOG\_INVALID\_MESSAGE\_ID line %1: invalid message identification '%2'**

An invalid message identification (ID) has been found during the read of a message file. Message IDs should comprise only alphanumeric characters and the underscore, and should not start with a digit.

**LOG\_INVALID\_MESSAGE\_ID (1) line %1: invalid message identification '%2'**

An invalid message identification (ID) has been found during the read of a message file. Message IDs should comprise only alphanumeric characters and the underscore, and should not start with a digit.

**LOG\_LOCK\_TEST\_MESSAGE this is a test message.**

This is a log message used in testing.

**LOG\_LOCK\_TEST\_MESSAGE (1) this is a test message.**

This is a log message used in testing.

**LOG\_NAMESPACE\_EXTRA\_ARGS line %1: \$NAMESPACE directive has too many arguments**

The \$NAMESPACE directive in a message file takes a single argument, a namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a \$NAMESPACE directive with more than one argument.

**LOG\_NAMESPACE\_EXTRA\_ARGS (1) line %1: \$NAMESPACE directive has too many arguments**

The \$NAMESPACE directive in a message file takes a single argument, a namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a \$NAMESPACE directive with more than one argument.

**LOG\_NAMESPACE\_INVALID\_ARG line %1: \$NAMESPACE directive has an invalid argument ('%2')**

The \$NAMESPACE argument in a message file should be a valid C++ namespace. This message is output if the simple check on the syntax of the string carried out by the reader fails.

**LOG\_NAMESPACE\_INVALID\_ARG (1) line %1: \$NAMESPACE directive has an invalid argument ('%2')**

The \$NAMESPACE argument in a message file should be a valid C++ namespace. This message is output if the simple check on the syntax of the string carried out by the reader fails.

**LOG\_NAMESPACE\_NO\_ARGS line %1: no arguments were given to the \$NAMESPACE directive**

The \$NAMESPACE directive in a message file takes a single argument, a C++ namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a \$NAMESPACE directive with no arguments.

**LOG\_NAMESPACE\_NO\_ARGS (1) line %1: no arguments were given to the \$NAMESPACE directive**

The \$NAMESPACE directive in a message file takes a single argument, a C++ namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a \$NAMESPACE directive with no arguments.

**LOG\_NO\_MESSAGE\_ID line %1: message definition line found without a message ID**

Within a message file, message are defined by lines starting with a "%". The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the "%" and nothing else.

**LOG\_NO\_MESSAGE\_ID (1) line %1: message definition line found without a message ID**

Within a message file, message are defined by lines starting with a "%". The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the "%" and nothing else.

**LOG\_NO\_MESSAGE\_TEXT line %1: line found containing a message ID ('%2') and no text**

Within a message file, message are defined by lines starting with a "%". The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the "%" and message identification, but no text.

**LOG\_NO\_MESSAGE\_TEXT (1) line %1: line found containing a message ID ('%2') and no text**

Within a message file, message are defined by lines starting with a "%". The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the "%" and message identification, but no text.

---

**LOG\_NO\_SUCH\_MESSAGE could not replace message text for '%1': no such message**

During start-up a local message file was read. A line with the listed message identification was found in the file, but the identification is not one contained in the compiled-in message dictionary. This message may appear a number of times in the file, once for every such unknown message identification.

There may be several reasons why this message may appear:

- The message ID has been mis-spelled in the local message file.
- The program outputting the message may not use that particular message (e.g. it originates in a module not used by the program).
- The local file was written for an earlier version of the Kea software and the later version no longer generates that message.

Whatever the reason, there is no impact on the operation of Kea.

**LOG\_NO\_SUCH\_MESSAGE (1) could not replace message text for '%1': no such message**

During start-up a local message file was read. A line with the listed message identification was found in the file, but the identification is not one contained in the compiled-in message dictionary. This message may appear a number of times in the file, once for every such unknown message identification.

There may be several reasons why this message may appear:

- The message ID has been mis-spelled in the local message file.
- The program outputting the message may not use that particular message (e.g. it originates in a module not used by the program).
- The local file was written for an earlier version of the Kea software and the later version no longer generates that message.

Whatever the reason, there is no impact on the operation of Kea.

**LOG\_OPEN\_OUTPUT\_FAIL unable to open %1 for output: %2**

Originating within the logging code, the program was not able to open the specified output file for the reason given.

**LOG\_OPEN\_OUTPUT\_FAIL (1) unable to open %1 for output: %2**

Originating within the logging code, the program was not able to open the specified output file for the reason given.

**LOG\_PREFIX\_EXTRA\_ARGS line %1: \$PREFIX directive has too many arguments**

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. This error is generated when the compiler finds a \$PREFIX directive with more than one argument.

Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

**LOG\_PREFIX\_EXTRA\_ARGS (1) line %1: \$PREFIX directive has too many arguments**

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. This error is generated when the compiler finds a \$PREFIX directive with more than one argument.

Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

**LOG\_PREFIX\_INVALID\_ARG line %1: \$PREFIX directive has an invalid argument ('%2')**

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. As such, it must adhere to restrictions on C++ symbol names (e.g. may only contain alphanumeric characters or underscores, and may not start with a digit). A \$PREFIX directive was found with an argument (given in the message) that violates those restrictions.

Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

**LOG\_PREFIX\_INVALID\_ARG (1) line %1: \$PREFIX directive has an invalid argument ('%2')**

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. As such, it must adhere to restrictions on C++ symbol names (e.g. may only contain alphanumeric characters or underscores, and may not start with a digit). A \$PREFIX directive was found with an argument (given in the message) that violates those restrictions.

Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

**LOG\_READING\_LOCAL\_FILE reading local message file %1**

This is an informational message output by Kea when it starts to read a local message file. (A local message file may replace the text of one or more messages; the ID of the message will not be changed though.)

**LOG\_READING\_LOCAL\_FILE (1) reading local message file %1**

This is an informational message output by Kea when it starts to read a local message file. (A local message file may replace the text of one or more messages; the ID of the message will not be changed though.)

**LOG\_READ\_ERROR error reading from message file %1: %2**

The specified error was encountered reading from the named message file.

**LOG\_READ\_ERROR (1) error reading from message file %1: %2**

The specified error was encountered reading from the named message file.

**LOG\_UNRECOGNIZED\_DIRECTIVE line %1: unrecognized directive '%2'**

Within a message file, a line starting with a dollar symbol was found (indicating the presence of a directive) but the first word on the line (shown in the message) was not recognized.

**LOG\_UNRECOGNIZED\_DIRECTIVE (1) line %1: unrecognized directive '%2'**

Within a message file, a line starting with a dollar symbol was found (indicating the presence of a directive) but the first word on the line (shown in the message) was not recognized.

**LOG\_WRITE\_ERROR error writing to %1: %2**

The specified error was encountered by the message compiler when writing to the named output file.

**LOG\_WRITE\_ERROR (1) error writing to %1: %2**

The specified error was encountered by the message compiler when writing to the named output file.

## NETCONF Module

**NETCONF\_BOOT\_UPDATE\_COMPLETED Boot-update configuration completed for server %1**

This informational message is issued when the initial configuration was retrieved from Netconf and successfully applied to Kea server.

**NETCONF\_BOOT\_UPDATE\_COMPLETED (1) Boot-update configuration completed for server %1**

This informational message is issued when the initial configuration was retrieved from Netconf and successfully applied to Kea server.

**NETCONF\_CONFIG\_CHANGED\_DETAIL YANG configuration changed: %1**

This debug message indicates a YANG configuration change. The format is the change operation (created, modified, deleted or moved) followed by xpaths and values of old and new nodes.

**NETCONF\_CONFIG\_CHANGED\_DETAIL (1) YANG configuration changed: %1**

This debug message indicates a YANG configuration change. The format is the change operation (created, modified, deleted or moved) followed by xpaths and values of old and new nodes.

**NETCONF\_CONFIG\_CHANGE\_EVENT Received YANG configuration change %1 event**

This informational message is issued when Netconf receives a YANG configuration change event. The type of event is printed.

**NETCONF\_CONFIG\_CHANGE\_EVENT (1) Received YANG configuration change %1 event**

This informational message is issued when Netconf receives a YANG configuration change event. The type of event is printed.

**NETCONF\_CONFIG\_CHECK\_FAIL Netconf configuration check failed: %1**

This error message indicates that Netconf had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**NETCONF\_CONFIG\_CHECK\_FAIL (1) Netconf configuration check failed: %1**

This error message indicates that Netconf had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

---

**NETCONF\_CONFIG\_FAIL Netconf configuration failed: %1**

This error message indicates that Netconf had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**NETCONF\_CONFIG\_FAIL (1) Netconf configuration failed: %1**

This error message indicates that Netconf had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

**NETCONF\_FAILED application experienced a fatal error: %1**

This is a fatal error message issued when the Netconf application got an unrecoverable error from within the event loop.

**NETCONF\_FAILED (1) application experienced a fatal error: %1**

This is a fatal error message issued when the Netconf application got an unrecoverable error from within the event loop.

**NETCONF\_GET\_CONFIG got configuration from %1 server: %2**

This debug message indicates that Netconf got the configuration from a Kea server. The server name and the retrieved configuration are printed.

**NETCONF\_GET\_CONFIG (1) got configuration from %1 server: %2**

This debug message indicates that Netconf got the configuration from a Kea server. The server name and the retrieved configuration are printed.

**NETCONF\_GET\_CONFIG\_FAILED getting configuration from %1 server failed: %2**

The error message indicates that Netconf got an error getting the configuration from a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

**NETCONF\_GET\_CONFIG\_FAILED (1) getting configuration from %1 server failed: %2**

The error message indicates that Netconf got an error getting the configuration from a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

**NETCONF\_GET\_CONFIG\_STARTED getting configuration from %1 server**

This informational message indicates that Netconf is trying to get the configuration from a Kea server.

**NETCONF\_GET\_CONFIG\_STARTED (1) getting configuration from %1 server**

This informational message indicates that Netconf is trying to get the configuration from a Kea server.

**NETCONF\_LOG\_CHANGE\_FAIL Netconf configuration change logging failed: %1**

The warning message indicates that the configuration change logging encountered an unexpected condition. Details of it will be logged.

**NETCONF\_LOG\_CHANGE\_FAIL (1) Netconf configuration change logging failed: %1**

The warning message indicates that the configuration change logging encountered an unexpected condition. Details of it will be logged.

**NETCONF\_RUN\_EXIT application is exiting the event loop**

This is a debug message issued when the Netconf application exits its event loop. This is a normal step during kea-netconf shutdown.

**NETCONF\_RUN\_EXIT (1) application is exiting the event loop**

This is a debug message issued when the Netconf application exits its event loop. This is a normal step during kea-netconf shutdown.

**NETCONF\_SET\_CONFIG set configuration to %1 server: %2**

This debug message indicates that Netconf set the configuration to a Kea server. The server name and the applied configuration are printed.

**NETCONF\_SET\_CONFIG (1) set configuration to %1 server: %2**

This debug message indicates that Netconf set the configuration to a Kea server. The server name and the applied configuration are printed.

---

**NETCONF\_SET\_CONFIG\_FAILED setting configuration to %1 server failed: %2**

The error message indicates that Netconf got an error setting the configuration to a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

**NETCONF\_SET\_CONFIG\_FAILED (1) setting configuration to %1 server failed: %2**

The error message indicates that Netconf got an error setting the configuration to a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

**NETCONF\_SET\_CONFIG\_STARTED setting configuration to %1 server**

This informational message indicates that Netconf is trying to set the configuration to a Kea server.

**NETCONF\_SET\_CONFIG\_STARTED (1) setting configuration to %1 server**

This informational message indicates that Netconf is trying to set the configuration to a Kea server.

**NETCONF\_STARTED Netconf (version %1) started**

This informational message indicates that Netconf has processed all configuration information and is ready to begin processing. The version is also printed.

**NETCONF\_STARTED (1) Netconf (version %1) started**

This informational message indicates that Netconf has processed all configuration information and is ready to begin processing. The version is also printed.

**NETCONF\_SUBSCRIBE\_CONFIG subscribing configuration changes for %1 server with %2 module**

This information message indicates that Netconf is trying to subscribe configuration changes for a Kea server. The names of the server and the module are printed.

**NETCONF\_SUBSCRIBE\_CONFIG (1) subscribing configuration changes for %1 server with %2 module**

This information message indicates that Netconf is trying to subscribe configuration changes for a Kea server. The names of the server and the module are printed.

**NETCONF\_SUBSCRIBE\_CONFIG\_FAILED subscribe configuration changes for %1 server with %2 module failed: %3**

The error message indicates that Netconf got an error subscribing configuration changes for a Kea server. The names of the server and the module, and the error are printed.

**NETCONF\_SUBSCRIBE\_CONFIG\_FAILED (1) subscribe configuration changes for %1 server with %2 module failed: %3**

The error message indicates that Netconf got an error subscribing configuration changes for a Kea server. The names of the server and the module, and the error are printed.

**NETCONF\_UPDATE\_CONFIG updating configuration with %1 server: %2**

This debug message indicates that Netconf update the configuration of a Kea server. The server name and the updated configuration are printed.

**NETCONF\_UPDATE\_CONFIG (1) updating configuration with %1 server: %2**

This debug message indicates that Netconf update the configuration of a Kea server. The server name and the updated configuration are printed.

**NETCONF\_UPDATE\_CONFIG\_COMPLETED completed updating configuration for %1 server**

This informational message indicates that Netconf updated with success the configuration of a Kea server.

**NETCONF\_UPDATE\_CONFIG\_COMPLETED (1) completed updating configuration for %1 server**

This informational message indicates that Netconf updated with success the configuration of a Kea server.

**NETCONF\_UPDATE\_CONFIG\_FAILED updating configuration with %1 server: %2**

The error message indicates that Netconf got an error updating the configuration of a Kea server. This includes a configuration rejected by a Kea server when it tried to apply it. The name of the server and the error are printed.

**NETCONF\_UPDATE\_CONFIG\_FAILED (1) updating configuration with %1 server: %2**

The error message indicates that Netconf got an error updating the configuration of a Kea server. This includes a configuration rejected by a Kea server when it tried to apply it. The name of the server and the error are printed.

---



**NETCONF\_UPDATE\_CONFIG\_STARTED started updating configuration for %1 server**

This informational message indicates that Netconf is trying to update the configuration of a Kea server.

**NETCONF\_UPDATE\_CONFIG\_STARTED (1) started updating configuration for %1 server**

This informational message indicates that Netconf is trying to update the configuration of a Kea server.

**NETCONF\_VALIDATE\_CONFIG validating configuration with %1 server: %2**

This debug message indicates that Netconf is validating the configuration with a Kea server. The server name and the validated configuration are printed.

**NETCONF\_VALIDATE\_CONFIG (1) validating configuration with %1 server: %2**

This debug message indicates that Netconf is validating the configuration with a Kea server. The server name and the validated configuration are printed.

**NETCONF\_VALIDATE\_CONFIG\_COMPLETED completed validating configuration for %1 server**

This informational message indicates that Netconf validated with success the configuration with a Kea server.

**NETCONF\_VALIDATE\_CONFIG\_COMPLETED (1) completed validating configuration for %1 server**

This informational message indicates that Netconf validated with success the configuration with a Kea server.

**NETCONF\_VALIDATE\_CONFIG\_FAILED validating configuration with %1 server got an error: %2**

The error message indicates that Netconf got an error validating the configuration with a Kea server. This message is produced when exception is thrown during an attempt to validate received configuration. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

**NETCONF\_VALIDATE\_CONFIG\_FAILED (1) validating configuration with %1 server got an error: %2**

The error message indicates that Netconf got an error validating the configuration with a Kea server. This message is produced when exception is thrown during an attempt to validate received configuration. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

**NETCONF\_VALIDATE\_CONFIG\_REJECTED validating configuration with %1 server was rejected: %2**

The warning message indicates that Netconf got an error validating the configuration with a Kea server. This message is printed when the configuration was rejected during normal processing. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

**NETCONF\_VALIDATE\_CONFIG\_REJECTED (1) validating configuration with %1 server was rejected: %2**

The warning message indicates that Netconf got an error validating the configuration with a Kea server. This message is printed when the configuration was rejected during normal processing. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

**NETCONF\_VALIDATE\_CONFIG\_STARTED started validating configuration for %1 server**

This informational message indicates that Netconf is trying to validate the configuration with a Kea server.

**NETCONF\_VALIDATE\_CONFIG\_STARTED (1) started validating configuration for %1 server**

This informational message indicates that Netconf is trying to validate the configuration with a Kea server.

## STAT Module

**STAT\_CMDS\_DEINIT\_FAILED unloading Stat Commands hooks library failed: %1**

This error message indicates an error during unloading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

**STAT\_CMDS\_DEINIT\_FAILED (1) unloading Stat Commands hooks library failed: %1**

This error message indicates an error during unloading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

**STAT\_CMDS\_DEINIT\_OK unloading Stat Commands hooks library successful**

This info message indicates that the Stat Commands hooks library has been removed successfully.

---

**STAT\_CMDS\_DEINIT\_OK (1) unloading Stat Commands hooks library successful**

This info message indicates that the Stat Commands hooks library has been removed successfully.

**STAT\_CMDS\_INIT\_FAILED loading Stat Commands hooks library failed: %1**

This error message indicates an error during loading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

**STAT\_CMDS\_INIT\_FAILED (1) loading Stat Commands hooks library failed: %1**

This error message indicates an error during loading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

**STAT\_CMDS\_INIT\_OK loading Stat Commands hooks library successful**

This info message indicates that the Stat Commands hooks library has been loaded successfully. Enjoy!

**STAT\_CMDS\_INIT\_OK (1) loading Stat Commands hooks library successful**

This info message indicates that the Stat Commands hooks library has been loaded successfully. Enjoy!

**STAT\_CMDS\_LEASE4\_GET stat-lease4-get command successful, parameters: %1 rows found: %2**

The stat-lease4-get command has been successful. The log will contain the parameters supplied and the number of rows found.

**STAT\_CMDS\_LEASE4\_GET (1) stat-lease4-get command successful, parameters: %1 rows found: %2**

The stat-lease4-get command has been successful. The log will contain the parameters supplied and the number of rows found.

**STAT\_CMDS\_LEASE4\_GET\_FAILED stat-lease4-get command failed: parameters: %1, reason: %2**

The stat-lease4-get command has failed. Both the parameters supplied and the reason for failure are logged.

**STAT\_CMDS\_LEASE4\_GET\_FAILED (1) stat-lease4-get command failed: parameters: %1, reason: %2**

The stat-lease4-get command has failed. Both the parameters supplied and the reason for failure are logged.

**STAT\_CMDS\_LEASE4\_GET\_INVALID stat-lease4-get command is malformed or invalid, reason: %1**

The stat-lease4-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

**STAT\_CMDS\_LEASE4\_GET\_INVALID (1) stat-lease4-get command is malformed or invalid, reason: %1**

The stat-lease4-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

**STAT\_CMDS\_LEASE4\_GET\_NO\_SUBNETS stat-lease4-get, parameters: %1, %2"**

The parameters submitted with stat-lease4-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

**STAT\_CMDS\_LEASE4\_GET\_NO\_SUBNETS (1) stat-lease4-get, parameters: %1, %2"**

The parameters submitted with stat-lease4-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

**STAT\_CMDS\_LEASE6\_GET stat-lease6-get command successful, parameters: %1 rows found: %2**

The stat-lease6-get command has been successful. The log will contain the parameters supplied and the number of rows found.

**STAT\_CMDS\_LEASE6\_GET (1) stat-lease6-get command successful, parameters: %1 rows found: %2**

The stat-lease6-get command has been successful. The log will contain the parameters supplied and the number of rows found.

**STAT\_CMDS\_LEASE6\_GET\_FAILED stat-lease4-get command failed: parameters: %1, reason: %2**

The stat-lease6-get command has failed. Both the parameters supplied and the reason for failure are logged.

**STAT\_CMDS\_LEASE6\_GET\_FAILED (1) stat-lease4-get command failed: parameters: %1, reason: %2**

The stat-lease6-get command has failed. Both the parameters supplied and the reason for failure are logged.

**STAT\_CMDS\_LEASE6\_GET\_INVALID stat-lease6-get command is malformed or invalid, reason: %1**

The stat-lease6-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

---

**STAT\_CMDS\_LEASE6\_GET\_INVALID (1) stat-lease6-get command is malformed or invalid, reason: %1**

The stat-lease6-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

**STAT\_CMDS\_LEASE6\_GET\_NO\_SUBNETS stat-lease6-get, parameters: %1, %2"**

The parameters submitted with stat-lease6-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

**STAT\_CMDS\_LEASE6\_GET\_NO\_SUBNETS (1) stat-lease6-get, parameters: %1, %2"**

The parameters submitted with stat-lease6-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

## USER Module

**USER\_CHK\_HOOK\_LOAD\_ERROR DHCP UserCheckHook could not be loaded: %1**

This is an error message issued when the DHCP UserCheckHook could not be loaded. The exact cause should be explained in the log message. User subnet selection will revert to default processing.

**USER\_CHK\_HOOK\_LOAD\_ERROR (1) DHCP UserCheckHook could not be loaded: %1**

This is an error message issued when the DHCP UserCheckHook could not be loaded. The exact cause should be explained in the log message. User subnet selection will revert to default processing.

**USER\_CHK\_HOOK\_UNLOAD\_ERROR DHCP UserCheckHook an error occurred unloading the library: %1**

This is an error message issued when an error occurs while unloading the UserCheckHook library. This is unlikely to occur and normal operations of the library will likely resume when it is next loaded.

**USER\_CHK\_HOOK\_UNLOAD\_ERROR (1) DHCP UserCheckHook an error occurred unloading the library: %1**

This is an error message issued when an error occurs while unloading the UserCheckHook library. This is unlikely to occur and normal operations of the library will likely resume when it is next loaded.

**USER\_CHK\_SUBNET4\_SELECT\_ERROR DHCP UserCheckHook an unexpected error occurred in subnet4\_select callout: %1**

This is an error message issued when the DHCP UserCheckHook subnet4\_select hook encounters an unexpected error. The message should contain a more detailed explanation.

**USER\_CHK\_SUBNET4\_SELECT\_ERROR (1) DHCP UserCheckHook an unexpected error occurred in subnet4\_select callout: %1**

This is an error message issued when the DHCP UserCheckHook subnet4\_select hook encounters an unexpected error. The message should contain a more detailed explanation.

**USER\_CHK\_SUBNET4\_SELECT\_REGISTRY\_NULL DHCP UserCheckHook UserRegistry has not been created.**

This is an error message issued when the DHCP UserCheckHook subnet4\_select hook has been invoked but the UserRegistry has not been created. This is a programmatic error and should not occur.

**USER\_CHK\_SUBNET4\_SELECT\_REGISTRY\_NULL (1) DHCP UserCheckHook UserRegistry has not been created.**

This is an error message issued when the DHCP UserCheckHook subnet4\_select hook has been invoked but the UserRegistry has not been created. This is a programmatic error and should not occur.

**USER\_CHK\_SUBNET6\_SELECT\_ERROR DHCP UserCheckHook an unexpected error occurred in subnet6\_select callout: %1**

This is an error message issued when the DHCP UserCheckHook subnet6\_select hook encounters an unexpected error. The message should contain a more detailed explanation.

**USER\_CHK\_SUBNET6\_SELECT\_ERROR (1) DHCP UserCheckHook an unexpected error occurred in subnet6\_select callout: %1**

This is an error message issued when the DHCP UserCheckHook subnet6\_select hook encounters an unexpected error. The message should contain a more detailed explanation.

---

**USER\_CHK\_SUBNET6\_SELECT\_REGISTRY\_NULL DHCP UserCheckHook UserRegistry has not been created.**

This is an error message issued when the DHCP UserCheckHook subnet6\_select hook has been invoked but the UserRegistry has not been created. This is a programmatic error and should not occur.

**USER\_CHK\_SUBNET6\_SELECT\_REGISTRY\_NULL (1) DHCP UserCheckHook UserRegistry has not been created.**

This is an error message issued when the DHCP UserCheckHook subnet6\_select hook has been invoked but the UserRegistry has not been created. This is a programmatic error and should not occur.

---